

PDS4 Data Dictionary

Abridged - Version 1.2.0.1

PDS4 Data Dictionary: Abridged - Version 1.2.0.1

Generated from the PDS4 Information Model Version 1.2.0.1 on Fri Mar 28 10:32:02 PDT 2014

Table of Contents

1. Introduction	1
Audience	1
Acknowledgements	1
Scope	1
Applicable Documents	1
Terminology	1
2. Product Classes in the common (pds) namespace.	3
Ingest_LDD	3
Product_AIP	3
Product_Attribute_Definition	4
Product_Browse	4
Product_Bundle	4
Product_Class_Definition	5
Product_Collection	5
Product_Context	5
Product_DIP	6
Product_DIP_Deep_Archive	6
Product_Data_Set_PDS3	6
Product_Document	7
Product_File_Repository	7
Product_File_Text	7
Product_Instrument_Host_PDS3	8
Product_Instrument_PDS3	8
Product_Mission_PDS3	8
Product_Native	9
Product_Observational	9
Product_Proxy_PDS3	10
Product_SIP	10
Product_SPICE_Kernel	10
Product_Service	11
Product_Software	11
Product_Subscription_PDS3	11
Product_Target_PDS3	12
Product_Thumbnail	12
Product_Update	12
Product_Volume_PDS3	13
Product_Volume_Set_PDS3	13
Product_XML_Schema	13
Product_Zipped	14
3. Support classes in the common (pds) namespace.	15
Agency	15
Alias	15
Alias_List	15
Archival_Information_Package	16
Array	16
Array_1D	17
Array_2D	17
Array_2D_Image	18
Array_2D_Map	18
Array_2D_Spectrum	19
Array_3D	20
Array_3D_Image	20
Array_3D_Movie	21
Array_3D_Spectrum	21
Axis_Array	22

Band_Bin *Deprecated*	23
Band_Bin_Set *Deprecated*	23
Bundle	23
Bundle_Member_Entry	24
Byte_Stream	24
Checksum_Manifest	25
Citation_Information	25
Collection	25
Conceptual_Object	26
Context_Area	26
DD_Association	27
DD_Association_External *Deprecated*	27
DD_Attribute	27
DD_Attribute_Full	28
DD_Class	29
DD_Class_Full	30
DD_Permissible_Value	30
DD_Permissible_Value_Full	31
DD_Rule	31
DD_Rule_Statement	31
DD_Value_Domain	32
DD_Value_Domain_Full	34
DIP_Deep_Archive	35
Data_Object	36
Digital_Object	36
Discipline_Area	36
Discipline_Facets	36
Display_2D_Image *Deprecated*	37
Dissemination_Information_Package	37
Document	38
Document_File	38
Document_Format	39
Document_Format_Set	39
Element_Array	39
Encoded_Binary	40
Encoded_Byte_Stream	41
Encoded_Header	41
Encoded_Image	41
Encoded_Native	42
External_Reference	42
External_Reference_Extended	43
Facility	43
Field	44
Field_Binary	44
Field_Bit	45
Field_Character	46
Field_Delimited	47
Field_Statistics	48
File	48
File_Area	49
File_Area_Binary	49
File_Area_Browse	50
File_Area_Checksum_Manifest	50
File_Area_Encoded_Image	50
File_Area_Inventory	51
File_Area_Native	51
File_Area_Observational	51
File_Area_Observational_Supplemental	52

File_Area_SPICE_Kernel	52
File_Area_Service_Description	53
File_Area_Text	53
File_Area_Transfer_Manifest	53
File_Area_XML_Schema	54
Geometry	54
Group	54
Group_Facet1	55
Group_Facet2	55
Group_Field_Binary	56
Group_Field_Character	56
Group_Field_Delimited	57
Header	57
Identification_Area	57
Information_Package	59
Information_Package_Component	59
Instrument	59
Instrument_Host	61
Internal_Reference	61
Inventory	62
Investigation	62
Investigation_Area	63
Local_Internal_Reference	63
Mission_Area	64
Modification_Detail	64
Modification_History	64
NSSDC	64
Node	65
Object_Statistics	65
Observation_Area	66
Observing_System	66
Observing_System_Component	67
Other	67
PDS_Affiliate	68
PDS_Guest	68
Packed_Data_Fields	69
Parsable_Byte_Stream	69
Physical_Object	70
Primary_Result_Summary	70
Product	71
Product_Components	71
Quaternion	71
Quaternion_Component	72
Record	72
Record_Binary	72
Record_Character	73
Record_Delimited	73
Reference_List	74
Resource	74
SPICE_Kernel	75
Science_Facets	75
Service_Description	76
Software	76
Software_Binary	77
Software_Script	77
Software_Source	78
Special_Constants	78
Stream_Text	79

Submission_Information_Package	79
Symbolic_Literals_PDS	80
TNDO_Context	80
TNDO_Supplemental	80
Table_Base	81
Table_Binary	81
Table_Character	81
Table_Delimited	82
Tagged_Digital_Child	83
Tagged_Digital_Object	83
Tagged_NonDigital_Child	83
Tagged_NonDigital_Object	83
Target	84
Target_Identification	84
Telescope	85
Terminological_Entry	86
Time_Coordinates	86
Transfer_Manifest	87
Uniformly_Sampled	87
Update	88
Update_Entry	88
Vector	88
Vector_Cartesian_3	89
Vector_Cartesian_3_Acceleration	89
Vector_Cartesian_3_Pointing	90
Vector_Cartesian_3_Position	90
Vector_Cartesian_3_Velocity	90
Vector_Component	91
XML_Schema	91
Zip	92
4. PDS3 catalog classes in the common (pds) namespace.	93
Data_Set_PDS3	93
Instrument_Host_PDS3	94
Instrument_PDS3	94
Mission_PDS3	95
Subscriber_PDS3	95
TNDO_Context_PDS3	95
Target_PDS3	96
Volume_PDS3	96
Volume_Set_PDS3	97
5. Classes in the Rings discipline namespace.	98
Radio_Occultation	98
Radio_Occultation_Support	100
Rings_Supplement	100
Stellar_Occultation	101
6. Classes in the Imaging discipline namespace.	103
Telemetry_Parameters	103
7. Classes in the Display namespace.	104
Color_Display_Settings	104
Display_Direction	104
Display_Settings	104
Movie_Display_Settings	105
8. Attributes in the common (pds) namespace.	106
abstract_desc in Data_Set_PDS3	106
abstract_flag in DD_Class	106
abstract_flag in DD_Class_Full	106
acknowledgement_text in Document	107
address in Facility	107

affiliation_type in PDS_Affiliate	107
alternate_designation in Target_Identification	108
alternate_id in Alias	108
alternate_telephone_number in PDS_Affiliate	108
alternate_title in Alias	109
altitude in Telescope	109
aperture in Telescope	109
archive_status in Data_Set_PDS3	109
archive_status in Volume_PDS3	111
archive_status_note in Volume_PDS3	113
attribute_concept in DD_Attribute_Full	113
author_list in Citation_Information	116
author_list in Document	116
author_list in Software	117
axes in Array	117
axes in Array_1D	117
axes in Array_2D	118
axes in Array_3D	118
axis_index_order in Array	118
axis_name in Axis_Array	119
band_number in Band_Bin *Deprecated*	119
band_width in Band_Bin *Deprecated*	119
bit_fields in Packed_Data_Fields	120
bit_mask in Object_Statistics	120
bit_string in Digital_Object	120
bundle_type in Bundle	120
center_wavelength in Band_Bin *Deprecated*	121
character_constraint in ASCII_AnyURI	121
character_constraint in ASCII_DOI	121
character_constraint in ASCII_Date	122
character_constraint in ASCII_Date_DOY	122
character_constraint in ASCII_Date_Time	122
character_constraint in ASCII_Date_Time_DOY	123
character_constraint in ASCII_Date_Time_UTC	123
character_constraint in ASCII_Date_Time_YMD	123
character_constraint in ASCII_Date_YMD	124
character_constraint in ASCII_Directory_Path_Name	124
character_constraint in ASCII_File_Name	124
character_constraint in ASCII_File_Specification_Name	125
character_constraint in ASCII_Integer	125
character_constraint in ASCII_LID	125
character_constraint in ASCII_LIDVID	126
character_constraint in ASCII_LIDVID_LID	126
character_constraint in ASCII_MD5_Checksum	126
character_constraint in ASCII_NonNegative_Integer	127
character_constraint in ASCII_Numeric_Base16	127
character_constraint in ASCII_Numeric_Base2	127
character_constraint in ASCII_Numeric_Base8	128
character_constraint in ASCII_Real	128
character_constraint in ASCII_Short_String_Collapsed	128
character_constraint in ASCII_Short_String_Preserved	129
character_constraint in ASCII_String	129
character_constraint in ASCII_Text_Collapsed	130
character_constraint in ASCII_Text_Preserved	130
character_constraint in ASCII_Time	130
character_constraint in ASCII_VID	131
character_constraint in Character_Data_Type	131
character_constraint in UTF8_Short_String_Collapsed	131

character_constraint in UTF8_Short_String_Preserved	132
character_constraint in UTF8_Text_Preserved	132
character_encoding in ASCII_AnyURI	132
character_encoding in Character_Data_Type	133
checksum_manifest_checksum in Information_Package_Component	133
checksum_type in Information_Package_Component	133
citation_text in Data_Set_PDS3	134
class_name in DD_Attribute_Full	134
collection_type in Collection	134
comment in Alias	135
comment in Color_Display_Settings	135
comment in Context_Area	135
comment in DD_Attribute	136
comment in DD_Attribute_Full	136
comment in DD_Class_Full	136
comment in Display_Direction	137
comment in File	137
comment in Ingest_LDD	137
comment in Internal_Reference	137
comment in Local_Internal_Reference	138
comment in Movie_Display_Settings	138
compile_note in Software_Source	138
conceptual_domain in DD_Value_Domain_Full	139
confidence_level_note in Data_Set_PDS3	139
constant_value in DD_Association	140
container_type in Zip	140
coordinate_source in Telescope	140
copyright in Document	142
country in Facility	142
creation_date_time in File	142
curating_node_id in Volume_PDS3	143
data_regime in Primary_Result_Summary *Deprecated*	143
data_set_desc in Data_Set_PDS3	145
data_set_id in Data_Set_PDS3	145
data_set_name in Data_Set_PDS3	145
data_set_release_date in Data_Set_PDS3	146
data_set_terse_desc in Data_Set_PDS3	146
data_type in Element_Array	146
data_type in Field_Binary	148
data_type in Field_Bit	150
data_type in Field_Character	151
data_type in Field_Delimited	152
data_type in Quaternion_Component	154
data_type in Vector	154
date_time in Update_Entry	154
definition in DD_Attribute	155
definition in DD_Attribute_Full	155
definition in DD_Class	155
definition in DD_Class_Full	155
definition in Terminological_Entry	156
description in Agency	156
description in Array	156
description in Bundle	157
description in Citation_Information	157
description in Collection	157
description in Document	158
description in Document_Format	158
description in Encoded_Byte_Stream	158

description in External_Reference	158
description in Facility	159
description in Field_Binary	159
description in Field_Bit	159
description in Field_Character	160
description in Field_Delimited	160
description in Field_Statistics	160
description in Information_Package	161
description in Instrument	161
description in Instrument_Host	161
description in Investigation	161
description in Modification_Detail	162
description in Node	162
description in Object_Statistics	162
description in Observing_System	163
description in Observing_System_Component	163
description in Other	163
description in PDS_Affiliate	164
description in PDS_Guest	164
description in Packed_Data_Fields	164
description in Parsable_Byte_Stream	165
description in Primary_Result_Summary	165
description in Quaternion	165
description in Quaternion_Component	165
description in Resource	166
description in Software	166
description in Table_Base	166
description in Target	167
description in Target_Identification	167
description in Telescope	167
description in Update	168
description in Update_Entry	168
description in Vector	168
description in Vector_Component	169
description in Volume_PDS3	169
description in Volume_Set_PDS3	169
description in Zip	169
detector_number in Band_Bin *Deprecated*	170
directory_path_name in Document_File	170
discipline_name in Discipline_Facets	170
document_name in Document	171
document_standard_id in Document_File	171
doi in Document	173
doi in External_Reference	173
domain in Science_Facets	173
editor_list in Citation_Information	174
editor_list in Document	174
electronic_mail_address in PDS_Affiliate	175
electronic_mail_address in PDS_Guest	175
elements in Axis_Array	175
encoding_standard_id in Encoded_Binary	176
encoding_standard_id in Encoded_Byte_Stream	176
encoding_standard_id in Encoded_Header	176
encoding_standard_id in Encoded_Image	177
encoding_standard_id in Encoded_Native	177
encoding_type in SPICE_Kernel	178
enumeration_flag in DD_Value_Domain	178
enumeration_flag in DD_Value_Domain_Full	179

error_constant in Special_Constants	179
facet1 in Group_Facet1	179
facet2 in Group_Facet2	181
field_delimiter in Table_Delimited	181
field_format in Field_Binary	182
field_format in Field_Bit	182
field_format in Field_Character	183
field_format in Field_Delimited	183
field_length in Field_Binary	183
field_length in Field_Character	184
field_location in Field_Binary	184
field_location in Field_Character	184
field_number in Field	185
fields in Group	185
fields in Record	185
file_name in File	185
file_size in File	186
files in Software_Binary	186
files in Software_Script	186
files in Software_Source	187
filter_number in Band_Bin *Deprecated*	187
first_sampling_parameter_value in Uniformly_Sampled	187
format_type in Document_Format	188
formation_rule in ASCII_DOI	188
formation_rule in ASCII_Date	188
formation_rule in ASCII_Date_DOY	189
formation_rule in ASCII_Date_Time	189
formation_rule in ASCII_Date_Time_DOY	189
formation_rule in ASCII_Date_Time_UTC	190
formation_rule in ASCII_Date_Time_YMD	190
formation_rule in ASCII_Date_YMD	190
formation_rule in ASCII_Directory_Path_Name	191
formation_rule in ASCII_File_Name	191
formation_rule in ASCII_File_Specification_Name	192
formation_rule in ASCII_LID	192
formation_rule in ASCII_LIDVID	192
formation_rule in ASCII_LIDVID_LID	193
formation_rule in ASCII_MD5_Checksum	193
formation_rule in ASCII_Time	193
formation_rule in ASCII_VID	194
formation_rule in Character_Data_Type	194
formation_rule in DD_Value_Domain	194
formation_rule in DD_Value_Domain_Full	195
full_name in Ingest_LDD	195
full_name in Subscriber_PDS3	195
full_name in Update_Entry	196
grating_position in Band_Bin *Deprecated*	196
group_length in Group_Field_Binary	196
group_length in Group_Field_Character	197
group_location in Group_Field_Binary	197
group_location in Group_Field_Character	197
group_number in Group	198
groups in Group	198
groups in Record	198
high_instrument_saturation in Special_Constants	199
high_representation_saturation in Special_Constants	199
information_model_version in Identification_Area	200
install_note in Software_Script	200

institution_name in Node	201
institution_name in PDS_Affiliate	201
instrument_desc in Instrument_PDS3	201
instrument_host_desc in Instrument_Host_PDS3	201
instrument_host_id in Instrument_Host_PDS3	202
instrument_host_name in Instrument_Host_PDS3	202
instrument_host_type in Instrument_Host_PDS3	203
instrument_host_version_id in Instrument_Host	203
instrument_id in Instrument_PDS3	203
instrument_name in Instrument_PDS3	204
instrument_serial_number in Instrument_PDS3	204
instrument_type in Instrument_PDS3	204
instrument_version_id in Instrument_PDS3	205
invalid_constant in Special_Constants	205
kernel_type in SPICE_Kernel	205
keyword in Citation_Information	206
language in Terminological_Entry	206
last_modification_date_time in Ingest_LDD	206
last_sampling_parameter_value in Uniformly_Sampled	207
ldd_version_id in Ingest_LDD	207
ldd_version_id in XML_Schema	207
lid_reference in Bundle_Member_Entry	208
lid_reference in Internal_Reference	208
lidvid_reference in Bundle_Member_Entry	208
lidvid_reference in Internal_Reference	209
line_display_direction in Display_2D_Image *Deprecated*	209
local_identifier in Axis_Array	209
local_identifier in Byte_Stream	210
local_identifier in DD_Association	210
local_identifier in DD_Attribute	210
local_identifier in DD_Attribute_Full	211
local_identifier in DD_Class	211
local_identifier in DD_Class_Full	211
local_identifier in DD_Rule	211
local_identifier in Field_Statistics	212
local_identifier in File	212
local_identifier in Geometry	212
local_identifier in Object_Statistics	213
local_identifier in Quaternion	213
local_identifier in Subscriber_PDS3	213
local_identifier in Update	214
local_identifier in Vector	214
local_identifier_reference in Local_Internal_Reference	214
local_mean_solar_time in Time_Coordinates	215
local_reference_type in Local_Internal_Reference	215
local_true_solar_time in Time_Coordinates	215
logical_identifier in Identification_Area	216
low_instrument_saturation in Special_Constants	216
low_representation_saturation in Special_Constants	217
maximum in Field_Statistics	217
maximum in Object_Statistics	217
maximum_characters in ASCII_AnyURI	218
maximum_characters in ASCII_DOI	218
maximum_characters in ASCII_Date	218
maximum_characters in ASCII_Date_DOY	219
maximum_characters in ASCII_Date_Time	219
maximum_characters in ASCII_Date_Time_DOY	219
maximum_characters in ASCII_Date_Time_UTC	220

maximum_characters in ASCII_Date_Time_YMD	220
maximum_characters in ASCII_Date_YMD	220
maximum_characters in ASCII_Directory_Path_Name	221
maximum_characters in ASCII_File_Name	221
maximum_characters in ASCII_File_Specification_Name	221
maximum_characters in ASCII_Integer	222
maximum_characters in ASCII_LID	222
maximum_characters in ASCII_LIDVID	222
maximum_characters in ASCII_LIDVID_LID	223
maximum_characters in ASCII_MD5_Checksum	223
maximum_characters in ASCII_NonNegative_Integer	223
maximum_characters in ASCII_Numeric_Base16	224
maximum_characters in ASCII_Numeric_Base2	224
maximum_characters in ASCII_Numeric_Base8	225
maximum_characters in ASCII_Real	225
maximum_characters in ASCII_Short_String_Collapsed	225
maximum_characters in ASCII_Short_String_Preserved	226
maximum_characters in ASCII_Text_Collapsed	226
maximum_characters in ASCII_Text_Preserved	226
maximum_characters in ASCII_Time	227
maximum_characters in ASCII_VID	227
maximum_characters in Character_Data_Type	227
maximum_characters in DD_Value_Domain	228
maximum_characters in DD_Value_Domain_Full	228
maximum_characters in UTF8_Short_String_Collapsed	228
maximum_characters in UTF8_Short_String_Preserved	229
maximum_characters in UTF8_Text_Preserved	229
maximum_field_length in Field_Delimited	230
maximum_occurrences in DD_Association	230
maximum_occurrences in DD_Association_External *Deprecated*	230
maximum_record_length in Record_Delimited	231
maximum_scaled_value in Object_Statistics	231
maximum_value in ASCII_Date_Time	231
maximum_value in ASCII_Date_Time_DOY	232
maximum_value in ASCII_Date_Time_UTC	232
maximum_value in ASCII_Date_Time_YMD	232
maximum_value in ASCII_Integer	232
maximum_value in ASCII_LID	233
maximum_value in ASCII_NonNegative_Integer	233
maximum_value in ASCII_Numeric_Base16	233
maximum_value in ASCII_Numeric_Base2	234
maximum_value in ASCII_Real	234
maximum_value in ASCII_Short_String_Collapsed	234
maximum_value in ASCII_Short_String_Preserved	235
maximum_value in ASCII_Text_Preserved	235
maximum_value in ASCII_Time	235
maximum_value in ASCII_VID	235
maximum_value in Character_Data_Type	236
maximum_value in DD_Value_Domain	236
maximum_value in DD_Value_Domain_Full	236
maximum_value in UTF8_Short_String_Collapsed	237
maximum_value in UTF8_Short_String_Preserved	237
maximum_value in UTF8_Text_Preserved	237
md5_checksum in File	238
md5_checksum in Object_Statistics	238
mean in Field_Statistics	238
mean in Object_Statistics	239
median in Field_Statistics	239

median in Object_Statistics	239
medium_type in NSSDC	240
medium_type in Volume_PDS3	240
member_status in Bundle_Member_Entry	240
minimum in Field_Statistics	241
minimum in Object_Statistics	241
minimum_characters in ASCII_AnyURI	241
minimum_characters in ASCII_DOI	241
minimum_characters in ASCII_Date	242
minimum_characters in ASCII_Date_DOY	242
minimum_characters in ASCII_Date_Time	242
minimum_characters in ASCII_Date_Time_DOY	243
minimum_characters in ASCII_Date_Time_UTC	243
minimum_characters in ASCII_Date_Time_YMD	243
minimum_characters in ASCII_Date_YMD	244
minimum_characters in ASCII_Directory_Path_Name	244
minimum_characters in ASCII_File_Name	244
minimum_characters in ASCII_File_Specification_Name	245
minimum_characters in ASCII_Integer	245
minimum_characters in ASCII_LID	245
minimum_characters in ASCII_LIDVID	246
minimum_characters in ASCII_LIDVID_LID	246
minimum_characters in ASCII_MD5_Checksum	247
minimum_characters in ASCII_NonNegative_Integer	247
minimum_characters in ASCII_Numeric_Base16	247
minimum_characters in ASCII_Numeric_Base2	248
minimum_characters in ASCII_Numeric_Base8	248
minimum_characters in ASCII_Real	248
minimum_characters in ASCII_Short_String_Collapsed	249
minimum_characters in ASCII_Short_String_Preserved	249
minimum_characters in ASCII_String	250
minimum_characters in ASCII_Text_Collapsed	250
minimum_characters in ASCII_Text_Preserved	250
minimum_characters in ASCII_Time	251
minimum_characters in ASCII_VID	251
minimum_characters in Character_Data_Type	251
minimum_characters in DD_Value_Domain	252
minimum_characters in DD_Value_Domain_Full	252
minimum_characters in UTF8_Short_String_Collapsed	252
minimum_characters in UTF8_Short_String_Preserved	253
minimum_characters in UTF8_String	253
minimum_characters in UTF8_Text_Preserved	253
minimum_occurrences in DD_Association	254
minimum_occurrences in DD_Association_External *Deprecated*	254
minimum_scaled_value in Object_Statistics	254
minimum_value in ASCII_Date_Time	255
minimum_value in ASCII_Date_Time_DOY	255
minimum_value in ASCII_Date_Time_UTC	255
minimum_value in ASCII_Date_Time_YMD	256
minimum_value in ASCII_Integer	256
minimum_value in ASCII_LID	256
minimum_value in ASCII_NonNegative_Integer	257
minimum_value in ASCII_Numeric_Base16	257
minimum_value in ASCII_Numeric_Base2	257
minimum_value in ASCII_Real	257
minimum_value in ASCII_Short_String_Collapsed	258
minimum_value in ASCII_Short_String_Preserved	258
minimum_value in ASCII_Text_Preserved	258

minimum_value in ASCII_Time	259
minimum_value in ASCII_VID	259
minimum_value in Character_Data_Type	259
minimum_value in DD_Value_Domain	260
minimum_value in DD_Value_Domain_Full	260
minimum_value in UTF8_Short_String_Collapsed	260
minimum_value in UTF8_Short_String_Preserved	260
minimum_value in UTF8_Text_Preserved	261
missing_constant in Special_Constants	261
mission_desc in Mission_PDS3	261
mission_name in Mission_PDS3	262
mission_objectives_summary in Mission_PDS3	262
mission_start_date in Mission_PDS3	262
mission_stop_date in Mission_PDS3	263
model_id in Instrument	263
modification_date in Modification_Detail	263
naif_host_id in Instrument_Host	264
naif_instrument_id in Instrument	264
name in Agency	264
name in Byte_Stream	265
name in DD_Association_External *Deprecated*	265
name in DD_Attribute	265
name in DD_Attribute_Full	266
name in DD_Class	266
name in DD_Class_Full	266
name in External_Reference_Extended	266
name in Facility	267
name in Field	267
name in Field_Binary	267
name in Field_Bit	268
name in Field_Character	268
name in Field_Delimited	268
name in Ingest_LDD	269
name in Instrument	269
name in Instrument_Host	269
name in Investigation	269
name in Investigation_Area	270
name in Node	270
name in Observing_System	271
name in Observing_System_Component	271
name in PDS_Affiliate	272
name in PDS_Guest	272
name in Quaternion	272
name in Quaternion_Component	273
name in Resource	273
name in Software	273
name in Target	274
name in Target_Identification	274
name in Terminological_Entry	274
name in Vector	275
name in Vector_Component	275
namespace_id in DD_Association_External *Deprecated*	275
namespace_id in DD_Attribute_Full	276
namespace_id in DD_Class_Full	276
namespace_id in Ingest_LDD	276
nil_reason in Symbolic_Literals_PDS	277
nillable_flag in DD_Attribute	277
nillable_flag in DD_Attribute_Full	277

not_applicable_constant in Special_Constants	278
nssdc_collection_id in NSSDC	278
object_length in Encoded_Byte_Stream	278
object_length in Header	279
object_length in Parsable_Byte_Stream	279
offset in Array	279
offset in Encoded_Byte_Stream	280
offset in Parsable_Byte_Stream	280
offset in Table_Base	280
orbit_direction in Target_PDS3	280
original_band in Band_Bin *Deprecated*	281
os_version in Software_Binary	281
os_version in Software_Source	281
parsing_standard_id in Checksum_Manifest	282
parsing_standard_id in Header	282
parsing_standard_id in Parsable_Byte_Stream	283
parsing_standard_id in SPICE_Kernel	283
parsing_standard_id in Service_Description	284
parsing_standard_id in Table_Delimited	284
parsing_standard_id in XML_Schema	285
pattern in ASCII_DOI	285
pattern in ASCII_Date	285
pattern in ASCII_Date_DOY	286
pattern in ASCII_Date_Time	286
pattern in ASCII_Date_Time_DOY	288
pattern in ASCII_Date_Time_UTC	288
pattern in ASCII_Date_Time_YMD	290
pattern in ASCII_Date_YMD	290
pattern in ASCII_LID	291
pattern in ASCII_MD5_Checksum	291
pattern in ASCII_Numeric_Base16	291
pattern in ASCII_Numeric_Base2	292
pattern in ASCII_Numeric_Base8	292
pattern in ASCII_Time	292
pattern in ASCII_VID	293
pattern in Character_Data_Type	293
pattern in DD_Value_Domain	294
pattern in DD_Value_Domain_Full	294
phone_book_flag in PDS_Affiliate	294
postal_address_text in PDS_Affiliate	294
preferred_flag in Terminological_Entry	295
primary_body_name in Target_PDS3	295
processing_level in Primary_Result_Summary	295
processing_level_id in Primary_Result_Summary *Deprecated*	296
producer_full_name in Data_Set_PDS3	297
product_class in Identification_Area	297
program_notes_id in Software_Binary	298
program_notes_id in Software_Source	299
programmers_manual_id in Software	299
publication_date in Document	299
publication_date in Volume_PDS3	300
publication_year in Citation_Information	300
purpose in Primary_Result_Summary	300
record_delimiter in Stream_Text	301
record_delimiter in Table_Binary	301
record_delimiter in Table_Character	301
record_delimiter in Table_Delimited	302
record_length in Record_Binary	302

record_length in Record_Character	303
records in File	303
records in Table_Base	303
records in Table_Delimited	303
reference_frame_id in Vector	304
reference_frame_id in Vector_Cartesian_3	304
reference_text in External_Reference	305
reference_type in Bundle_Member_Entry	305
reference_type in DD_Association	306
reference_type in DD_Association_External *Deprecated*	306
reference_type in Internal_Reference	307
reference_type in Inventory	313
registered_by in DD_Attribute_Full	313
registered_by in DD_Class_Full	313
registration_authority_id in DD_Attribute_Full	314
registration_authority_id in DD_Class_Full	314
registration_date in PDS_Affiliate	314
registration_date in PDS_Guest	315
repetitions in Group	315
revision_id in Document	315
rotation_direction in Target_PDS3	315
rule_assign in DD_Rule	316
rule_context in DD_Rule	316
rule_description in DD_Rule_Statement	316
rule_message in DD_Rule_Statement	317
rule_test in DD_Rule_Statement	317
rule_type in DD_Rule_Statement	317
rule_value in DD_Rule_Statement	318
sample_display_direction in Display_2D_Image *Deprecated*	318
sampling_parameter_interval in Uniformly_Sampled	318
sampling_parameter_name in Uniformly_Sampled	319
sampling_parameter_scale in Uniformly_Sampled	319
sampling_parameter_unit in Uniformly_Sampled	320
saturated_constant in Special_Constants	320
scaling_factor in Band_Bin *Deprecated*	320
scaling_factor in Element_Array	321
scaling_factor in Field_Binary	321
scaling_factor in Field_Bit	321
scaling_factor in Field_Character	322
scaling_factor in Field_Delimited	322
sequence_number in Axis_Array	322
sequence_number in Quaternion_Component	323
sequence_number in Vector_Component	323
serial_number in Instrument	323
serial_number in Instrument_Host	324
software_dialect in Software_Source	324
software_format_type in Software_Binary	324
software_format_type in Software_Source	324
software_id in Software	325
software_language in Software_Source	325
software_type in Software	325
software_version_id in Software	326
solar_longitude in Time_Coordinates	326
sort_name in PDS_Affiliate	326
sort_name in PDS_Guest	326
specified_unit_id in DD_Value_Domain	327
specified_unit_id in DD_Value_Domain_Full	327
specified_unit_id in Unit_Of_Measure	327

specified_unit_id in Units_of_Acceleration	328
specified_unit_id in Units_of_Amount_Of_Substance	328
specified_unit_id in Units_of_Angle	328
specified_unit_id in Units_of_Angular_Velocity	329
specified_unit_id in Units_of_Area	329
specified_unit_id in Units_of_Frame_Rate	330
specified_unit_id in Units_of_Frequency	330
specified_unit_id in Units_of_Length	330
specified_unit_id in Units_of_Map_Scale	331
specified_unit_id in Units_of_Mass	331
specified_unit_id in Units_of_Misc	331
specified_unit_id in Units_of_None	332
specified_unit_id in Units_of_Optical_Path_Length	332
specified_unit_id in Units_of_Pressure	332
specified_unit_id in Units_of_Radiance	333
specified_unit_id in Units_of_Rates	333
specified_unit_id in Units_of_Solid_Angle	333
specified_unit_id in Units_of_Spectral_Irradiance	334
specified_unit_id in Units_of_Spectral_Radiance	334
specified_unit_id in Units_of_Storage	335
specified_unit_id in Units_of_Temperature	335
specified_unit_id in Units_of_Time	335
specified_unit_id in Units_of_Velocity	336
specified_unit_id in Units_of_Voltage	336
specified_unit_id in Units_of_Volume	336
specified_unit_id in Units_of_Wavenumber	337
standard_deviation in Band_Bin *Deprecated*	337
standard_deviation in Field_Statistics	337
standard_deviation in Object_Statistics	338
start_bit in Field_Bit	338
start_date in Investigation	338
start_date_time in Data_Set_PDS3 *Deprecated*	339
start_date_time in Time_Coordinates	339
start_time in Data_Set_PDS3	339
starting_point_identifier in Document_Format	340
steward_id in DD_Attribute_Full	340
steward_id in DD_Class_Full	341
steward_id in Ingest_LDD	341
stop_bit in Field_Bit	342
stop_date in Investigation	342
stop_date_time in Data_Set_PDS3 *Deprecated*	342
stop_date_time in Time_Coordinates	342
stop_time in Data_Set_PDS3	343
subfacet1 in Group_Facet1	343
subfacet2 in Group_Facet2	343
submitter_name in DD_Attribute	344
submitter_name in DD_Attribute_Full	344
submitter_name in DD_Class	344
submitter_name in DD_Class_Full	345
subscription_id in Subscriber_PDS3	345
supported_architecture_note in Software_Binary	345
supported_architecture_note in Software_Source	346
supported_environment_note in Software_Script	346
supported_operating_system_note in Software_Binary	346
supported_operating_system_note in Software_Source	347
system_requirements_note in Software_Binary	347
system_requirements_note in Software_Script	347
system_requirements_note in Software_Source	348

target_desc in Target_PDS3	348
target_name in Target_PDS3	348
target_type in Target_PDS3	348
team_name in PDS_Affiliate	349
telephone_number in PDS_Affiliate	349
telescope_latitude in Telescope	350
telescope_longitude in Telescope	350
title in Identification_Area	350
transfer_manifest_checksum in Information_Package_Component	351
type in DD_Attribute_Full	351
type in DD_Class_Full	351
type in Facility	352
type in Instrument	352
type in Instrument_Host	355
type in Investigation	356
type in Investigation_Area	357
type in Observing_System_Component	358
type in Primary_Result_Summary *Deprecated*	359
type in Quaternion	360
type in Resource	360
type in Target	361
type in Target_Identification	362
type in Unit_Of_Measure	363
type in Units_of_Acceleration	363
type in Units_of_Amount_Of_Substance	363
type in Units_of_Angle	364
type in Units_of_Angular_Velocity	364
type in Units_of_Area	364
type in Units_of_Frame_Rate	365
type in Units_of_Frequency	365
type in Units_of_Length	365
type in Units_of_Map_Scale	366
type in Units_of_Mass	366
type in Units_of_Misc	366
type in Units_of_None	367
type in Units_of_Optical_Path_Length	367
type in Units_of_Pressure	367
type in Units_of_Radiance	368
type in Units_of_Rates	368
type in Units_of_Solid_Angle	368
type in Units_of_Spectral_Irradiance	369
type in Units_of_Spectral_Radiance	369
type in Units_of_Storage	369
type in Units_of_Temperature	370
type in Units_of_Time	370
type in Units_of_Velocity	370
type in Units_of_Voltage	371
type in Units_of_Volume	371
type in Units_of_Wavenumber	371
type in Vector	372
unit in Axis_Array *Deprecated*	372
unit in Element_Array	372
unit in Field_Binary	373
unit in Field_Bit	373
unit in Field_Character	373
unit in Field_Delimited	374
unit in Vector_Component	374
unit_id in Unit_Of_Measure	374

unit_id in Units_of_Acceleration	374
unit_id in Units_of_Amount_Of_Substance	375
unit_id in Units_of_Angle	375
unit_id in Units_of_Angular_Velocity	376
unit_id in Units_of_Area	376
unit_id in Units_of_Frame_Rate	376
unit_id in Units_of_Frequency	377
unit_id in Units_of_Length	377
unit_id in Units_of_Map_Scale	378
unit_id in Units_of_Mass	378
unit_id in Units_of_Misc	379
unit_id in Units_of_None	379
unit_id in Units_of_Optical_Path_Length	379
unit_id in Units_of_Pressure	380
unit_id in Units_of_Radiance	380
unit_id in Units_of_Rates	380
unit_id in Units_of_Solid_Angle	381
unit_id in Units_of_Spectral_Irradiance	381
unit_id in Units_of_Spectral_Radiance	382
unit_id in Units_of_Storage	382
unit_id in Units_of_Temperature	383
unit_id in Units_of_Time	383
unit_id in Units_of_Velocity	384
unit_id in Units_of_Voltage	384
unit_id in Units_of_Volume	384
unit_id in Units_of_Wavenumber	385
unit_of_measure_type in DD_Value_Domain	385
unit_of_measure_type in DD_Value_Domain_Full	387
unknown_constant in Special_Constants	388
url in External_Reference_Extended	388
url in Resource	389
users_manual_id in Software	389
valid_maximum in Special_Constants	389
valid_minimum in Special_Constants	390
value in DD_Permissible_Value	390
value in DD_Permissible_Value_Full	391
value in Quaternion_Component	391
value in Vector_Component	391
value_begin_date in DD_Permissible_Value_Full	392
value_data_type in DD_Value_Domain	392
value_data_type in DD_Value_Domain_Full	394
value_end_date in DD_Permissible_Value_Full	395
value_meaning in DD_Permissible_Value	396
value_meaning in DD_Permissible_Value_Full	396
value_offset in Band_Bin *Deprecated*	396
value_offset in Element_Array	397
value_offset in Field_Binary	397
value_offset in Field_Bit	397
value_offset in Field_Character	398
value_offset in Field_Delimited	398
vector_components in Vector	398
version_id in DD_Attribute	399
version_id in DD_Attribute_Full	399
version_id in DD_Class	399
version_id in DD_Class_Full	399
version_id in Identification_Area	400
version_id in Instrument_Host *Deprecated*	400
version_id in Modification_Detail	400

version_id in Software *Deprecated*	401
volume_de_fullname in Volume_PDS3	401
volume_format in Volume_PDS3	401
volume_id in Volume_PDS3	402
volume_name in Volume_PDS3	402
volume_series_name in Volume_Set_PDS3	402
volume_set_id in Volume_PDS3	403
volume_set_id in Volume_Set_PDS3	403
volume_set_name in Volume_Set_PDS3	403
volume_size in Volume_PDS3	404
volume_version_id in Volume_PDS3	404
volumes in Volume_Set_PDS3	404
wavelength_range in Science_Facets	404
x in Vector_Cartesian_3	405
xml_schema_base_type in ASCII_AnyURI	405
xml_schema_base_type in ASCII_Boolean	406
xml_schema_base_type in ASCII_DOI	406
xml_schema_base_type in ASCII_Date	406
xml_schema_base_type in ASCII_Date_DOY	407
xml_schema_base_type in ASCII_Date_Time	407
xml_schema_base_type in ASCII_Date_Time_DOY	407
xml_schema_base_type in ASCII_Date_Time_UTC	408
xml_schema_base_type in ASCII_Date_Time_YMD	408
xml_schema_base_type in ASCII_Date_YMD	409
xml_schema_base_type in ASCII_Directory_Path_Name	409
xml_schema_base_type in ASCII_File_Name	409
xml_schema_base_type in ASCII_File_Specification_Name	410
xml_schema_base_type in ASCII_Integer	410
xml_schema_base_type in ASCII_LID	410
xml_schema_base_type in ASCII_LIDVID	411
xml_schema_base_type in ASCII_LIDVID_LID	411
xml_schema_base_type in ASCII_MD5_Checksum	411
xml_schema_base_type in ASCII_NonNegative_Integer	412
xml_schema_base_type in ASCII_Numeric_Base16	412
xml_schema_base_type in ASCII_Numeric_Base2	413
xml_schema_base_type in ASCII_Numeric_Base8	413
xml_schema_base_type in ASCII_Real	413
xml_schema_base_type in ASCII_Short_String_Collapsed	414
xml_schema_base_type in ASCII_Short_String_Preserved	414
xml_schema_base_type in ASCII_String	414
xml_schema_base_type in ASCII_Text_Collapsed	415
xml_schema_base_type in ASCII_Text_Preserved	415
xml_schema_base_type in ASCII_Time	416
xml_schema_base_type in ASCII_VID	416
xml_schema_base_type in Character_Data_Type	416
xml_schema_base_type in UTF8_Short_String_Collapsed	417
xml_schema_base_type in UTF8_Short_String_Preserved	417
xml_schema_base_type in UTF8_String	417
xml_schema_base_type in UTF8_Text_Preserved	418
y in Vector_Cartesian_3	418
z in Vector_Cartesian_3	418
9. Attributes in the Rings discipline namespace.	419
SCLK_start_time in Radio_Occultation	419
SCLK_start_time in Stellar_Occultation	419
SCLK_stop_time in Radio_Occultation	419
SCLK_stop_time in Stellar_Occultation	420
along_track_timing_offset in Radio_Occultation	420
dsn_station_number in Radio_Occultation	420

dsn_station_number in Radio_Occultation_Support	421
earth_received_start_time_utc in Radio_Occultation	421
earth_received_stop_time_utc in Radio_Occultation	421
frequency_band in Radio_Occultation	422
frequency_band in Radio_Occultation_Support	423
highest_detectable_opacity in Radio_Occultation	423
highest_detectable_opacity in Stellar_Occultation	424
light_source_incidence_angle in Radio_Occultation	424
light_source_incidence_angle in Stellar_Occultation	425
lowest_detectable_opacity in Radio_Occultation	425
lowest_detectable_opacity in Stellar_Occultation	426
maximum_light_source_incidence_angle in Radio_Occultation	426
maximum_observed_event_time in Radio_Occultation_Support	426
maximum_observed_ring_azimuth in Radio_Occultation	427
maximum_observed_ring_azimuth in Stellar_Occultation	427
maximum_observed_ring_elevation in Radio_Occultation	427
maximum_observed_ring_elevation in Stellar_Occultation	428
maximum_radial_sampling_interval in Radio_Occultation	428
maximum_radial_sampling_interval in Stellar_Occultation	429
maximum_ring_longitude in Radio_Occultation	429
maximum_ring_longitude in Stellar_Occultation	429
maximum_ring_radius in Radio_Occultation	430
maximum_ring_radius in Stellar_Occultation	430
maximum_wavelength in Radio_Occultation	430
maximum_wavelength in Stellar_Occultation	431
minimum_light_source_incidence_angle in Radio_Occultation	431
minimum_observed_event_time in Radio_Occultation_Support	431
minimum_observed_ring_azimuth in Radio_Occultation	432
minimum_observed_ring_azimuth in Stellar_Occultation	432
minimum_observed_ring_elevation in Radio_Occultation	433
minimum_observed_ring_elevation in Stellar_Occultation	433
minimum_radial_sampling_interval in Radio_Occultation	433
minimum_radial_sampling_interval in Stellar_Occultation	434
minimum_ring_longitude in Radio_Occultation	434
minimum_ring_longitude in Stellar_Occultation	435
minimum_ring_radius in Radio_Occultation	435
minimum_ring_radius in Stellar_Occultation	435
minimum_wavelength in Radio_Occultation	436
minimum_wavelength in Stellar_Occultation	436
observed_event_start_tdb in Radio_Occultation	436
observed_event_start_tdb in Stellar_Occultation	437
observed_event_stop_tdb in Radio_Occultation	437
observed_event_stop_tdb in Stellar_Occultation	437
observed_ring_elevation in Radio_Occultation	438
observed_ring_elevation in Stellar_Occultation	438
occultation_type in Radio_Occultation	439
occultation_type in Radio_Occultation_Support	439
occultation_type in Stellar_Occultation	440
orbit_number in Radio_Occultation	440
orbit_number in Radio_Occultation_Support	441
orbit_number in Stellar_Occultation	441
planetary_occultation_flag in Radio_Occultation	441
planetary_occultation_flag in Radio_Occultation_Support	442
planetary_occultation_flag in Stellar_Occultation	442
radial_resolution in Radio_Occultation	443
radial_resolution in Stellar_Occultation	443
radial_sampling_interval in Radio_Occultation	443
radial_sampling_interval in Stellar_Occultation	444

reference_time_utc in Radio_Occultation	444
reference_time_utc in Radio_Occultation_Support	445
ring_event_start_tdb in Radio_Occultation	445
ring_event_start_tdb in Stellar_Occultation	445
ring_event_start_time_utc in Radio_Occultation	446
ring_event_start_time_utc in Stellar_Occultation	446
ring_event_stop_tdb in Radio_Occultation	446
ring_event_stop_tdb in Stellar_Occultation	447
ring_event_stop_time_utc in Radio_Occultation	447
ring_event_stop_time_utc in Stellar_Occultation	447
ring_observation_id in Radio_Occultation	448
ring_observation_id in Radio_Occultation_Support	448
ring_observation_id in Rings_Supplement	449
ring_observation_id in Stellar_Occultation	449
ring_occultation_direction in Radio_Occultation	450
ring_occultation_direction in Radio_Occultation_Support	451
ring_occultation_direction in Stellar_Occultation	451
ring_profile_direction in Radio_Occultation	452
ring_profile_direction in Radio_Occultation_Support	453
ring_profile_direction in Stellar_Occultation	453
sampling_parameter_interval in Radio_Occultation_Support	454
sampling_parameter_name in Radio_Occultation_Support	454
sampling_parameter_unit in Radio_Occultation_Support	454
source_pds3_id in Radio_Occultation	455
source_pds3_id in Rings_Supplement	455
source_pds3_id in Stellar_Occultation	455
spacecraft_event_start_time_utc in Radio_Occultation	456
spacecraft_event_stop_time_utc in Radio_Occultation	456
spice_filename in Radio_Occultation_Support	457
star_name in Stellar_Occultation	457
sub_stellar_clock_angle in Stellar_Occultation	457
sub_stellar_ring_azimuth in Stellar_Occultation	458
wavelength in Radio_Occultation	458
wavelength in Stellar_Occultation	459
10. Attributes in the Imaging discipline namespace.	460
application_process_id in Telemetry_Parameters	460
application_process_name in Telemetry_Parameters	460
earth_received_start_date_time in Telemetry_Parameters	460
earth_received_stop_date_time in Telemetry_Parameters	461
expected_packets in Telemetry_Parameters	461
packet_map_mask in Telemetry_Parameters	461
received_packets in Telemetry_Parameters	462
spice_file_name in Telemetry_Parameters	462
telemetry_format_id in Telemetry_Parameters	462
telemetry_provider_id in Telemetry_Parameters	463
telemetry_source_name in Telemetry_Parameters	463
telemetry_source_type in Telemetry_Parameters	463
11. Attributes in the Display namespace.	465
blue_channel_band in Color_Display_Settings	465
color_display_axis in Color_Display_Settings	465
frame_rate in Movie_Display_Settings	465
green_channel_band in Color_Display_Settings	466
horizontal_display_axis in Display_Direction	466
horizontal_display_direction in Display_Direction	466
loop_back_and_forth_flag in Movie_Display_Settings	467
loop_count in Movie_Display_Settings	468
loop_delay in Movie_Display_Settings	468
loop_flag in Movie_Display_Settings	468

red_channel_band in Color_Display_Settings	469
time_display_axis in Movie_Display_Settings	469
vertical_display_axis in Display_Direction	469
vertical_display_direction in Display_Direction	470
12. Data Types in the common (pds) namespace.	471
ASCII_AnyURI	471
ASCII_Boolean	471
ASCII_DOI	471
ASCII_Date	471
ASCII_Date_DOY	472
ASCII_Date_Time	472
ASCII_Date_Time_DOY	473
ASCII_Date_Time_UTC	473
ASCII_Date_Time_YMD	474
ASCII_Date_YMD	474
ASCII_Directory_Path_Name	474
ASCII_File_Name	475
ASCII_File_Specification_Name	475
ASCII_Integer	475
ASCII_LID	475
ASCII_LIDVID	476
ASCII_LIDVID_LID	476
ASCII_MD5_Checksum	476
ASCII_NonNegative_Integer	476
ASCII_Numeric_Base16	477
ASCII_Numeric_Base2	477
ASCII_Numeric_Base8	477
ASCII_Real	477
ASCII_Short_String_Collapsed	478
ASCII_Short_String_Preserved	478
ASCII_String	478
ASCII_Text_Collapsed	478
ASCII_Text_Preserved	479
ASCII_Time	479
ASCII_VID	479
Binary_Data_Type	479
Character_Data_Type	480
Complex	480
ComplexLSB16	480
ComplexLSB8	480
ComplexMSB16	481
ComplexMSB8	481
Data_Type	481
Decimal_Integer	481
Decimal_Real	481
IEEE754LSBDouble	482
IEEE754LSBSingle	482
IEEE754MSBDouble	482
IEEE754MSBSingle	482
SignedBitString	483
SignedByte	483
SignedLSB2	483
SignedLSB4	483
SignedLSB8	483
SignedMSB2	484
SignedMSB4	484
SignedMSB8	484
UTF8_Short_String_Collapsed	484

UTF8_Short_String_Preserved	485
UTF8_String	485
UTF8_Text_Preserved	485
UnsignedBitString	485
UnsignedByte	485
UnsignedLSB2	486
UnsignedLSB4	486
UnsignedLSB8	486
UnsignedMSB2	486
UnsignedMSB4	487
UnsignedMSB8	487
13. Units of Measure in the common (pds) namespace.	488
Unit_Of_Measure	488
Units_of_Acceleration	488
Units_of_Amount_Of_Substance	488
Units_of_Angle	488
Units_of_Angular_Velocity	489
Units_of_Area	489
Units_of_Frame_Rate	489
Units_of_Frequency	489
Units_of_Length	489
Units_of_Map_Scale	490
Units_of_Mass	490
Units_of_Misc	490
Units_of_None	490
Units_of_Optical_Path_Length	491
Units_of_Pressure	491
Units_of_Radiance	491
Units_of_Rates	491
Units_of_Solid_Angle	491
Units_of_Spectral_Irradiance	492
Units_of_Spectral_Radiance	492
Units_of_Storage	492
Units_of_Temperature	493
Units_of_Time	493
Units_of_Velocity	493
Units_of_Voltage	493
Units_of_Volume	494
Units_of_Wavenumber	494

Chapter 1. Introduction

The Planetary Data System (PDS) PDS4 Data Dictionary defines the organization and components of PDS4 product labels. Components of a product label include classes and their attributes.

Audience

The PDS4 Data Dictionary - Abridged - has been abstracted from the unabridged version with the needs of data providers and data end users in mind. It contains full definitions but not all the fine detail or repetition necessary to support the underlying Information Model.

Acknowledgements

The PDS4 Data Dictionary and the PDS4 Information Model is a joint effort involving representatives from each of the PDS nodes functioning as the PDS4 Data Design Working Group.

Scope

The PDS4 Data Dictionary defines the common and discipline level classes and attributes used to create PDS4 product labels. It also defines the meta-attributes (i.e. attributes about attributes) used to define attributes. This abridged version includes only one entry for each attribute where the unabridged version includes an entry for each use of an attribute in a class.

Applicable Documents

Controlling Documents

- PDS4 Information Model Specification - The PDS4 Information Model is used as the source for class, attribute, and data type definitions. The model is presented in document format as the PDS4 Information Model Specification.
- ISO/IEC 11179:3 Registry Metamodel and Basic Attributes Specification, 2003. - The ISO/IEC 11179 specification provides the schema for the PDS4 data dictionary.

Reference Documents

- Planetary Science Data Dictionary - The online version of the PDS3 data dictionary was used as the source for a few data elements being carried over from the PDS3 data standards.

Terminology

This document uses very specific engineering terminology to describe the various structures involved. It is particularly important that readers who have absorbed the PDS Standards Reference bear in mind that terms which are familiar in that context can have very different meanings in the present document.

Following are some definitions of essential terms used throughout this document.

- An *attribute* is a property or characteristic that provides a unit of information. For example, color and length are possible attributes.
- A *class* is a set of attributes (including a name) which defines a family. A class is generic a template from which individual members of the family may be constructed.

- A *conceptual object* is an object which is intangible (and, because it is intangible, does not fit into a digital archive). Examples of conceptual objects include the Cassini mission and NASA's strategic plan for solar system exploration. Note that a PDF describing the Cassini mission is a digital object, not a conceptual object (nor a component of a conceptual object).
- A *data element* is a unit of data for which the definition, identification, representation and *permissible values* are specified by means of a set of attributes. For example, the concept of a *calibration_lamp_state_flag* is used in the PDS archive to indicate whether the lamp used for onboard camera calibration was turned on or off during the capture of an image. The *data element* aspect of this concept is the named attribute (or data element) *calibration_lamp_state_flag*.
- A *data object* is a physical, conceptual, or digital object.
- A *digital object* is an object which is real data for example, a binary image of a redwood tree or an ASCII table of atmospheric composition versus altitude.
- *Formal* as used in the definition of attributes that are names indicates that an established procedure was involved in creating the name.
- A *unique identifier* is a special type of identifier used to provide a reference number which is unique in a context.
- *Local* refers to the context within a single label.
- *Logical* as used in the definition of logical identifier indicates that the identifier logically groups a set of objects.
- A *physical object* is an object which is physical or tangible (and, therefore, does not itself fit into a digital archive). Examples of physical objects include the planet Saturn and the Venus Express magnetometer. Note that an ASCII file describing Saturn is a digital object, not a physical object (nor a component of a physical object).
- A *resource* is the target (referent) of any Uniform Resource Identifier; the thing to which a URI points.

Chapter 2. Product Classes in the common (pds) namespace.

These classes define the PDS4 products.

Ingest_LDD

Name: Ingest_LDD			Version Id: 1.0.0.0
<i>Description:</i> The Ingest_LDD class provides a form for collecting class and attribute definitions.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Ingest_LDD			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	ldd_version_id	1..1	None
	full_name	1..1	None
	steward_id	1..1	None
	namespace_id	1..1	None
	comment	0..1	None
	last_modification_date_time	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	local_attribute	1..Unbounded	DD_Attribute
	local_class	0..Unbounded	DD_Class
	local_rule	0..Unbounded	DD_Rule
<i>Referenced from:</i> None			

Product_AIP

Name: Product_AIP			Version Id: 1.n.0.0
<i>Description:</i> The Product AIP class defines a product for the Archival Information Package.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_AIP			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	has_Information_Package_Component	1..Unbounded	Information_Package_Component
	product_data_object	1..1	Archival_Information_Package
<i>Referenced from:</i> None			

Product_Attribute_Definition

Name: Product_Attribute_Definition			Version Id: 1.0.0.0
<i>Description:</i> The Product Attribute Definition provides an attribute definition in XML encoding.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Attribute_Definition			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	DD_Attribute_Full
<i>Referenced from:</i> None			

Product_Browse

Name: Product_Browse			Version Id: 1.0.0.0
<i>Description:</i> The Product Browse class defines a product consisting of one encoded byte stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Browse			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..Unbounded	File_Area_Browse
<i>Referenced from:</i> None			

Product_Bundle

Name: Product_Bundle			Version Id: 1.0.0.0
<i>Description:</i> A Product_Bundle is an aggregate product and has a table of references to one or more collections.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Bundle			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	context_area	0..1	Context_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Bundle
	file_area	0..1	File_Area_Text
	member_entry	1..Unbounded	Bundle_Member_Entry
<i>Referenced from:</i> None			

Product_Class_Definition

Name: Product_Class_Definition			Version Id: 1.0.0.0
<i>Description:</i> The Product Class Definition provides a class definition in XML encoding.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Class_Definition			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	DD_Class_Full
<i>Referenced from:</i> None			

Product_Collection

Name: Product_Collection			Version Id: 1.0.0.0
<i>Description:</i> A Product_Collection has a table of references to one or more basic products. The references are stored in a table called the inventory.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Collection			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	context_area	0..1	Context_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Collection
	file_area_inventory	1..1	File_Area_Inventory
<i>Referenced from:</i> None			

Product_Context

Name: Product_Context			Version Id: 1.0.0.0
<i>Description:</i> The Product Context class describes something that provides context and provenance for an observational product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Context			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	has_discipline_area	0..1	Discipline_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Agency, Facility, Instrument, Instrument_Host,

Product Classes in the
common (pds) namespace.

Name: Product_Context			Version Id: 1.0.0.0
			Investigation, Node, Other, PDS_Affiliate, PDS_Guest, Resource, Target, Telescope
<i>Referenced from:</i> None			

Product_DIP

Name: Product_DIP			Version Id: 1.n.0.0
<i>Description:</i> The Product DIP class defines a product for the Dissemination Information Package.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_DIP			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	has_Information_Package_Component	1..Unbounded	Information_Package_Component
	product_data_object	1..1	Dissemination_Information_Package
<i>Referenced from:</i> None			

Product_DIP_Deep_Archive

Name: Product_DIP_Deep_Archive			Version Id: 1.1.0.0
<i>Description:</i> The Product DIP_Deep_Archive class defines a product for the Dissemination Information Package for the deep archive.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_DIP_Deep_Archive			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	has_Information_Package_Component	1..Unbounded	Information_Package_Component
	product_data_object	1..1	DIP_Deep_Archive
<i>Referenced from:</i> None			

Product_Data_Set_PDS3

Name: Product_Data_Set_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Data Set PDS3 product is used to create proxy labels for the data sets in the PDS3 Data Set catalog.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active

Name: Product_Data_Set_PDS3			Version Id: 1.0.0.0
<i>Class Hierarchy:</i> Product :: Product_Data_Set_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Data_Set_PDS3
<i>Referenced from:</i> None			

Product_Document

Name: Product_Document			Version Id: 1.0.0.0
<i>Description:</i> A Product Document is a product consisting of a single logical document that may be comprised of one or more document formats.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Document			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	context_area	0..1	Context_Area
	reference_list	0..1	Reference_List
	product_description	1..1	Document
	document_format_set	1..Unbounded	Document_Format_Set
<i>Referenced from:</i> None			

Product_File_Repository

Name: Product_File_Repository			Version Id: 1.0.0.0
<i>Description:</i> The Product File Repository class consists of a single text file. This product is used to register a file in a repository.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_File_Repository			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..1	File_Area_Binary
<i>Referenced from:</i> None			

Product_File_Text

Name: Product_File_Text			Version Id: 1.0.0.0
<i>Description:</i> The Product File Text consists of a single text file with ASCII character encoding.			

Name: Product_File_Text			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_File_Text			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..1	File_Area_Text
<i>Referenced from:</i> None			

Product_Instrument_Host_PDS3

Name: Product_Instrument_Host_PDS3			Version Id: 1.0.0.0
<i>Description:</i> An Instrument Host product describes an instrument host. This product captures the PDS3 catalog instrument host information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Instrument_Host_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Instrument_Host_PDS3
<i>Referenced from:</i> None			

Product_Instrument_PDS3

Name: Product_Instrument_PDS3			Version Id: 1.0.0.0
<i>Description:</i> An Instrument product describes an instrument. This product captures the PDS3 catalog instrument information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Instrument_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Instrument_PDS3
<i>Referenced from:</i> None			

Product_Mission_PDS3

Name: Product_Mission_PDS3			Version Id: 1.0.0.0
<i>Description:</i> An Mission product describes a mission. This product captures the PDS3 catalog mission information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active

Name: Product_Mission_PDS3			Version Id: 1.0.0.0
<i>Class Hierarchy:</i> Product :: Product_Mission_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Mission_PDS3
<i>Referenced from:</i> None			

Product_Native

Name: Product_Native			Version Id: 1.2.0.0
<i>Description:</i> Product_Native is used to describe digital objects in the original format returned by the spacecraft or experimental system when that format cannot be described using one of the PDS4 formats specified for observational data (tables or arrays, excluding Array_1D).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Native			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	context_area	0..1	Context_Area
	reference_list	0..1	Reference_List
	file_area	1..Unbounded	File_Area_Native
<i>Referenced from:</i> None			

Product_Observational

Name: Product_Observational			Version Id: 1.0.0.0
<i>Description:</i> A Product_Observational is a set of one or more information objects produced by an observing system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Observational			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	observation_area	1..1	Observation_Area
	reference_list	0..1	Reference_List
	file_area	1..Unbounded	File_Area_Observational
	file_area_supplemental	0..Unbounded	File_Area_Observational_Supplemental
<i>Referenced from:</i> None			

Product_Proxy_PDS3

Name: Product_Proxy_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Product Proxy PDS3 class defines a product with enough information to register a PDS3 data product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Proxy_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..Unbounded	File_Area_Binary
<i>Referenced from:</i> None			

Product_SIP

Name: Product_SIP			Version Id: 1.1.0.0
<i>Description:</i> The Product SIP class defines a product for the Submission Information Package.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_SIP			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	has_Information_Package_Component	1..Unbounded	Information_Package_Component
	product_data_object	1..1	Submission_Information_Package
<i>Referenced from:</i> None			

Product_SPICE_Kernel

Name: Product_SPICE_Kernel			Version Id: 1.0.0.0
<i>Description:</i> The Product SPICE Kernel class defines a SPICE kernel product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_SPICE_Kernel			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	context_area	1..1	Context_Area
	reference_list	0..1	Reference_List
	file_area	1..1	File_Area_SPICE_Kernel
<i>Referenced from:</i> None			

Product_Service

Name: Product_Service			Version Id: 1.0.0.0
<i>Description:</i> The Product Service class defines a product for registering services. Service descriptions from this product are used to register services as intrinsic registry objects.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Service			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	0..Unbounded	File_Area_Service_Description
<i>Referenced from:</i> None			

Product_Software

Name: Product_Software			Version Id: 1.0.0.0
<i>Description:</i> Product Software is a product consisting of a set of one or more software formats.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Software			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_description	1..1	Software
	software_format_set	0..Unbounded	Software_Binary, Software_Script, Software_Source
<i>Referenced from:</i> None			

Product_Subscription_PDS3

Name: Product_Subscription_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Product_Subscription_PDS3 class provides the list of subscriptions for a PDS3 subscriber.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Subscription_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	subscriber	1..1	Subscriber_PDS3
<i>Referenced from:</i> None			

Product_Target_PDS3

Name: Product_Target_PDS3			Version Id: 1.0.0.0
<i>Description:</i> A target product describes a target. This product captures a reduced set of the PDS3 catalog target information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Target_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Target_PDS3
<i>Referenced from:</i> None			

Product_Thumbnail

Name: Product_Thumbnail			Version Id: 1.0.0.0
<i>Description:</i> The Product Thumbnail class defines a product consisting of one encoded byte stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Thumbnail			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..1	File_Area_Encoded_Image
<i>Referenced from:</i> None			

Product_Update

Name: Product_Update			Version Id: 1.0.0.0
<i>Description:</i> The Product Update class defines a product consisting of update information and optional references to other products.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Update			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Update
<i>Referenced from:</i> None			

Product_Volume_PDS3

Name: Product_Volume_PDS3			Version Id: 1.0.0.0
<i>Description:</i> A Product Volume PDS3 product captures the PDS3 volume information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Volume_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Volume_PDS3
<i>Referenced from:</i> None			

Product_Volume_Set_PDS3

Name: Product_Volume_Set_PDS3			Version Id: 1.0.0.0
<i>Description:</i> A Product Volume Set PDS3 product captures the PDS3 volume set information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Volume_Set_PDS3			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	product_data_object	1..1	Volume_Set_PDS3
<i>Referenced from:</i> None			

Product_XML_Schema

Name: Product_XML_Schema			Version Id: 1.0.0.0
<i>Description:</i> The Product_XML_Schema describes a resource used for the PDS4 implementation into XML.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_XML_Schema			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	reference_list	0..1	Reference_List
	file_area	1..Unbounded	File_Area_XML_Schema
<i>Referenced from:</i> None			

Product_Zipped

Name: Product_Zipped		Version Id: 1.0.0.0	
<i>Description:</i> The Product_Zipped is a product with references to other products. The referenced products and all associated products and files are packaged into a single ZIP file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product :: Product_Zipped			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
	internal_reference	1..Unbounded	Internal_Reference
	has_zip	1..1	Zip
	file	1..1	File
<i>Referenced from:</i> None			

Chapter 3. Support classes in the common (pds) namespace.

The classes in this section are used by the product classes.

Agency

Name: Agency			Version Id: 1.0.0.0
<i>Description:</i> The Agency class provides a description of an entity that provides regional or national level governance over nodes within the federated Planetary Data System.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Agency			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	European Space Agency, National Aeronautics and Space Administration
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Context			

Alias

Name: Alias			Version Id: 1.0.0.0
<i>Description:</i> The Alias class provides a single alternate name and identification for this product in this or some other archive or data system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Alias			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	alternate_id	0..1	None
	alternate_title	0..1	None
	comment	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Alias_List			

Alias_List

Name: Alias_List			Version Id: 1.0.0.0
<i>Description:</i> The Alias_List class provides a list of paired alternate names and identifications for this product in this or some other archive or data system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Alias_List			

Support classes in the
common (pds) namespace.

Name: Alias_List			Version Id: 1.0.0.0
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	alias	1..Unbounded	Alias
<i>Referenced from: Identification_Area</i>			

Archival_Information_Package

Name: Archival_Information_Package			Version Id: 1.n.0.0
<i>Description:</i> The Archival Information Package (AIP) class defines an Information Package consisting of the Content Information and the associated Preservation Description Information (PDI), which is preserved within an archive that conforms to the Open Archive Information System (OAIS) Reference Model.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package :: Archival_Information_Package			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from: Product_AIP</i>			

Array

Name: Array			Version Id: 1.0.0.0
<i>Description:</i> The Array class defines a homogeneous N-dimensional array of scalars. The Array class is the parent class for all n-dimensional arrays of scalars.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	None
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	0..Unbounded	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from: None</i>			

Array_1D

Name: Array_1D			Version Id: 1.0.0.0
<i>Description:</i> The Array 1D class is the parent class for all one dimensional array based classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_1D			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	1
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	1..1	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_2D

Name: Array_2D			Version Id: 1.0.0.0
<i>Description:</i> The Array 2D class is the parent class for all two dimensional array based classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_2D			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	2
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	2..2	Axis_Array
	associated_Special_Constants	0..1	Special_Constants

Support classes in the
common (pds) namespace.

Name: Array_2D			Version Id: 1.0.0.0
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_ reference	0..Unbounded	Local_Internal_ Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_2D_Image

Name: Array_2D_Image			Version Id: 1.0.0.0
<i>Description:</i> The Array 2D Image class is an extension of the Array 2D class and defines a two dimensional image.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_2D :: Array_2D_Image			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	2
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	2..2	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_ reference	0..Unbounded	Local_Internal_ Reference
	has_Display_2d_Image	0..1	Display_2D_Image *Deprecated*
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_2D_Map

Name: Array_2D_Map			Version Id: 1.1.0.0
<i>Description:</i> The Array 2D Map class is an extension of the Array 2D class and defines a two dimensional map.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_2D :: Array_2D_Map			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None

Name: Array_2D_Map			Version Id: 1.1.0.0
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	2
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	2..2	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
	has_Display_2d_Image	0..1	Display_2D_Image *Deprecated*
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_2D_Spectrum

Name: Array_2D_Spectrum			Version Id: 1.1.0.0
<i>Description:</i> The Array 2D Spectrum class is an extension of the Array 2D class and defines a two dimensional spectrum.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_2D :: Array_2D_Spectrum			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	2
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	2..2	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference

Support classes in the
common (pds) namespace.

Name: Array_2D_Spectrum			Version Id: 1.1.0.0
	has_Display_2d_Image	0..1	Display_2D_Image *Deprecated*
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_3D

Name: Array_3D			Version Id: 1.0.0.0
<i>Description:</i> The Array 3D class is the parent class for all three dimensional array based classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_3D			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	3
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	3..3	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_3D_Image

Name: Array_3D_Image			Version Id: 1.1.0.0
<i>Description:</i> The Array 3D Image class is an extension of the Array 3D class and defines a three dimensional image.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_3D :: Array_3D_Image			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	3
	axis_index_order	1..1	Last Index Fastest

Support classes in the
common (pds) namespace.

Name: Array_3D_Image			Version Id: 1.1.0.0
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	3..3	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_3D_Movie

Name: Array_3D_Movie			Version Id: 1.n.0.0
<i>Description:</i> The Array 3D Movie class is an extension of the Array 3D class and defines a movie as a set of two dimensional images in a time series.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_3D :: Array_3D_Movie			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	3
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	3..3	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Array_3D_Spectrum

Name: Array_3D_Spectrum			Version Id: 1.0.0.0
<i>Description:</i> The Array 3D Spectrum class is an extension of the Array 3D class and defines a three dimensional spectrum.			

Support classes in the
common (pds) namespace.

Name: Array_3D_Spectrum			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Array :: Array_3D :: Array_3D_Spectrum			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	axes	1..1	3
	axis_index_order	1..1	Last Index Fastest
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Element_Array	1..1	Element_Array
	has_Axis_Array	3..3	Axis_Array
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Object_Statistics
	data_object	1..1	Digital_Object
	local_internal_reference	0..Unbounded	Local_Internal_Reference
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Axis_Array

Name: Axis_Array			Version Id: 1.0.0.0
<i>Description:</i> The Axis Array class is used as a component of the array class and defines an axis of the array.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Axis_Array			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	axis_name	1..1	None
	local_identifier	0..1	None
	elements	1..1	None
	unit *Deprecated*	0..1	None
	sequence_number	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Band_Bin_Set	0..1	Band_Bin_Set *Deprecated*
<i>Referenced from:</i> Array_2D_Image, Array_2D_Spectrum, Array_3D_Image, Array, Array_2D, Array_3D, Array_3D_Spectrum, Array_3D_Movie, Array_2D_Map, Array_1D			

Band_Bin *Deprecated*

Name: Band_Bin *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The Band_Bin class specifies the characteristics of an individual spectral band in a spectral cube.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Deprecated
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Band_Bin *Deprecated*			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	band_number	1..1	None
	band_width	1..1	None
	center_wavelength	1..1	None
	detector_number	0..1	None
	filter_number	0..1	None
	grating_position	0..1	None
	original_band	0..1	None
	standard_deviation	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Band_Bin_Set *Deprecated*			

Band_Bin_Set *Deprecated*

Name: Band_Bin_Set *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The Band_Bin_Set class contains the spectral characteristics for all the spectral bands in a cube.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Deprecated
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Band_Bin_Set *Deprecated*			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_band_bin	1..Unbounded	Band_Bin *Deprecated*
<i>Referenced from:</i> Axis_Array			

Bundle

Name: Bundle			Version Id: 1.0.0.0
<i>Description:</i> The Bundle class describes a collection of collections.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Bundle			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	bundle_type	1..1	Archive, Supplemental
	description	0..1	None

Support classes in the
common (pds) namespace.

Name: Bundle			Version Id: 1.0.0.0
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Bundle			

Bundle_Member_Entry

Name: Bundle_Member_Entry			Version Id: 1.0.0.0
<i>Description:</i> The Bundle Member Entry class provides a member reference to a collection.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Bundle_Member_Entry			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	lid_reference	0..1	None
	lidvid_reference	0..1	None
	member_status	1..1	Primary, Secondary
	reference_type	1..1	bundle_has_browse_collection, bundle_has_calibration_collection, bundle_has_context_collection, bundle_has_data_collection, bundle_has_document_collection, bundle_has_geometry_collection, bundle_has_member_collection, bundle_has_schema_collection, bundle_has_spice_kernel_collection
<i>No Associations</i>			
<i>Referenced from:</i> Product_Bundle			

Byte_Stream

Name: Byte_Stream			Version Id: 1.0.0.0
<i>Description:</i> The Byte Stream class defines a stream of bytes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Checksum_Manifest

Name: Checksum_Manifest			Version Id: 1.0.0.0
<i>Description:</i> The Checksum_Manifest class defines a two column table for file references and checksums. The table structure is compatible with the output from an MD5 checksum utility.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Stream_Text :: Checksum_Manifest			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	MD5Deep 4.n
	description	0..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Checksum_Manifest			

Citation_Information

Name: Citation_Information			Version Id: 1.0.0.0
<i>Description:</i> The Citation_Information class provides specific fields often used in citing the product in journal articles, abstract services, and other reference contexts.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Citation_Information			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	author_list	0..1	None
	editor_list	0..1	None
	publication_year	1..1	None
	keyword	0..Unbounded	None
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Identification_Area			

Collection

Name: Collection			Version Id: 1.0.0.0
<i>Description:</i> The Collection class provides a description of a set of products.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Collection			

Support classes in the
common (pds) namespace.

Name: Collection			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	collection_type	1..1	Browse, Calibration, Context, Data, Document, Geometry, Miscellaneous, SPICE Kernel, XML Schema
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Product_Collection			

Conceptual_Object

Name: Conceptual_Object			Version Id: 1.0.0.0
<i>Description:</i> The Conceptual Object class defines a non-tangible object that is also not a digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Data_Object :: Conceptual_Object			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> Update, Vector, Object_Statistics, Quaternion, Volume_PDS3, Investigation, Other, Data_Set_PDS3, DD_Class, Geometry, Bundle, DD_Attribute, Volume_Set_PDS3, Field_Statistics, Resource, DD_Attribute_Full, Observing_System, Agency, Node, Ingest_LDD, DD_Class_Full, Mission_PDS3			

Context_Area

Name: Context_Area			Version Id: 1.0.0.0
<i>Description:</i> The Context Area provides context information for a product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Context_Area			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	comment	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_time_coordinates	0..1	Time_Coordinates
	has_primary_result_description	0..1	Primary_Result_Summary
	has_investigation_area	0..Unbounded	Investigation_Area
	has_observing_system	0..Unbounded	Observing_System
	has_target_identification	0..Unbounded	Target_Identification
	has_mission_area	0..1	Mission_Area
	has_discipline_area	0..1	Discipline_Area
<i>Referenced from:</i> Product_SPICE_Kernel, Product_Native, Product_Collection, Product_Document, Product_Bundle			

DD_Association

Name: DD_Association			Version Id: 1.0.0.0
<i>Description:</i> The DD_Association class defines the association between two classes or a class and an attribute in a data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Association			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	1..Unbounded	None
	reference_type	1..1	attribute_of, component_of, extension_of, parent_of, restriction_of, subclass_of
	minimum_occurrences	1..1	None
	maximum_occurrences	1..1	None
	constant_value	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> DD_Class, DD_Class_Full			

DD_Association_External *Deprecated*

Name: DD_Association_External *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The DD_Association_External class defines the association between classes and attributes within the local data dictionary and those external to the local data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Deprecated
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Association_External *Deprecated*			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	namespace_id	1..1	None
	reference_type	1..1	attribute_of, component_of, extension_of, parent_of, restriction_of, subclass_of
	minimum_occurrences	1..1	None
	maximum_occurrences	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> DD_Class			

DD_Attribute

Name: DD_Attribute			Version Id: 1.0.0.0
<i>Description:</i> The DD_Attribute class defines an attribute for a data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Attribute			

Support classes in the
common (pds) namespace.

Name: DD_Attribute			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	version_id	1..1	None
	local_identifier	1..1	None
	nillable_flag	1..1	None
	submitter_name	1..1	None
	definition	1..1	None
	comment	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..Unbounded	Internal_Reference
	data_object	1..1	Conceptual_Object
	terminological_entry	0..Unbounded	Terminological_Entry
	value_domain_entry	1..1	DD_Value_Domain
<i>Referenced from:</i> Ingest_LDD			

DD_Attribute_Full

Name: DD_Attribute_Full			Version Id: 1.0.0.0
<i>Description:</i> The DD_Attribute_Full class provides a more complete definition of an attribute in the data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Attribute_Full			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	version_id	1..1	None
	class_name	1..1	None
	local_identifier	1..1	None
	steward_id	1..1	atm, geo, img, naif, ops, pds, ppi, rings, rs, sbn
	type	1..1	PDS3, PDS4
	namespace_id	1..1	None
	nillable_flag	1..1	None
	submitter_name	1..1	None
	definition	1..1	None
	comment	0..1	None
	registered_by	1..1	None
	registration_authority_id	1..1	0001_NASA_PDS_1
	attribute_concept	1..1	Address, Angle, Attribute, Bit, Checksum, Collection, Constant, Cosine, Count, DOI, Delimiter,

Support classes in the
common (pds) namespace.

Name: DD_Attribute_Full			Version Id: 1.0.0.0
			Description, Deviation, Direction, Distance, Duration, Factor, Flag, Format, Group, Home, ID, Latitude, Length, List, Location, Logical, Longitude, Mask, Maximum, Mean, Median, Minimum, Name, Note, Number, Offset, Order, Parallel, Password, Path, Pattern, Pixel, Quaternion, Radius, Ratio, Reference, Resolution, Role, Rotation, Scale, Sequence, Set, Size, Status, Summary, Syntax, Temperature, Text, Title, Type, Unit, Unknown, Value, Vector
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	terminological_entry	1..Unbounded	Terminological_Entry
	value_domain_entry	0..1	DD_Value_Domain_Full
<i>Referenced from: Product_Attribute_Definition</i>			

DD_Class

Name: DD_Class			Version Id: 1.0.0.0
<i>Description:</i> The DD_Class class defines a class for a data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Class			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	version_id	1..1	None
	local_identifier	1..1	None
	submitter_name	1..1	None
	definition	1..1	None
	abstract_flag	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..Unbounded	Internal_Reference
	data_object	1..1	Conceptual_Object

Support classes in the
common (pds) namespace.

Name: DD_Class			Version Id: 1.0.0.0
	dd_association	1..Unbounded	DD_Association, DD_Association_External *Deprecated*
	terminological_entry	0..Unbounded	Terminological_Entry
<i>Referenced from:</i> Ingest_LDD			

DD_Class_Full

Name: DD_Class_Full			Version Id: 1.0.0.0
<i>Description:</i> The DD_Class_Full class provides a more complete definition of a class for a data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Class_Full			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	version_id	1..1	None
	local_identifier	1..1	None
	steward_id	1..1	atm, geo, img, naif, ops, pds, ppi, rings, rs, sbn
	type	1..1	PDS3, PDS4
	namespace_id	1..1	None
	submitter_name	1..1	None
	definition	1..1	None
	comment	0..1	None
	registered_by	1..1	None
	registration_authority_id	1..1	None
	abstract_flag	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	dd_association	0..Unbounded	DD_Association
	terminological_entry	0..Unbounded	Terminological_Entry
<i>Referenced from:</i> Product_Class_Definition			

DD_Permissible_Value

Name: DD_Permissible_Value			Version Id: 1.0.0.0
<i>Description:</i> The DD_Permissible_Value class lists permissible values and their meanings.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Permissible_Value			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	value	1..1	None

Support classes in the
common (pds) namespace.

Name: DD_Permissible_Value			Version Id: 1.0.0.0
	value_meaning	1..1	None
<i>No Associations</i>			
<i>Referenced from: DD_Value_Domain</i>			

DD_Permissible_Value_Full

Name: DD_Permissible_Value_Full			Version Id: 1.0.0.0
<i>Description:</i> The DD_Permissible_Value_Full class lists permissible values, their meanings, and the dates when active.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Permissible_Value_Full			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	value	1..1	None
	value_meaning	0..1	None
	value_begin_date	1..1	None
	value_end_date	1..1	None
<i>No Associations</i>			
<i>Referenced from: DD_Value_Domain_Full</i>			

DD_Rule

Name: DD_Rule			Version Id: 1.0.0.0
<i>Description:</i> The DD_Rule class defines a Schematron rule for a data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Rule			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	1..1	None
	rule_context	1..1	None
	rule_assign	0..Unbounded	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	rule_statement	1..Unbounded	DD_Rule_Statement
<i>Referenced from: Ingest_LDD</i>			

DD_Rule_Statement

Name: DD_Rule_Statement			Version Id: 1.0.0.0
<i>Description:</i> The DD_Rule_Statement class defines a Schematron rule statement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: DD_Rule_Statement			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	rule_type	1..1	Assert, Assert Every, Assert If, Report
	rule_test	1..1	None

Support classes in the
common (pds) namespace.

Name: DD_Rule_Statement			Version Id: 1.0.0.0
	rule_message	1..1	None
	rule_description	0..1	None
	rule_value	0..Unbounded	None
<i>No Associations</i>			
<i>Referenced from:</i> DD_Rule			

DD_Value_Domain

Name: DD_Value_Domain			Version Id: 1.0.0.0
<i>Description:</i> The DD_Value_Domain class defines an attribute's permissible values and their constraints.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Value_Domain			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	enumeration_flag	1..1	None
	value_data_type	1..1	ASCII_AnyURI, ASCII_Boolean, ASCII_DOI, ASCII_Date_DOY, ASCII_Date_Time, ASCII_Date_Time_DOY, ASCII_Date_Time_UTC, ASCII_Date_Time_YMD, ASCII_Date_YMD, ASCII_Directory_Path_Name, ASCII_File_Name, ASCII_File_Specification_Name, ASCII_Integer, ASCII_LID, ASCII_LIDVID, ASCII_LIDVID_LID, ASCII_MD5_Checksum, ASCII_NonNegative_Integer, ASCII_Numeric_Base16, ASCII_Numeric_Base2, ASCII_Numeric_Base8, ASCII_Real, ASCII_Short_String_Collapsed, ASCII_Short_String_Preserved, ASCII_Text_Collapsed, ASCII_Text_Preserved, ASCII_Time, ASCII_VID, UTF8_Short_String_Collapsed, UTF8_Short_String_Preserved, UTF8_

Support classes in the
common (pds) namespace.

Name: DD_Value_Domain			Version Id: 1.0.0.0
			Text_Preserved, Vector_Cartesian_3, Vector_Cartesian_3_Acceleration, Vector_Cartesian_3_Pointing, Vector_Cartesian_3_Position, Vector_Cartesian_3_Velocity
	formation_rule	0..1	None
	minimum_characters	0..1	None
	maximum_characters	0..1	None
	minimum_value	0..1	None
	maximum_value	0..1	None
	pattern	0..1	None
	unit_of_measure_type	0..1	Units_of_Acceleration, Units_of_Amount_Of_Substance, Units_of_Angle, Units_of_Angular_Velocity, Units_of_Area, Units_of_Frame_Rate, Units_of_Frequency, Units_of_Length, Units_of_Map_Scale, Units_of_Mass, Units_of_Misc, Units_of_None, Units_of_Optical_Path_Length, Units_of_Pressure, Units_of_Radiance, Units_of_Rates, Units_of_Solid_Angle, Units_of_Spectral_Irradiance, Units_of_Spectral_Radiance, Units_of_Storage, Units_of_Temperature, Units_of_Time, Units_of_Velocity, Units_of_Voltage, Units_of_Volume, Units_of_Wavenumber
	specified_unit_id	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	permissible_value	0..Unbounded	DD_Permissible_Value
<i>Referenced from: DD_Attribute</i>			

DD_Value_Domain_Full

Name: DD_Value_Domain_Full			Version Id: 1.0.0.0
<i>Description:</i> The DD_Value_Domain_Full class provides a more complete definition of a attribute's value domain.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: DD_Value_Domain_Full			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	enumeration_flag	1..1	None
	value_data_type	1..1	ASCII_AnyURI, ASCII_Boolean, ASCII_DOI, ASCII_Date_DOY, ASCII_Date_Time, ASCII_Date_Time_DOY, ASCII_Date_Time_UTC, ASCII_Date_Time_YMD, ASCII_Date_YMD, ASCII_Directory_Path_Name, ASCII_File_Name, ASCII_File_Specification_Name, ASCII_Integer, ASCII_LID, ASCII_LIDVID, ASCII_LIDVID_LID, ASCII_MD5_Checksum, ASCII_NonNegative_Integer, ASCII_Numeric_Base16, ASCII_Numeric_Base2, ASCII_Numeric_Base8, ASCII_Real, ASCII_Short_String_Collapsed, ASCII_Short_String_Preserved, ASCII_Text_Collapsed, ASCII_Text_Preserved, ASCII_Time, ASCII_VID, UTF8_Short_String_Collapsed, UTF8_Short_String_Preserved, UTF8_Text_Preserved
	formation_rule	0..1	None
	minimum_characters	0..1	None
	maximum_characters	0..1	None
	minimum_value	0..1	None
	maximum_value	0..1	None

Name: DD_Value_Domain_Full			Version Id: 1.0.0.0
	pattern	0..1	None
	unit_of_measure_type	0..1	Units_of_Amount_of_Substance, Units_of_Angle, Units_of_Angular_Velocity, Units_of_Area, Units_of_Frame_Rate, Units_of_Frequency, Units_of_Length, Units_of_Map_Scale, Units_of_Mass, Units_of_Misc, Units_of_None, Units_of_Optical_Path_Length, Units_of_Pressure, Units_of_Radiance, Units_of_Rates, Units_of_Solid_Angle, Units_of_Spectral_Irradiance, Units_of_Spectral_Radiance, Units_of_Storage, Units_of_Temperature, Units_of_Time, Units_of_Velocity, Units_of_Voltage, Units_of_Volume, Units_of_Wavenumber
	conceptual_domain	1..1	Boolean, Integer, Name, Numeric, Real, Short_String, Text, Time, Type, Unknown
	specified_unit_id	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	permissible_value	0..Unbounded	DD_Permissible_Value_Full
<i>Referenced from: DD_Attribute_Full</i>			

DIP_Deep_Archive

Name: DIP_Deep_Archive			Version Id: 1.1.0.0
<i>Description:</i> The Dissemination Information Package Deep Archive class is an Information Package derived from one or more AIPs and is received by the National Space Science Data Center (NSSDC).			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package :: DIP_Deep_Archive			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	description	1..1	None
<i>No Associations</i>			

Support classes in the
common (pds) namespace.

Name: DIP_Deep_Archive	Version Id: 1.1.0.0
<i>Referenced from:</i> Product_DIP_Deep_Archive	

Data_Object

Name: Data_Object	Version Id: 1.0.0.0		
<i>Description:</i> The Data_Object class defines a thing about which almost nothing is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Data_Object			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Digital_Object

Name: Digital_Object	Version Id: 1.0.0.0		
<i>Description:</i> The Digital Object class defines a sequence of digital bits.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Data_Object :: Digital_Object			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	bit_string	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Encoded_Byte_Stream, XML_Schema, Stream_Text, Array_2D_Image, Array_2D_Spectrum, Service_Description, Table_Binary, Header, Table_Character, Software_Source, Array_3D_Image, Array, Checksum_Manifest, Software_Script, Transfer_Manifest, File, Document_File, Encoded_Header, Document, Encoded_Binary, Parsable_Byte_Stream, Encoded_Native, Array_2D, Table_Base, Table_Delimited, Array_3D, Encoded_Image, Inventory, Array_3D_Spectrum, Software, Array_3D_Movie, Array_2D_Map, SPICE_Kernel, Array_1D, Software_Binary			

Discipline_Area

Name: Discipline_Area	Version Id: 1.0.0.0		
<i>Description:</i> The Discipline area allows the insertion of discipline specific metadata.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Discipline_Area			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> Context_Area, Observation_Area, Product_Context			

Discipline_Facets

Name: Discipline_Facets	Version Id: 1.1.0.0
<i>Description:</i> The Discipline_Facets class contains the discipline-related search facets. It is required and may not be repeated. Note that Science_Facets was modeled with Discipline_Facets as	

Support classes in the common (pds) namespace.

Name: Discipline_Facets			Version Id: 1.1.0.0
a component and Discipline_Facets was modeled with Group_Facet1 and Group_Facet2 as components. This dependency hierarchy was flattened and only Science_Facets exists in the schema.			
Namespace Id: pds	Steward: pds	Role: concrete	Status: Active
Class Hierarchy: Product_Components :: Discipline_Facets			
Attribute(s)	Name	Cardinality	Value
	discipline_name	1..1	Atmospheres, Fields, Flux Measurements, Imaging, Particles, Ring-Moon Systems, Small Bodies, Spectroscopy
Association(s)	Name	Cardinality	Class
	has_Group_Facet1	0..Unbounded	Group_Facet1
	has_Group_Facet2	0..Unbounded	Group_Facet2
Referenced from: Science_Facets			

Display_2D_Image *Deprecated*

Name: Display_2D_Image *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The Display_2D_Image class provides attributes to enable the display of a 2 dimensional image.			
Namespace Id: pds	Steward: pds	Role: concrete	Status: Deprecated
Class Hierarchy: Tagged_NonDigital_Object :: TNDO_Supplemental :: Display_2D_Image *Deprecated*			
Attribute(s)	Name	Cardinality	Value
	line_display_direction	1..1	Down, Up
	sample_display_direction	1..1	Right
No Associations			
Referenced from: Array_2D_Image, Array_2D_Spectrum, Array_2D_Map			

Dissemination_Information_Package

Name: Dissemination_Information_Package			Version Id: 1.n.0.0
<i>Description:</i> The Dissemination Information Package (DIP) class defines an Information Package, derived from one or more AIPs, that is received by a consumer.			
Namespace Id: pds	Steward: ops	Role: concrete	Status: Active
Class Hierarchy: Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package :: Dissemination_Information_Package			
Attribute(s)	Name	Cardinality	Value
	description	1..1	None
No Associations			
Referenced from: Product_DIP			

Document

Name: Document			Version Id: 1.0.0.0
<i>Description:</i> The Document class describes a document.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Document			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	revision_id	0..1	None
	document_name	0..1	None
	doi	0..1	None
	author_list	0..1	None
	editor_list	0..1	None
	acknowledgement_text	0..1	None
	copyright	0..1	None
	publication_date	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Product_Document			

Document_File

Name: Document_File			Version Id: 1.0.0.0
<i>Description:</i> The Document File class describes a file which is a part of a document.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: File :: Document_File			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	file_name	1..1	None
	local_identifier	0..1	None
	creation_date_time	0..1	None
	file_size	0..1	None
	records	0..1	None
	md5_checksum	0..1	None
	comment	0..1	None
	directory_path_name	0..1	None
	document_standard_id	1..1	7-Bit ASCII Text, Encapsulated Postscript, GIF, HTML 2.0, HTML 3.2, HTML 4.0, HTML 4.01, JPEG, LaTEX, Microsoft Word, PDF, PDF/A, PNG, Postscript, Rich Text, TIFF, UTF-8 Text

Support classes in the common (pds) namespace.

Name: Document_File			Version Id: 1.0.0.0
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Document_Format_Set			

Document_Format

Name: Document_Format			Version Id: 1.0.0.0
<i>Description:</i> The Document Format provides a description of a variant of a logical document that is stored in a specific format. For example the PDS Standards Reference has HTML and PDF formatted versions.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Document_Format			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	starting_point_identifier	0..1	None
	format_type	1..1	Multiple File, Single File, multiple file, single file
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Document_Format_Set			

Document_Format_Set

Name: Document_Format_Set			Version Id: 1.0.0.0
<i>Description:</i> The Document Format Set class is a set consisting of a document format and associated files.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Document_Format_Set			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	document_format	1..1	Document_Format
	document_file	1..Unbounded	Document_File
<i>Referenced from:</i> Product_Document			

Element_Array

Name: Element_Array			Version Id: 1.0.0.0
<i>Description:</i> The Element Array class is used as a component of the array class and defines an element of the array.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Element_Array			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	data_type	1..1	ComplexLSB16, ComplexLSB8,

Name: Element_Array			Version Id: 1.0.0.0
			ComplexMSB16, ComplexMSB8, IEEE754LSBDouble, IEEE754LSBSingle, IEEE754MSBDouble, IEEE754MSBSingle, SignedBitString, SignedByte, SignedLSB2, SignedLSB4, SignedLSB8, SignedMSB2, SignedMSB4, SignedMSB8, UnsignedBitString, UnsignedByte, UnsignedLSB2, UnsignedLSB4, UnsignedLSB8, UnsignedMSB2, UnsignedMSB4, UnsignedMSB8
	unit	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Array_2D_Image, Array_2D_Spectrum, Array_3D_Image, Array, Array_2D, Array_3D, Array_3D_Spectrum, Array_3D_Movie, Array_2D_Map, Array_1D			

Encoded_Binary

Name: Encoded_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Encoded Binary class describes a binary encoded byte stream. This class is used to describe files in the repository that are being registered using Product_File_Repository.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Encoded_Byte_Stream :: Encoded_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	encoding_standard_id	1..1	CCSDS Space Communications Protocols
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Binary, File_Area_Observational_Supplemental			

Encoded_Byte_Stream

Name: Encoded_Byte_Stream			Version Id: 1.0.0.0
<i>Description:</i> The Encoded Byte Stream class defines byte streams that must be decoded by software before use. These byte streams must only use standard encodings. The Encoded Byte Stream class is the parent class for all encoded byte streams.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Encoded_Byte_Stream			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	encoding_standard_id	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental			

Encoded_Header

Name: Encoded_Header			Version Id: 1.0.0.0
<i>Description:</i> The Encoded Header class describes a header that has been encoded using an encoding scheme that is compliant to an external standard.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Encoded_Byte_Stream :: Encoded_Header			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	encoding_standard_id	1..1	TIFF
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Encoded_Image

Name: Encoded_Image			Version Id: 1.0.0.0
<i>Description:</i> The Encoded Image class is used for ancillary images in standard formats, such as JPEG.			

Support classes in the
common (pds) namespace.

Name: Encoded_Image			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Encoded_Byte_Stream :: Encoded_Image			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	encoding_standard_id	1..1	GIF, J2C, JPEG, PDF, PDF/A, PNG, TIFF
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Browse, File_Area_Encoded_Image			

Encoded_Native

Name: Encoded_Native			Version Id: 1.0.0.0
<i>Description:</i> The Encoded Native class describes a binary encoded byte stream. This class is used to describe data objects for Product_Native.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Encoded_Byte_Stream :: Encoded_Native			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	encoding_standard_id	1..1	SEED 2.4
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Native			

External_Reference

Name: External_Reference			Version Id: 1.0.0.0
<i>Description:</i> The External_Reference class is used to reference a source outside the PDS registry system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: External_Reference			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: External_Reference			Version Id: 1.0.0.0
	doi	0..1	None
	reference_text	1..1	None
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Reference_List, Observing_System_Component			

External_Reference_Extended

Name: External_Reference_Extended			Version Id: 1.0.0.0
<i>Description:</i> The External_Reference_Extended class is used to reference a source outside the PDS registry system. This extension is used in the local data dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: External_Reference :: External_Reference_Extended			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	doi	0..1	None
	reference_text	1..1	None
	description	0..1	None
	name	0..1	None
	url	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Terminological_Entry			

Facility

Name: Facility			Version Id: 1.0.0.0
<i>Description:</i> The Facility class provides a name and address for a terrestrial observatory or laboratory.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Facility			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	type	0..1	Laboratory, Observatory
	address	0..1	None
	country	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

Field

Name: Field			Version Id: 1.0.0.0
<i>Description:</i> The Field class defines a field of a record and is the parent class of all specific field classes.The Field class defines a field of a record or a field of a group and is the parent class of all specific field classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Field			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	field_number	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Field_Binary

Name: Field_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Field_Binary class defines a field of a binary record or a field of a binary group.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Field :: Field_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	field_number	0..1	None
	field_location	1..1	None
	data_type	1..1	ASCII_AnyURI, ASCII_Boolean, ASCII_DOI, ASCII_ Date, ASCII_Date_ DOY, ASCII_Date_ Time, ASCII_Date_ Time_DOY, ASCII_ Date_Time_UTC, ASCII_Date_Time_ YMD, ASCII_ Date_YMD, ASCII_ Directory_Path_ Name, ASCII_File_ Name, ASCII_File_ Specification_Name, ASCII_Integer, ASCII_ LID, ASCII_LIDVID, ASCII_LIDVID_ LID, ASCII_MD5_ Checksum, ASCII_ NonNegative_Integer, ASCII_Numeric_ Base16, ASCII_ Numeric_Base2, ASCII_Numeric_ Base8, ASCII_Real,

Name: Field_Binary			Version Id: 1.0.0.0
			ASCII_String, ASCII_Time, ASCII_VID, ComplexLSB16, ComplexLSB8, ComplexMSB16, ComplexMSB8, IEEE754LSBDouble, IEEE754LSBSingle, IEEE754MSBDouble, IEEE754MSBSingle, SignedBitString, SignedByte, SignedLSB2, SignedLSB4, SignedLSB8, SignedMSB2, SignedMSB4, SignedMSB8, UTF8_String, UnsignedBitString, UnsignedByte, UnsignedLSB2, UnsignedLSB4, UnsignedLSB8, UnsignedMSB2, UnsignedMSB4, UnsignedMSB8
	field_length	1..1	None
	field_format	0..1	None
	unit	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Field_Statistics
	has_Packed_Data_Fields	0..1	Packed_Data_Fields
<i>Referenced from:</i> Group_Field_Binary, Record_Binary			

Field_Bit

Name: Field_Bit			Version Id: 1.0.0.0
<i>Description:</i> The Field_Bit class provides parameters for extracting one field out of a string of bytes which contains packed data (that is, data values either smaller than a single byte, or crossing byte boundaries, or both).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Field :: Field_Bit			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: Field_Bit			Version Id: 1.0.0.0
	name	1..1	None
	field_number	0..1	None
	start_bit	1..1	None
	stop_bit	1..1	None
	data_type	1..1	SignedBitString, UnsignedBitString
	field_format	0..1	None
	unit	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	associated_Special_Constants	0..1	Special_Constants
<i>Referenced from:</i> Packed_Data_Fields			

Field_Character

Name: Field_Character			Version Id: 1.0.0.0
<i>Description:</i> The Field_Character class defines a field of a character record or a field of a character group.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Field :: Field_Character			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	field_number	0..1	None
	field_location	1..1	None
	data_type	1..1	ASCII_AnyURI, ASCII_Boolean, ASCII_DOI, ASCII_Date, ASCII_Date_DOY, ASCII_Date_Time, ASCII_Date_Time_DOY, ASCII_Date_Time_UTC, ASCII_Date_Time_YMD, ASCII_Date_YMD, ASCII_Directory_Path_Name, ASCII_File_Name, ASCII_File_Specification_Name, ASCII_Integer, ASCII_LID, ASCII_LIDVID, ASCII_LIDVID_LID, ASCII_MD5_Checksum, ASCII_NonNegative_Integer,

Name: Field_Character			Version Id: 1.0.0.0
			ASCII_Numeric_Base16, ASCII_Numeric_Base2, ASCII_Numeric_Base8, ASCII_Real, ASCII_String, ASCII_Time, ASCII_VID, UTF8_String
	field_length	1..1	None
	field_format	0..1	None
	unit	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Field_Statistics
<i>Referenced from:</i> Group_Field_Character, Record_Character			

Field_Delimited

Name: Field_Delimited			Version Id: 1.0.0.0
<i>Description:</i> The Field_Delimited class defines a field of a delimited record or a field of a delimited group.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Field :: Field_Delimited			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	field_number	0..1	None
	data_type	1..1	ASCII_AnyURI, ASCII_Boolean, ASCII_DOI, ASCII_Date, ASCII_Date_DOY, ASCII_Date_Time, ASCII_Date_Time_DOY, ASCII_Date_Time_UTC, ASCII_Date_Time_YMD, ASCII_Date_YMD, ASCII_Directory_Path_Name, ASCII_File_Name, ASCII_File_Specification_Name, ASCII_Integer, ASCII_LID, ASCII_LIDVID, ASCII_LIDVID_LID, ASCII_MD5_

Support classes in the
common (pds) namespace.

Name: Field_Delimited			Version Id: 1.0.0.0
			Checksum, ASCII_NonNegative_Integer, ASCII_Numeric_Base16, ASCII_Numeric_Base2, ASCII_Numeric_Base8, ASCII_Real, ASCII_String, ASCII_Time, ASCII_VID, UTF8_String
	maximum_field_length	0..1	None
	field_format	0..1	None
	unit	0..1	None
	scaling_factor	0..1	None
	value_offset	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	associated_Special_Constants	0..1	Special_Constants
	associated_Statistics	0..1	Field_Statistics
<i>Referenced from:</i> Record_Delimited, Group_Field_Delimited			

Field_Statistics

Name: Field_Statistics			Version Id: 1.0.0.0
<i>Description:</i> The Field Statistics class provides a set of metrics for a column formed by a field in a repeating record.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Field_Statistics			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	0..1	None
	maximum	0..1	None
	minimum	0..1	None
	mean	0..1	None
	standard_deviation	0..1	None
	median	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Field_Delimited, Field_Character, Field_Binary			

File

Name: File	Version Id: 1.0.0.0
<i>Description:</i> The File class consists of attributes that describe a file in a data store.	

Name: File			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: File			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	file_name	1..1	None
	local_identifier	0..1	None
	creation_date_time	0..1	None
	file_size	0..1	None
	records	0..1	None
	md5_checksum	0..1	None
	comment	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Native, File_Area_SPICE_Kernel, Product_Zipped, File_Area_Transfer_Manifest, File_Area_Binary, File_Area_Inventory, File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Checksum_Manifest, File_Area_XML_Schema, File_Area_Browse, File_Area_Text, File_Area_Service_Description, File_Area_Encoded_Image			

File_Area

Name: File_Area			Version Id: 1.0.0.0
<i>Description:</i> The File_Area class defines a File and its component data objects.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

File_Area_Binary

Name: File_Area_Binary			Version Id: 1.0.0.0
<i>Description:</i> The File Area Binary class describes a file that contains an encoded byte stream.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Binary			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	0..Unbounded	Encoded_Binary
<i>Referenced from:</i> Product_Proxy_PDS3, Product_File_Repository			

File_Area_Browse

Name: File_Area_Browse		Version Id: 1.0.0.0	
<i>Description:</i> The File Area Browse class describes a file and one or more tagged_data_objects contained within the file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Browse			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..Unbounded	Array_1D, Array_2D, Array_2D_Image, Array_2D_Map, Array_2D_Spectrum, Array_3D, Array_3D_Image, Array_3D_Movie, Array_3D_Spectrum, Encoded_Header, Encoded_Image, Header, Stream_Text, Table_Binary, Table_Character, Table_Delimited
<i>Referenced from:</i> Product_Browse			

File_Area_Checksum_Manifest

Name: File_Area_Checksum_Manifest		Version Id: 1.0.0.0	
<i>Description:</i> The File Area Checksum Manifest class describes a file that contains a two column table for file references and checksums.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Checksum_Manifest			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	Checksum_Manifest
<i>Referenced from:</i> Information_Package_Component			

File_Area_Encoded_Image

Name: File_Area_Encoded_Image		Version Id: 1.0.0.0	
<i>Description:</i> The File Area Encoded Image class describes a file that contains an Encoded Image object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Encoded_Image			
<i>No Attributes</i>			

Support classes in the
common (pds) namespace.

Name: File_Area_Encoded_Image			Version Id: 1.0.0.0
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	Encoded_Image
<i>Referenced from:</i> Product_Thumbnail			

File_Area_Inventory

Name: File_Area_Inventory			Version Id: 1.0.0.0
<i>Description:</i> The File Area Inventory class describes a file and an inventory consisting of references to members.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Inventory			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	Inventory
<i>Referenced from:</i> Product_Collection			

File_Area_Native

Name: File_Area_Native			Version Id: 1.2.0.0
<i>Description:</i> The File Area Native describes tagged_data_objects collected from an instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Native			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..Unbounded	Encoded_Native
<i>Referenced from:</i> Product_Native			

File_Area_Observational

Name: File_Area_Observational			Version Id: 1.0.0.0
<i>Description:</i> The File Area Observational class describes, for an observational product, a file and one or more tagged_data_objects contained within the file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Observational			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..Unbounded	Array_1D, Array_2D, Array_2D_Image, Array_2D_

Support classes in the
common (pds) namespace.

Name: File_Area_Observational			Version Id: 1.0.0.0
			Map, Array_2D_Spectrum, Array_3D, Array_3D_Image, Array_3D_Movie, Array_3D_Spectrum, Encoded_Header, Header, Stream_Text, Table_Binary, Table_Character, Table_Delimited
<i>Referenced from:</i> Product_Observational			

File_Area_Observational_Supplemental

Name: File_Area_Observational_Supplemental			Version Id: 1.0.0.0
<i>Description:</i> The File Area Observational Supplemental class describes, for an observational product, additional files and tagged_data_objects contained within the file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Observational_Supplemental			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..Unbounded	Array_1D, Array_2D, Array_2D_Image, Array_2D_Map, Array_2D_Spectrum, Array_3D, Array_3D_Image, Array_3D_Movie, Array_3D_Spectrum, Encoded_Binary, Encoded_Byte_Stream, Encoded_Header, Encoded_Image, Header, Parsable_Byte_Stream, Stream_Text, Table_Binary, Table_Character, Table_Delimited
<i>Referenced from:</i> Product_Observational			

File_Area_SPICE_Kernel

Name: File_Area_SPICE_Kernel			Version Id: 1.0.0.0
<i>Description:</i> The File Area SPICE Kernel class describes a file that contains a SPICE Kernel object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_SPICE_Kernel			
<i>No Attributes</i>			

Name: File_Area_SPICE_Kernel			Version Id: 1.0.0.0
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	SPICE_Kernel
<i>Referenced from:</i> Product_SPICE_Kernel			

File_Area_Service_Description

Name: File_Area_Service_Description			Version Id: 1.0.0.0
<i>Description:</i> The File Area Service Description class describes a file that contains a service description.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Service_Description			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..Unbounded	Service_Description
<i>Referenced from:</i> Product_Service			

File_Area_Text

Name: File_Area_Text			Version Id: 1.0.0.0
<i>Description:</i> The File Area Text class describes a file that contains a text stream object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Text			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	Stream_Text
<i>Referenced from:</i> Product_File_Text, Product_Bundle			

File_Area_Transfer_Manifest

Name: File_Area_Transfer_Manifest			Version Id: 1.0.0.0
<i>Description:</i> The File Area Transfer Manifest class describes a file that contains a two column table that maps the logical identifiers and version ids of products to their file specification names.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_Transfer_Manifest			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	Transfer_Manifest
<i>Referenced from:</i> Information_Package_Component			

File_Area_XML_Schema

Name: File_Area_XML_Schema			Version Id: 1.0.0.0
<i>Description:</i> The File Area XML Schema class describes a file that contains a resource used for the PDS4 implementation into XML.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: File_Area :: File_Area_XML_Schema			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_File	1..1	File
	has_tagged_data_object	1..1	XML_Schema
<i>Referenced from:</i> Product_XML_Schema			

Geometry

Name: Geometry			Version Id: 1.n.0.0
<i>Description:</i> The Geometry class groups geometry information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Geometry			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	vector	0..Unbounded	Vector
<i>Referenced from:</i> None			

Group

Name: Group			Version Id: 1.0.0.0
<i>Description:</i> The Group class defines a group of (repeating) fields and, possibly, (sub) groups; it is the parent class of all specific group classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Group			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	group_number	0..1	None
	repetitions	1..1	None
	fields	1..1	None
	groups	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Group_Facet1

Name: Group_Facet1			Version Id: 1.1.0.0
<i>Description:</i> The Group_Facet1 class contains a single facet restricted according to the value of discipline_name. It also contains zero or more subfacets restricted according to the value of the facet. Note that Science_Facets was modeled with Discipline_Facets as a component and Discipline_Facets was modeled with Group_Facet1 and Group_Facet2 as components. This dependency hierarchy was flattened and only Science_Facets exists in the schema.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Group_Facet1			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	facet1	0..1	2D, Color, Color Movie, Dust Study, Dynamical Properties, Electric, Electrons, Gas Study, Grayscale, Historical Reference, Ions, Lightcurve, Linear, Magnetic, Meteoritics, Meteorology, Movie, Neutrals, Photometry, Physical Properties, Polarimetry, Production Rates, Ring Compositional Map, Ring Occultation Profile, Ring Thermal Map, Satellite Astrometry, Shape Model, Spectral Cube, Spectral Image, Structure, Tabulated, Taxonomy
	subfacet1	0..Unbounded	None
<i>No Associations</i>			
<i>Referenced from:</i> Discipline_Facets			

Group_Facet2

Name: Group_Facet2			Version Id: 1.1.0.0
<i>Description:</i> The Group_Facet2 class contains a single facet restricted according to the value of discipline_name. It also contains zero or more subfacets restricted according to the value of the facet. Note that Science_Facets was modeled with Discipline_Facets as a component and Discipline_Facets was modeled with Group_Facet1 and Group_Facet2 as components. This dependency hierarchy was flattened and only Science_Facets exists in the schema.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Group_Facet2			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: Group_Facet2			Version Id: 1.1.0.0
	facet2	0..1	Background, Cosmic Ray, Energetic, Plasma, Solar Energetic, Waves
	subfacet2	0..Unbounded	None
<i>No Associations</i>			
<i>Referenced from:</i> Discipline_Facets			

Group_Field_Binary

Name: Group_Field_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Group_Field_Binary class allows a group of table fields.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Group :: Group_Field_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	group_number	0..1	None
	repetitions	1..1	None
	fields	1..1	None
	groups	1..1	None
	group_location	1..1	None
	group_length	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Group_Field_Binary	1..Unbounded	Field_Binary, Group_Field_Binary
<i>Referenced from:</i> Group_Field_Binary, Record_Binary			

Group_Field_Character

Name: Group_Field_Character			Version Id: 1.0.0.0
<i>Description:</i> The Group_Field_Character class allows a group of table fields.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Group :: Group_Field_Character			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	group_number	0..1	None
	repetitions	1..1	None
	fields	1..1	None
	groups	1..1	None
	group_location	1..1	None
	group_length	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Group_Field_Character	1..Unbounded	Field_Character, Group_Field_Character
<i>Referenced from:</i> Group_Field_Character, Record_Character			

Group_Field_Delimited

Name: Group_Field_Delimited			Version Id: 1.0.0.0
<i>Description:</i> The Field_Group_Delimited class allows a group of delimited fields.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Group :: Group_Field_Delimited			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	group_number	0..1	None
	repetitions	1..1	None
	fields	1..1	None
	groups	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Delimited_Field_Grouped	1..Unbounded	Field_Delimited, Group_Field_Delimited
<i>Referenced from:</i> Record_Delimited, Group_Field_Delimited			

Header

Name: Header			Version Id: 1.0.0.0
<i>Description:</i> The Header class describes a data object header.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Header			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	1..1	None
	parsing_standard_id	1..1	7-Bit ASCII Text, CDF 3.4 ISTEP/IACG, FITS 3.0, ISIS2, ISIS3, PDS DSV 1, PDS ODL 2, PDS3, Pre-PDS3, UTF-8 Text, VICAR1, VICAR2
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Identification_Area

Name: Identification_Area			Version Id: 1.0.0.0
<i>Description:</i> The identification area consists of attributes that identify and name an object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active

Support classes in the
common (pds) namespace.

Name: Identification_Area			Version Id: 1.0.0.0
<i>Class Hierarchy:</i> Product_Components :: Identification_Area			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	logical_identifier	1..1	None
	version_id	1..1	None
	title	1..1	None
	information_model_version	1..1	1.2.0.1
	product_class	1..1	Product_AIP, Product_Attribute_Definition, Product_Browse, Product_Bundle, Product_Class_Definition, Product_Collection, Product_Context, Product_DIP, Product_DIP_Deep_Archive, Product_Data_Set_PDS3, Product_Document, Product_File_Repository, Product_File_Text, Product_Instrument_Host_PDS3, Product_Instrument_PDS3, Product_Mission_PDS3, Product_Native, Product_Observational, Product_Proxy_PDS3, Product_SIP, Product_SPICE_Kernel, Product_Service, Product_Software, Product_Subscription_PDS3, Product_Target_PDS3, Product_Thumbnail, Product_Update, Product_Volume_PDS3, Product_Volume_Set_PDS3, Product_XML_Schema, Product_Zipped
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	alias_list	0..1	Alias_List
	citation_information	0..1	Citation_Information
	modification_history	0..1	Modification_History
<i>Referenced from:</i> Product_Observational, Product_Update, Product_Proxy_PDS3, Product_Zipped, Product_Target_PDS3, Product_Attribute_Definition, Product_SPICE_Kernel, Product_Class_Definition, Product_Native, Product_Service, Product_File_Text, Product_Browse, Product_File_Repository, Product_Collection, Product_Volume_Set_PDS3, Product_DIP, Product_Document, Product_XML_Schema, Product_DIP_Deep_Archive, Product_Bundle,			

Support classes in the
common (pds) namespace.

Name: Identification_Area	Version Id: 1.0.0.0
Product_Instrument_PDS3, Product_Thumbnail, Product_AIP, Product_Subscription_PDS3, Product_Data_Set_PDS3, Product, Product_Instrument_Host_PDS3, Product_Mission_PDS3, Product_Volume_PDS3, Product_SIP, Product_Software, Product_Context	

Information_Package

Name: Information_Package	Version Id: 1.1.0.0		
<i>Description:</i> The Information Package class defines the Information Package as described in the OAIS Reference Model and is the parent class of all specific IP classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Information_Package_Component

Name: Information_Package_Component	Version Id: 1.1.0.0		
<i>Description:</i> The Information_Package_Component class associates a Bundle, Collections or Basic Products with Checksum and Storage Manifests.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package_Component			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	checksum_manifest_checksum	0..1	None
	checksum_type	0..1	None
	transfer_manifest_checksum	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	1..Unbounded	Internal_Reference
	has_Checksum_Manifest	0..1	File_Area_Checksum_Manifest
	has_Transfer_Manifest	0..1	File_Area_Transfer_Manifest
<i>Referenced from:</i> Product_DIP, Product_DIP_Deep_Archive, Product_AIP, Product_SIP			

Instrument

Name: Instrument	Version Id: 1.0.0.0		
<i>Description:</i> The Instrument class provides a description of a physical object that collects data.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Instrument			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: Instrument		Version Id: 1.0.0.0	
	name	0..1	None
	type	1..Unbounded	Accelerometer, Alpha Particle Detector, Alpha Particle X-Ray Spectrometer, Altimeter, Anemometer, Atomic Force Microscope, Barometer, Biology Experiments, Bolometer, Camera, Cosmic Ray Detector, Drilling Tool, Dust Detector, Electrical Probe, Energetic Particle Detector, Gamma Ray Detector, Gas Analyzer, Grinding Tool, Hygrometer, Imager, Imaging Spectrometer, Inertial Measurement Unit, Infrared Spectrometer, Laser Induced Breakdown Spectrometer, Magnetometer, Mass Spectrometer, Microwave Spectrometer, Moessbauer Spectrometer, Naked Eye, Neutral Particle Detector, Neutron Detector, Photometer, Plasma Analyzer, Plasma Detector, Plasma Wave Spectrometer, Polarimeter, RADAR, Radio Science, Radio Spectrometer, Radio Telescope, Radiometer, Reflectometer, Robotic Arm, Spectrograph Imager, Spectrometer, Thermal Imager, Thermal Probe, Thermometer, Ultraviolet Spectrometer, Wet Chemistry Laboratory, X-ray Detector, X-ray Diffraction Spectrometer, X-

Support classes in the
common (pds) namespace.

Name: Instrument			Version Id: 1.0.0.0
			ray Fluorescence Spectrometer
	model_id	0..1	None
	naif_instrument_id	0..1	None
	serial_number	0..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

Instrument_Host

Name: Instrument_Host			Version Id: 1.0.0.0
<i>Description:</i> The Instrument Host class provides a description of the physical object upon which an instrument is mounted.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Instrument_Host			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	instrument_host_version_id	0..1	None
	version_id *Deprecated*	0..1	None
	type	1..1	Earth Based, Earth-based, Lander, Rover, Spacecraft
	naif_host_id	0..1	None
	serial_number	0..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

Internal_Reference

Name: Internal_Reference			Version Id: 1.0.0.0
<i>Description:</i> The Internal_Reference class is used to cross-reference other products in the PDS registry system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Internal_Reference			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	lid_reference	0..1	None
	lidvid_reference	0..1	None
	reference_type	1..1	None

Support classes in the common (pds) namespace.

Name: Internal_Reference			Version Id: 1.0.0.0
	comment	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Reference_List, Product_Zipped, Investigation_Area, DD_Class, Update_Entry, Target_Identification, Information_Package_Component, DD_Attribute, Observing_System_Component			

Inventory

Name: Inventory			Version Id: 1.0.0.0
<i>Description:</i> The Inventory class defines the inventory for members of a collection.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Table_Delimited :: Inventory			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	PDS DSV 1
	description	0..1	None
	records	1..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
	field_delimiter	1..1	Comma, Horizontal Tab, Semicolon, Vertical Bar, comma, horizontal tab, semicolon, vertical bar
	reference_type	1..1	inventory_has_member_product
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
	uniformly_sampled	0..1	Uniformly_Sampled
	has_delimited_record	1..1	Record_Delimited
<i>Referenced from:</i> File_Area_Inventory			

Investigation

Name: Investigation			Version Id: 1.0.0.0
<i>Description:</i> The Investigation class provides a description of activities involved in the collection of data.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Investigation			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Name: Investigation			Version Id: 1.0.0.0
	name	0..1	None
	type	1..1	Individual Investigation, Mission, Observing Campaign, Other Investigation
	start_date	1..1	None
	stop_date	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Context			

Investigation_Area

Name: Investigation_Area			Version Id: 1.0.0.0
<i>Description:</i> The Investigation_Area class provides information about an investigation (mission, observing campaign or other coordinated, large-scale data collection effort).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Investigation_Area			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	type	1..1	Individual Investigation, Mission, Observing Campaign, Other Investigation
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	1..Unbounded	Internal_Reference
<i>Referenced from:</i> Context_Area, Observation_Area			

Local_Internal_Reference

Name: Local_Internal_Reference			Version Id: 1.0.0.0
<i>Description:</i> The Local Internal_Reference class is used to cross-reference other Description Objects in a PDS4 label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Local_Internal_Reference			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	comment	0..1	None
	local_identifier_reference	1..1	None
	local_reference_type	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Display_Settings, Array_2D_Image, Array_2D_Spectrum, Array_3D_Image, Array, Array_2D, Array_3D, Array_3D_Spectrum, Array_3D_Movie, Array_2D_Map, Array_1D			

Mission_Area

Name: Mission_Area			Version Id: 1.0.0.0
<i>Description:</i> The mission area allows the insertion of mission specific metadata.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Mission_Area			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> Context_Area, Observation_Area			

Modification_Detail

Name: Modification_Detail			Version Id: 1.0.0.0
<i>Description:</i> The Modification_Detail class provides the details of one round of modification for the product. The first, required, instance of this class documents the date the product was first registered.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Modification_Detail			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	modification_date	1..1	None
	version_id	1..1	None
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Modification_History			

Modification_History

Name: Modification_History			Version Id: 1.0.0.0
<i>Description:</i> The Modification_History class tracks the history of changes made to the product once it enters the registry system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Modification_History			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	modification_detail	1..Unbounded	Modification_Detail
<i>Referenced from:</i> Identification_Area			

NSSDC

Name: NSSDC			Version Id: 1.0.0.0
<i>Description:</i> The NSSDC Information class provides identification information for data submitted to the NSSDC.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: NSSDC			

Support classes in the common (pds) namespace.

Name: NSSDC			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	medium_type	1..1	None
	nssdc_collection_id	1..1	None
<i>No Associations</i>			
<i>Referenced from: Data_Set_PDS3</i>			

Node

Name: Node			Version Id: 1.0.0.0
<i>Description:</i> The Node class provides a description of an entity that provides local governance within the federated Planetary Data System.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Node			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	Engineering, Geosciences, Imaging, Management, Navigation and Ancillary Information Facility, Planetary Atmospheres, Planetary Plasma Interactions, Planetary Rings, Planetary Science Archive, Radio Science, Small Bodies
	institution_name	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from: Product_Context</i>			

Object_Statistics

Name: Object_Statistics			Version Id: 1.0.0.0
<i>Description:</i> The Object Statistics class provides a set of values that provide metrics about the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Object_Statistics			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	0..1	None
	maximum	0..1	None
	minimum	0..1	None
	mean	0..1	None
	standard_deviation	0..1	None

Support classes in the
common (pds) namespace.

Name: Object_Statistics			Version Id: 1.0.0.0
	bit_mask	0..1	None
	median	0..1	None
	md5_checksum	0..1	None
	maximum_scaled_value	0..1	None
	minimum_scaled_value	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Array_2D_Image, Array_2D_Spectrum, Array_3D_Image, Array, Array_2D, Array_3D, Array_3D_Spectrum, Array_3D_Movie, Array_2D_Map, Array_1D			

Observation_Area

Name: Observation_Area			Version Id: 1.0.0.0
<i>Description:</i> The observation area consists of attributes that provide information about the circumstances under which the data were collected.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Context_Area :: Observation_Area			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	comment	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_time_coordinates	1..1	Time_Coordinates
	has_primary_result_description	0..1	Primary_Result_Summary
	has_investigation_area	1..Unbounded	Investigation_Area
	has_observing_system	1..Unbounded	Observing_System
	has_target_identification	1..Unbounded	Target_Identification
	has_mission_area	0..1	Mission_Area
	has_discipline_area	0..1	Discipline_Area
<i>Referenced from:</i> Product_Observational			

Observing_System

Name: Observing_System			Version Id: 1.0.0.0
<i>Description:</i> The Observing System class describes the entire suite used to collect the data.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Observing_System			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>

Support classes in the
common (pds) namespace.

Name: Observing_System			Version Id: 1.0.0.0
	observing_system_component	1..Unbounded	Observing_System_Component
	data_object	1..1	Conceptual_Object, Physical_Object
<i>Referenced from:</i> Context_Area, Observation_Area			

Observing_System_Component

Name: Observing_System_Component			Version Id: 1.0.0.0
<i>Description:</i> The Observing System Component class references one or more subsystems used to collect data. A subsystem can be an instrument_host, instrument, or any other similar product. Each subsystem is categorized as either a sensor or a source. If the observing system includes both a sensor and a source, Observing System Component occurs twice (once for each type) otherwise it only occurs once.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: Observing_System_Component			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	type	1..1	Artificial Illumination, Instrument, Laboratory, Literature Search, Naked Eye, Observatory, Spacecraft, Telescope
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..1	Internal_Reference
	external_reference	0..Unbounded	External_Reference
<i>Referenced from:</i> Observing_System			

Other

Name: Other			Version Id: 1.0.0.0
<i>Description:</i> The Other class provides a description of activities involved in the collection of data which are not otherwise modeled.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Other			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Context			

PDS_Affiliate

Name: PDS_Affiliate			Version Id: 1.0.0.0
<i>Description:</i> The PDS Affiliate class provides a description of a person who has an association with the planetary science community and has access to PDS resources not normally allowed to the general public.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: PDS_Affiliate			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	registration_date	1..1	None
	electronic_mail_address	0..Unbounded	None
	sort_name	1..1	None
	affiliation_type	1..1	Affiliate, Data Provider, Manager, Technical Staff
	alternate_telephone_number	0..1	None
	institution_name	1..1	None
	phone_book_flag	1..1	None
	postal_address_text	1..1	None
	team_name	0..Unbounded	Engineering, Geosciences, Headquarters, Imaging, Management, National Space Science Data Center, Navigation and Ancillary Information Facility, Planetary Atmospheres, Planetary Plasma Interactions, Planetary Rings, Radio Science, Small Bodies
	telephone_number	0..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

PDS_Guest

Name: PDS_Guest			Version Id: 1.0.0.0
<i>Description:</i> The PDS_Guest class is the default description of a person who has an association with the planetary science community and who has the most limited access to PDS resources.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: PDS_Guest			

Support classes in the common (pds) namespace.

Name: PDS_Guest			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	registration_date	1..1	None
	electronic_mail_address	0..Unbounded	None
	sort_name	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

Packed_Data_Fields

Name: Packed_Data_Fields			Version Id: 1.0.0.0
<i>Description:</i> The Packed_Data_Fields class contains field definitions for extracting packed data from the associated byte string field.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Packed_Data_Fields			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	bit_fields	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Field_Bit	1..Unbounded	Field_Bit
<i>Referenced from:</i> Field_Binary			

Parsable_Byte_Stream

Name: Parsable_Byte_Stream			Version Id: 1.0.0.0
<i>Description:</i> The Parsable Byte Stream class defines byte streams that have standard parsing rules. The Parsable Byte Stream class is the parent class for all parsable byte streams.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental			

Physical_Object

Name: Physical_Object			Version Id: 1.0.0.0
<i>Description:</i> The Physical Object class defines a tangible object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Data_Object :: Physical_Object			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> Instrument_Host_PDS3, Target_PDS3, Instrument_Host, Volume_PDS3, Instrument, Instrument_PDS3, Target, Data_Set_PDS3, PDS_Affiliate, Facility, Volume_Set_PDS3, Observing_System, PDS_Guest			

Primary_Result_Summary

Name: Primary_Result_Summary			Version Id: 1.1.0.0
<i>Description:</i> The Primary_Result_Summary class provides a high-level description of the types of products included in the collection or bundle			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Primary_Result_Summary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	type *Deprecated*	0..1	Altimetry, Astrometry, Count, E/B-Field Vectors, Gravity Model, Image, Lightcurves, Map, Meteorology, Null Result, Occultation, Photometry, Physical Parameters, Polarimetry, Radiometry, Reference, Shape Model, Spectrum
	purpose	1..1	Calibration, Checkout, Engineering, Navigation, Science
	data_regime *Deprecated*	0..Unbounded	Dust, Electric Field, Electrons, Far Infrared, Gamma Ray, Infrared, Ions, Magnetic Field, Microwave, Millimeter, Near Infrared, Particles, Pressure, Radio, Sub-Millimeter, Temperature, Ultraviolet, Visible, X-Ray
	processing_level	1..1	Calibrated, Derived, Partially Processed, Raw, Telemetry

Support classes in the common (pds) namespace.

Name: Primary_Result_Summary			Version Id: 1.1.0.0
	processing_level_id *Deprecated*	0..1	Calibrated, Derived, Partially Processed, Raw, Telemetry
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Science_Facet	0..Unbounded	Science_Facets
<i>Referenced from:</i> Context_Area, Observation_Area			

Product

Name: Product			Version Id: 1.0.0.0
<i>Description:</i> A Product is a uniquely identified object that is managed by a registry/repository. It consists of one or more tagged data objects.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_identification_area	1..1	Identification_Area
<i>Referenced from:</i> None			

Product_Components

Name: Product_Components			Version Id: 1.0.0.0
<i>Description:</i> The Product Component class is an abstract class for the components of the Product class.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Quaternion

Name: Quaternion			Version Id: 1.n.0.0
<i>Description:</i> The Quaternion class models a mathematical construct that consists of four individual numeric components. Quaternions are a convenient mechanism for encapsulating orientation information since they require only four units of numeric storage, as opposed to the nine needed for a rotation matrix.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Quaternion			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	local_identifier	0..1	None

Support classes in the common (pds) namespace.

Name: Quaternion			Version Id: 1.n.0.0
	type	1..1	SPICE, Spacecraft Telemetry
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	quaternion_component	4..4	Quaternion_Component
<i>Referenced from:</i> None			

Quaternion_Component

Name: Quaternion_Component			Version Id: 1.n.0.0
<i>Description:</i> The Quaternion_Component class provides a component of a quaternion.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: Quaternion_Component			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	data_type	1..1	ASCII_Real
	value	1..1	None
	sequence_number	1..1	None
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Quaternion			

Record

Name: Record			Version Id: 1.0.0.0
<i>Description:</i> The Record class defines a record of a file and is the parent class of all specific record classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Record			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	fields	1..1	None
	groups	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Record_Binary

Name: Record_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Record_Binary class is a component of the table class and defines a record of the table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active

Support classes in the
common (pds) namespace.

Name: Record_Binary			Version Id: 1.0.0.0
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Record :: Record_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	fields	1..1	None
	groups	1..1	None
	record_length	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Table_Field	1..Unbounded	Field_Binary, Group_Field_Binary
<i>Referenced from:</i> Table_Binary			

Record_Character

Name: Record_Character			Version Id: 1.0.0.0
<i>Description:</i> The Record_Character class is a component of the table class and defines a record of the table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Record :: Record_Character			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	fields	1..1	None
	groups	1..1	None
	record_length	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Character_Field	1..Unbounded	Field_Character, Group_Field_Character
<i>Referenced from:</i> Table_Character, Transfer_Manifest			

Record_Delimited

Name: Record_Delimited			Version Id: 1.0.0.0
<i>Description:</i> The Record_Delimited class is a component of the delimited table (spreadsheet) class and defines a record of the delimited table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Record :: Record_Delimited			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	fields	1..1	None
	groups	1..1	None
	maximum_record_length	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Delimited_Field	1..Unbounded	Field_Delimited, Group_Field_Delimited
<i>Referenced from:</i> Table_Delimited, Inventory			

Reference_List

Name: Reference_List			Version Id: 1.0.0.0
<i>Description:</i> The Reference_List class provides lists general references and cross-references for the product. References cited elsewhere in the label need not be repeated here.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Reference_List			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..Unbounded	Internal_Reference
	external_reference	0..Unbounded	External_Reference
<i>Referenced from:</i> Product_Observational, Product_Update, Product_Proxy_PDS3, Product_Target_PDS3, Product_Attribute_Definition, Product_SPICE_Kernel, Product_Class_Definition, Product_Native, Product_Service, Product_File_Text, Product_Browse, Product_File_Repository, Product_Collection, Product_Volume_Set_PDS3, Product_DIP, Product_Document, Product_XML_Schema, Product_DIP_Deep_Archive, Product_Bundle, Product_Instrument_PDS3, Product_Thumbnail, Product_AIP, Product_Subscription_PDS3, Product_Data_Set_PDS3, Product_Instrument_Host_PDS3, Product_Mission_PDS3, Product_Volume_PDS3, Product_SIP, Product_Software, Product_Context			

Resource

Name: Resource			Version Id: 1.0.0.0
<i>Description:</i> The Resource class provides a description of a web resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Resource			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	type	1..1	Information.Agency, Information.Instrument, Information.Instrument_Host, Information.Investigation, Information.Node, Information.Person, Information.Resource, Information.Science_Portal, Information.Target, System.Browse, System.Directory_Listing, System.Registry_Query, System.Search, System.Transform, System.Transport
	url	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>

Support classes in the
common (pds) namespace.

Name: Resource			Version Id: 1.0.0.0
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Context			

SPICE_Kernel

Name: SPICE_Kernel			Version Id: 1.0.0.0
<i>Description:</i> The SPICE Kernel class describes a SPICE object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: SPICE_Kernel			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	SPICE
	description	0..1	None
	kernel_type	1..1	CK, DBK, DSK, EK, FK, IK, LSK, MK, PCK, SCLK, SPK
	encoding_type	1..1	Binary, Character
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_SPICE_Kernel			

Science_Facets

Name: Science_Facets			Version Id: 1.1.0.0
<i>Description:</i> The Science_Facets class contains the science-related search facets. It is optional and may be repeated if an product has facets related to, for example, two different disciplines (as defined by the discipline_name facet). Note that Science_Facets was modeled with Discipline_Facets as a component and Discipline_Facets was modeled with Group_Facet1 and Group_Facet2 as components. This dependency hierarchy was flattened and only Science_Facets exists in the schema.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Science_Facets			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	wavelength_range	0..Unbounded	Far Infrared, Gamma Ray, Infrared, Microwave, Millimeter, Near Infrared, Radio, Submillimeter, Ultraviolet, Visible, X-ray
	domain	0..Unbounded	Atmosphere, Heliosphere, Interior,

Support classes in the
common (pds) namespace.

Name: Science_Facets			Version Id: 1.1.0.0
			Interstellar, Ionosphere, Magnetosphere, Surface
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	has_Discipline_Facets	1..1	Discipline_Facets
<i>Referenced from:</i> Primary_Result_Summary			

Service_Description

Name: Service_Description			Version Id: 1.0.0.0
<i>Description:</i> The Service Description class defines a file that contains a standardized service specification.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Service_Description			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	WADL, WSDL 2.n
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Service_Description			

Software

Name: Software			Version Id: 1.0.0.0
<i>Description:</i> The Software class describes a software product			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Software			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	software_version_id	1..1	None
	version_id *Deprecated*	0..1	None
	author_list	0..1	None
	programmers_manual_id	1..1	None
	software_id	1..1	None
	software_type	1..1	None
	users_manual_id	1..1	None
	description	1..1	None

Support classes in the
common (pds) namespace.

Name: Software			Version Id: 1.0.0.0
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Product_Software			

Software_Binary

Name: Software_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Software Script class provides a description of a software code that is stored as a compiled binary file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Software_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	files	1..1	None
	os_version	1..Unbounded	None
	program_notes_id	1..1	None
	software_format_type	1..1	None
	supported_architecture_note	1..Unbounded	None
	supported_operating_system_note	1..Unbounded	None
	system_requirements_note	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Product_Software			

Software_Script

Name: Software_Script			Version Id: 1.0.0.0
<i>Description:</i> The Software Script class provides a description of a software code that is stored as a script.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Software_Script			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	files	1..1	None
	install_note	1..1	None
	supported_environment_note	1..1	None
	system_requirements_note	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Product_Software			

Software_Source

Name: Software_Source			Version Id: 1.0.0.0
<i>Description:</i> The Software Script class provides a description of a software code that is stored as source code.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Software_Source			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	compile_note	1..1	None
	files	1..1	None
	os_version	1..1	None
	program_notes_id	1..1	None
	software_dialect	1..1	None
	software_format_type	1..1	None
	software_language	1..1	None
	supported_architecture_note	1..Unbounded	None
	supported_operating_system_note	1..Unbounded	None
	system_requirements_note	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> Product_Software			

Special_Constants

Name: Special_Constants			Version Id: 1.0.0.0
<i>Description:</i> The Special Constants class provides a set of values used to indicate special cases that occur in the data.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Special_Constants			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	saturated_constant	0..1	None
	missing_constant	0..1	None
	error_constant	0..1	None
	invalid_constant	0..1	None
	unknown_constant	0..1	None
	not_applicable_constant	0..1	None
	valid_maximum	0..1	254, 32767, 65522
	high_instrument_saturation	0..1	-32765, 255, 3, 65534, FF7FFFFE, FFFCFFFF

Support classes in the common (pds) namespace.

Name: Special_Constants			Version Id: 1.0.0.0
	high_representation_saturation	0..1	-32764, 255, 4, 65535, FF7FFFFF, FFFBFFFF
	valid_minimum	0..1	-32752, 1, 3, 5, FF7FFFFA, FFEFFFFFFF
	low_instrument_saturation	0..1	-32766, 0, 2, FF7FFFFD, FFFDFFFF
	low_representation_saturation	0..1	-32767, 1, 16#FF7FFFFC#, 16#FFFEFFFF#
<i>No Associations</i>			
<i>Referenced from:</i> Field_Delimited, Field_Character, Array_2D_Image, Array_2D_Spectrum, Array_3D_Image, Array, Field_Binary, Array_2D, Field_Bit, Array_3D, Array_3D_Spectrum, Array_3D_Movie, Array_2D_Map, Array_1D			

Stream_Text

Name: Stream_Text			Version Id: 1.0.0.0
<i>Description:</i> The Stream text class defines a text object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Stream_Text			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	None
	description	0..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse, File_Area_Text			

Submission_Information_Package

Name: Submission_Information_Package			Version Id: 1.1.0.0
<i>Description:</i> The Submission Information Package (SIP) class is an Information Package that is delivered by a Data Provider to an archive that conforms to the Open Archive Information System (OAIS) Reference Model for use in the construction of one or more AIPs.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Information_Package :: Submission_Information_Package			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: Submission_Information_Package			Version Id: 1.1.0.0
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from: Product_SIP</i>			

Symbolic_Literals_PDS

Name: Symbolic_Literals_PDS			Version Id: 1.0.0.0
<i>Description:</i> The Symbolic_Literals_PDS class is used to collect orphan attributes for the pds namespace. These attributes are members by default of the USER class but not members of any domain class.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Symbolic_Literals_PDS			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	nil_reason	0..1	anticipated, inapplicable, missing, unknown
<i>No Associations</i>			
<i>Referenced from: None</i>			

TNDO_Context

Name: TNDO_Context			Version Id: 1.0.0.0
<i>Description:</i> The Tagged NonDigital Object (TNDO) Context class is an abstract class for the context class hierarchy.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from: None</i>			

TNDO_Supplemental

Name: TNDO_Supplemental			Version Id: 1.0.0.0
<i>Description:</i> The Tagged NonDigital Object (TNDO) Supplemental class is an abstract class for the supplemental class hierarchy.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from: None</i>			

Table_Base

Name: Table_Base			Version Id: 1.0.0.0
<i>Description:</i> The Table Base class defines a heterogeneous repeating record of scalars. The Table Base class is the parent class for all heterogeneous repeating record of scalars.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Table_Base			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	records	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> None			

Table_Binary

Name: Table_Binary			Version Id: 1.0.0.0
<i>Description:</i> The Table Binary class is an extension of table base and defines a simple binary table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Table_Base :: Table_Binary			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	records	1..1	None
	description	0..1	None
	record_delimiter	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
	uniformly_sampled	0..1	Uniformly_Sampled
	has_Record	1..1	Record_Binary
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Table_Character

Name: Table_Character			Version Id: 1.0.0.0
<i>Description:</i> The Table Character class is an extension of table base and defines a simple character table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Table_Base :: Table_Character			

Name: Table_Character			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	records	1..1	None
	description	0..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
	uniformly_sampled	0..1	Uniformly_Sampled
	has_Record	1..1	Record_Character
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse			

Table_Delimited

Name: Table_Delimited			Version Id: 1.0.0.0
<i>Description:</i> The Table_Delimited class defines a simple table (spreadsheet) with delimited fields and records.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: Table_Delimited			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	PDS DSV 1
	description	0..1	None
	records	1..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
	field_delimiter	1..1	Comma, Horizontal Tab, Semicolon, Vertical Bar, comma, horizontal tab, semicolon, vertical bar
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
	uniformly_sampled	0..1	Uniformly_Sampled
	has_delimited_record	1..1	Record_Delimited

Name: Table_Delimited	Version Id: 1.0.0.0
<i>Referenced from:</i> File_Area_Observational_Supplemental, File_Area_Observational, File_Area_Browse	

Tagged_Digital_Child

Name: Tagged_Digital_Child		Version Id: 1.0.0.0	
<i>Description:</i> The Tagged Digital Child class is an abstract class for the components of classes in the tagged digital object class hierarchy.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Tagged_Digital_Object

Name: Tagged_Digital_Object		Version Id: 1.0.0.0	
<i>Description:</i> The Tagged Digital Object class is an abstract class for the digital class hierarchy. A tagged object is an information object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Tagged_NonDigital_Child

Name: Tagged_NonDigital_Child		Version Id: 1.0.0.0	
<i>Description:</i> The Tagged NonDigital Child class is an abstract class for the components of classes in the tagged nondigital object class hierarchy.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Tagged_NonDigital_Object

Name: Tagged_NonDigital_Object		Version Id: 1.0.0.0	
<i>Description:</i> The Tagged NonDigital Object class is an abstract class for the physical and conceptual class hierarchy. A tagged object is an information object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> abstract	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object			
<i>No Attributes</i>			

Support classes in the
common (pds) namespace.

Name: Tagged_NonDigital_Object		Version Id: 1.0.0.0
<i>No Associations</i>		
<i>Referenced from: None</i>		

Target

Name: Target		Version Id: 1.0.0.0	
<i>Description:</i> The Target class provides a description of a physical object that is the object of data collection.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Target			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	type	0..Unbounded	Asteroid, Comet, Dust, Dwarf Planet, Galaxy, Globular Cluster, Meteorite, Meteoroid, Meteoroid Stream, Nebula, Open Cluster, Planet, Planetary Nebula, Planetary System, Plasma Cloud, Ring, Satellite, Star, Star Cluster, Sun, Terrestrial Sample, Trans-Neptunian Object
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Context			

Target_Identification

Name: Target_Identification		Version Id: 1.0.0.0	
<i>Description:</i> The Target_Identification class provides detailed target identification information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Target_Identification			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	alternate_designation	0..Unbounded	None
	type	1..1	Asteroid, Comet, Dust, Dwarf Planet, Galaxy, Globular Cluster, Meteorite, Meteoroid, Meteoroid Stream, Nebula, Open Cluster, Planet, Planetary Nebula, Planetary

Support classes in the
common (pds) namespace.

Name: Target_Identification			Version Id: 1.0.0.0
			System, Plasma Cloud, Ring, Satellite, Star, Star Cluster, Sun, Terrestrial Sample, Trans-Neptunian Object
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..1	Internal_Reference
<i>Referenced from:</i> Context_Area, Observation_Area			

Telescope

Name: Telescope			Version Id: 1.0.0.0
<i>Description:</i> The Telescope class provides coordinates and parameters for terrestrial, ground-based telescopes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context :: Telescope			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	aperture	1..1	None
	telescope_longitude	0..1	None
	telescope_latitude	0..1	None
	altitude	1..1	None
	coordinate_source	1..1	Aerial Survey - North American (1983) Datum, Astronomical, Doppler determined - WGS 72 Datum, Geodetic - Adindan Datum, Geodetic - Australian Datum, Geodetic - Campo Inchauspe (Argentina) Datum, Geodetic - Cape (South Africa) Datum, Geodetic - Corregio Alegre (Brazil) Datum, Geodetic - Datum Unknown, Geodetic - European 1979 Datum, Geodetic - European Datum, Geodetic - GRS 80 Datum, Geodetic - Hermannskogel Datum, Geodetic - Indian Datum, Geodetic - La Canoa (Venezuela) Datum, Geodetic - New Zealand Datum, Geodetic - North

Name: Telescope			Version Id: 1.0.0.0
			American (1927) Datum, Geodetic - Old Hawaiian Datum, Geodetic - Ordnance Survey of Great Britain (1936) Datum, Geodetic - Ordnance Survey of Great Britain (SN) 1980 Datum, Geodetic - Potsdam Datum, Geodetic - Puerto Rican (1940) Datum, Geodetic - South American Datum, Geodetic - Tokyo Datum, Geodetic - WGS 84 Datum, Satellite Determined - Datum Unknown, Unknown
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from: Product_Context</i>			

Terminological_Entry

Name: Terminological_Entry			Version Id: 1.0.0.0
<i>Description:</i> The terminological_entry class provides the name (designation) and definition of the attribute in a specified natural language.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: Terminological_Entry			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	definition	1..1	None
	language	1..1	English, Russian
	preferred_flag	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	source	0..Unbounded	External_Reference_Extended
<i>Referenced from:</i> DD_Class, DD_Attribute, DD_Attribute_Full, DD_Class_Full			

Time_Coordinates

Name: Time_Coordinates			Version Id: 1.0.0.0
<i>Description:</i> The Time_Coordinates class provides a list of time coordinates.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Time_Coordinates			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>

Support classes in the
common (pds) namespace.

Name: Time_Coordinates			Version Id: 1.0.0.0
	start_date_time	1..1	None
	stop_date_time	1..1	None
	local_mean_solar_time	0..1	None
	local_true_solar_time	0..1	None
	solar_longitude	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Context_Area, Observation_Area			

Transfer_Manifest

Name: Transfer_Manifest			Version Id: 1.0.0.0
<i>Description:</i> The Transfer_Manifest class defines a table that maps product LIDVIDs to the file_specification_names of the products' XML label files.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Table_Base :: Table_Character :: Transfer_Manifest			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	records	1..1	None
	description	0..1	None
	record_delimiter	1..1	Carriage-Return Line-Feed, carriage-return line-feed
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
	uniformly_sampled	0..1	Uniformly_Sampled
	has_Record	1..1	Record_Character
<i>Referenced from:</i> File_Area_Transfer_Manifest			

Uniformly_Sampled

Name: Uniformly_Sampled			Version Id: 1.0.0.0
<i>Description:</i> The Uniformly_Sampled class provides parameters for a uniformly sampled table.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Child :: Uniformly_Sampled			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	sampling_parameter_name	1..1	None
	sampling_parameter_interval	1..1	None
	sampling_parameter_unit	1..1	None

Support classes in the common (pds) namespace.

Name: Uniformly_Sampled			Version Id: 1.0.0.0
	first_sampling_parameter_value	1..1	None
	last_sampling_parameter_value	1..1	None
	sampling_parameter_scale	0..1	Exponential, Linear, Logarithmic
<i>No Associations</i>			
<i>Referenced from:</i> Table_Binary, Table_Character, Transfer_Manifest, Table_Delimited, Inventory			

Update

Name: Update			Version Id: 1.0.0.0
<i>Description:</i> The Update class consists of update information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Update			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	local_identifier	0..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	update_entry	1..Unbounded	Update_Entry
<i>Referenced from:</i> Product_Update			

Update_Entry

Name: Update_Entry			Version Id: 1.0.0.0
<i>Description:</i> The Update Entry class provides the date and description of an update.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Update_Entry			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	date_time	1..1	None
	full_name	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	internal_reference	0..1	Internal_Reference
<i>Referenced from:</i> Update			

Vector

Name: Vector			Version Id: 1.0.0.0
<i>Description:</i> The Vector class provides the components of either a velocity or position vector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector			

Name: Vector			Version Id: 1.0.0.0
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	1..1	None
	local_identifier	0..1	None
	type	1..1	Acceleration, Pointing, Position, Velocity
	data_type	1..1	ASCII_Real
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	vector_components	1..1	None
	description	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
	vector_component	1..Unbounded	Vector_Component
<i>Referenced from: Geometry</i>			

Vector_Cartesian_3

Name: Vector_Cartesian_3			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Cartesian_3_Base class is the parent class of 3 element Cartesian vectors.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector_Cartesian_3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	x	1..1	None
	y	1..1	None
	z	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Vector_Cartesian_3_Acceleration

Name: Vector_Cartesian_3_Acceleration			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Cartesian_3_Acceleration class is a 3 element Cartesian vector for acceleration coordinates.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector_Cartesian_3 :: Vector_Cartesian_3_Acceleration			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	x	1..1	None
	y	1..1	None

Support classes in the common (pds) namespace.

Name: Vector_Cartesian_3_Acceleration			Version Id: 1.0.0.0
	z	1..1	None
<i>No Associations</i>			
<i>Referenced from: None</i>			

Vector_Cartesian_3_Pointing

Name: Vector_Cartesian_3_Pointing			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Cartesian_3_Pointing class is a 3 element normalized Cartesian vector for pointing.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector_Cartesian_3 :: Vector_Cartesian_3_Pointing			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	x	1..1	None
	y	1..1	None
	z	1..1	None
<i>No Associations</i>			
<i>Referenced from: None</i>			

Vector_Cartesian_3_Position

Name: Vector_Cartesian_3_Position			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Cartesian_3_Position class is a 3 element Cartesian vector for position coordinates.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector_Cartesian_3 :: Vector_Cartesian_3_Position			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	x	1..1	None
	y	1..1	None
	z	1..1	None
<i>No Associations</i>			
<i>Referenced from: None</i>			

Vector_Cartesian_3_Velocity

Name: Vector_Cartesian_3_Velocity			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Cartesian_3_Velocity class is a 3 element Cartesian vector for velocity coordinates.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active

Name: Vector_Cartesian_3_Velocity			Version Id: 1.0.0.0
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Vector_Cartesian_3 :: Vector_Cartesian_3_Velocity			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	reference_frame_id	1..1	ICRF, MOON_ME_DE421
	x	1..1	None
	y	1..1	None
	z	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Vector_Component

Name: Vector_Component			Version Id: 1.0.0.0
<i>Description:</i> The Vector_Component class provides a component of a vector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Child :: Vector_Component			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	unit	0..1	None
	value	1..1	None
	sequence_number	1..1	None
	description	0..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Vector			

XML_Schema

Name: XML_Schema			Version Id: 1.0.0.0
<i>Description:</i> The XML Schema class defines a resource used for the PDS4 implementation into XML.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_Digital_Object :: Byte_Stream :: Parsable_Byte_Stream :: XML_Schema			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	name	0..1	None
	local_identifier	0..1	None
	offset	1..1	None
	object_length	0..1	None
	parsing_standard_id	1..1	Schematron ISO/IEC 19757-3:2006, XML Schema Version 1.1
	description	0..1	None

Support classes in the
common (pds) namespace.

Name: XML_Schema			Version Id: 1.0.0.0
	ldd_version_id	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Digital_Object
<i>Referenced from:</i> File_Area_XML_Schema			

Zip

Name: Zip			Version Id: 1.0.0.0
<i>Description:</i> The Zip class describes a zip file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Supplemental :: Zip			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	container_type	1..1	GZIP, LZIP, TAR, ZIP
	description	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Product_Zipped			

Chapter 4. PDS3 catalog classes in the common (pds) namespace.

These classes are used to archive PDS3 catalog information.

Data_Set_PDS3

<i>Name:</i> Data_Set_PDS3			<i>Version Id:</i> 1.0.0.0
<i>Description:</i> The Data Set PDS3 class is used to capture the data set information from the PDS3 Data Set Catalog.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Data_Set_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	data_set_id	1..1	None
	data_set_name	1..1	None
	data_set_release_date	1..1	None
	start_time	0..1	None
	start_date_time *Deprecated*	0..1	None
	stop_time	0..1	None
	stop_date_time *Deprecated*	0..1	None
	producer_full_name	1..1	None
	citation_text	1..1	None
	data_set_terse_desc	1..1	None
	abstract_desc	1..1	None
	data_set_desc	1..1	None
	confidence_level_note	1..1	None
	archive_status	1..1	ARCHIVED, ARCHIVED_ ACCUMULATING, IN_LIEN_ RESOLUTION, IN_ LIEN_RESOLUTION_ ACCUMULATING, IN_PEER_REVIEW, IN_PEER_REVIEW_ ACCUMULATING, IN_QUEUE, IN_QUEUE_ ACCUMULATING, LOCALLY_ ARCHIVED, LOCALLY_ ARCHIVED_ ACCUMULATING, PRE_PEER_ REVIEW, PRE_

Name: Data_Set_PDS3			Version Id: 1.0.0.0
			PEER_REVIEW_ ACCUMULATING, SAFED, SUPERSEDED
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object, Physical_Object
	nssdc	0..Unbounded	NSSDC
<i>Referenced from:</i> Product_Data_Set_PDS3			

Instrument_Host_PDS3

Name: Instrument_Host_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Instrument Host class provides a description of the physical object upon which an instrument is mounted. This class captures the PDS3 catalog Instrument Host information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Instrument_Host_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	instrument_host_name	1..1	None
	instrument_host_desc	1..1	None
	instrument_host_id	1..1	None
	instrument_host_type	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Instrument_Host_PDS3			

Instrument_PDS3

Name: Instrument_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Instrument class provides a description of a physical object that collects data. This class captures the PDS3 catalog Instrument information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Instrument_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	instrument_name	1..1	None
	instrument_desc	1..1	None
	instrument_id	1..1	None
	instrument_serial_ number	1..1	None
	instrument_type	1..1	None
	instrument_version_id	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Instrument_PDS3			

Mission_PDS3

Name: Mission_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Mission PDS3 class describes an activity involved in the collection of data. This class captures the PDS3 catalog Mission information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Mission_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	mission_name	1..1	None
	mission_desc	1..1	None
	mission_objectives_summary	1..1	None
	mission_start_date	1..1	None
	mission_stop_date	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object
<i>Referenced from:</i> Product_Mission_PDS3			

Subscriber_PDS3

Name: Subscriber_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Subscriber PDS3 class provides the name of the subscriber and their subscription list.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Subscriber_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	full_name	1..1	None
	local_identifier	0..1	None
	subscription_id	1..Unbounded	None
<i>No Associations</i>			
<i>Referenced from:</i> Product_Subscription_PDS3			

TNDO_Context_PDS3

Name: TNDO_Context_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Tagged NonDigital Object (TNDO) Context PDS3 class is an abstract class for the PDS3 context class hierarchy.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3			
<i>No Attributes</i>			
<i>No Associations</i>			
<i>Referenced from:</i> None			

Target_PDS3

Name: Target_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Target class provides a description of a physical object that is the object of data collection. This class captures the PDS3 catalog Target information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Target_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	target_name	1..1	None
	orbit_direction	0..Unbounded	None
	primary_body_name	1..1	None
	rotation_direction	0..1	None
	target_desc	1..1	None
	target_type	1..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Physical_Object
<i>Referenced from:</i> Product_Target_PDS3			

Volume_PDS3

Name: Volume_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Volume_PDS3 class is used to capture the volume information from the PDS3 Data Set Catalog.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Volume_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	archive_status	1..1	ARCHIVED, ARCHIVED_ ACCUMULATING, IN_LIEN_ RESOLUTION, IN_ LIEN_RESOLUTION_ ACCUMULATING, IN_PEER_REVIEW, IN_PEER_REVIEW_ ACCUMULATING, IN_QUEUE, IN_QUEUE_ ACCUMULATING, LOCALLY_ ARCHIVED, LOCALLY_ ARCHIVED_ ACCUMULATING, PRE_PEER_ REVIEW, PRE_ PEER_REVIEW_ ACCUMULATING,

Name: Volume_PDS3			Version Id: 1.0.0.0
			SAFED, SUPERSEDED
	archive_status_note	1..1	None
	curating_node_id	0..Unbounded	None
	medium_type	1..1	None
	publication_date	1..1	None
	volume_de_fullname	1..1	None
	volume_format	1..1	None
	volume_id	1..1	None
	volume_name	1..1	None
	volume_set_id	1..1	None
	volume_size	1..1	None
	volume_version_id	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object, Physical_Object
<i>Referenced from:</i> Product_Volume_PDS3			

Volume_Set_PDS3

Name: Volume_Set_PDS3			Version Id: 1.0.0.0
<i>Description:</i> The Volume_Set_PDS3 class is used to capture the volume set information from the PDS3 Data Set Catalog.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Tagged_NonDigital_Object :: TNDO_Context_PDS3 :: Volume_Set_PDS3			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	volume_series_name	1..1	None
	volume_set_id	1..1	None
	volume_set_name	1..1	None
	volumes	1..1	None
	description	0..1	None
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	data_object	1..1	Conceptual_Object, Physical_Object
<i>Referenced from:</i> Product_Volume_Set_PDS3			

Chapter 5. Classes in the Rings discipline namespace.

These classes have been defined for the Rings science discipline and can be used in the label's discipline area.

Radio_Occultation

Name: Radio_Occultation			Version Id: 1.1.0.0
<i>Description:</i> This class is required for all radio ring occultations			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Radio_Occultation			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	ring_observation_id	1..1	None
	orbit_number	0..Unbounded	None
	SCLK_start_time	0..1	None
	SCLK_stop_time	0..1	None
	occultation_type	1..1	Radio, Solar, Stellar
	dsn_station_number	1..1	None
	source_pds3_id	0..Unbounded	None
	frequency_band	1..1	C, D, E, F, G, H, K, Ka, Ku, Q, R, S, U, V, W, X, Y
	ring_occultation_direction	1..1	Both, Egress, Ingress, Multiple
	ring_profile_direction	1..1	Egress, Ingress, Multiple
	planetary_occultation_flag	0..1	N, Y
	wavelength	0..1	None
	minimum_wavelength	0..1	None
	reference_time_utc	1..1	None
	maximum_wavelength	0..1	None
	radial_resolution	1..1	None
	radial_sampling_interval	0..1	None
	minimum_radial_sampling_interval	0..1	None
	maximum_radial_sampling_interval	0..1	None
	observed_event_start_tdb	0..1	None
	observed_event_stop_tdb	0..1	None

Classes in the Rings
discipline namespace.

Name: Radio_Occultation			Version Id: 1.1.0.0
	spacecraft_event_start_time_utc	1..1	None
	spacecraft_event_stop_time_utc	1..1	None
	ring_event_start_time_utc	0..1	None
	ring_event_stop_time_utc	0..1	None
	ring_event_start_tdb	0..1	None
	ring_event_stop_tdb	0..1	None
	earth_received_start_time_utc	0..1	None
	earth_received_stop_time_utc	0..1	None
	minimum_ring_radius	1..1	None
	maximum_ring_radius	1..1	None
	minimum_ring_longitude	1..1	None
	maximum_ring_longitude	1..1	None
	minimum_observed_ring_azimuth	1..1	None
	maximum_observed_ring_azimuth	1..1	None
	observed_ring_elevation	0..1	None
	minimum_observed_ring_elevation	0..1	None
	maximum_observed_ring_elevation	0..1	None
	light_source_incidence_angle	0..1	None
	minimum_light_source_incidence_angle	0..1	None
	maximum_light_source_incidence_angle	0..1	None
	lowest_detectable_opacity	0..1	None
	highest_detectable_opacity	0..1	None
	along_track_timing_offset	0..1	None
<i>No Associations</i>			
<i>Referenced from: None</i>			

Radio_Occultation_Support

Name: Radio_Occultation_Support			Version Id: 1.1.0.0
<i>Description:</i> This class is required for all radio ring occultation calibration and geometry supplemental files.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Radio_Occultation_Support			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	ring_observation_id	1..1	None
	orbit_number	0..Unbounded	None
	spice_filename	0..Unbounded	None
	occultation_type	1..1	Radio, Solar, Stellar
	dsn_station_number	1..1	None
	frequency_band	1..1	C, D, E, F, G, H, K, Ka, Ku, Q, R, S, U, V, W, X, Y
	ring_occultation_direction	1..1	Both, Egress, Ingress, Multiple
	ring_profile_direction	1..1	Egress, Ingress, Multiple
	planetary_occultation_flag	0..1	N, Y
	sampling_parameter_name	1..1	None
	sampling_parameter_unit	1..1	None
	sampling_parameter_interval	1..1	None
	reference_time_utc	1..1	None
	minimum_observed_event_time	1..1	None
	maximum_observed_event_time	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> None			

Rings_Supplement

Name: Rings_Supplement			Version Id: 1.1.0.0
<i>Description:</i> This class is required for all Rings Node curated data products			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Rings_Supplement			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	ring_observation_id	1..1	None
	source_pds3_id	0..Unbounded	None

Name: Rings_Supplement		Version Id: 1.1.0.0
<i>No Associations</i>		
<i>Referenced from: None</i>		

Stellar_Occultation

Name: Stellar_Occultation		Version Id: 1.1.0.0	
<i>Description:</i> This class is required for all stellar ring occultations			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Stellar_Occultation			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	ring_observation_id	1..1	None
	orbit_number	0..Unbounded	None
	SCLK_start_time	0..1	None
	SCLK_stop_time	0..1	None
	occultation_type	1..1	Radio, Solar, Stellar
	source_pds3_id	0..Unbounded	None
	ring_occultation_direction	1..1	Both, Egress, Ingress, Multiple
	star_name	1..1	None
	ring_profile_direction	1..1	Egress, Ingress, Multiple
	planetary_occultation_flag	0..1	N, Y
	wavelength	0..1	None
	minimum_wavelength	0..1	None
	maximum_wavelength	0..1	None
	radial_resolution	1..1	None
	radial_sampling_interval	0..1	None
	minimum_radial_sampling_interval	0..1	None
	maximum_radial_sampling_interval	0..1	None
	observed_event_start_tdb	0..1	None
	observed_event_stop_tdb	0..1	None
	ring_event_start_time_utc	0..1	None
	ring_event_stop_time_utc	0..1	None
	ring_event_start_tdb	0..1	None
	ring_event_stop_tdb	0..1	None
	minimum_ring_radius	1..1	None

Classes in the Rings
discipline namespace.

Name: Stellar_Occultation			Version Id: 1.1.0.0
	maximum_ring_radius	1..1	None
	sub_stellar_ring_azimuth	0..1	None
	minimum_ring_longitude	1..1	None
	sub_stellar_clock_angle	0..1	None
	maximum_ring_longitude	1..1	None
	minimum_observed_ring_azimuth	1..1	None
	maximum_observed_ring_azimuth	1..1	None
	observed_ring_elevation	0..1	None
	minimum_observed_ring_elevation	0..1	None
	maximum_observed_ring_elevation	0..1	None
	light_source_incidence_angle	0..1	None
	lowest_detectable_opacity	0..1	None
	highest_detectable_opacity	0..1	None
<i>No Associations</i>			
<i>Referenced from: None</i>			

Chapter 6. Classes in the Imaging discipline namespace.

These classes have been defined for the Imaging science discipline and can be used in the label's discipline area.

Telemetry_Parameters

Name: Telemetry_Parameters			Version Id: 1.0.0.0
<i>Description:</i> The Telemetry_Parameters class contains downlink-related attributes used primarily during mission operations.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Telemetry_Parameters			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	application_process_id	0..1	None
	application_process_name	0..1	None
	earth_received_start_date_time	0..1	None
	earth_received_stop_date_time	0..1	None
	expected_packets	0..1	None
	packet_map_mask	0..1	None
	received_packets	0..1	None
	spice_file_name	0..1	None
	telemetry_format_id	0..1	None
	telemetry_provider_id	0..1	None
	telemetry_source_name	0..1	None
	telemetry_source_type	0..1	DATA_PRODUCT, SFDU
<i>No Associations</i>			
<i>Referenced from:</i> None			

Chapter 7. Classes in the Display namespace.

This dictionary describes how to display Array data on a display device.

Color_Display_Settings

Name: Color_Display_Settings			Version Id: 1.0.0.0
<i>Description:</i> The Color_Display_Settings class provides guidance to data users on how to display a multi-banded Array object on a color-capable display device.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Color_Display_Settings			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	color_display_axis	1..1	None
	comment	0..1	None
	red_channel_band	1..1	None
	green_channel_band	1..1	None
	blue_channel_band	1..1	None
<i>No Associations</i>			
<i>Referenced from:</i> Display_Settings			

Display_Direction

Name: Display_Direction			Version Id: 1.0.0.0
<i>Description:</i> The Display_Direction class specifies how two of the dimensions of an Array object should be displayed in the vertical (line) and horizontal (sample) dimensions of a display device.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Display_Direction			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	comment	0..1	None
	horizontal_display_axis	1..1	None
	horizontal_display_direction	1..1	Left to Right, Right to Left
	vertical_display_axis	1..1	None
	vertical_display_direction	1..1	Bottom to Top, Top to Bottom
<i>No Associations</i>			
<i>Referenced from:</i> Display_Settings			

Display_Settings

Name: Display_Settings			Version Id: 1.0.0.0
<i>Description:</i> The Display_Settings class contains one or more classes describing how data should be displayed on a display device.			

Name: Display_Settings			Version Id: 1.0.0.0
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Display_Settings			
<i>No Attributes</i>			
<i>Association(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Class</i>
	local_internal_reference	1..1	Local_Internal_Reference
	has_display_direction	1..1	Display_Direction
	has_color_display_settings	0..1	Color_Display_Settings
	has_movie_display_settings	0..1	Movie_Display_Settings
<i>Referenced from:</i> None			

Movie_Display_Settings

Name: Movie_Display_Settings			Version Id: 1.0.0.0
<i>Description:</i> The Movie_Display_Settings class provides default values for the display of a multi-banded Array using a software application capable of displaying video content.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Role:</i> concrete	<i>Status:</i> Active
<i>Class Hierarchy:</i> Product_Components :: Movie_Display_Settings			
<i>Attribute(s)</i>	<i>Name</i>	<i>Cardinality</i>	<i>Value</i>
	time_display_axis	1..1	None
	comment	0..1	None
	frame_rate	0..1	None
	loop_flag	0..1	false, true
	loop_count	0..1	None
	loop_delay	0..1	None
	loop_back_and_forth_flag	0..1	false, true
<i>No Associations</i>			
<i>Referenced from:</i> Display_Settings			

Chapter 8. Attributes in the common (pds) namespace.

These attributes are used by the classes in the common (pds) namespace.

abstract_desc in Data_Set_PDS3

Name: abstract_desc			Version Id: 1.0.0.0
<i>Description:</i> The abstract desc attribute provides a summary of a text, scientific article, or document.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

abstract_flag in DD_Class

Name: abstract_flag			Version Id: 1.0.0.0
<i>Description:</i> The abstract flag attribute indicates whether or not the class can be instantiated. Abstract flag is only included if a value of 'true' is desired and indicates that the class is abstract and cannot be used in a label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

abstract_flag in DD_Class_Full

Name: abstract_flag			Version Id: 1.0.0.0
<i>Description:</i> The abstract flag attribute indicates whether or not the class can be instantiated. Abstract flag is only included if a value of 'true' is desired and indicates that the class is abstract and cannot be used in a label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	

Name: abstract_flag		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

acknowledgement_text in Document

Name: acknowledgement_text		Version Id: 1.0.0.0	
<i>Description:</i> The acknowledgement_text attribute is a character string which recognizes another's contribution, authority, or right.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

address in Facility

Name: address		Version Id: 1.0.0.0	
<i>Description:</i> The address attribute provides a mailing address.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Facility	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Address	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

affiliation_type in PDS_Affiliate

Name: affiliation_type		Version Id: 1.0.0.0	
<i>Description:</i> The affiliation type data attribute describes the type of relationship an individual has with the PDS.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Affiliate	The PDS_Affiliate has affiliation type Affiliate	
	Data Provider	The PDS_Affiliate has affiliation type Data Provider	

Name: affiliation_type		Version Id: 1.0.0.0
	Manager	The PDS_Affiliate has affiliation type Manager
	Technical Staff	The PDS_Affiliate has affiliation type Technical Staff

alternate_designation in Target_Identification

Name: alternate_designation			Version Id: 1.0.0.0
<i>Description:</i> The alternate_designation attribute provides aliases.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target_ Identification	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

alternate_id in Alias

Name: alternate_id			Version Id: 1.0.0.0
<i>Description:</i> The alternate_id attribute provides an additional identifier supplied by the data provider.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Alias	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

alternate_telephone_number in PDS_Affiliate

Name: alternate_telephone_number			Version Id: 1.0.0.0
<i>Description:</i> The telephone_number attribute provides a telephone number in international notation in compliance with the E.164 telephone number format recommendation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_ Affiliate	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

alternate_title in Alias

Name: alternate_title			Version Id: 1.0.0.0
<i>Description:</i> The alternate_title attribute provides an alternate title for the product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Alias	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Title	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

altitude in Telescope

Name: altitude			Version Id: 1.0.0.0
<i>Description:</i> The altitude attribute provides the height of anything above a given reference plane.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Telescope	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> m	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

aperture in Telescope

Name: aperture			Version Id: 1.0.0.0
<i>Description:</i> The aperture attribute provides the diameter of an opening, usually circular, that limits the quantity of light that can enter an optical instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Telescope	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> m	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

archive_status in Data_Set_PDS3

Name: archive_status		Version Id: 1.0.0.0
<i>Description:</i> The ARCHIVE_STATUS attribute indicates the stage to which a data set has progressed in the archiving process, from IN QUEUE through ARCHIVED. It can also take on the values SUPERSEDED or SAFED, which indicate that the data set is not part of the active archive. ACCUMULATING can be appended to some values to indicate that the data set is incomplete and/or that not all components have reached the stage given by the root value; ACCUMULATING		

Attributes in the common
(pds) namespace.

Name: archive_status			Version Id: 1.0.0.0
would be used, for example, when the archive is being delivered incrementally, as from a mission that lasts many months or years.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Status	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ARCHIVED	Archive status of the PDS3 data set is ARCHIVED (passed peer review with all liens resolved. Available through the Data Set Catalog and at NSSDC).	
	ARCHIVED_ACCUMULATING	Archive status of the PDS3 data set is ARCHIVED_ACCUMULATING (some parts of the data set are ARCHIVED, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).	
	IN_LIEN_RESOLUTION	Archive status of the PDS3 data set is IN_LIEN_RESOLUTION (peer review completed; liens are in the process of being resolved; use with caution).	
	IN_LIEN_RESOLUTION_ACCUMULATING	Archive status of the PDS3 data set is IN_LIEN_RESOLUTION_ACCUMULATING (some parts of the data set are IN LIEN_RESOLUTION, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).	
	IN_PEER_REVIEW	Archive status of the PDS3 data set is IN_PEER_REVIEW (under peer review at the curation node but evaluation is not complete; use with caution).	
	IN_PEER_REVIEW_ACCUMULATING	Archive status of the PDS3 data set is IN_PEER_REVIEW_ACCUMULATING (some parts of the data set are IN PEER REVIEW, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).	
	IN_QUEUE	Archive status of the PDS3 data set is IN_QUEUE (received at the curation node but no action has been taken by the curation node; use with caution).	
	IN_QUEUE_ACCUMULATING	Archive status of the PDS3 data set is IN_QUEUE_ACCUMULATING (some parts of the data set are IN_QUEUE, but other parts have not yet been delivered to PDS; use with caution).	
	LOCALLY_ARCHIVED	Archive status of the PDS3 data set is LOCALLY_ARCHIVED (passed peer review with all liens resolved; considered archived by	

Name: archive_status		Version Id: 1.0.0.0
		the curation node but awaiting completion of the standard archiving process; possible TBD items include the arrival of the archive volume at NSSDC and ingestion of catalog information into the Data Set Catalog).
	LOCALLY_ARCHIVED_ACCUMULATING	Archive status of the PDS3 data set is LOCALLY_ARCHIVED_ACCUMULATING (some parts of the data set are LOCALLY_ARCHIVED , but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).
	PRE_PEER_REVIEW	Archive status of the PDS3 data set is PRE_PEER_REVIEW (being prepared for peer review under the direction of the curation node; use with caution).'
	PRE_PEER_REVIEW_ACCUMULATING	Archive status of the PDS3 data set is PRE_PEER_REVIEW_ACCUMULATING (some parts of the data set are in PRE_PEER_REVIEW , but other parts are IN_QUEUE and/or have not yet been delivered to PDS; use with caution).
	SAFED	Archive status of the PDS3 data set is SAFED (the data set has been received by the PDS with no evaluation; data will not be formally archived).
	SUPERSEDED	Archive status of the PDS3 data set is SUPERSEDED (this data set has been replaced by a newer version, implying that the data set is not to be used unless the requester has specific reasons; when a data set has been superseded the Engineering Node, will notify NSSDC that their databases need to be updated to advise users of the new status and the location of the replacement data set).

archive_status in Volume_PDS3

Name: archive_status		Version Id: 1.0.0.0	
<i>Description:</i> The ARCHIVE_STATUS attribute indicates the stage to which a data set has progressed in the archiving process, from IN_QUEUE through ARCHIVED. It can also take on the values SUPERSEDED or SAFED, which indicate that the data set is not part of the active archive. ACCUMULATING can be appended to some values to indicate that the data set is incomplete and/or that not all components have reached the stage given by the root value; ACCUMULATING would be used, for example, when the archive is being delivered incrementally, as from a mission that lasts many months or years.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Status	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	

Attributes in the common
(pds) namespace.

<i>Name: archive_status</i>		<i>Version Id: 1.0.0.0</i>
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	ARCHIVED	Archive status of the PDS3 volume is ARCHIVED (passed peer review with all liens resolved. Available through the Data Set Catalog and at NSSDC).
	ARCHIVED_ACCUMULATING	Archive status of the PDS3 volume is ARCHIVED_ACCUMULATING (some parts of the volume are ARCHIVED, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).
	IN_LIEN_RESOLUTION	Archive status of the PDS3 volume is IN_LIEN_RESOLUTION (peer review completed; liens are in the process of being resolved; use with caution).
	IN_LIEN_RESOLUTION_ACCUMULATING	Archive status of the PDS3 volume is IN_LIEN_RESOLUTION_ACCUMULATING (some parts of the volume are IN LIEN RESOLUTION, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).
	IN_PEER_REVIEW	Archive status of the PDS3 volume is IN_PEER_REVIEW (under peer review at the curation node but evaluation is not complete; use with caution).
	IN_PEER_REVIEW_ACCUMULATING	Archive status of the PDS3 volume is IN_PEER_REVIEW_ACCUMULATING (some parts of the volume are IN PEER REVIEW, but other parts are in earlier stages of the archiving process and/or have not yet been delivered to PDS; use with caution).
	IN_QUEUE	Archive status of the PDS3 volume is IN_QUEUE (received at the curation node but no action has been taken by the curation node; use with caution).
	IN_QUEUE_ACCUMULATING	Archive status of the PDS3 volume is IN_QUEUE_ACCUMULATING (some parts of the volume are IN QUEUE, but other parts have not yet been delivered to PDS; use with caution).
	LOCALLY_ARCHIVED	Archive status of the PDS3 volume is LOCALLY_ARCHIVED (passed peer review with all liens resolved; considered archived by the curation node but awaiting completion of the standard archiving process; possible TBD items include the arrival of the archive volume at NSSDC and ingestion of catalog information into the Data Set Catalog).
	LOCALLY_ARCHIVED_ACCUMULATING	Archive status of the PDS3 volume is LOCALLY_ARCHIVED_ACCUMULATING (some parts of the volume are LOCALLY ARCHIVED, but other parts are in earlier stages

Attributes in the common
(pds) namespace.

Name: archive_status		Version Id: 1.0.0.0
		of the archiving process and/or have not yet been delivered to PDS; use with caution).
	PRE_PEER_REVIEW	Archive status of the PDS3 volume is PRE_PEER_REVIEW (being prepared for peer review under the direction of the curation node; use with caution).
	PRE_PEER_REVIEW_ACCUMULATING	Archive status of the PDS3 volume is PRE_PEER_REVIEW_ACCUMULATING (some parts of the volume are in PRE PEER REVIEW, but other parts are IN QUEUE and/or have not yet been delivered to PDS; use with caution).
	SAFED	Archive status of the PDS3 volume is SAFED (the volume has been received by the PDS with no evaluation; data will not be formally archived).
	SUPERSEDED	Archive status of the PDS3 volume is SUPERSEDED (this volume has been replaced by a newer version, implying that the volume is not to be used unless the requester has specific reasons; when a volume has been superseded the Engineering Node, will notify NSSDC that their databases need to be updated to advise users of the new status and the location of the replacement volume).

archive_status_note in Volume_PDS3

Name: archive_status_note		Version Id: 1.0.0.0	
<i>Description:</i> The archive status note attribute provides a comment about the archive status.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

attribute_concept in DD_Attribute_Full

Name: attribute_concept		Version Id: 1.0.0.0	
<i>Description:</i> The attribute_concept attribute provides the type of information (classification) conveyed by the attribute -- e.g., stop_date_time has attribute_concept = date_time.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Attributes in the common
(pds) namespace.

Name: attribute_concept			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Address	The attribute has been classified as being an Address	
	Angle	The attribute has been classified as being an Angle	
	Attribute	The attribute has been classified as being an Attribute	
	Bit	The attribute has been classified as being a Bit	
	Checksum	The attribute has been classified as being a Checksum	
	Collection	The attribute has been classified as being a Collection	
	Constant	The attribute has been classified as being a Constant	
	Cosine	The attribute has been classified as being a Cosine	
	Count	The attribute has been classified as being a Count	
	DOI	The attribute has been classified as being a DOI	
	Delimiter	The attribute has been classified as being a Delimiter	
	Description	The attribute has been classified as being a Description	
	Deviation	The attribute has been classified as being a Deviation	
	Direction	The attribute has been classified as being a Direction	
	Distance	The attribute has been classified as being a Distance	
	Duration	The attribute has been classified as being a Duration	
	Factor	The attribute has been classified as being a Factor	
	Flag	The attribute has been classified as being a Flag	
	Format	The attribute has been classified as being a Format	
	Group	The attribute has been classified as being a Group	
	Home	The attribute has been classified as being a Home	
	ID	The attribute has been classified as being an Identifier	
	Latitude	The attribute has been classified as being a Latitude	

Attributes in the common
(pds) namespace.

Name: attribute_concept		Version Id: 1.0.0.0
	Length	The attribute has been classified as being a Length
	List	The attribute has been classified as being a List
	Location	The attribute has been classified as being a Location
	Logical	The attribute has been classified as being a Logical
	Longitude	The attribute has been classified as being a Longitude
	Mask	The attribute has been classified as being a Mask
	Maximum	The attribute has been classified as being a Maximum
	Mean	The attribute has been classified as being a Mean
	Median	The attribute has been classified as being a Median
	Minimum	The attribute has been classified as being a Minimum
	Name	The attribute has been classified as being a Name
	Note	The attribute has been classified as being a Note
	Number	The attribute has been classified as being a Number
	Offset	The attribute has been classified as being an Offset
	Order	The attribute has been classified as being an Order
	Parallel	The attribute has been classified as being a Parallel
	Password	The attribute has been classified as being a Password
	Path	The attribute has been classified as being a Path
	Pattern	The attribute has been classified as being a Pattern
	Pixel	The attribute has been classified as being a Pixel
	Quaternion	The attribute has been classified as being a Quaternion
	Radius	The attribute has been classified as being a Radius
	Ratio	The attribute has been classified as being a Ratio
	Reference	The attribute has been classified as being a Reference
	Resolution	The attribute has been classified as being a Resolution
	Role	The attribute has been classified as being a Role
	Rotation	The attribute has been classified as being a Rotation

Attributes in the common
(pds) namespace.

Name: attribute_concept		Version Id: 1.0.0.0
	Scale	The attribute has been classified as being a Scale
	Sequence	The attribute has been classified as being a Sequence
	Set	The attribute has been classified as being a Set
	Size	The attribute has been classified as being a Size
	Status	The attribute has been classified as being a Status
	Summary	The attribute has been classified as being a Summary
	Syntax	The attribute has been classified as being a Syntax
	Temperature	The attribute has been classified as being a Temperature
	Text	The attribute has been classified as being a Text
	Title	The attribute has been classified as being a Title
	Type	The attribute has been classified as being a Type
	Unit	The attribute has been classified as being a Unit
	Unknown	The attribute has an Unknown classification
	Value	The attribute has been classified as being a Value
	Vector	The attribute has been classified as being a Vector

author_list in Citation_Information

Name: author_list		Version Id: 1.0.0.0	
<i>Description:</i> The author_list attribute provides a list of people to be cited as the authors of the associated product. Lists are constructed with last names first and first and middle names and/or initials following. Initials are terminated by periods and delimited by single spaces. Suffixes (if applicable) follow everything else, after a final comma. Hyphenated names may be reduced to initials as "J.-P." Each person's full name is separated from the next by a semi-colon. There is no "and" before the last name. If there is no author list, editor_list must be present and non-null.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Citation_Information	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> List	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

author_list in Document

Name: author_list		Version Id: 1.0.0.0
<i>Description:</i> The author_list attribute provides a list of people to be cited as the authors of the associated product. Lists are constructed with last names first and first and middle names and/or initials following. Initials are terminated by periods and delimited by single spaces. Suffixes		

Name: author_list			Version Id: 1.0.0.0
(if applicable) follow everything else, after a final comma. Hyphenated names may be reduced to initials as "J.-P." Each person's full name is separated from the next by a semi-colon. There is no "and" before the last name. If there is no author list, editor_list must be present and non-null.			
Namespace Id: pds	Steward: pds	Class Name: Document	Type: UTF8_Text_Preserved
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: List	Conceptual Domain: Text
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

author_list in Software

Name: author_list			Version Id: 1.0.0.0
<i>Description:</i> The author_list attribute provides a list of people to be cited as the authors of the associated product. Lists are constructed with last names first and first and middle names and/or initials following. Initials are terminated by periods and delimited by single spaces. Suffixes (if applicable) follow everything else, after a final comma. Hyphenated names may be reduced to initials as "J.-P." Each person's full name is separated from the next by a semi-colon. There is no "and" before the last name. If there is no author list, editor_list must be present and non-null.			
Namespace Id: pds	Steward: ops	Class Name: Software	Type: UTF8_Text_Preserved
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: List	Conceptual Domain: Text
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

axes in Array

Name: axes			Version Id: 1.0.0.0
<i>Description:</i> The axes attribute provides a count of the axes.			
Namespace Id: pds	Steward: pds	Class Name: Array	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: 16	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

axes in Array_1D

Name: axes			Version Id: 1.0.0.0
<i>Description:</i> The axes attribute provides a count of the axes.			
Namespace Id: pds	Steward: pds	Class Name: Array_1D	Type: ASCII_Integer

Name: axes			Version Id: 1.0.0.0
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> 16	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Array_1D has 1 axis	

axes in Array_2D

Name: axes			Version Id: 1.0.0.0
<i>Description:</i> The axes attribute provides a count of the axes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Array_2D	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> 16	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	2	Array_2D has 2 axes	

axes in Array_3D

Name: axes			Version Id: 1.0.0.0
<i>Description:</i> The axes attribute provides a count of the axes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Array_3D	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> 16	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	3	Array_2D has 3 axes	

axis_index_order in Array

Name: axis_index_order			Version Id: 1.0.0.0
<i>Description:</i> The axis_index_order attribute provides the axis index that varies fastest with respect to storage order.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Array	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Order	<i>Conceptual Domain:</i> Short_String

Name: axis_index_order		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	Value	Value Meaning
	Last Index Fastest	The values of a multi-dimensional array are stored in an order such that the last index changes fastest and the first index slowest.

axis_name in Axis_Array

Name: axis_name		Version Id: 1.0.0.0	
<i>Description:</i> The axis_name attribute provides a word or combination of words by which the axis is known.			
Namespace Id: pds	Steward: pds	Class Name: Axis_Array	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

band_number in Band_Bin *Deprecated*

Name: band_number		Version Id: 1.0.0.0	
<i>Description:</i> The band_number attribute provides a number corresponding to the band in the spectral cube. The band number is equivalent to the instrument band number.			
Namespace Id: pds	Steward: img	Class Name: Band_Bin *Deprecated*	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: 512	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

band_width in Band_Bin *Deprecated*

Name: band_width		Version Id: 1.0.0.0	
<i>Description:</i> The band_width attributes provides the width, at half height, of the band.			
Namespace Id: pds	Steward: img	Class Name: Band_Bin *Deprecated*	Type: ASCII_Real
Minimum Value: 0	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Length	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Real
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

bit_fields in Packed_Data_Fields

Name: bit_fields			Version Id: 1.0.0.0
<i>Description:</i> The bit_fields attribute provides the number of defined bit fields (Field_Bit definitions) within the Packed_Data_Field.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Packed_Data_Fields	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

bit_mask in Object_Statistics

Name: bit_mask			Version Id: 1.0.0.0
<i>Description:</i> The bit_mask attribute is a series of binary digits identifying the active bits in a value; it has exactly the same number of the bits as the array element to which it is applied.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Numeric_Base2
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Mask	<i>Conceptual Domain:</i> Numeric
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

bit_string in Digital_Object

Name: bit_string			Version Id: 1.0.0.0
<i>Description:</i> The bit string attribute is a sequence of digital bits. It is the content of a digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Digital_Object	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

bundle_type in Bundle

Name: bundle_type			Version Id: 1.0.0.0
<i>Description:</i> The bundle_type attribute provides a classification for the bundle.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: bundle_type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Archive	The Bundle contains at least one data collection	
	Supplemental	The Bundle does not contain a data collection	

center_wavelength in Band_Bin *Deprecated*

Name: center_wavelength			Version Id: 1.0.0.0
<i>Description:</i> The center_wavelength attribute provides the wavelength or frequency describing the center of a bin along the band axis of a spectral cube. When describing data from a spectrometer, the value corresponds to the peak of the response function for a particular detector and/or grating position.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Band_Bin *Deprecated*	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in ASCII_AnyURI

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_AnyURI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_AnyURI must be limited to the ASCII encoding character set.	

character_constraint in ASCII_DOI

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed

Name: character_constraint			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_DOI must be ASCII	

character_constraint in ASCII_Date

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date must be ASCII	

character_constraint in ASCII_Date_DOY

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date_DOY	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_DOY must be ASCII	

character_constraint in ASCII_Date_Time

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date_Time	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255

Name: character_constraint			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_Time must be ASCII	

character_constraint in ASCII_Date_Time_DOY

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_Time_DOY must be ASCII	

character_constraint in ASCII_Date_Time_UTC

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_Time_UTC must be ASCII	

character_constraint in ASCII_Date_Time_YMD

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			

Name: character_constraint			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_Time_YMD must be ASCII	

character_constraint in ASCII_Date_YMD

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Date_YMD must be ASCII	

character_constraint in ASCII_Directory_Path_Name

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Directory_Path_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Directory_Path_Name must be ASCII	

character_constraint in ASCII_File_Name

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			

Name: character_constraint			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_File_Name must be ASCII	

character_constraint in ASCII_File_Specification_Name

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Specification_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_File_Specification_Name must be ASCII	

character_constraint in ASCII_Integer

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in ASCII_LID

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			

Name: character_constraint			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_LID must be ASCII	

character_constraint in ASCII_LIDVID

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_LIDVID must be ASCII	

character_constraint in ASCII_LIDVID_LID

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_LIDVID_LID must be ASCII	

character_constraint in ASCII_MD5_Checksum

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed

Name: character_constraint			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_MD5_Checksum must be ASCII	

character_constraint in ASCII_NonNegative_Integer

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in ASCII_Numeric_Base16

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in ASCII_Numeric_Base2

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: character_constraint			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Numeric_Base2 must be ASCII	

character_constraint in ASCII_Numeric_Base8

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base8	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Numeric_Base8 must be ASCII	

character_constraint in ASCII_Real

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Real	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in ASCII_Short_String_Collapsed

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			

Name: character_constraint			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Short_String_Collapsed must be ASCII	

character_constraint in ASCII_Short_String_Preserved

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Short_String_Preserved must be ASCII	

character_constraint in ASCII_String

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_String	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_String must be ASCII	

character_constraint in ASCII_Text_Collapsed

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Text_Collapsed must be ASCII	

character_constraint in ASCII_Text_Preserved

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Text_Preserved must be ASCII	

character_constraint in ASCII_Time

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_Time must be ASCII	

character_constraint in ASCII_VID

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII	Values of ASCII_VID must be ASCII	

character_constraint in Character_Data_Type

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in UTF8_Short_String_Collapsed

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in UTF8_Short_String_Preserved

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_constraint in UTF8_Text_Preserved

Name: character_constraint			Version Id: 1.0.0.0
<i>Description:</i> The character_constraint attribute limits the characters allowed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

character_encoding in ASCII_AnyURI

Name: character_encoding			Version Id: 1.0.0.0
<i>Description:</i> The character_encoding attribute identifies the standard that maps a set of allowed characters to their machine readable code.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_AnyURI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	UTF-8	Values of ASCII_AnyURI have UTF-8 character encoding.	

character_encoding in Character_Data_Type

Name: character_encoding			Version Id: 1.0.0.0
<i>Description:</i> The character_encoding attribute identifies the standard that maps a set of allowed characters to their machine readable code.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	UTF-8	Values of Character_Data_Type have UTF-8 character encoding	

checksum_manifest_checksum in Information_Package_Component

Name: checksum_manifest_checksum			Version Id: 1.0.0.0
<i>Description:</i> The checksum manifest checksum provides the checksum for the checksum manifest file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Information_Package_Component	<i>Type:</i> ASCII_MD5_Checksum
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Checksum	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

checksum_type in Information_Package_Component

Name: checksum_type			Version Id: 1.0.0.0
<i>Description:</i> The checksum type attribute provides the name of the checksum algorithm used to calculate the checksum value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Information_Package_Component	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: checksum_type		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

citation_text in Data_Set_PDS3

Name: citation_text		Version Id: 1.0.0.0	
<i>Description:</i> The citation_text attribute provides a character string containing a literature or other citation in sufficient detail that the material could be located in PDS or elsewhere.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

class_name in DD_Attribute_Full

Name: class_name		Version Id: 1.0.0.0	
<i>Description:</i> The class_name attribute provides the common name by which the class is identified, as well as the class within which the attribute is used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

collection_type in Collection

Name: collection_type		Version Id: 1.0.0.0	
<i>Description:</i> The collection_type attribute provides a classification for the collection.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Collection	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Browse	This is a BROWSE collection	
	Calibration	This is a CALIBRATION collection	
	Context	This is a CONTEXT collection	

Name: collection_type		Version Id: 1.0.0.0
	Data	This is a DATA collection
	Document	This is a DOCUMENT collection
	Geometry	This is a GEOMETRY collection
	Miscellaneous	This is a MISCELLANEOUS collection
	SPICE Kernel	This is a SPICE Kernel collection
	XML Schema	This is an XML SCHEMA collection

comment in Alias

Name: comment		Version Id: 1.0.0.0	
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Alias	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Color_Display_Settings

Name: comment		Version Id: 1.0.0.0	
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Color_Display_Settings	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Context_Area

Name: comment		Version Id: 1.0.0.0	
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Context_Area	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text

Name: comment		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

comment in DD_Attribute

Name: comment		Version Id: 1.0.0.0	
<i>Description: The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_Attribute</i>	<i>Type: ASCII_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in DD_Attribute_Full

Name: comment		Version Id: 1.0.0.0	
<i>Description: The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_Attribute_Full</i>	<i>Type: ASCII_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in DD_Class_Full

Name: comment		Version Id: 1.0.0.0	
<i>Description: The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_Class_Full</i>	<i>Type: ASCII_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Display_Direction

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Display_Direction	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in File

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Ingest_LDD

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Internal_Reference

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute provides one or more remarks or thoughts relevant to the object.			

Name: comment			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Internal_Reference	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Local_Internal_Reference

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Local_Internal_Reference	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

comment in Movie_Display_Settings

Name: comment			Version Id: 1.0.0.0
<i>Description:</i> The comment attribute is a character string expressing one or more remarks or thoughts relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

compile_note in Software_Source

Name: compile_note			Version Id: 1.0.0.0
<i>Description:</i> The compile note attribute provides a brief statement giving particulars about the compilation of the software source.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: compile_note			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

conceptual_domain in DD_Value_Domain_Full

Name: conceptual_domain			Version Id: 1.0.0.0
<i>Description:</i> The conceptual_domain attribute provides the domain to which the value has been assigned.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Boolean	The value is classified as Boolean	
	Integer	The value is classified as Integer	
	Name	The value is classified as Name	
	Numeric	The value is classified as Numeric	
	Real	The value is classified as Real	
	Short_String	The value is classified as Short_String	
	Text	The value is classified as Text	
	Time	The value is classified as Time	
	Type	The value is classified as Type	
	Unknown	The value has an Unknown classification	

confidence_level_note in Data_Set_PDS3

Name: confidence_level_note			Version Id: 1.0.0.0
<i>Description:</i> The confidence_level_note attribute is a text field which characterizes the reliability of data within a data set or the reliability of a particular programming algorithm or software component. Essentially, this note discusses the level of confidence in the accuracy of the data or in the ability of the software to produce accurate results.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: confidence_level_note		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

constant_value in DD_Association

Name: constant_value		Version Id: 1.0.0.0	
<i>Description: The constant value attribute provides the value to be used if an attribute is static.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_Association</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Value</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

container_type in Zip

Name: container_type		Version Id: 1.0.0.0	
<i>Description: The container type attribute indicates the method used to package the components.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Zip</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Type</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	GZIP	Product_Zipped is in container type GZIP	
	LZIP	Product_Zipped is in container type LZIP	
	TAR	Product_Zipped is in container type TAR	
	ZIP	Product_Zipped is in container type ZIP	

coordinate_source in Telescope

Name: coordinate_source		Version Id: 1.0.0.0	
<i>Description: The coordinate_source provides the name of the source of a set of coordinates.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Telescope</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Text</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Attributes in the common
(pds) namespace.

Name: coordinate_source		Version Id: 1.0.0.0
	Aerial Survey - North American (1983) Datum	The coordinate source is Aerial survey - North American (1983) Datum
	Astronomical	The coordinate source is Astronomical
	Doppler determined - WGS 72 Datum	The coordinate source is Doppler determined - WGS 72 Datum
	Geodetic - Adindan Datum	The coordinate source is Geodetic - Adindan Datum
	Geodetic - Australian Datum	The coordinate source is Geodetic - Australian Datum
	Geodetic - Campo Inchauspe (Argentina) Datum	The coordinate source is Geodetic - Campo Inchauspe (Argentina) Datum
	Geodetic - Cape (South Africa) Datum	The coordinate source is Geodetic - Cape (South Africa) Datum
	Geodetic - Corregio Alegre (Brazil) Datum	The coordinate source is Geodetic - Corregio Alegre (Brazil) Datum
	Geodetic - Datum Unknown	The coordinate source is Geodetic - Datum Unknown
	Geodetic - European 1979 Datum	The coordinate source is Geodetic - European 1979 Datum
	Geodetic - European Datum	The coordinate source is Geodetic - European Datum
	Geodetic - GRS 80 Datum	The coordinate source is Geodetic - GRS 80 Datum
	Geodetic - Hermannskogel Datum	The coordinate source is Geodetic - Hermannskogel Datum
	Geodetic - Indian Datum	The coordinate source is Geodetic - Indian Datum
	Geodetic - La Canoa (Venezuela) Datum	The coordinate source is Geodetic - La Canoa (Venezuela) Datum
	Geodetic - New Zealand Datum	The coordinate source is Geodetic - New Zealand Datum
	Geodetic - North American (1927) Datum	The coordinate source is Geodetic - North American (1927) Datum
	Geodetic - Old Hawaiian Datum	The coordinate source is Geodetic - Old Hawaiian Datum
	Geodetic - Ordnance Survey of Great Britain (1936) Datum	The coordinate source is Geodetic - Ordnance Survey of Great Britain (1936) Datum
	Geodetic - Ordnance Survey of Great Britain (SN) 1980 Datum	The coordinate source is Geodetic - Ordnance Survey of Great Britain (SN) 1980 Datum
	Geodetic - Potsdam Datum	The coordinate source is Geodetic - Potsdam Datum
	Geodetic - Puerto Rican (1940) Datum	The coordinate source is Geodetic - Puerto Rican (1940) Datum

Name: coordinate_source		Version Id: 1.0.0.0
	Geodetic - South American Datum	The coordinate source is Geodetic - South American Datum
	Geodetic - Tokyo Datum	The coordinate source is Geodetic - Tokyo Datum
	Geodetic - WGS 84 Datum	The coordinate source is Geodetic - WGS 84 Datum
	Satellite Determined - Datum Unknown	The coordinate source is Satellite determined - Datum Unknown
	Unknown	The coordinate source is Unknown

copyright in Document

Name: copyright		Version Id: 1.0.0.0	
<i>Description:</i> The copyright attribute is a character string giving information about the exclusive right to make copies, license, and otherwise exploit an object, whether physical or digital.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

country in Facility

Name: country		Version Id: 1.0.0.0	
<i>Description:</i> country			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Facility	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

creation_date_time in File

Name: creation_date_time		Version Id: 1.0.0.0	
<i>Description:</i> The creation_date_time attribute provides a date and time when the object was created.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_Date_Time
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: creation_date_time			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

curating_node_id in Volume_PDS3

Name: curating_node_id			Version Id: 1.0.0.0
<i>Description:</i> The curating_node_id attribute provides the id of the node currently maintaining the data set or volume and is responsible for maintaining catalog information.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

data_regime in Primary_Result_Summary

Deprecated

Name: data_regime *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The data_regime attribute provides the wavelength (or an analogous concept for things like particle detectors) of the observations, stated as a category.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_Result_Summary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Deprecated	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Dust	Particles ranging in size from a few molecules to approximately 0.1 micrometer in diameter.	
	Electric Field	A vector force field controlled primarily by the presence of electrons and/or ions	
	Electrons	Subatomic particles with negative elementary charge.	
	Far Infrared	Electromagnetic radiation in the approximate range: 1 THz - 10 THz (frequency), 30 micrometers - 300 micrometers (wavelength), or 4 meV - 40 meV (photon energy)	
	Gamma Ray	Electromagnetic radiation in the approximate range: greater than 10 EHz (frequency), less than	

Attributes in the common
(pds) namespace.

<i>Name: data_regime *Deprecated*</i>		<i>Version Id: 1.0.0.0</i>
		0.01 nm (wavelength), or more than 100 keV (photon energy)
	Infrared	Electromagnetic radiation in the approximate range: 300 GHz - 405 THz (frequency), 750 nm - 1 mm (wavelength), or 1.24 meV - 1.7 eV (photon energy)
	Ions	Atoms or molecules in which the number of electrons and protons is unequal, giving them a net negative or positive electric charge.
	Magnetic Field	A vector force field produced by moving electric charges (currents) and/or the intrinsic magnetic properties of materials
	Microwave	Electromagnetic radiation in the approximate range: 300 MHz - 300 GHz (frequency), 1 mm - 1 m (wavelength), or 12 micro eV - 1.2 meV (photon energy)
	Millimeter	Electromagnetic radiation in the approximate range: 30 GHz - 300 GHz (frequency), 1 mm - 10 mm (wavelength), or 120 micro eV - 1.2 meV (photon energy)
	Near Infrared	Electromagnetic radiation in the approximate range: 300 THz - 1.5 PHz (frequency), 1 micrometer - 5 micrometer (wavelength), or 1 eV - 6 eV (photon energy)
	Particles	Discrete (but small) objects that can be characterized by a few simple physical properties such as volume and mass.
	Pressure	Measurement of ambient atmospheric pressure.
	Radio	Electromagnetic radiation in the approximate range: 3 Hz - 300 GHz (frequency), 1 mm - 100,000 km (wavelength), or 12 feV - 1.2 meV (photon energy)
	Sub-Millimeter	Electromagnetic radiation in the approximate range: 0.3 THz - 3 THz (frequency), 0.1 mm - 1 mm (wavelength), or 1.2 meV - 12 meV (photon energy)
	Temperature	Measurement of ambient temperature.
	Ultraviolet	Electromagnetic radiation in the approximate range: 790 THz - 30 PHz (frequency), 10 nm - 390 nm (wavelength), or 3 eV - 120 eV (photon energy)
	Visible	Electromagnetic radiation in the approximate range: 405 THz - 790 THz (frequency), 390 nm - 750 nm (wavelength), or 1.7 eV - 3.3 eV (photon energy)
	X-Ray	Electromagnetic radiation in the approximate range: 30 PHz - 30 EHz (frequency), 0.01 nm - 10 nm (wavelength), or 120 eV - 120 keV (photon energy))

data_set_desc in Data_Set_PDS3

Name: data_set_desc			Version Id: 1.0.0.0
<i>Description:</i> The data_set_desc attribute describes the content and type of a data set and provides information required to use the data (such as binning information).			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

data_set_id in Data_Set_PDS3

Name: data_set_id			Version Id: 1.0.0.0
<i>Description:</i> The data set id provides a formal name used to refer to a data set.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

data_set_name in Data_Set_PDS3

Name: data_set_name			Version Id: 1.0.0.0
<i>Description:</i> The data_set_name attribute provides the full name given to a data set or a data product. The data_set_name typically identifies the instrument that acquired the data of that instrument Example value data_set_id. Note This attribute is defined in the AMMOS Magellan catalog as an alias for file_name to provide backward compatibility			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

data_set_release_date in Data_Set_PDS3

Name: data_set_release_date			Version Id: 1.0.0.0
<i>Description:</i> The data_set_release_date attribute provides the date when a data set is released by the data producer for archive or publication. In many systems this represents the end of a proprietary or validation period. Formation rule In AMMOS identify the date at which a product may be released to the general public from proprietary access. AMMOS-related systems should apply this attribute only to proprietary data.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

data_set_terse_desc in Data_Set_PDS3

Name: data_set_terse_desc			Version Id: 1.0.0.0
<i>Description:</i> A one line description of the data set			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

data_type in Element_Array

Name: data_type			Version Id: 1.0.0.0
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Element_Array	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ComplexLSB16	Values of Array_Element are stored as two 64-bit floating point numbers with the least significant byte first	

Attributes in the common
(pds) namespace.

<i>Name: data_type</i>		<i>Version Id: 1.0.0.0</i>
	ComplexLSB8	Values of Array_Element are stored as two 32-bit floating point numbers with the least significant byte first
	ComplexMSB16	Values of Array_Element are stored as two 64-bit floating point numbers with the more significant byte first
	ComplexMSB8	Values of Array_Element are stored as two 32-bit floating point numbers with the more significant byte first
	IEEE754LSBDouble	Values of Array_Element are stored as 64-bit IEEE binary floating point numbers with the least significant byte first
	IEEE754LSBSingle	Values of Array_Element are stored as 32-bit IEEE binary floating point numbers with the least significant byte first
	IEEE754MSBDouble	Values of Array_Element are stored as 64-bit IEEE binary floating point numbers with the most significant byte first
	IEEE754MSBSingle	Values of Array_Element are stored as 32-bit IEEE binary floating point numbers with the most significant byte first
	SignedBitString	Values of Array_Element are stored as signed bit strings
	SignedByte	Values of Array_Element are stored as 8-bit signed binary integers
	SignedLSB2	Values of Array_Element are stored as 16-bit signed binary integers with the less significant byte first
	SignedLSB4	Values of Array_Element are stored as 32-bit signed binary integers with the less significant byte first
	SignedLSB8	Values of Array_Element are stored as 64-bit signed binary integers with the less significant byte first
	SignedMSB2	Values of Array_Element are stored as 16-bit signed binary integers with the more significant byte first
	SignedMSB4	Values of Array_Element are stored as two's-complement 32-bit binary integers with the most significant byte first
	SignedMSB8	Values of Array_Element are stored as two's-complement 64-bit binary integers with the most significant byte first
	UnsignedBitString	Values of Array_Element are stored as unsigned bit strings
	UnsignedByte	Values of Array_Element are stored as 8-bit unsigned binary integers
	UnsignedLSB2	Values of Array_Element are stored as 16-bit unsigned binary integers with the less significant byte first

Name: data_type		Version Id: 1.0.0.0
	UnsignedLSB4	Values of Array_Element are stored as 32-bit unsigned binary integers with the least significant byte first
	UnsignedLSB8	Values of Array_Element are stored as 64-bit unsigned binary integers with the least significant byte first
	UnsignedMSB2	Values of Array_Element are stored as 16-bit unsigned binary integers with the more significant byte first
	UnsignedMSB4	Values of Array_Element are stored as 32-bit unsigned binary integers with the most significant byte first
	UnsignedMSB8	Values of Array_Element are stored as 64-bit unsigned binary integers with the most significant byte first

data_type in Field_Binary

Name: data_type			Version Id: 1.0.0.0
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_AnyURI	Values in Field_Binary have data type ASCII_AnyURI	
	ASCII_Boolean	Values in Field_Binary have data type ASCII_Boolean	
	ASCII_DOI	Values in Field_Binary have data type ASCII_DOI	
	ASCII_Date	Values in Field_Binary have data type ASCII_Date	
	ASCII_Date_DOY	Values in Field_Binary have data type ASCII_Date_DOY	
	ASCII_Date_Time	Values in Field_Binary have data type ASCII_Date_Time	
	ASCII_Date_Time_DOY	Values in Field_Binary have data type ASCII_Date_Time_DOY	
	ASCII_Date_Time_UTC	Values in Field_Binary have data type ASCII_Date_Time_UTC	
	ASCII_Date_Time_YMD	Values in Field_Binary have data type ASCII_Date_Time_YMD	
	ASCII_Date_YMD	Values in Field_Binary have data type ASCII_Date_YMD	

Attributes in the common
(pds) namespace.

<i>Name: data_type</i>		<i>Version Id: 1.0.0.0</i>
ASCII_Directory_Path_Name	ASCII_Directory_Path_Name	Values in Field_Binary have data type ASCII_Directory_Path_Name
ASCII_File_Name	ASCII_File_Name	Values in Field_Binary have data type ASCII_File_Name
ASCII_File_Specification_Name	ASCII_File_Specification_Name	Values in Field_Binary have data type ASCII_File_Specification_Name
ASCII_Integer	ASCII_Integer	Values in Table_Binary_Field have data type ASCII_Integer
ASCII_LID	ASCII_LID	Values in Field_Binary have data type ASCII_LID
ASCII_LIDVID	ASCII_LIDVID	Values in Field_Binary have data type ASCII_LIDVID
ASCII_LIDVID_LID	ASCII_LIDVID_LID	Values in Field_Binary have data type ASCII_LIDVID_LID
ASCII_MD5_Checksum	ASCII_MD5_Checksum	Values in Field_Binary have data type ASCII_MD5_Checksum
ASCII_NonNegative_Integer	ASCII_NonNegative_Integer	Values in Field_Binary have data type ASCII_NonNegative_Integer
ASCII_Numeric_Base16	ASCII_Numeric_Base16	Values in Field_Binary have data type ASCII_Numeric_Base16
ASCII_Numeric_Base2	ASCII_Numeric_Base2	Values in Field_Binary have data type ASCII_Numeric_Base2
ASCII_Numeric_Base8	ASCII_Numeric_Base8	Values in Field_Binary have data type ASCII_Numeric_Base8
ASCII_Real	ASCII_Real	Values in Field_Binary have data type ASCII_Real
ASCII_String	ASCII_String	Values in Field_Binary have data type ASCII_String
ASCII_Time	ASCII_Time	Values in Field_Binary have data type ASCII_Time
ASCII_VID	ASCII_VID	Values in Field_Binary have data type ASCII_VID
ComplexLSB16	ComplexLSB16	Values in Field_Binary have data type ComplexLSB16
ComplexLSB8	ComplexLSB8	Values in Field_Binary have data type ComplexLSB8
ComplexMSB16	ComplexMSB16	Values in Field_Binary have data type ComplexMSB16
ComplexMSB8	ComplexMSB8	Values in Field_Binary have data type ComplexMSB8
IEEE754LSBDouble	IEEE754LSBDouble	Values in Field_Binary have data type IEEE754LSBDouble
IEEE754LSBSingle	IEEE754LSBSingle	Values in Field_Binary have data type IEEE754LSBSingle
IEEE754MSBDouble	IEEE754MSBDouble	Values in Field_Binary have data type IEEE754MSBDouble

Attributes in the common
(pds) namespace.

Name: data_type		Version Id: 1.0.0.0
	IEEE754MSBSingle	Values in Field_Binary have data type IEEE754MSBSingle
	SignedBitString	Values in Field_Binary have data type SignedBitString
	SignedByte	Values in Field_Binary have data type SignedByte
	SignedLSB2	Values in Field_Binary have data type SignedLSB2
	SignedLSB4	Values in Field_Binary have data type SignedLSB4
	SignedLSB8	Values in Field_Binary have data type SignedLSB8
	SignedMSB2	Values in Field_Binary have data type SignedMSB2
	SignedMSB4	Values in Field_Binary have data type SignedMSB4
	SignedMSB8	Values in Field_Binary have data type SignedMSB8
	UTF8_String	Values in Field_Binary have data type UTF8_String
	UnsignedBitString	Values in Field_Binary have data type UnsignedBitString
	UnsignedByte	Values in Field_Binary have data type UnsignedByte
	UnsignedLSB2	Values in Field_Binary have data type UnsignedLSB2
	UnsignedLSB4	Values in Field_Binary have data type UnsignedLSB4
	UnsignedLSB8	Values in Field_Binary have data type UnsignedLSB8
	UnsignedMSB2	Values in Field_Binary have data type UnsignedMSB2
	UnsignedMSB4	Values in Field_Binary have data type UnsignedMSB4
	UnsignedMSB8	Values in Field_Binary have data type UnsignedMSB8

data_type in Field_Bit

Name: data_type		Version Id: 1.0.0.0	
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String

Attributes in the common
(pds) namespace.

Name: data_type		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	SignedBitString	Values of Array_Element are stored as signed bit strings
	UnsignedBitString	Values of Array_Element are stored as unsigned bit strings

data_type in Field_Character

Name: data_type		Version Id: 1.0.0.0	
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_AnyURI	Values in Field_Character have data type ASCII_AnyURI	
	ASCII_Boolean	Values in Field_Character have data type ASCII_Boolean	
	ASCII_DOI	Values in Field_Character have data type ASCII_DOI	
	ASCII_Date	Values in Field_Character have data type ASCII_Date	
	ASCII_Date_DOY	Values in Field_Character have data type ASCII_Date_DOY	
	ASCII_Date_Time	Values in Field_Character have data type ASCII_Date_Time	
	ASCII_Date_Time_DOY	Values in Field_Character have data type ASCII_Date_Time_DOY	
	ASCII_Date_Time_UTC	Values in Field_Character have data type ASCII_Date_Time_UTC	
	ASCII_Date_Time_YMD	Values in Field_Character have data type ASCII_Date_Time_YMD	
	ASCII_Date_YMD	Values in Field_Character have data type ASCII_Date_YMD	
	ASCII_Directory_Path_Name	Values in Field_Character have data type ASCII_Directory_Path_Name	
	ASCII_File_Name	Values in Field_Character have data type ASCII_File_Name	
	ASCII_File_Specification_Name	Values in Field_Character have data type ASCII_File_Specification_Name	

Attributes in the common
(pds) namespace.

Name: data_type		Version Id: 1.0.0.0
	ASCII_Integer	Values in Field_Character have data type ASCII_Integer
	ASCII_LID	Values in Field_Character have data type ASCII_LID
	ASCII_LIDVID	Values in Field_Character have data type ASCII_LIDVID
	ASCII_LIDVID_LID	Values in Field_Character have data type ASCII_LIDVID_LID
	ASCII_MD5_Checksum	Values in Field_Character have data type ASCII_MD5_Checksum
	ASCII_NonNegative_Integer	Values in Field_Character have data type ASCII_NonNegative_Integer
	ASCII_Numeric_Base16	Values in Field_Character have data type ASCII_Numeric_Base16
	ASCII_Numeric_Base2	Values in Field_Character have data type ASCII_Numeric_Base2
	ASCII_Numeric_Base8	Values in Field_Character have data type ASCII_Numeric_Base8
	ASCII_Real	Values in Field_Character have data type ASCII_Real
	ASCII_String	Values in Field_Character have data type ASCII_String
	ASCII_Time	Values in Field_Character have data type ASCII_Time
	ASCII_VID	Values in Field_Character have data type ASCII_VID
	UTF8_String	Values in Field_Character have data type UTF8_String

data_type in Field_Delimited

Name: data_type		Version Id: 1.0.0.0	
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_AnyURI	The delimited field has data type ASCII_AnyURI	
	ASCII_Boolean	Values in Field_Delimited have data type ASCII_Boolean	
	ASCII_DOI	The delimited field has data type ASCII_DOI	

Attributes in the common
(pds) namespace.

Name: data_type		Version Id: 1.0.0.0
ASCII_Date	Values in Field_Delimited have data type ASCII_Date	
ASCII_Date_DOY	The delimited field has data type ASCII_Date_DOY	
ASCII_Date_Time	Values in Field_Delimited have data type ASCII_Date_Time	
ASCII_Date_Time_DOY	The delimited field has data type ASCII_Date_Time_DOY	
ASCII_Date_Time_UTC	The delimited field has data type ASCII_Date_Time_UTC	
ASCII_Date_Time_YMD	The delimited field has data type ASCII_Date_Time_YMD	
ASCII_Date_YMD	The delimited field has data type ASCII_Date_YMD	
ASCII_Directory_Path_Name	Values in Field_Delimited have data type ASCII_Directory_Path_Name	
ASCII_File_Name	The delimited field has data type ASCII_File_Name	
ASCII_File_Specification_Name	The delimited field has data type ASCII_File_Specification_Name	
ASCII_Integer	The delimited field has data type ASCII_Integer	
ASCII_LID	The delimited field has data type ASCII_LID	
ASCII_LIDVID	The delimited field has data type ASCII_LIDVID	
ASCII_LIDVID_LID	Values in Field_Delimited have data type ASCII_LIDVID_LID	
ASCII_MD5_Checksum	The delimited field has data type ASCII_MD5_Checksum	
ASCII_NonNegative_Integer	The delimited field has data type ASCII_NonNegative_Integer	
ASCII_Numeric_Base16	The delimited field has data type ASCII_Numeric_Base16	
ASCII_Numeric_Base2	The delimited field has data type ASCII_Numeric_Base2	
ASCII_Numeric_Base8	Values in Field_Delimited have data type ASCII_Numeric_Base8	
ASCII_Real	The delimited field has data type ASCII_Real	
ASCII_String	Values in Field_Delimited have data type ASCII_String	
ASCII_Time	The delimited field has data type ASCII_Time	
ASCII_VID	The delimited field has data type ASCII_VID	
UTF8_String	Values in Field_Delimited have data type UTF8_String	

data_type in Quaternion_Component

Name: data_type			Version Id: 1.0.0.0
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion_Component	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_Real	The value is expressed using the data type ASCII_Real	

data_type in Vector

Name: data_type			Version Id: 1.0.0.0
<i>Description:</i> The data_type attribute provides the hardware representation used to store a value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_Real	The value is expressed using the data type ASCII_Real	

date_time in Update_Entry

Name: date_time			Version Id: 1.0.0.0
<i>Description:</i> The date_time attribute provides the date and time of an event.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Update_Entry	<i>Type:</i> ASCII_Date_Time
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

definition in DD_Attribute

Name: definition			Version Id: 1.0.0.0
<i>Description:</i> The definition attribute provides a statement, picture in words, or account that defines the term.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

definition in DD_Attribute_Full

Name: definition			Version Id: 1.0.0.0
<i>Description:</i> The definition attribute provides a statement, picture in words, or account that defines the term.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

definition in DD_Class

Name: definition			Version Id: 1.0.0.0
<i>Description:</i> The definition attribute provides a statement, picture in words, or account that defines the term.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

definition in DD_Class_Full

Name: definition			Version Id: 1.0.0.0
<i>Description:</i> The definition attribute provides a statement, picture in words, or account that defines the term.			

Name: definition			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_ <i>Class_Full</i>	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

definition in Terminological_Entry

Name: definition			Version Id: 1.0.0.0
<i>Description:</i> The definition attribute provides a statement, picture in words, or account that defines the term.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Terminological_Entry	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Agency

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Agency	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Array

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Array	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: description			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Bundle

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Citation_Information

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a short (5KB or less) description of the product as a whole.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Citation_Information	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Collection

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Collection	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Document

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Document_Format

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document_Format	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Encoded_Byte_Stream

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Encoded_Byte_Stream	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in External_Reference

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			

Name: description			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> External_Reference	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Facility

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Facility	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Field_Binary

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Field_Bit

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: description			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Field_Character

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_ Character	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Field_Delimited

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_ Delimited	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Field_Statistics

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_ Statistics	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Information_Package

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Information_Package	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Instrument

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Instrument_Host

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Investigation

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			

Name: description			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Investigation	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Modification_Detail

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Modification_Detail	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Node

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Node	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Object_Statistics

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: description			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Observing_System

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Observing_System	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Observing_System_Component

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Observing_System_Component	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

description in Other

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Other	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text

Name: description		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

description in PDS_Affiliate

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: PDS_Affiliate</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in PDS_Guest

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: PDS_Guest</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Packed_Data_Fields

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Packed_Data_Fields</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Parsable_Byte_Stream

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Parsable_Byte_Stream	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Primary_Result_Summary

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_Result_Summary	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Quaternion

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Quaternion_Component

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			

Name: description			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion_ Component	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Resource

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Resource	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Software

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Table_Base

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_ Base	<i>Type:</i> UTF8_Text_Preserved

Name: description			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Target

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Target_Identification

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides additional information or clarification, as needed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target_Identification	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Telescope

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Telescope	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text

Name: description		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

description in Update

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Update</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Update_Entry

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Update_Entry</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Vector

Name: description		Version Id: 1.0.0.0	
<i>Description: The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Vector</i>	<i>Type: UTF8_Text_Preserved</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Description</i>	<i>Conceptual Domain: Text</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Vector_Component

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_ Component	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Volume_PDS3

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_ PDS3	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Volume_Set_PDS3

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_ Set_PDS3	<i>Type:</i> UTF8_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

description in Zip

Name: description			Version Id: 1.0.0.0
<i>Description:</i> The description attribute provides a statement, picture in words, or account that describes or is otherwise relevant to the object.			

Name: description			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Zip	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

detector_number in Band_Bin *Deprecated*

Name: detector_number			Version Id: 1.0.0.0
<i>Description:</i> The detector_number attribute provides the spectrometer detector number corresponding to a band of a spectral cube. Detector numbers are usually assigned consecutively from 1, in order of increasing wavelength.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Band_Bin *Deprecated*	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

directory_path_name in Document_File

Name: directory_path_name			Version Id: 1.0.0.0
<i>Description:</i> The directory_path_name attribute provides a sequence of names that locates a directory in a hierarchy of directories.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document_File	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

discipline_name in Discipline_Facets

Name: discipline_name			Version Id: 1.0.0.0
<i>Description:</i> The discipline_name attribute describes the observing discipline (as opposed to a PDS Discipline Node Name, though the concepts and values are similar). Some of these values are, with respect to the PDS Nodes, inter-disciplinary and should be used when they are applicable in preference to the more restrictive values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Discipline_Facets	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: discipline_name			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Atmospheres	atmospheric observations	
	Fields	electric and magnetic field data	
	Flux Measurements	photometry/polarimetry not resulting in images or spectra	
	Imaging	any non-spectroscopic image, of any dimensionality (color, movies, etc.)	
	Particles	ions, electrons, and anything not classified as 'dust'	
	Ring-Moon Systems	other ring or ring-moon system data	
	Small Bodies	other small body observations, including dust, shape models, etc.	
	Spectroscopy	light wavelength/wave number spectra of any and all dimensionalities	

document_name in Document

Name: document_name			Version Id: 1.0.0.0
<i>Description:</i> The document_title attribute provides the full name of the published document. This optional attribute is used only if the title in the identification area of the document product is not sufficient.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

document_standard_id in Document_File

Name: document_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The document_standard_id attribute provides the formal name of a standard used for the structure of a document file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document_File	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String

Attributes in the common
(pds) namespace.

Name: document_standard_id		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	7-Bit ASCII Text	The Document_File contains simple text using only the 7-Bit ASCII character set. ANSI X3.4-1986.
	Encapsulated Postscript	The Document_File is governed by the external standard Encapsulated Postscript (EPS).
	GIF	The Document_File is governed by the standard Graphics Interchange Format (GIF).
	HTML 2.0	The Document_File is governed by the standard HyperText Markup Language (HTML), IETF RFC 2070.
	HTML 3.2	The Document_File is governed by the standard HyperText Markup Language (HTML), W3C Recommendation 14-Jan-1997.
	HTML 4.0	The Document_File is governed by the standard HyperText Markup Language (HTML), ISO 8879:1986.
	HTML 4.01	The Document_File is governed by the standard HyperText Markup Language (HTML), ISO/IEC 15445:2000.
	JPEG	The Document_File is governed by the standard Joint Photographic Experts Group (JPEG), ISO/IEC 10918-1.
	LaTEX	The Document_File is governed by the standard LaTEX, Version LaTeX2e.
	Microsoft Word	The Document_File is governed by a Microsoft Word standard, Microsoft Corporation.
	PDF	The Document_File is governed by the standard Portable Document Format (PDF), ISO 32000-1:2008.
	PDF/A	The Document_File is governed by the standard Portable Document Format / Archive (PDF/A), ISO 19005-1:2005.
	PNG	The Document_File is governed by the standard Portable Network Graphics (PNG), ISO/IEC 15948:2004.
	Postscript	The Document_File is governed by the standard Postscript (PS)
	Rich Text	The Document_File is governed by the standard Rich Text Format (RTF), Microsoft Corporation.
	TIFF	The Document_File is governed by the standard Tagged Image File Format (TIFF), Version 6.n, 1992.
	UTF-8 Text	The Document_File contains simple text using UTF-8 Unicode character encodings. RFC 3629.

doi in Document

Name: doi			Version Id: 1.0.0.0
<i>Description:</i> The doi attribute provides the Digital Object Identifier for an object, assigned by the appropriate DOI System Registration Agency.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> DOI	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

doi in External_Reference

Name: doi			Version Id: 1.0.0.0
<i>Description:</i> The doi attribute provides the Digital Object Identifier for an object, assigned by the appropriate DOI System Registration Agency.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> External_Reference	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> DOI	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

domain in Science_Facets

Name: domain			Version Id: 1.0.0.0
<i>Description:</i> The radial "zone" or "shell" of the target for which the observations were collected or which are represented in the product(s). The value may depend on wavelength_range and size of the target.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Science_Facets	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Atmosphere	an envelope of uncharged gases and particles surrounding the target and bound to it primarily by gravitational forces	
	Heliosphere	the solar atmosphere extending roughly from the outer corona to the edge of the solar plasma at	

Attributes in the common
(pds) namespace.

Name: domain		Version Id: 1.0.0.0
		the heliopause, which separates primarily solar plasma from the interstellar medium.
	Interior	the solid and/or liquid portion of a target enclosed by its surface.
	Interstellar	the region between stars, which is outside of any star's heliopause.
	Ionosphere	an envelope of plasma and charged particles surrounding the target and bound to it primarily by gravitational forces.
	Magnetosphere	an envelope of charged particles, bounded on the upper side by the magnetopause and which is primarily under the control of the target body's magnetic field.
	Surface	the boundary between the solid/liquid portion of a target and its atmosphere, ionosphere, or magnetosphere (or space).

editor_list in Citation_Information

Name: editor_list		Version Id: 1.0.0.0	
<i>Description:</i> The editor_list attribute provides a list of people to be cited as the editors of the associated product. Lists are constructed with last names first and first and middle names and/or initials following. Initials are terminated by periods and delimited by single spaces. Suffixes (if applicable) follow everything else, after a final comma. Hyphenated names may be reduced to initials as "J.-P." Each person's full name is separated from the next by a semi-colon. There is no "and" before the last name.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Citation_Information	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> List	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

editor_list in Document

Name: editor_list		Version Id: 1.0.0.0	
<i>Description:</i> The editor_list attribute provides a list of people to be cited as the editors of the associated product. Lists are constructed with last names first and first and middle names and/or initials following. Initials are terminated by periods and delimited by single spaces. Suffixes (if applicable) follow everything else, after a final comma. Hyphenated names may be reduced to initials as "J.-P." Each person's full name is separated from the next by a semi-colon. There is no "and" before the last name.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> UTF8_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: editor_list			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> List	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

electronic_mail_address in PDS_Affiliate

Name: electronic_mail_address			Version Id: 1.0.0.0
<i>Description:</i> The electronic mail address attribute provides a multi-part email address: the first part (the user name), which identifies a unique user, is separated by an "at sign" from the host name, which uniquely identifies the mail server.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Address	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

electronic_mail_address in PDS_Guest

Name: electronic_mail_address			Version Id: 1.0.0.0
<i>Description:</i> The electronic mail address attribute provides a multi-part email address: the first part (the user name), which identifies a unique user, is separated by an "at sign" from the host name, which uniquely identifies the mail server.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Guest	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Address	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

elements in Axis_Array

Name: elements			Version Id: 1.0.0.0
<i>Description:</i> The elements attribute provides the count of the number of elements along an array axis.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Axis_Array	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer

Name: elements		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

encoding_standard_id in Encoded_Binary

Name: encoding_standard_id		Version Id: 1.0.0.0	
<i>Description: The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded Byte Stream digital object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Encoded_Binary</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: ID</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	CCSDS Space Communications Protocols	The digital object is governed by the Consultative Committee for Space Data Systems (CCSDS) recommended standards on telecommand, telemetry and space datalink protocols.	

encoding_standard_id in Encoded_Byte_Stream

Name: encoding_standard_id		Version Id: 1.0.0.0	
<i>Description: The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded Byte Stream digital object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Encoded_Byte_Stream</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: ID</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

encoding_standard_id in Encoded_Header

Name: encoding_standard_id		Version Id: 1.0.0.0	
<i>Description: The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded Byte Stream digital object.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Encoded_Header</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>

Name: encoding_standard_id			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	TIFF	The Header is governed by the standard Tagged Image File Format (TIFF), Version 6.n, 1992.	

encoding_standard_id in Encoded_Image

Name: encoding_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Encoded_Image	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	GIF	The Encoded_Image is governed by the standard Graphics Interchange Format (GIF).	
	J2C	The Encoded_Image is governed by the standard JPEG2000 compressed image codestream.	
	JPEG	The Encoded_Image is governed by the standard Joint Photographic Experts Group (JPEG), ISO/IEC 10918-1.	
	PDF	The Encoded_Image is governed by the standard Portable Document Format (PDF), ISO 32000-1:2008.	
	PDF/A	The Encoded_Image is governed by the standard Portable Document Format / Archive (PDF/A), ISO 19005-1:2005.	
	PNG	The Encoded_Image is governed by the standard Portable Network Graphics (PNG), ISO/IEC 15948:2004.	
	TIFF	The Encoded_Image is governed by the standard Tagged Image File Format (TIFF), Version 6.n, 1992.	

encoding_standard_id in Encoded_Native

Name: encoding_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The encoding_standard_id attribute provides the formal name of a standard used for the structure of an Encoded Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Encoded_Native	<i>Type:</i> ASCII_Short_String_Collapsed

Name: encoding_standard_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	SEED 2.4	SEED (Standard for the Exchange of Earthquake Data) is an international standard format for archiving seismic data. The standard is maintained by the International Federation of Digital Seismograph Networks (FDSN). The details of the format are documented in the SEED Reference Manual, version 2.4 (published: 2009-01).	

encoding_type in SPICE_Kernel

Name: encoding_type			Version Id: 1.0.0.0
<i>Description:</i> The encoding_type attribute provides the storage format (binary or character).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> SPICE_Kernel	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Binary	The data object contains binary and possibly some character encoded data.	
	Character	The data object contains only character encoded data, for example ASCII or UTF-8 encoded characters.	

enumeration_flag in DD_Value_Domain

Name: enumeration_flag			Version Id: 1.0.0.0
<i>Description:</i> The enumeration_flag attribute indicates whether there is an enumerated set of permissible values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

enumeration_flag in DD_Value_Domain_Full

Name: enumeration_flag			Version Id: 1.0.0.0
<i>Description:</i> The enumeration_flag attribute indicates whether there is an enumerated set of permissible values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

error_constant in Special_Constants

Name: error_constant			Version Id: 1.0.0.0
<i>Description:</i> The error_constant attribute provides a value that indicates the original value was in error.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Constant	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

facet1 in Group_Facet1

Name: facet1			Version Id: 1.0.0.0
<i>Description:</i> The facet1 attribute provides a sub-categorization under the discipline_name. The values are restricted according to the value of discipline_name.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Facet1	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	2D (Spectroscopy)	A 2D array in which each pixel value directly represents the spectral measurement at that point. The physical axes of the array align with the axes of the spectral data.	

Attributes in the common
(pds) namespace.

<i>Name: facet1</i>		<i>Version Id: 1.0.0.0</i>
	Color (Imaging)	3D data, typically with two spatial axes, where the third axis contains display color levels (RGB, CMYK, false color, etc.)
	Color Movie (Imaging)	4D data, typically with two spatial, one color, and one temporal axis
	Dust Study (Small Bodies)	Dust measurements of all kinds and all targets
	Dynamical Properties (Small Bodies)	Orbital parameters, proper elements, etc.
	Electric (Fields)	Electrical field measurements
	Electrons (Particles)	Electron measurements
	Gas Study (Small Bodies)	Gas measurements of all kinds and targets
	Grayscale (Imaging)	2D data, typically with two spatial axes
	Historical Reference (Small Bodies)	Discovery circumstances, reference collections
	Ions (Particles)	Ion measurements
	Lightcurve (Small Bodies)	Light intensity variation with time, including rotational, secular, and occultation light curves
	Linear (Spectroscopy)	A table representing a single spectrum
	Magnetic (Fields)	Magnetic field measurements
	Meteoritics (Small Bodies)	Meteoroid streams, meteorite studies
	Meteorology (Atmospheres)	Meteorological observations
	Movie (Imaging)	3D data, typically with two spatial and one temporal axis
	Neutrals (Particles)	Neutral particle measurements
	Photometry (Flux Measurements)	Photon measurements resulting in magnitudes, colors, etc.
	Physical Properties (Small Bodies)	Mass, density, albedo, etc.
	Polarimetry (Flux Measurements)	Linear and circular polarization studies
	Production Rates (Small Bodies)	Quantification of mass loss from, e.g., the nucleus of a comet: molecular production rates, Af?, etc.
	Ring Compositional Map (Ring-Moon Systems)	3D data, typically with two spatial axes, where the third axis uses either color or intensity to depict chemical or particle size variations within the rings.
	Ring Occultation Profile (Ring-Moon Systems)	Derived ring occultation data uniformly sampled along the radial axis. The occulted signal may be either, radio, solar, or stellar in origin.
	Ring Thermal Map (Ring-Moon Systems)	3D data, typically with two spatial axes, where the third axis uses either color or intensity to depict temperature variations within the rings.

Name: facet1		Version Id: 1.0.0.0
	Satellite Astrometry (Ring-Moon Systems)	Astrometry of natural satellite in ring systems
	Shape Model (Small Bodies)	Shape models, slope models, terrain models, elevation models, etc.
	Spectral Cube (Spectroscopy)	Any 3D structure containing spectral data
	Spectral Image (Spectroscopy)	A 2D image of a spectrum, as projected on a focal plane. There may be multiple orders present, and the axes of the spectrum/spectra typically do not align with the edges of the image.
	Structure (Atmospheres)	Atmospheric structure observations
	Tabulated (Spectroscopy)	A table with one spectrum per record, possibly for a different target in each record
	Taxonomy (Small Bodies)	Physical and dynamical taxonomies of small bodies

facet2 in Group_Facet2

Name: facet2			Version Id: 1.0.0.0
<i>Description:</i> The facet2 attribute provides a sub-categorization under the discipline_name. The values are restricted according to the value of discipline_name.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Facet2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Background (Fields)	slowly varying background field (typically at less than 100 Hz)	
	Cosmic Ray (Particles)	> 10 MeV	
	Energetic (Particles)	> 30keV	
	Plasma (Particles)	< 30keV	
	Solar Energetic (Particles)	0.1-10MeV	
	Waves (Fields)	higher frequency field variations and/or oscillations (typically at greater than 100 Hz).	

field_delimiter in Table_Delimited

Name: field_delimiter		Version Id: 1.0.0.0
<i>Description:</i> The field_delimiter attribute provides the character or characters that indicate the end of a character string.		

Attributes in the common
(pds) namespace.

Name: field_delimiter			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Delimited	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Delimiter	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Comma	Fields in the delimited table are delimited by ASCII commas (0x2C)	
	Horizontal Tab	Fields in the delimited table are delimited by horizontal tab characters (0x09)	
	Semicolon	Fields in the delimited table are delimited by ASCII semicolons (0x3B)	
	Vertical Bar	Fields in the delimited table are delimited by ASCII vertical bar characters (' ' - 0x7C)	
	comma - *Deprecated*	Fields in the delimited table are delimited by ASCII commas (0x2C)	
	horizontal tab - *Deprecated*	Fields in the delimited table are delimited by horizontal tab characters (0x09)	
	semicolon - *Deprecated*	Fields in the delimited table are delimited by ASCII semicolons (0x3B)	
	vertical bar - *Deprecated*	Fields in the delimited table are delimited by ASCII vertical bar characters (' ' - 0x7C)	

field_format in Field_Binary

Name: field_format			Version Id: 1.0.0.0
<i>Description:</i> The field_format attribute gives the magnitude and precision of the data value. The standard POSIX string formats are used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Format	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

field_format in Field_Bit

Name: field_format			Version Id: 1.0.0.0
<i>Description:</i> The field_format attribute gives the magnitude and precision of the data value. The standard POSIX string formats are used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Short_String_Collapsed

Name: field_format			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Format	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

field_format in Field_Character

Name: field_format			Version Id: 1.0.0.0
<i>Description:</i> The field_format attribute gives the magnitude and precision of the data value. The standard POSIX string formats are used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Format	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

field_format in Field_Delimited

Name: field_format			Version Id: 1.0.0.0
<i>Description:</i> The field_format attribute gives the magnitude and precision of the data value. The standard POSIX string formats are used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Format	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

field_length in Field_Binary

Name: field_length			Version Id: 1.0.0.0
<i>Description:</i> The field_length attribute provides the number of bytes in the field.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer

Name: field_length		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

field_length in Field_Character

Name: field_length		Version Id: 1.0.0.0	
<i>Description:</i> The field_length attribute provides the number of bytes in the field.			
Namespace Id: pds	Steward: pds	Class Name: Field_Character	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Storage	Default Unit Id: byte	Attribute Concept: Length	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

field_location in Field_Binary

Name: field_location		Version Id: 1.0.0.0	
<i>Description:</i> The field_location attribute provides the starting byte for a field within a record or group, counting from '1'.			
Namespace Id: pds	Steward: pds	Class Name: Field_Binary	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Storage	Default Unit Id: byte	Attribute Concept: Location	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

field_location in Field_Character

Name: field_location		Version Id: 1.0.0.0	
<i>Description:</i> The field_location attribute provides the starting byte for a field within a record or group, counting from '1'.			
Namespace Id: pds	Steward: pds	Class Name: Field_Character	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Storage	Default Unit Id: byte	Attribute Concept: Location	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

field_number in Field

Name: field_number			Version Id: 1.0.0.0
<i>Description:</i> The field_number attribute provides the position of a field, within a series of fields, counting from 1. If two fields within a record are physically separated by one or more groups, they have consecutive field numbers; the fields within the intervening group(s) are numbered separately. Fields within a group separated by one or more (sub)groups, will also have consecutive field numbers.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

fields in Group

Name: fields			Version Id: 1.0.0.0
<i>Description:</i> The fields attribute provides a count of the total number of scalar fields directly associated with a group. Fields within (sub) groups of the group are not included in this count.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

fields in Record

Name: fields			Version Id: 1.0.0.0
<i>Description:</i> The fields attribute provides a count of the total number of scalar fields directly associated with a table record. Fields within groups within the record are not included in this count.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Record	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

file_name in File

Name: file_name			Version Id: 1.0.0.0
<i>Description:</i> The file_name attribute provides the name of a file.			

Name: file_name			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

file_size in File

Name: file_size			Version Id: 1.0.0.0
<i>Description:</i> The file_size attribute provides the size of the file.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_NonNegative_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Size	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

files in Software_Binary

Name: files			Version Id: 1.0.0.0
<i>Description:</i> The files attribute provides the number of files.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

files in Software_Script

Name: files			Version Id: 1.0.0.0
<i>Description:</i> The files attribute provides the number of files.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Script	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer

Name: files		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

files in Software_Source

Name: files		Version Id: 1.0.0.0	
<i>Description:</i> The files attribute provides the number of files.			
Namespace Id: pds	Steward: ops	Class Name: Software_ Source	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

filter_number in Band_Bin *Deprecated*

Name: filter_number		Version Id: 1.0.0.0	
<i>Description:</i> The filter_number attribute of a spectral cube describes the physical location of a band (identified by the band_number) in a detector array. Filter 1 is on the leading edge of the array.			
Namespace Id: pds	Steward: img	Class Name: Band_Bin *Deprecated*	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

first_sampling_parameter_value in Uniformly_Sampled

Name: first_sampling_parameter_value		Version Id: 1.0.0.0	
<i>Description:</i> The first_sampling_parameter_value element provides the first value in an ascending series and is therefore the minimum value at which a given data item was sampled.			
Namespace Id: pds	Steward: pds	Class Name: Uniformly_Sampled	Type: ASCII_Real
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Real
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

format_type in Document_Format

Name: format_type			Version Id: 1.0.0.0
<i>Description:</i> The format type attribute indicates the digital format used.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document_Format	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Multiple File	The Document_Format has multiple files	
	Single File	The Document_Format has a single file	
	multiple file - *Deprecated*	The Document_Format has multiple files	
	single file - *Deprecated*	The Document_Format has a single file	

formation_rule in ASCII_DOI

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	nn.nnnn/nnn	Values of ASCII_DOI are constructed using the template nn.nnnn/nnn where nn identifies the DOI registry, nnnn identifies the DOI registrant, and nnn uniquely identifies the document or other work.	

formation_rule in ASCII_Date

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String

Name: formation_rule		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	Value	Value Meaning
	YYYY-MM-DD/ YYYY-DOY	Values of ASCII_Date are constructed as either YYYY-MM-DD or as YYYY-DDD where YYYY is the year, MM is the month (01-12), DD is the day-of-month (01-31), and DDD is the day-of-year (001-366)

formation_rule in ASCII_Date_DOY

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_DOY	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	YYYY-DOY	Values of ASCII_Date_DOY are constructed as YYYY-DDD where YYYY is the 4-digit year and DDD is the day-of-year (001-366)	

formation_rule in ASCII_Date_Time

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_Time	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	YYYY-MM-DDTHH:MM:SS.SSS(Z)/ YYYY-DOYTHH:MM:SS.SSS(Z)	TBD_value_meaning	

formation_rule in ASCII_Date_Time_DOY

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_Time_DOY	Type: ASCII_Short_String_Collapsed

Name: formation_rule			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	YYYY- DOYTHH:MM:SS.SSS(Z)	TBD_value_meaning	

formation_rule in ASCII_Date_Time_UTC

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date_Time_UTC	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	YYYY-MM- DDTHH:MM:SS.SSSZ/ YYYY- DOYTHH:MM:SS.SSSZ	TBD_value_meaning	

formation_rule in ASCII_Date_Time_YMD

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date_Time_YMD	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	YYYY-MM- DDTHH:MM:SS.SSS(Z)	TBD_value_meaning	

formation_rule in ASCII_Date_YMD

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			

Name: formation_rule			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	YYYY-MM-DD	Values of ASCII_Date_YMD are constructed as YYYY-MM-DD where YYYY is the year, MM is the month (01-12), and DD is the day-of-month (01-31)	

formation_rule in ASCII_Directory_Path_Name

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Directory_Path_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	dir1/dir2/	Values of ASCII_Directory_Path_Name are constructed of directory names (strings) separated by forward slashes	

formation_rule in ASCII_File_Name

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	file_name.file_extension	Values of ASCII_File_Name comprise a base file name, a period ('.'), and an extension	

formation_rule in ASCII_File_Specification_ Name

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Specification_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	dir1/dir2/file_name.file_extension	Values of ASCII_File_Specification_Name comprise a series of directory names (separated by forward slashes), a file base name, a period ("."), and an extension	

formation_rule in ASCII_LID

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	urn:nasa:pds:xxxx	Values of ASCII_LID have the form urn:nasa:pds:xxxx where xxxx is a character string	

formation_rule in ASCII_LIDVID

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Attributes in the common
(pds) namespace.

Name: formation_rule		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	urn:nasa:pds:xxxx::M.n	Values of ASCII_LIDVID have the form urn:nasa:pds:xxxx::M.n where xxxx is a character string and M and n are non-negative integers

formation_rule in ASCII_LIDVID_LID

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	urn:nasa:pds:xxxx	TBD_value_meaning	
	urn:nasa:pds:xxxx::M.n	Values of ASCII_LIDVID_LID have the form urn:nasa:pds:xxxx::M.n where xxxx is a character string and M and n are non-negative integers	

formation_rule in ASCII_MD5_Checksum

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	0123456789abcdef	Values of ASCII_MD5_Checksum are constructed from the characters 0,1,2,3,4,5,6,7,8,9,a,b,c,d,e, and/or f	

formation_rule in ASCII_Time

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed

Name: formation_rule			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	HH:MM:SS.SSS	TBD_value_meaning	

formation_rule in ASCII_VID

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	M.m	Values of ASCII_VID have the form M.N where M and n are non-negative integers	

formation_rule in Character_Data_Type

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

formation_rule in DD_Value_Domain

Name: formation_rule			Version Id: 1.0.0.0
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Text_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text

Name: formation_rule		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

formation_rule in DD_Value_Domain_Full

Name: formation_rule		Version Id: 1.0.0.0	
<i>Description:</i> The formation_rule attribute provides a 'user friendly' instruction for forming values.			
Namespace Id: pds	Steward: ops	Class Name: DD_Value_Domain_Full	Type: ASCII_Text_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Text
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

full_name in Ingest_LDD

Name: full_name		Version Id: 1.0.0.0	
<i>Description:</i> The full_name attribute provides the complete name for a person and includes titles and suffixes.			
Namespace Id: pds	Steward: ops	Class Name: Ingest_LDD	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

full_name in Subscriber_PDS3

Name: full_name		Version Id: 1.0.0.0	
<i>Description:</i> The full_name attribute provides the complete name for a person and includes titles and suffixes.			
Namespace Id: pds	Steward: ops	Class Name: Subscriber_PDS3	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

full_name in Update_Entry

Name: full_name			Version Id: 1.0.0.0
<i>Description:</i> The full_name attribute provides the complete name for a person and includes titles and suffixes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Update_Entry	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

grating_position in Band_Bin *Deprecated*

Name: grating_position			Version Id: 1.0.0.0
<i>Description:</i> The grating_position attribute of a spectral qube describes the grating position which corresponds to the band. Grating positions are usually assigned consecutively from 0, and increasing position causes increasing wavelength for each detector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Band_Bin *Deprecated*	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

group_length in Group_Field_Binary

Name: group_length			Version Id: 1.0.0.0
<i>Description:</i> The group_length attribute provides the total length, in bytes, of a repeating field and/or group structure. It is the number of bytes in the repeating fields/groups plus any embedded unused bytes that are also repeated multiplied by the number of repetitions.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Field_Binary	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

group_length in Group_Field_Character

Name: group_length			Version Id: 1.0.0.0
<i>Description:</i> The group_length attribute provides the total length, in bytes, of a repeating field and/or group structure. It is the number of bytes in the repeating fields/groups plus any embedded unused bytes that are also repeated multiplied by the number of repetitions.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Field_Character	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

group_location in Group_Field_Binary

Name: group_location			Version Id: 1.0.0.0
<i>Description:</i> The group_location attribute provides the starting position for a Group_Field_Binary within the containing Record_Binary or Group_Field_Binary class, in bytes. Location "1" denotes the first byte of the containing class.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Field_Binary	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Location	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

group_location in Group_Field_Character

Name: group_location			Version Id: 1.0.0.0
<i>Description:</i> The group_location attribute provides the starting position for a Group_Field_Character within the containing Record_Character or Group_Field_Character class, in bytes. Location "1" denotes the first byte of the containing class.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Field_Character	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Location	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

group_number in Group

Name: group_number			Version Id: 1.0.0.0
<i>Description:</i> The group_number attribute provides the position of a group, within a series of groups, counting from 1. If two groups within a record are physically separated by one or more fields, they have consecutive group numbers; the intervening fields are numbered separately. Groups within a parent group, but separated by one or more fields, will also have consecutive group numbers.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

groups in Group

Name: groups			Version Id: 1.0.0.0
<i>Description:</i> The groups attribute provides a count of the number of (sub)groups within the repeating structure of a group. (Subsub)groups within (sub)groups within the group are not included in this count.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

groups in Record

Name: groups			Version Id: 1.0.0.0
<i>Description:</i> The groups attribute provides a count of the total number of groups directly associated with a table record. Groups within groups within the record are not included in this count.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Record	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

high_instrument_saturation in Special_Constants

Name: high_instrument_saturation			Version Id: 1.0.0.0
<i>Description:</i> The high_instrument_saturation attribute specifies a special value whose presence indicates the measuring instrument was saturated at the high end. The value must be less than the value of the valid_minimum attribute or more than the value of the valid_maximum attribute. Values of this attribute should be represented in the same data_type as the elements in the object with which the Special_Constants class is associated.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	-32765	conventional PDS3 and ISIS 2/3 qube value for a two byte signed integer data type	
	255	conventional ISIS 2/3 qube value for a one byte unsigned integer data type	
	3	conventional PDS3 qube value for any unsigned integer data type	
	65534	conventional ISIS 3 qube value for a two byte unsigned integer data type	
	FF7FFFE	conventional PDS3 and ISIS 2/3 qube value for a four byte IEEE floating point data type	
	FFFCFFFF	conventional PDS3 and ISIS 2 qube value for a four byte VAX floating point data type	

high_representation_saturation in Special_Constants

Name: high_representation_saturation			Version Id: 1.0.0.0
<i>Description:</i> The high_representative_saturation attribute specifies a special value whose presence indicates the true value cannot be represented in the chosen data type and length -- in this case being above the allowable range -- which may happen during conversion from another data type. The value must be less than the value of the valid_minimum attribute or more than the value of the valid_maximum attribute. Values of this attribute should be represented in the same data_type as the elements in the object with which the Special_Constants class is associated.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: high_representation_saturation		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	-32764	conventional PDS3 and ISIS 2/3 qube value for a two byte signed integer data type
	255	conventional ISIS 2/3 qube value for a one byte unsigned integer data type
	4	conventional PDS3 qube value for any unsigned integer data type
	65535	conventional ISIS 3 qube value for a two byte unsigned integer data type
	FF7FFFFF	conventional PDS3 and ISIS 2/3 qube value for a four byte IEEE floating point data type
	FFFBFFFF	conventional PDS3 and ISIS 2 qube value for a four byte VAX floating point data type

information_model_version in Identification_Area

Name: information_model_version		Version Id: 1.0.0.0	
<i>Description:</i> The information_model_version attribute provides the version identification of the PDS Information Model on which the label and schema are based.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Identification_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1.2.0.1	This version of the information model is an operational release.	

install_note in Software_Script

Name: install_note		Version Id: 1.0.0.0	
<i>Description:</i> The install note attribute provides a brief statement giving particulars about the installation of the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Script	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

institution_name in Node

Name: institution_name			Version Id: 1.0.0.0
<i>Description:</i> The institution_name attribute provides the name of the associated institution.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Node	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> [a-zA-Z]{1}([-/, _a-zA-Z0-9]*)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

institution_name in PDS_Affiliate

Name: institution_name			Version Id: 1.0.0.0
<i>Description:</i> The institution_name attribute provides the name of the associated institution.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> [a-zA-Z]{1}([-/, _a-zA-Z0-9]*)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_desc in Instrument_PDS3

Name: instrument_desc			Version Id: 1.0.0.0
<i>Description:</i> The instrument_desc attribute describes a given instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_host_desc in Instrument_Host_PDS3

Name: instrument_host_desc			Version Id: 1.0.0.0
<i>Description:</i> The instrument_host_desc provides a description of an instrument host			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_Host_PDS3	<i>Type:</i> ASCII_Text_Preserved

Attributes in the common
(pds) namespace.

Name: instrument_host_desc			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_host_id in Instrument_Host_PDS3

Name: instrument_host_id			Version Id: 1.0.0.0
<i>Description:</i> The instrument_host_id attribute provides a unique identifier for the host on which an instrument is located. This host can be either a spacecraft or an earth base (e.g. earth).			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_Host_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_host_name in Instrument_Host_PDS3

Name: instrument_host_name			Version Id: 1.0.0.0
<i>Description:</i> The instrument_host_name attribute provides the full name of the platform or facility upon which an instrument or other device is mounted. For example, the host can be a spacecraft, a ground-based telescope, or a laboratory.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_Host_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_host_type in Instrument_Host_PDS3

Name: instrument_host_type			Version Id: 1.0.0.0
<i>Description:</i> The instrument_host_type attribute provides the type of host on which an instrument is based. For example instrument is located on a spacecraft instrument_host_type attribute would have the value SPACECRAFT.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_Host_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_host_version_id in Instrument_Host

Name: instrument_host_version_id			Version Id: 1.0.0.0
<i>Description:</i> The instrument_host_version_id attribute provides the version of the instrument host.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_id in Instrument_PDS3

Name: instrument_id			Version Id: 1.0.0.0
<i>Description:</i> The instrument id provides a formal name used to refer to an instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_name in Instrument_PDS3

Name: instrument_name			Version Id: 1.0.0.0
<i>Description:</i> The instrument_name attribute provides a unique name for an instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_serial_number in Instrument_PDS3

Name: instrument_serial_number			Version Id: 1.0.0.0
<i>Description:</i> The instrument serial number element provides the manufacturer's serial number assigned to an instrument. This number may be used to uniquely identify a particular instrument for tracing its components or determining its calibration history, for example.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_type in Instrument_PDS3

Name: instrument_type			Version Id: 1.0.0.0
<i>Description:</i> The instrument_type attribute identifies the type of an instrument. Example values: POLARIMETER SPECTROMETER			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

instrument_version_id in Instrument_PDS3

Name: instrument_version_id			Version Id: 1.0.0.0
<i>Description:</i> The Instrument_Version_Id element identifies the specific model of an instrument used to obtain data. For example, this keyword could be used to distinguish between an engineering model of a camera used to acquire test data, and a flight model of a camera used to acquire science data during a mission.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Instrument_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

invalid_constant in Special_Constants

Name: invalid_constant			Version Id: 1.0.0.0
<i>Description:</i> The invalid_constant attribute provides a value that indicates the original value was outside the valid range for the parameter.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Constant	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

kernel_type in SPICE_Kernel

Name: kernel_type			Version Id: 1.0.0.0
<i>Description:</i> The kernel_type attribute identifies the type of SPICE kernel.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> SPICE_Kernel	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	CK	SPICE_Kernel is type CK (orientation kernel)	
	DBK	SPICE_Kernel is type DBK (database kernel)	
	DSK	SPICE_Kernel is type DSK (digital shape kernel)	
	EK	SPICE_Kernel is type EK (events kernel)	

Attributes in the common
(pds) namespace.

Name: kernel_type		Version Id: 1.0.0.0
	FK	SPICE_Kernel is type FK (frames kernel)
	IK	SPICE_Kernel is type IK (instrument kernel)
	LSK	SPICE_Kernel is type LSK (leap seconds kernel)
	MK	SPICE_Kernel is type MK (meta kernel names SPICE kernels to be used together)
	PCK	SPICE_Kernel is type PCL (planetary constants kernel)
	SCLK	SPICE_Kernel is type SCLK (spacecraft clock kernel)
	SPK	SPICE_Kernel is type SPK (ephemeris kernel)

keyword in Citation_Information

Name: keyword		Version Id: 1.0.0.0	
<i>Description:</i> The keyword attribute provides one or more words to be used for keyword search.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Citation_Information	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

language in Terminological_Entry

Name: language		Version Id: 1.0.0.0	
<i>Description:</i> The language attribute provides the language used for definition and designation of the term.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Terminological_Entry	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	English	Values in Terminological_Entry are in English	
	Russian	Values in Terminological_Entry are in Russian	

last_modification_date_time in Ingest_LDD

Name: last_modification_date_time		Version Id: 1.0.0.0
<i>Description:</i> The last_modification_date_time attribute gives the most recent date and time that a change was made.		

Name: last_modification_date_time			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> ASCII_Date_Time_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

last_sampling_parameter_value in Uniformly_Sampled

Name: last_sampling_parameter_value			Version Id: 1.0.0.0
<i>Description:</i> The last_sampling_parameter_value element provides the last value in an ascending series and is therefore the maximum value at which a given data item was sampled.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Uniformly_Sampled	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

Idd_version_id in Ingest_LDD

Name: Idd_version_id			Version Id: 1.0.0.0
<i>Description:</i> The Idd_version_id attribute provides the version of the Local Data Dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

Idd_version_id in XML_Schema

Name: Idd_version_id			Version Id: 1.0.0.0
<i>Description:</i> The Idd_version_id attribute provides the version of the Local Data Dictionary.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> XML_Schema	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: ldd_version_id			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lid_reference in Bundle_Member_Entry

Name: lid_reference			Version Id: 1.0.0.0
<i>Description:</i> The lid_reference attribute provides the logical_identifier for a product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle_Member_Entry	<i>Type:</i> ASCII_LID
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Reference	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lid_reference in Internal_Reference

Name: lid_reference			Version Id: 1.0.0.0
<i>Description:</i> The lid_reference attribute provides the logical_identifier for a product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Internal_Reference	<i>Type:</i> ASCII_LID
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Reference	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lidvid_reference in Bundle_Member_Entry

Name: lidvid_reference			Version Id: 1.0.0.0
<i>Description:</i> The lidvid_reference attribute provides the logical_identifier plus version_id, which uniquely identifies a product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle_Member_Entry	<i>Type:</i> ASCII_LIDVID
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Reference	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lidvid_reference in Internal_Reference

Name: lidvid_reference			Version Id: 1.0.0.0
<i>Description:</i> The lidvid_reference attribute provides the logical_identifier plus version_id, which uniquely identifies a product.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Internal_Reference	<i>Type:</i> ASCII_LIDVID
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Reference	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

line_display_direction in Display_2D_Image *Deprecated*

Name: line_display_direction			Version Id: 1.0.0.0
<i>Description:</i> The line_display_direction element is the preferred orientation of lines within an image for viewing on a display device. Note that if this keyword is present in a label, the sample_display_direction keyword must also be present and must contain a value orthogonal to the value selected for this keyword.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Display_2D_Image *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Direction	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Down	The preferred orientation of lines within an image for viewing on a display device is Down	
	Up	The preferred orientation of lines within an image for viewing on a display device is Up	

local_identifier in Axis_Array

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Axis_Array	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None

Name: local_identifier		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

local_identifier in Byte_Stream

Name: local_identifier		Version Id: 1.0.0.0	
<i>Description: The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Byte_ Stream</i>	<i>Type: ASCII_Short_ String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Association

Name: local_identifier		Version Id: 1.0.0.0	
<i>Description: The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_ Association</i>	<i>Type: ASCII_Short_ String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Attribute

Name: local_identifier		Version Id: 1.0.0.0	
<i>Description: The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.</i>			
<i>Namespace Id: pds</i>	<i>Steward: ops</i>	<i>Class Name: DD_ Attribute</i>	<i>Type: ASCII_Short_ String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Attribute_Full

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Class

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Class_Full

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in DD_Rule

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			

Name: local_identifier			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Rule	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in Field_Statistics

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Statistics	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in File

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in Geometry

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Geometry	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: local_identifier			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

local_identifier in Object_Statistics

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

local_identifier in Quaternion

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

local_identifier in Subscriber_PDS3

Name: local_identifier			Version Id: 1.0.0.0
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Subscriber_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: local_identifier		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

local_identifier in Update

Name: local_identifier		Version Id: 1.0.0.0	
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Update	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier in Vector

Name: local_identifier		Version Id: 1.0.0.0	
<i>Description:</i> The local_identifier attribute provides a character string which uniquely identifies the containing object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_identifier_reference in Local_Internal_Reference

Name: local_identifier_reference		Version Id: 1.0.0.0	
<i>Description:</i> The local_identifier_reference attribute provides a character string which is used to reference a uniquely identified object within the label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Local_Internal_Reference	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_mean_solar_time in Time_Coordinates

Name: local_mean_solar_time			Version Id: 1.0.0.0
<i>Description:</i> The local_mean_solar_time attribute provides the hour angle of the fictitious mean Sun at a fixed point on a rotating solar system body.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Time_Coordinates	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 8	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_reference_type in Local_Internal_Reference

Name: local_reference_type			Version Id: 1.0.0.0
<i>Description:</i> The local_reference_type attribute provides the name of the local association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Local_Internal_Reference	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

local_true_solar_time in Time_Coordinates

Name: local_true_solar_time			Version Id: 1.0.0.0
<i>Description:</i> The local_true_solar_time (LTST) attribute provides the local time on a rotating solar system body where LTST is 12 h at the sub-solar point (SSP) and increases 1 h for each 15 degree increase in east longitude away from the SSP for prograde rotation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Time_Coordinates	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 8	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

logical_identifier in Identification_Area

Name: logical_identifier			Version Id: 1.0.0.0
<i>Description:</i> A logical identifier identifies the set of all versions of an object. It is an object identifier without a version.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Identification_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

low_instrument_saturation in Special_Constants

Name: low_instrument_saturation			Version Id: 1.0.0.0
<i>Description:</i> The low_instrument_saturation attribute specifies a special value whose presence indicates the measuring instrument was saturated at the low end. The value must be less than the value of the valid_minimum attribute. Values of this attribute should be represented in the same data_type as the elements in the object with which the Special_Constants class is associated.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	-32766	conventional PDS3 and ISIS 2/3 qube value for a two byte signed integer data type	
	0	conventional ISIS 2/3 qube value for a one byte unsigned integer data type	
	2	conventional PDS3 and ISIS 3 qube value for any unsigned integer data type	
	FF7FFFFD	conventional PDS3 and ISIS 2/3 qube value for a four byte IEEE floating point data type	
	FFFDFFFF	conventional PDS3 and ISIS 2 qube value for a four byte VAX floating point data type	

low_representation_saturation in Special_Constants

Name: low_representation_saturation		Version Id: 1.0.0.0	
<i>Description:</i> The low_representative_saturation attribute specifies a special value whose presence indicates the true value cannot be represented in the chosen data type and length -- in this case being below the allowable range -- which may happen during conversion from another data type. The value must be less than the value of the valid_minimum attribute. Values of this attribute should be represented in the same data_type as the elements in the object with which the Special_Constants class is associated.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	-32767	conventional ISIS qube value for any two byte signed integer data type	
	1	conventional ISIS qube value for any unsigned data type	
	16#FF7FFFC#	Not VAX	
	16#FFFEFFFF#	VAX	

maximum in Field_Statistics

Name: maximum		Version Id: 1.0.0.0	
<i>Description:</i> The maximum attribute provides the largest stored value which appears in the field over all records (empty fields and Special_Constants values are excluded).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum in Object_Statistics

Name: maximum		Version Id: 1.0.0.0	
<i>Description:</i> The maximum attribute provides the largest value which appears in the stored array after application of any bit mask (Special_Constants values are excluded).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real

Name: maximum			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_AnyURI

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_AnyURI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_DOI

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Date

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String

Name: maximum_characters		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

maximum_characters in ASCII_Date_DOY

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_DOY	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_characters in ASCII_Date_Time

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_Time	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_characters in ASCII_Date_Time_DOY

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_Time_DOY	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_characters in ASCII_Date_Time_UTC

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Date_Time_YMD

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Date_YMD

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Directory_Path_Name

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Directory_Path_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_Directory_Path_Name may have no more than 255 characters	

maximum_characters in ASCII_File_Name

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_File_Name may have no more than 255 characters	

maximum_characters in ASCII_File_Specification_Name

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Specification_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String

Name: maximum_characters		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	Value	Value Meaning
	255	Values of ASCII_File_Specification_Name may have no more than 255 characters

maximum_characters in ASCII_Integer

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Integer	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_characters in ASCII_LID

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_LID	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	255	Values of ASCII_LID may have no more than 255 characters	

maximum_characters in ASCII_LIDVID

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_LIDVID	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String

Name: maximum_characters		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	255	Values of ASCII_LIDVID may have no more than 255 characters

maximum_characters in ASCII_LIDVID_LID

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_LIDVID_LID may have no more than 255 characters	

maximum_characters in ASCII_MD5_Checksum

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	32	Values of ASCII_MD5_Checksum may have no more than 32 characters	

maximum_characters in ASCII_NonNegative_Integer

Name: maximum_characters		Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.		

Attributes in the common
(pds) namespace.

Name: maximum_characters			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Numeric_Base16

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_Numeric_Base16 may have no more than 255 characters	

maximum_characters in ASCII_Numeric_Base2

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_Numeric_Base2 may have no more than 255 characters	

maximum_characters in ASCII_Numeric_Base8

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base8	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_Numeric_Base8 may have no more than 255 characters	

maximum_characters in ASCII_Real

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Real	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Short_String_Collapsed

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Name: maximum_characters		Version Id: 1.0.0.0
	255	Values of ASCII_Short_String_Collapsed may have no more than 255 characters

maximum_characters in ASCII_Short_String_Preserved

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	Values of ASCII_Short_String_Preserved may have no more than 255 characters	

maximum_characters in ASCII_Text_Collapsed

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_characters in ASCII_Text_Preserved

Name: maximum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed

Name: maximum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_characters in ASCII_Time

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_characters in ASCII_VID

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	100	Values of ASCII_VID may have no more than 100 characters	

maximum_characters in Character_Data_Type

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed

Name: maximum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_characters in DD_Value_Domain

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_ Value_Domain	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_characters in DD_Value_Domain_Full

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_ Value_Domain_Full	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_characters in UTF8_Short_String_Collapsed

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_ Short_String_Collapsed	<i>Type:</i> ASCII_Short_ String_Collapsed

Attributes in the common
(pds) namespace.

Name: maximum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	UTF8_Short_String_Collapsed may have no more than 255 characters	

maximum_characters in UTF8_Short_String_Preserved

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	255	UTF8_Short_String_Preserved may have no more than 255 characters	

maximum_characters in UTF8_Text_Preserved

Name: maximum_characters			Version Id: 1.0.0.0
<i>Description:</i> The maximum_characters attribute provides the upper, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_field_length in Field_Delimited

Name: maximum_field_length			Version Id: 1.0.0.0
<i>Description:</i> The maximum_field_length attribute sets an upper, inclusive bound on the number of bytes in the field.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_occurrences in DD_Association

Name: maximum_occurrences			Version Id: 1.0.0.0
<i>Description:</i> The maximum occurrences attribute indicates the number of times something may occur. It is also called the maximum cardinality. The asterisk character is used as a value to indicate that no upper bound exists.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_occurrences in DD_Association_External *Deprecated*

Name: maximum_occurrences			Version Id: 1.0.0.0
<i>Description:</i> The maximum occurrences attribute indicates the number of times something may occur. It is also called the maximum cardinality. The asterisk character is used as a value to indicate that no upper bound exists.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association_External *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_record_length in Record_ Delimited

Name: maximum_record_length			Version Id: 1.0.0.0
<i>Description:</i> The maximum_record_length attribute provides the maximum length of a record, including the record delimiter.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Record_ Delimited	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_scaled_value in Object_Statistics

Name: maximum_scaled_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_scaled_value attribute provides the maximum value after application of scaling_factor and value_offset (see their definitions; maximum_scaled_value is the maximum of Ov).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_ Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Date_Time

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_ Date_Time	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Date_Time_DOY

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Date_Time_UTC

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Date_Time_YMD

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Integer

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Integer	<i>Type:</i> ASCII_Short_String_Collapsed

Name: maximum_value			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_LID

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_NonNegative_Integer

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Numeric_Base16

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String

Name: maximum_value		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

maximum_value in ASCII_Numeric_Base2

Name: maximum_value		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Numeric_Base2	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_value in ASCII_Real

Name: maximum_value		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Real	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_value in ASCII_Short_String_Collapsed

Name: maximum_value		Version Id: 1.0.0.0	
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Short_String_Collapsed	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

maximum_value in ASCII_Short_String_Preserved

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Text_Preserved

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_Time

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in ASCII_VID

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed

Name: maximum_value			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in Character_Data_Type

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in DD_Value_Domain

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in DD_Value_Domain_Full

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in UTF8_Short_String_Collapsed

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in UTF8_Short_String_Preserved

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_value in UTF8_Text_Preserved

Name: maximum_value			Version Id: 1.0.0.0
<i>Description:</i> The maximum_value attribute provides the upper, inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

md5_checksum in File

Name: md5_checksum			Version Id: 1.0.0.0
<i>Description:</i> The md5_checksum attribute is the 32-character hexadecimal number computed for a file using the MD5 algorithm.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_MD5_Checksum
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 32	<i>Maximum Characters:</i> 32
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Checksum	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> ([a-f0-9]{32})	
<i>Permissible Value(s)</i>	<i>No Values</i>		

md5_checksum in Object_Statistics

Name: md5_checksum			Version Id: 1.0.0.0
<i>Description:</i> The md5_checksum attribute is the 32-character hexadecimal number computed for a file using the MD5 algorithm.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_MD5_Checksum
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 32	<i>Maximum Characters:</i> 32
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Checksum	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> ([a-f0-9]{32})	
<i>Permissible Value(s)</i>	<i>No Values</i>		

mean in Field_Statistics

Name: mean			Version Id: 1.0.0.0
<i>Description:</i> The mean attribute provides the sum of the stored field values divided by the number of values in all records (empty fields and Special_Constants values are excluded from both the sum and the count).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

mean in Object_Statistics

Name: mean			Version Id: 1.0.0.0
<i>Description:</i> The mean attribute provides the sum of the stored array element values (after application of any bit mask) divided by the number of elements (Special_Constants values are excluded from both the sum and the count).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

median in Field_Statistics

Name: median			Version Id: 1.0.0.0
<i>Description:</i> The median attribute provides the number separating the larger half of stored field values from the algebraically smaller half over all records (empty fields and Special_Constants values are excluded from the sort).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

median in Object_Statistics

Name: median			Version Id: 1.0.0.0
<i>Description:</i> The median attribute provides the number separating the larger half of stored array element values from the algebraically smaller half after application of any bit mask (Special_Constants values are excluded from the sort).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

medium_type in NSSDC

Name: medium_type			Version Id: 1.0.0.0
<i>Description:</i> The medium_type attribute identifies the physical storage medium for a data volume. Examples: CD-ROM, CARTRIDGE TAPE.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> NSSDC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

medium_type in Volume_PDS3

Name: medium_type			Version Id: 1.0.0.0
<i>Description:</i> The medium_type attribute identifies the physical storage medium for a data volume. Examples: CD-ROM, CARTRIDGE TAPE.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

member_status in Bundle_Member_Entry

Name: member_status			Version Id: 1.0.0.0
<i>Description:</i> The member_status attribute indicates whether the collection is primary and whether the file_specification_name has been provided for the product_collection label.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle_Member_Entry	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Primary	The collection is a primary member of the bundle	
	Secondary	The collection is a secondary member of the bundle	

minimum in Field_Statistics

Name: minimum			Version Id: 1.0.0.0
<i>Description:</i> The minimum attribute provides the algebraically smallest stored value which appears in the field over all records (empty fields and Special_Constants values are excluded).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum in Object_Statistics

Name: minimum			Version Id: 1.0.0.0
<i>Description:</i> The minimum attribute provides the algebraically smallest value which appears in the stored array after application of any bit mask (Special_Constants values are excluded).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_AnyURI

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_AnyURI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_DOI

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			

Name: minimum_characters			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Date

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Date_DOY

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Date_Time

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: minimum_characters			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_characters in ASCII_Date_Time_DOY

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_characters in ASCII_Date_Time_UTC

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_characters in ASCII_Date_Time_YMD

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Date_YMD

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Directory_Path_Name

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Directory_Path_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Directory_Path_Name must have at least 1 character	

minimum_characters in ASCII_File_Name

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Name	<i>Type:</i> ASCII_Short_String_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_File_Name must have at least one character	

minimum_characters in ASCII_File_Specification_Name

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_File_Specification_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_File_Specification_Name must have at least 1 character	

minimum_characters in ASCII_Integer

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_LID

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			

Attributes in the common
(pds) namespace.

Name: minimum_characters			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	14	Values of ASCII_LID must have at least 14 characters	

minimum_characters in ASCII_LIDVID

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	19	Values of ASCII_LIDVID must have at least 19 characters	

minimum_characters in ASCII_LIDVID_LID

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	14	Values of ASCII_LIDVID_LID must have at least 14 characters	

minimum_characters in ASCII_MD5_ Checksum

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	32	Values of ASCII_MD5_Checksum must have at least 32 characters	

minimum_characters in ASCII_NonNegative_Integer

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Numeric_Base16

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: minimum_characters		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	1	Values of ASCII_Numeric_Base16 must have at least 1 character

minimum_characters in ASCII_Numeric_Base2

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Numeric_Base2 must have at least 1 character	

minimum_characters in ASCII_Numeric_Base8

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base8	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Numeric_Base8 must have at least 1 character	

minimum_characters in ASCII_Real

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Real	<i>Type:</i> ASCII_Short_String_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_Short_String_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Short_String_Collapsed must have at least 1 character	

minimum_characters in ASCII_Short_String_Preserved

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Short_String_Preserved must have at least 1 character	

minimum_characters in ASCII_String

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_String	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_String must have at least 1 character	

minimum_characters in ASCII_Text_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	Values of ASCII_Text_Collapsed must have at least 1 character	

minimum_characters in ASCII_Text_Preserved

Name: minimum_characters			Version Id: 1.0.0.0
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: minimum_characters		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	1	Values of ASCII_Text_Preserved must have at least 1 character

minimum_characters in ASCII_Time

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_characters in ASCII_VID

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	3	Values of ASCII_VID must have at least 3 characters	

minimum_characters in Character_Data_Type

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String

Name: minimum_characters		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

minimum_characters in DD_Value_Domain

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: ops	Class Name: DD_Value_Domain	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

minimum_characters in DD_Value_Domain_Full

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: ops	Class Name: DD_Value_Domain_Full	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

minimum_characters in UTF8_Short_String_Collapsed

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
Namespace Id: pds	Steward: pds	Class Name: UTF8_Short_String_Collapsed	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Count	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	

Name: minimum_characters		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	1	UTF8_Short_String_Collapsed must have at least 1 character

minimum_characters in UTF8_Short_String_Preserved

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	UTF8_Short_String_Preserved must have at least 1 character	

minimum_characters in UTF8_String

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_String	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	UTF8_String must have at least 1 character	

minimum_characters in UTF8_Text_Preserved

Name: minimum_characters		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_characters attribute provides the lower, inclusive bound on the number of characters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed

Name: minimum_characters			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	1	UTF8_Text_Preserved must have at least 1 character	

minimum_occurrences in DD_Association

Name: minimum_occurrences			Version Id: 1.0.0.0
<i>Description:</i> The minimum occurrences attribute indicates the number of times something may occur. It is also called the minimum cardinality.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_occurrences in DD_Association_External *Deprecated*

Name: minimum_occurrences			Version Id: 1.0.0.0
<i>Description:</i> The minimum occurrences attribute indicates the number of times something may occur. It is also called the minimum cardinality.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association_External *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_scaled_value in Object_Statistics

Name: minimum_scaled_value		Version Id: 1.0.0.0
<i>Description:</i> The minimum_scaled_value attribute provides the minimum value after application of scaling_factor and value_offset (see their definitions; minimum_scaled_value is the minimum of Ov).		

Name: minimum_scaled_value			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Date_Time

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Date_Time_DOY

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Date_Time_UTC

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String

Name: minimum_value		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

minimum_value in ASCII_Date_Time_YMD

Name: minimum_value		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Date_Time_YMD	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

minimum_value in ASCII_Integer

Name: minimum_value		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_Integer	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

minimum_value in ASCII_LID

Name: minimum_value		Version Id: 1.0.0.0	
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
Namespace Id: pds	Steward: pds	Class Name: ASCII_LID	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Value	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

minimum_value in ASCII_NonNegative_Integer

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	0	The minimum value for ASCII_NonNegative_Integer is zero	

minimum_value in ASCII_Numeric_Base16

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Numeric_Base2

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Real

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			

Name: minimum_value			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Real	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Short_String_Collapsed

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Short_String_Preserved

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in ASCII_Text_Preserved

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed

Name: minimum_value			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_value in ASCII_Time

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_value in ASCII_VID

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_value in Character_Data_Type

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_value in DD_Value_Domain

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in DD_Value_Domain_Full

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in UTF8_Short_String_Collapsed

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in UTF8_Short_String_Preserved

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			

Name: minimum_value			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_ Short_String_Preserved	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_value in UTF8_Text_Preserved

Name: minimum_value			Version Id: 1.0.0.0
<i>Description:</i> The minimum_value attribute provides the lower inclusive bound on the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_ Text_Preserved	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

missing_constant in Special_Constants

Name: missing_constant			Version Id: 1.0.0.0
<i>Description:</i> The missing_constant attribute provides a value that indicates the original value was missing, such as due to a gap in coverage.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_ Constants	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Constant	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

mission_desc in Mission_PDS3

Name: mission_desc			Version Id: 1.0.0.0
<i>Description:</i> The mission_desc attribute summarizes major aspects of a planetary mission or project, including the number and type of spacecraft, the target body or bodies and major accomplishments.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Mission_ PDS3	<i>Type:</i> ASCII_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None

Name: mission_desc			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

mission_name in Mission_PDS3

Name: mission_name			Version Id: 1.0.0.0
<i>Description:</i> The mission_name attribute identifies a major planetary mission or project. A given planetary mission may be associated with one or more spacecraft.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Mission_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

mission_objectives_summary in Mission_PDS3

Name: mission_objectives_summary			Version Id: 1.0.0.0
<i>Description:</i> The mission_objectives_summary attribute describes the major scientific objectives of a planetary mission or project.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Mission_PDS3	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Summary	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

mission_start_date in Mission_PDS3

Name: mission_start_date			Version Id: 1.0.0.0
<i>Description:</i> The mission_start_date attribute provides the date of the beginning of a mission in UTC system format.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Mission_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Short_String

Name: mission_start_date		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

mission_stop_date in Mission_PDS3

Name: mission_stop_date		Version Id: 1.0.0.0	
<i>Description:</i> The mission_stop_date attribute provides the date of the end of a mission in UTC system format.			
Namespace Id: pds	Steward: ops	Class Name: Mission_PDS3	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Time	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

model_id in Instrument

Name: model_id		Version Id: 1.0.0.0	
<i>Description:</i> The model_id attribute helps discriminate instrument hardware. For example "flight", "engineering", or "proto" have been used.			
Namespace Id: pds	Steward: pds	Class Name: Instrument	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: ID	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

modification_date in Modification_Detail

Name: modification_date		Version Id: 1.0.0.0	
<i>Description:</i> The modification_date attribute provides date the modifications were completed			
Namespace Id: pds	Steward: pds	Class Name: Modification_Detail	Type: ASCII_Date_YMD
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Time	Conceptual Domain: Time
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

naif_host_id in Instrument_Host

Name: naif_host_id			Version Id: 1.0.0.0
<i>Description:</i> The naif_instrument_id element provides the numeric ID used within the SPICE system to identify the spacecraft, spacecraft structure or science instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

naif_instrument_id in Instrument

Name: naif_instrument_id			Version Id: 1.0.0.0
<i>Description:</i> The naif_instrument_id element provides the numeric ID used within the SPICE system to identify the spacecraft, spacecraft structure or science instrument.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Agency

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Agency	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	European Space Agency	The Agency has name European Space Agency	
	National Aeronautics and Space Administration	The Agency has name National Aeronautics and Space Administration	

name in Byte_Stream

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Byte_Stream	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in DD_Association_External *Deprecated*

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association_External *Deprecated*	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in DD_Attribute

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in DD_Attribute_Full

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in DD_Class

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in DD_Class_Full

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in External_Reference_Extended

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			

Attributes in the common
(pds) namespace.

Name: name			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> External_Reference_Extended	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Facility

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Facility	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Field

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Field_Binary

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: name			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Field_Bit

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Field_Character

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Field_Delimited

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Ingest_LDD

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Instrument

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Instrument_Host

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Investigation

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			

Attributes in the common
(pds) namespace.

Name: name			Version Id: 1.0.0.0
Namespace Id: pds	Steward: pds	Class Name: Investigation	Type: UTF8_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

name in Investigation_Area

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
Namespace Id: pds	Steward: pds	Class Name: Investigation_Area	Type: UTF8_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		
<i>Extended Value(s) for: pds:Product_Observational/ pds:Observation_Area/ pds:Investigation_Area</i>	<i>Value</i>	<i>Value Meaning</i>	
	\$name	The value for name is to be provided by software during template processing.	

name in Node

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
Namespace Id: pds	Steward: ops	Class Name: Node	Type: UTF8_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	<i>Value</i>	<i>Value Meaning</i>	
	Engineering	The Node has name Engineering	
	Geosciences	The Node has name Geosciences	
	Imaging	The Node has name Imaging	

Name: name		Version Id: 1.0.0.0
	Management	The Node has name Management
	Navigation and Ancillary Information Facility	The Node has name Navigation and Ancillary Information Facility
	Planetary Atmospheres	The Node has name Planetary Atmospheres
	Planetary Plasma Interactions	The Node has name Planetary Plasma Interactions
	Planetary Rings	The Node has name Planetary Rings
	Planetary Science Archive	The Node has name Planetary Science Archive
	Radio Science	The Node has name Radio Science
	Small Bodies	The Node has name Small Bodies

name in Observing_System

Name: name		Version Id: 1.0.0.0	
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Observing_System	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		
<i>Extended Value(s) for:</i> pds:Product_Observational/ pds:Observation_Area/ pds:Observing_System	<i>Value</i>	<i>Value Meaning</i>	
	\$name	The value for name is to be provided by software during template processing.	

name in Observing_System_Component

Name: name		Version Id: 1.0.0.0	
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Observing_System_Component	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Attributes in the common
(pds) namespace.

Name: name		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	
<i>Extended Value(s) for: pds:Product_ Observational/ pds:Observation_ Area/pds:Observing_ System/pds:Observing_ System_Component</i>	<i>Value</i>	<i>Value Meaning</i>
	\$name	The value for name is to be provided by software during template processing.

name in PDS_Affiliate

Name: name		Version Id: 1.0.0.0	
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in PDS_Guest

Name: name		Version Id: 1.0.0.0	
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Guest	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Quaternion

Name: name		Version Id: 1.0.0.0	
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion	<i>Type:</i> UTF8_Short_String_Collapsed

Name: name			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Quaternion_Component

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion_Component	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Resource

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Resource	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Software

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: name			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Target

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

name in Target_Identification

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a human-readable primary name/identification in the standard format for the target type.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target_ Identification	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		
<i>Extended Value(s)</i> <i>for:</i> pds:Product_ Observational/ pds:Observation_ Area/pds:Target_ Identification	<i>Value</i>	<i>Value Meaning</i>	
	\$name	The value for name is to be provided by software during template processing.	

name in Terminological_Entry

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			

Attributes in the common
(pds) namespace.

Name: name			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Terminological_Entry	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Vector

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

name in Vector_Component

Name: name			Version Id: 1.0.0.0
<i>Description:</i> The name attribute provides a word or combination of words by which the object is known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Component	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

namespace_id in DD_Association_External *Deprecated*

Name: namespace_id			Version Id: 1.0.0.0
<i>Description:</i> The namespace_id attribute provides the abbreviation of the XML schema namespace container for this logical grouping of classes and attributes. It is assigned by the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association_External *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed

Name: namespace_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

namespace_id in DD_Attribute_Full

Name: namespace_id			Version Id: 1.0.0.0
<i>Description:</i> The namespace_id attribute provides the abbreviation of the XML schema namespace container for this logical grouping of classes and attributes. It is assigned by the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

namespace_id in DD_Class_Full

Name: namespace_id			Version Id: 1.0.0.0
<i>Description:</i> The namespace_id attribute provides the abbreviation of the XML schema namespace container for this logical grouping of classes and attributes. It is assigned by the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

namespace_id in Ingest_LDD

Name: namespace_id			Version Id: 1.0.0.0
<i>Description:</i> The namespace_id attribute provides the abbreviation of the XML schema namespace container for this logical grouping of classes and attributes. It is assigned by the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String

Attributes in the common
(pds) namespace.

Name: namespace_id		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

nil_reason in Symbolic_Literals_PDS

Name: nil_reason		Version Id: 1.0.0.0	
<i>Description:</i> The nil_reason attribute provides the permissible values allowed as reasons when an attribute assigned a nil value.			
Namespace Id: pds	Steward: ops	Class Name: Symbolic_Literals_PDS	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	anticipated	The value is temporarily not available.	
	inapplicable	There is no value.	
	missing	The correct value is not readily available to the sender of this data. However, a correct value probably exists.	
	unknown	The correct value is not readily available to the sender of this data. Furthermore, a correct value may not exist.	

nillable_flag in DD_Attribute

Name: nillable_flag		Version Id: 1.0.0.0	
<i>Description:</i> The nillable_flag attribute indicates whether an attribute is allowed to take on nil as a value.			
Namespace Id: pds	Steward: ops	Class Name: DD_Attribute	Type: ASCII_Boolean
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Flag	Conceptual Domain: Boolean
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

nillable_flag in DD_Attribute_Full

Name: nillable_flag		Version Id: 1.0.0.0	
<i>Description:</i> The nillable_flag attribute indicates whether an attribute is allowed to take on nil as a value.			

Name: nillable_flag			Version Id: 1.0.0.0
Namespace Id: pds	Steward: ops	Class Name: DD_Attribute_Full	Type: ASCII_Boolean
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Flag	Conceptual Domain: Boolean
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

not_applicable_constant in Special_Constants

Name: not_applicable_constant			Version Id: 1.0.0.0
<i>Description:</i> The not_applicable_constant attribute provides a value that indicates the parameter is not applicable.			
Namespace Id: pds	Steward: pds	Class Name: Special_Constants	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Constant	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

nssdc_collection_id in NSSDC

Name: nssdc_collection_id			Version Id: 1.0.0.0
<i>Description:</i> An NSSDC Collection ID is an NSSDC assigned identifier for a collection of PDS datasets.			
Namespace Id: pds	Steward: ops	Class Name: NSSDC	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: ID	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

object_length in Encoded_Byte_Stream

Name: object_length			Version Id: 1.0.0.0
<i>Description:</i> The object_length attribute provides the length of the digital object in bytes.			
Namespace Id: pds	Steward: pds	Class Name: Encoded_Byte_Stream	Type: ASCII_Integer

Name: object_length			Version Id: 1.0.0.0
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

object_length in Header

Name: object_length			Version Id: 1.0.0.0
<i>Description:</i> The object_length attribute provides the length of the digital object in bytes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Header	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

object_length in Parsable_Byte_Stream

Name: object_length			Version Id: 1.0.0.0
<i>Description:</i> The object_length attribute provides the length of the digital object in bytes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Parsable_Byte_Stream	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

offset in Array

Name: offset			Version Id: 1.0.0.0
<i>Description:</i> The offset attribute provides the displacement of the object starting position from the beginning of the parent structure (file, record, etc.). If there is no displacement, offset=0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Array	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

offset in Encoded_Byte_Stream

Name: offset			Version Id: 1.0.0.0
<i>Description:</i> The offset attribute provides the displacement of the object starting position from the beginning of the parent structure (file, record, etc.). If there is no displacement, offset=0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Encoded_Byte_Stream	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

offset in Parsable_Byte_Stream

Name: offset			Version Id: 1.0.0.0
<i>Description:</i> The offset attribute provides the displacement of the object starting position from the beginning of the parent structure (file, record, etc.). If there is no displacement, offset=0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Parsable_Byte_Stream	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

offset in Table_Base

Name: offset			Version Id: 1.0.0.0
<i>Description:</i> The offset attribute provides the displacement of the object starting position from the beginning of the parent structure (file, record, etc.). If there is no displacement, offset=0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Base	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

orbit_direction in Target_PDS3

Name: orbit_direction			Version Id: 1.0.0.0
<i>Description:</i> The orbit_direction element provides the direction of movement along the orbit about the primary as seen from the north pole of the 'invariable plane of the solar system', which is the			

Name: orbit_direction			Version Id: 1.0.0.0
plane passing through the center of mass of the solar system and perpendicular to the angular momentum vector of the solar system orbit motion. PROGRADE for positive rotation according to the right-hand rule, RETROGRADE for negative rotation.			
Namespace Id: pds	Steward: ops	Class Name: Target_PDS3	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Direction	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

original_band in Band_Bin *Deprecated*

Name: original_band			Version Id: 1.0.0.0
<i>Description:</i> The original_band attribute of a spectral qube provides the sequence of band numbers in the qube relative to some original qube. In the original qube, the values are just consecutive integers beginning with 1. In a qube which contains a subset of the bands in the original qube, the values are the original sequence numbers from that qube.			
Namespace Id: pds	Steward: img	Class Name: Band_Bin *Deprecated*	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: 512	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

os_version in Software_Binary

Name: os_version			Version Id: 1.0.0.0
<i>Description:</i> The OS version attribute indicates the version of an operating system.			
Namespace Id: pds	Steward: ops	Class Name: Software_Binary	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

os_version in Software_Source

Name: os_version			Version Id: 1.0.0.0
<i>Description:</i> The OS version attribute indicates the version of an operating system.			
Namespace Id: pds	Steward: ops	Class Name: Software_Source	Type: ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: os_version			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

parsing_standard_id in Checksum_Manifest

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Checksum_Manifest	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	MD5Deep 4.n	The checksum manifest is governed by the Message-Digest Algorithm (MD5) output of the MD5 Deep Package Version 4.n.	

parsing_standard_id in Header

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Header	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	7-Bit ASCII Text	The Header contains simple text using only the 7-Bit ASCII character set. ANSI X3.4-1986.	
	CDF 3.4 ISTP/IACG	The Header is governed by Version 3.4 of the CDF format specification, the ISTP/IACG guidelines and PDS constraints.	
	FITS 3.0	The Header is governed by the standard Flexible Image Transport System (FITS), Version 3.0.	
	ISIS2	The Header is governed by the standard Integrated Software for Imagers and	

Attributes in the common
(pds) namespace.

Name: parsing_standard_id		Version Id: 1.0.0.0
		Spectrometers (ISIS), USGS Astrogeology Isis Cube, Version 2.
	ISIS3	The Header is governed by the standard Integrated Software for Imagers and Spectrometers (ISIS), USGS Astrogeology ISIS Cube, Version 3.
	PDS DSV 1	The Header is governed by the standard Planetary Data System (PDS) Delimiter Separated Values (DSV) Format, Version 1.n.
	PDS ODL 2	The Header is governed by the standard Planetary Data System (PDS) Object Description Language (ODL), Version 2.n.
	PDS3	The Header is governed by the Planetary Data System (PDS) Data Standards Version 3.n.
	Pre-PDS3	The Header is governed by Planetary Data System (PDS) Data Standards prior to Version 3.0.
	UTF-8 Text	The Header contains simple text using UTF-8 Unicode character encodings. RFC 3629.
	VICAR1	The Header is governed by the standard Video Image Communication And Retrieval (VICAR).
	VICAR2	The Header is governed by the standard Video Image Communication And Retrieval (VICAR).

parsing_standard_id in Parsable_Byte_Stream

Name: parsing_standard_id		Version Id: 1.0.0.0	
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Parsable_Byte_Stream	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nullable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

parsing_standard_id in SPICE_Kernel

Name: parsing_standard_id		Version Id: 1.0.0.0	
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> SPICE_Kernel	<i>Type:</i> ASCII_Short_String_Collapsed

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	SPICE	The SPICE_Kernel is governed by the standard Spacecraft Planet Instrument C-matrix Events (SPICE).	

parsing_standard_id in Service_Description

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Service_Description	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	WADL	The service is governed by the standard Web Application Description Language (WADL).	
	WSDL 2.n	The service is governed by the standard Web Services Description Language (WSDL) Version 2.n.	

parsing_standard_id in Table_Delimited

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Delimited	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	PDS DSV 1	The table format is governed by the standard Planetary Data System (PDS) Delimiter Separated Values (DSV) Format, Version 1.n.	

parsing_standard_id in XML_Schema

Name: parsing_standard_id			Version Id: 1.0.0.0
<i>Description:</i> The parsing_standard_id attribute provides the formal name of a standard used for the structure of a Parsable Byte Stream digital object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> XML_Schema	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Schematron ISO/IEC 19757-3:2006	Schematron is governed by the standard for Schematron	
	XML Schema Version 1.1	XML_Schema is governed by the standard for XML_Schema	

pattern in ASCII_DOI

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	10\.\S+\S+		

pattern in ASCII_Date

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}		

Name: pattern		Version Id: 1.0.0.0
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6])))	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))	

pattern in ASCII_Date_DOY

Name: pattern		Version Id: 1.0.0.0	
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6])))		

pattern in ASCII_Date_Time

Name: pattern		Version Id: 1.0.0.0	
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6])))		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2]		

Attributes in the common
(pds) namespace.

Name: pattern	Version Id: 1.0.0.0
	[0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3]))):[0-5][0-9](Z)?
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3]))):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-4]))(Z)?
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)24:00(:00(\.0+?)?)?(Z)?
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-4]))(Z)?
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)24:00(:00(\.0+?)?)?(Z)?

pattern in ASCII_Date_Time_DOY

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-4]))(Z)?		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))(T)24:00(:00(\.0+)?))?(Z)?		

pattern in ASCII_Date_Time_UTC

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Attributes in the common
(pds) namespace.

Name: pattern	Version Id: 1.0.0.0
	(-)?[0-9]{4}(Z)
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2] [0-9][0-9]) (3((([0-5] [0-9]) (6[0-6]))))(T ((([0-1][0-9]) (2[0-3]))): [0-5][0-9](Z)
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2] [0-9][0-9]) (3((([0-5] [0-9]) (6[0-6]))))(T ((([0-1][0-9]) (2[0-3]))): [0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2] [0-9][0-9]) (3((([0-5] [0-9]) (6[0-6]))))(T ((([0-1][0-9]) (2[0-4])) (Z)
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2] [0-9][0-9]) (3((([0-5] [0-9]) (6[0-6]))) (T)24:00(:00(\.0+)?))? (Z)
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2] [0-9][0-9]) (3((([0-5] [0-9]) (6[0-6]))))(Z)
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))(Z)
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1])) (T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1])) (T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]: ((([0-5][0-9]) 60)\.([0-9] {1,4}))?(Z)
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1])) (T)(([0-1][0-9]) (2[0-4]))(Z)
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9])

Name: pattern		Version Id: 1.0.0.0
	([1-2][0-9])(3[0-1]) (T)24:00(:00(\\0+?)?)? (Z)	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9])(3[0-1])) (Z)	

pattern in ASCII_Date_Time_YMD

Name: pattern		Version Id: 1.0.0.0	
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9])(3[0-1])) (T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9])(3[0-1])) (T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]: (([0-5][0-9]) 60)\\. ([0-9]{1,4}))?(Z)?		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9])(3[0-1])) (T)(([0-1][0-9]) (2[0-4]))(Z)?		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9])(3[0-1])) (T)24:00(:00(\\0+?)?)? (Z)?		

pattern in ASCII_Date_YMD

Name: pattern		Version Id: 1.0.0.0	
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed

Name: pattern			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	(-)?[0-9]{4}		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))		

pattern in ASCII_LID

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

pattern in ASCII_MD5_Checksum

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	[0-9a-fA-F]{32}	Values of ASCII_MD5_Checksum are constructed of 32 characters from the set of digits 0-9 and the letters a-f and A-F	

pattern in ASCII_Numeric_Base16

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			

Name: pattern			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

pattern in ASCII_Numeric_Base2

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	[0-1]{1,255}	Values of ASCII_Numeric_Base2 are constructed from 1-255 characters, each of which is either 0 or 1	

pattern in ASCII_Numeric_Base8

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base8	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	[0-7]{1,255}	Values of ASCII_Numeric_Base8 are constructed from 1-255 characters, each of which is a digit in the range 0-7	

pattern in ASCII_Time

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			

Attributes in the common
(pds) namespace.

Name: pattern			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	((([0-1][0-9]) (2[0-3])):[0-5][0-9](Z))		
	((([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)(\.[0-9]+))(Z))		
	((([0-1][0-9]) (2[0-4]))(Z))		
	24:00(:00(\.0+)))(Z)		

pattern in ASCII_VID

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	0\,([1-9] ([0-9][0-9]+))		
	[1-9][0-9]*		
	[1-9][0-9]*\.[0-9]+		

pattern in Character_Data_Type

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

pattern in DD_Value_Domain

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

pattern in DD_Value_Domain_Full

Name: pattern			Version Id: 1.0.0.0
<i>Description:</i> The pattern attribute provides a symbolic instruction for forming values.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Pattern	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

phone_book_flag in PDS_Affiliate

Name: phone_book_flag			Version Id: 1.0.0.0
<i>Description:</i> The phone_book_flag attribute indicates whether or not this person should be included in the phone book.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

postal_address_text in PDS_Affiliate

Name: postal_address_text			Version Id: 1.0.0.0
<i>Description:</i> The postal address text attribute provides a mailing address.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Text_Preserved

Name: postal_address_text			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

preferred_flag in Terminological_Entry

Name: preferred_flag			Version Id: 1.0.0.0
<i>Description:</i> The preferred_flag indicates whether this entry is preferred over all other entries.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Terminological_Entry	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Flag	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

primary_body_name in Target_PDS3

Name: primary_body_name			Version Id: 1.0.0.0
<i>Description:</i> The primary_body_name attribute identifies the primary body with which a given target body is associated as a secondary body.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Target_ PDS3	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

processing_level in Primary_Result_Summary

Name: processing_level			Version Id: 1.0.0.0
<i>Description:</i> The processing_level attribute provides a broad indication of data processing level.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_ Result_Summary	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None

Attributes in the common
(pds) namespace.

Name: processing_level		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	Calibrated	Data converted to physical units, which makes values independent of the instrument.
	Derived	Results that have been distilled from one or more calibrated data products (for example, maps, gravity or magnetic fields, or ring particle size distributions). Supplementary data, such as calibration tables or tables of viewing geometry, used to interpret observational data should also be classified as 'derived' data if not easily matched to one of the other three categories.
	Partially Processed	Data that have been processed beyond the raw stage but which have not yet reached calibrated status.
	Raw	Original data from an instrument. If compression, reformatting, packetization, or other translation has been applied to facilitate data transmission or storage, those processes will be reversed so that the archived data are in a PDS approved archive format.
	Telemetry	An encoded byte stream used to transfer data from one or more instruments to temporary storage where the raw instrument data will be extracted.

processing_level_id in Primary_Result_Summary *Deprecated*

Name: processing_level_id *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The processing_level_id attribute provides a broad indication of data processing level.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_Result_Summary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Deprecated	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Calibrated	Data converted to physical units, which makes values independent of the instrument.	
	Derived	Results that have been distilled from one or more calibrated data products (for example, maps, gravity or magnetic fields, or ring particle size distributions). Supplementary data, such as calibration tables or tables of viewing geometry, used to interpret observational data should also be classified as 'derived' data if not easily matched to one of the other three categories.	

Name: processing_level_id *Deprecated*		Version Id: 1.0.0.0
	Partially Processed	Data that have been processed beyond the raw stage but which have not yet reached calibrated status.
	Raw	Original data from an instrument. If compression, reformatting, packetization, or other translation has been applied to facilitate data transmission or storage, those processes will be reversed so that the archived data are in a PDS approved archive format.
	Telemetry	An encoded byte stream used to transfer data from one or more instruments to temporary storage where the raw instrument data will be extracted.

producer_full_name in Data_Set_PDS3

Name: producer_full_name		Version Id: 1.0.0.0	
<i>Description:</i> The producer_full_name attribute provides the full_name of the individual mainly responsible for the production of the data set. This individual does not have to be registered with the PDS.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

product_class in Identification_Area

Name: product_class		Version Id: 1.0.0.0	
<i>Description:</i> The product_class attribute provides the name of the product class. For example the value of the attribute product_class must be Product_Document for any Product_Document.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Identification_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Product_AIP	This is a product of type Product_AIP	
	Product_Attribute_Definition	This is a product of type Product_Attribute_Definition	
	Product_Browse	This is a product of type Product_Browse	
	Product_Bundle	This is a product of type Product_Bundle	

Attributes in the common
(pds) namespace.

Name: product_class		Version Id: 1.0.0.0
	Product_Class_Definition	This is a product of type Product_Class_Definition
	Product_Collection	This is a product of type Product_Collection
	Product_Context	This is a product of type Product_Context
	Product_DIP	This is a product of type Product_DIP
	Product_DIP_Deep_Archive	This is a product of type Product_DIP_Deep_Archive
	Product_Data_Set_PDS3	This is a product of type Product_Data_Set_PDS3
	Product_Document	This is a product of type Product_Document
	Product_File_Repository	This is a product of type Product_File_Repository
	Product_File_Text	This is a product of type Product_File_Text
	Product_Instrument_Host_PDS3	This is a product of type Product_Instrument_Host_PDS3
	Product_Instrument_PDS3	This is a product of type Product_Instrument_PDS3
	Product_Mission_PDS3	This is a product of type Product_Mission_PDS3
	Product_Native	This is a product of type Product_Native
	Product_Observational	This is a product of type Product_Observational
	Product_Proxy_PDS3	This is a product of type Product_Proxy_PDS3
	Product_SIP	This is a product of type Product_SIP
	Product_SPICE_Kernel	This is a product of type Product_SPICE_Kernel
	Product_Service	This is a product of type Product_Service
	Product_Software	This is a product of type Product_Software
	Product_Subscription_PDS3	This is a product of type Product_Subscription_PDS3
	Product_Target_PDS3	This is a product of type Product_Target_PDS3
	Product_Thumbnail	This is a product of type Product_Thumbnail
	Product_Update	This is a product of type Product_Update
	Product_Volume_PDS3	This is a product of type Product_Volume_PDS3
	Product_Volume_Set_PDS3	This is a product of type Product_Volume_Set_PDS3
	Product_XML_Schema	This is a product of type Product_XML_Schema
	Product_Zipped	This is a product of type Product_Zipped

program_notes_id in Software_Binary

Name: program_notes_id		Version Id: 1.0.0.0	
<i>Description:</i> The program notes id attribute provides an identifier to a brief statement giving particulars about a software program.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Short_String_Collapsed

Name: program_notes_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

program_notes_id in Software_Source

Name: program_notes_id			Version Id: 1.0.0.0
<i>Description:</i> The program notes id attribute provides an identifier to a brief statement giving particulars about a software program.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

programmers_manual_id in Software

Name: programmers_manual_id			Version Id: 1.0.0.0
<i>Description:</i> The programmers manual id attribute provides an identifier to a document giving instruction about the programming of the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

publication_date in Document

Name: publication_date			Version Id: 1.0.0.0
<i>Description:</i> The publication_date attribute provides the date on which an item was published.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	

Name: publication_date		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

publication_date in Volume_PDS3

Name: publication_date		Version Id: 1.0.0.0	
<i>Description:</i> The publication_date attribute provides the date on which an item was published.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nullable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

publication_year in Citation_Information

Name: publication_year		Version Id: 1.0.0.0	
<i>Description:</i> The publication_year attribute provides the year in which the product should be considered as published. Generally, this will be the year the data were declared "Certified" or "Archived".			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Citation_Information	<i>Type:</i> ASCII_Date
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nullable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

purpose in Primary_Result_Summary

Name: purpose		Version Id: 1.0.0.0	
<i>Description:</i> The purpose attribute provides an indication of the primary purpose of the observations included.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_Result_Summary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nullable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Calibration	Data collected to determine the relationship between measurement values and physical units.	
	Checkout	Data collected during operational tests	

Name: purpose		Version Id: 1.0.0.0
	Engineering	Data collected about support systems and structures, which are ancillary to the primary measurements.
	Navigation	Data collected to support navigation
	Science	Data collected primarily to answer questions about the targets of the investigation.

record_delimiter in Stream_Text

Name: record_delimiter		Version Id: 1.0.0.0	
<i>Description:</i> The record_delimiter attribute provides the character or characters used to indicate the end of a record.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Stream_Text	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Delimiter	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Carriage-Return Line-Feed	Records in the stream text are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	
	carriage-return line-feed - *Deprecated*	Records in the stream text are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	

record_delimiter in Table_Binary

Name: record_delimiter		Version Id: 1.0.0.0	
<i>Description:</i> The record_delimiter attribute provides the character or characters used to indicate the end of a record.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Binary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Delimiter	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

record_delimiter in Table_Character

Name: record_delimiter		Version Id: 1.0.0.0
<i>Description:</i> The record_delimiter attribute provides the character or characters used to indicate the end of a record.		

Attributes in the common
(pds) namespace.

Name: record_delimiter			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_ Character	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Delimiter	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Carriage-Return Line- Feed	Records in the character table are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	
	carriage-return line- feed - *Deprecated*	Records in the character table are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	

record_delimiter in Table_Delimited

Name: record_delimiter			Version Id: 1.0.0.0
<i>Description:</i> The record_delimiter attribute provides the character or characters used to indicate the end of a record.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_ Delimited	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Delimiter	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Carriage-Return Line- Feed	Records in the delimited table are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	
	carriage-return line- feed - *Deprecated*	Records in the delimited table are delimited by ASCII carriage-return line-feed pairs (0x0D0x0A)	

record_length in Record_Binary

Name: record_length			Version Id: 1.0.0.0
<i>Description:</i> The record_length attribute provides the length of a record, including a record delimiter, if present.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Record_ Binary	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: record_length		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

record_length in Record_Character

Name: record_length		Version Id: 1.0.0.0	
<i>Description:</i> The record_length attribute provides the length of a record, including the record delimiter.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Record_Character	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Storage	<i>Default Unit Id:</i> byte	<i>Attribute Concept:</i> Length	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

records in File

Name: records		Version Id: 1.0.0.0	
<i>Description:</i> The records attribute provides a count of records.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> File	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

records in Table_Base

Name: records		Version Id: 1.0.0.0	
<i>Description:</i> The records attribute provides a count of records.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Base	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

records in Table_Delimited

Name: records		Version Id: 1.0.0.0
<i>Description:</i> The records attribute provides a count of records.		

Attributes in the common
(pds) namespace.

Name: records			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Table_Delimited	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

reference_frame_id in Vector

Name: reference_frame_id			Version Id: 1.0.0.0
<i>Description:</i> The reference frame id attribute identifies a reference frame, an origin and set of axes, the physical realization of a reference system, i.e., the reference frame orientation and axes are established by the reported coordinates of datum points in the reference system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ICRF	International celestial reference frame	
	MOON_ME_DE421	Moon mean Earth based on JPL DE421	

reference_frame_id in Vector_Cartesian_3

Name: reference_frame_id			Version Id: 1.0.0.0
<i>Description:</i> The reference frame id attribute identifies a reference frame, an origin and set of axes, the physical realization of a reference system, i.e., the reference frame orientation and axes are established by the reported coordinates of datum points in the reference system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Cartesian_3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ICRF	International celestial reference frame	
	MOON_ME_DE421	Moon mean Earth based on JPL DE421	

reference_text in External_Reference

Name: reference_text			Version Id: 1.0.0.0
<i>Description:</i> The reference_text attribute provides a complete bibliographic citation for a published work.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> External_Reference	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

reference_type in Bundle_Member_Entry

Name: reference_type			Version Id: 1.0.0.0
<i>Description:</i> The reference_type attribute provides the name of the association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Bundle_Member_Entry	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	bundle_has_browse_collection	The bundle has a browse collection member	
	bundle_has_calibration_collection	The bundle has a calibration collection member	
	bundle_has_context_collection	The bundle has a context collection member	
	bundle_has_data_collection	The bundle has a data collection member	
	bundle_has_document_collection	The bundle has a document collection member	
	bundle_has_geometry_collection	The bundle has a geometry collection member	
	bundle_has_member_collection	The bundle has a member collection member	
	bundle_has_schema_collection	The bundle has a schema collection member	
	bundle_has_spice_kernel_collection	The bundle has a spice kernel collection member	

reference_type in DD_Association

Name: reference_type			Version Id: 1.0.0.0
<i>Description:</i> The reference_type attribute provides the name of the association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	attribute_of	The referenced attribute is a member of this class	
	component_of	The referenced class is a component of this class	
	extension_of - *Deprecated*	The referenced class is an extension of this class	
	parent_of	This class is a parent of the referenced class	
	restriction_of - *Deprecated*	The referenced class is a restriction of this class	
	subclass_of - *Deprecated*	The referenced class is a subclass of this class	

reference_type in DD_Association_External *Deprecated*

Name: reference_type			Version Id: 1.0.0.0
<i>Description:</i> The reference_type attribute provides the name of the association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Association_External *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	attribute_of	The referenced attribute is a member of this class	
	component_of	The referenced class is a component of this class	
	extension_of	The referenced class is an extension of this class	
	parent_of	This class is a parent of the referenced class	
	restriction_of	The referenced class is a restriction of this class	
	subclass_of	The referenced class is a subclass of this class	

reference_type in Internal_Reference

Name: reference_type			Version Id: 1.0.0.0
<i>Description:</i> The reference_type attribute provides the name of the association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Internal_Reference	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		
<i>Extended Value(s) for: pds:Observing_System_Component/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>	
	is_instrument	The referenced class is a context product describing the instrument.	
	is_instrument_host	The referenced class is a context product describing the instrument_host	
	is_other	The referenced class is a context product describing something not classified	
	is_facility	The referenced class is a context product describing the facility	
	is_telescope	The referenced class is a context product describing the telescope	
<i>Extended Value(s) for: pds:Product_AIP/pds:Information_Package_Component/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>	
	package_has_collection	The Archival Information Package contains a Collection.	
	package_has_bundle	The Archival Information Package contains a Bundle.	
	package_has_product	The Archival Information Package contains a basic Product.	
	package_compiled_from_package	The Archival Information Package is compiled from a Submission Information Package.	
<i>Extended Value(s) for: pds:Product_Browse/ pds:Reference_List/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>	
	browse_to_data	The browse product is associated to a data product	
	browse_to_thumbnail	The browse product is associated to a thumbnail	
<i>Extended Value(s) for: pds:Product_Bundle/ pds:Context_Area/</i>	<i>Value</i>	<i>Value Meaning</i>	

Attributes in the common
(pds) namespace.

Name: reference_type		Version Id: 1.0.0.0
<i>pds:Investigation_Area/pds:Internal_Reference</i>		
	bundle_to_investigation	The bundle is associated to an investigation
<i>Extended Value(s) for: pds:Product_Bundle/pds:Reference_List/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	bundle_to_errata	The bundle is associated to an errata document
	bundle_to_document	The bundle is associated to a document
	bundle_to_investigation	The bundle is associated to an investigation
	bundle_to_instrument	The bundle is associated to an instrument
	bundle_to_instrument_host	The bundle is associated to an instrument host
	bundle_to_target	The bundle is associated to a target
	bundle_to_associate	The bundle is associated to product
<i>Extended Value(s) for: pds:Product_Collection/pds:Context_Area/pds:Investigation_Area/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	collection_to_investigation	The collection is associated to an investigation
<i>Extended Value(s) for: pds:Product_Collection/pds:Reference_List/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	collection_to_resource	The collection is associated to a resource
	collection_to_associate	The collection is associated to product
	collection_to_calibration	The collection is associated to calibration data
	collection_to_geometry	The collection is associated to geometry
	collection_to_spice_kernel	The collection is associated to spice kernels
	collection_curated_by_node	The collection is curated by the referenced node
	collection_to_document	The collection is associated to a document
	collection_to_browse	The collection is associated to a browse product
	collection_to_context	The collection is associated to a context product
	collection_to_data	The collection is associated to a data product

Attributes in the common
(pds) namespace.

Name: reference_type		Version Id: 1.0.0.0
	collection_to_schema	The collection is associated to a schema document
	collection_to_errata	The collection is associated to an errata document
	collection_to_bundle	The collection is associated to a bundle
	collection_to_personnel	The collection is associated to personnel
	collection_to_investigation	The collection is associated to an investigation
	collection_to_instrument	The collection is associated to an instrument
	collection_to_instrument_host	The collection is associated to an instrument host
	collection_to_target	The collection is associated to a target
<i>Extended Value(s) for: pds:Product_Context/ pds:Reference_List/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	context_to_associate	The context product is associated to a product
	instrument_to_document	The instrument is associated to a document
	instrument_to_instrument_host	The instrument is associated to an instrument host
	instrument_host_to_document	The instrument host is associated to a document
	instrument_host_to_instrument	The instrument_host is associated to an instrument
	instrument_host_to_investigation	The instrument host is associated to an investigation
	instrument_host_to_target	The instrument host is associated to a target
	investigation_to_document	The investigation is associated to a document
	investigation_to_instrument	The investigation is associated to an instrument
	investigation_to_instrument_host	The investigation is associated to an instrument_host
	investigation_to_target	The investigation is associated to a target
	node_to_personnel	The node is associated to a person
	node_to_agency	The node is associated to an agency
	node_to_manager	The node is associated to a manager
	node_to_operator	The node is associated to an operator
	node_to_data_archivist	The node is associated to a data archivist
	resource_to_instrument	The resource is associated to an instrument
	resource_to_instrument_host	The resource is associated to an instrument host

Attributes in the common
(pds) namespace.

Name: reference_type		Version Id: 1.0.0.0
	resource_to_investigation	The resource is associated to an investigation
	resource_to_target	The resource is associated to a target
	target_to_document	The target is associated to a document
	target_to_instrument	The target is associated to an instrument
	target_to_instrument_host	The target is associated to an instrument_host
	target_to_investigation	The target is associated to an investigation
<i>Extended Value(s) for: pds:Product_ DIP/pds:Information_ Package_Component/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	package_has_collection	The Dissemination Information Package contains a Collection.
	package_has_bundle	The Dissemination Information Package contains a Bundle.
	package_has_product	The Dissemination Information Package contains a basic Product.
	package_compiled_from_package	The Dissemination Information Package is compiled from an Archival Information Package.
<i>Extended Value(s) for: pds:Product_ DIP_Deep_Archive/ pds:Information_ Package_Component/ pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	package_has_collection	The Dissemination Information Package contains a Collection.
	package_has_bundle	The Dissemination Information Package contains a Bundle.
	package_has_product	The Dissemination Information Package contains a basic Product.
	package_compiled_from_package	The Dissemination Information Package is compiled from an Archival Information Package.
<i>Extended Value(s) for: pds:Product_ Document/ pds:Context_Area/ pds:Investigation_ Area/pds:Internal_ Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	document_to_investigation	The document is associated to an investigation
<i>Extended Value(s) for: pds:Product_ Document/</i>	<i>Value</i>	<i>Value Meaning</i>

Attributes in the common
(pds) namespace.

Name: reference_type		Version Id: 1.0.0.0
<i>pds:Context_Area/pds:Target_Identification/pds:Internal_Reference</i>		
	document_to_target	The document is associated to a target
<i>Extended Value(s) for: pds:Product_Document/pds:Reference_List/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	document_to_associate	The document is associated to product
	document_to_investigation	The document is associated to an investigation
	document_to_instrument_host	The document is associated to an instrument_host
	document_to_instrument	The document is associated to an instrument
	document_to_target	The document is associated to a target
<i>Extended Value(s) for: pds:Product_Native/pds:Reference_List/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	described_by_document	The format of the digital object must be described one or more referenced documents
<i>Extended Value(s) for: pds:Product_Observational/pds:Observation_Area/pds:Investigation_Area/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	data_to_investigation	The data product is associated to an investigation
<i>Extended Value(s) for: pds:Product_Observational/pds:Observation_Area/pds:Target_Identification/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	data_to_target	The data product is associated to a target
	collection_to_target	The collection is associated to a target
	bundle_to_target	The bundle is associated to a target
	document_to_target	The document is associated to a target
<i>Extended Value(s) for: pds:Product_Observational/pds:Reference_List/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	data_to_resource	The data product is associated to a resource

Attributes in the common
(pds) namespace.

Name: reference_type		Version Id: 1.0.0.0
	data_to_calibration_document	The data product is associated to a calibration document
	data_to_calibration_product	The data product is associated to a calibration product
	data_to_raw_product	The data product is associated to a raw product
	data_to_calibrated_product	The data product is associated to a calibrated product
	data_to_geometry	The data product is associated to geometry
	data_to_spice_kernel	The data product is associated to spice kernel(s)
	data_to_thumbnail	The data product is associated to a thumbnail
	data_to_document	The data product is associated to a document
	data_curated_by_node	The data product is curated by the referenced node
	data_to_browse	The data product is associated to a browse product
	data_to_ancillary_data	The referencing data product requires the referenced data product to provide specific support for its own use. For example, a table with footnotes can be archived as two products: a data table file with a field giving a footnote code number; and a footnotes file sorted by those code numbers. The label of the data table would then reference the footnotes file with an association type of "data_to_ancillary_data".
<i>Extended Value(s) for: pds:Product_SIP/pds:Information_Package_Component/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	package_has_collection	The Submission Information Package contains a Collection.
	package_has_bundle	The Submission Information Package contains a Bundle.
	package_has_product	The Submission Information Package is contains a basic Product.
<i>Extended Value(s) for: pds:Product_Zipped/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	zip_to_package	The zip file contains a copy of the package
<i>Extended Value(s) for: pds:Update_Entry/pds:Internal_Reference</i>	<i>Value</i>	<i>Value Meaning</i>
	data_to_update	The data product is associated to an update product
	collection_to_update	The collection is associated to an update product
	bundle_to_update	The bundle is associated to an update product

reference_type in Inventory

Name: reference_type			Version Id: 1.0.0.0
<i>Description:</i> The reference_type attribute provides the name of the association.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Inventory	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	inventory_has_member_product	The collection inventory has member products identified by either LIDVID or LID references	

registered_by in DD_Attribute_Full

Name: registered_by			Version Id: 1.0.0.0
<i>Description:</i> The registered_by attribute provides the name of the person or organization that registered the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

registered_by in DD_Class_Full

Name: registered_by			Version Id: 1.0.0.0
<i>Description:</i> The registered_by attribute provides the name of the person or organization that registered the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

registration_authority_id in DD_Attribute_Full

Name: registration_authority_id			Version Id: 1.0.0.0
<i>Description:</i> The registration_authority_id attribute provides the name of the organization that registered the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	0001_NASA_PDS_1	The Attribute Registration_Authority is 0001_NASA_PDS_1	

registration_authority_id in DD_Class_Full

Name: registration_authority_id			Version Id: 1.0.0.0
<i>Description:</i> The registration_authority_id attribute provides the name of the organization that registered the object.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

registration_date in PDS_Affiliate

Name: registration_date			Version Id: 1.0.0.0
<i>Description:</i> The registration_date attribute provides the date of registration within the PDS system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

registration_date in PDS_Guest

Name: registration_date			Version Id: 1.0.0.0
<i>Description:</i> The registration_date attribute provides the date of registration within the PDS system.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Guest	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

repetitions in Group

Name: repetitions			Version Id: 1.0.0.0
<i>Description:</i> The repetitions attribute provides the number of times a set of repeating fields and, possibly, (sub)groups is replicated within a group.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

revision_id in Document

Name: revision_id			Version Id: 1.0.0.0
<i>Description:</i> The revision_id attribute provides the revision level of a document, which may be set outside PDS and may be different from its version_id.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

rotation_direction in Target_PDS3

Name: rotation_direction			Version Id: 1.0.0.0
<i>Description:</i> The rotation_direction element provides the direction of rotation as viewed from the north pole of the 'invariable plane of the solar system', which is the plane passing through the center of mass of the solar system and perpendicular to the angular momentum vector of			

Name: rotation_direction			Version Id: 1.0.0.0
the solar system. The value for this element is PROGRADE for counter -clockwise rotation, RETROGRADE for clockwise rotation and SYNCHRONOUS for satellites which are tidally locked with the primary. Sidereal_rotation_period and rotation_direction_type are unknown for a number of satellites, and are not applicable (N/A) for satellites which are tumbling.			
Namespace Id: pds	Steward: ops	Class Name: Target_PDS3	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Direction	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

rule_assign in DD_Rule

Name: rule_assign			Version Id: 1.0.0.0
<i>Description:</i> The rule_assign attribute provides an assignment statement for a schematron rule.			
Namespace Id: pds	Steward: ops	Class Name: DD_Rule	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

rule_context in DD_Rule

Name: rule_context			Version Id: 1.0.0.0
<i>Description:</i> The rule_context attribute provides the xpath for the rule.			
Namespace Id: pds	Steward: ops	Class Name: DD_Rule	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

rule_description in DD_Rule_Statement

Name: rule_description			Version Id: 1.0.0.0
<i>Description:</i> The rule_description attribute provides a description of the rule statement suitable for user documentation.			
Namespace Id: pds	Steward: ops	Class Name: DD_Rule_Statement	Type: ASCII_Short_String_Collapsed

Name: rule_description			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

rule_message in DD_Rule_Statement

Name: rule_message			Version Id: 1.0.0.0
<i>Description:</i> The rule_message attribute provides a message to be displayed by the schematron processor when the test condition is met.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Rule_Statement	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

rule_test in DD_Rule_Statement

Name: rule_test			Version Id: 1.0.0.0
<i>Description:</i> The rule_test attribute provides the body of the statement to be executed by the schematron processor.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Rule_Statement	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

rule_type in DD_Rule_Statement

Name: rule_type			Version Id: 1.0.0.0
<i>Description:</i> The rule_type attribute indicates the type of statement to be executed.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Rule_Statement	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: rule_type		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	Assert	The rule statement type is generic Assert.
	Assert Every	The rule statement type is Assert Every.
	Assert If	The rule statement type is Assert If.
	Report	The rule statement type is Report.

rule_value in DD_Rule_Statement

Name: rule_value		Version Id: 1.0.0.0	
<i>Description:</i> The rule_value attribute provides values to be used to complete certain schematon statements.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Rule_Statement	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sample_display_direction in Display_2D_Image *Deprecated*

Name: sample_display_direction		Version Id: 1.0.0.0	
<i>Description:</i> The sample_display_direction attribute provides the preferred orientation of samples within a line for viewing on a display device. The attribute sample_display_direction must be used with line_display_direction.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Display_2D_Image *Deprecated*	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Direction	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Right	The preferred orientation of samples within an line for viewing on a display device is Right	

sampling_parameter_interval in Uniformly_Sampled

Name: sampling_parameter_interval		Version Id: 1.0.0.0
<i>Description:</i> The sampling_parameter_interval element identifies the spacing of points at which data are sampled and at which a value for an instrument or dataset parameter is available. This		

Name: sampling_parameter_interval			Version Id: 1.0.0.0
sampling interval can be either the original (raw) sampling or the result of some resampling process. For example, in 48-second magnetometer data the sampling interval is 48. The sampling parameter (time, in the example) is identified by the sampling_parameter_name element.			
Namespace Id: pds	Steward: pds	Class Name: Uniformly_Sampled	Type: ASCII_Real
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Real
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

sampling_parameter_name in Uniformly_Sampled

Name: sampling_parameter_name			Version Id: 1.0.0.0
<i>Description:</i> The sampling_parameter_name element provides the name of the parameter which determines the sampling interval of a particular instrument or dataset parameter. For example, magnetic field intensity is sampled in time increments, and a spectrum is sampled in wavelength or frequency.			
Namespace Id: pds	Steward: pds	Class Name: Uniformly_Sampled	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Name	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

sampling_parameter_scale in Uniformly_Sampled

Name: sampling_parameter_scale			Version Id: 1.0.0.0
<i>Description:</i> The sampling_parameter_scale element specifies whether the sampling interval is linear or something other such as logarithmic.			
Namespace Id: pds	Steward: pds	Class Name: Uniformly_Sampled	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Scale	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	Exponential	Values of Uniformly_Sampled are given at uniform spacings of the exponential of an	

Name: sampling_parameter_scale		Version Id: 1.0.0.0
		independent variable [e.g., log(1), log(2), log(3), log(4), ...]
	Linear	Values of Uniformly_Sampled are given at uniform (linear) spacings of an independent variable [e.g., 1, 2, 3, 4, ...]
	Logarithmic	Values of Uniformly_Sampled are given at uniform spacings of the logarithm of an independent variable [e.g., 1, 10, 100, 1000, ...]

sampling_parameter_unit in Uniformly_Sampled

Name: sampling_parameter_unit		Version Id: 1.0.0.0	
<i>Description:</i> The sampling_parameter_unit element specifies the unit of measure of associated data sampling parameters.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Uniformly_Sampled	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

saturated_constant in Special_Constants

Name: saturated_constant		Version Id: 1.0.0.0	
<i>Description:</i> The saturated_constant attribute provides a value that indicates the original value was invalid because of sensor saturation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Constant	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

scaling_factor in Band_Bin *Deprecated*

Name: scaling_factor		Version Id: 1.0.0.0	
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Band_Bin *Deprecated*	<i>Type:</i> ASCII_Real

Name: scaling_factor			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

scaling_factor in Element_Array

Name: scaling_factor			Version Id: 1.0.0.0
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Element_ Array	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Factor	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

scaling_factor in Field_Binary

Name: scaling_factor			Version Id: 1.0.0.0
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_ Binary	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Factor	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

scaling_factor in Field_Bit

Name: scaling_factor			Version Id: 1.0.0.0
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: scaling_factor			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Factor	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

scaling_factor in Field_Character

Name: scaling_factor			Version Id: 1.0.0.0
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Factor	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

scaling_factor in Field_Delimited

Name: scaling_factor			Version Id: 1.0.0.0
<i>Description:</i> The scaling_factor attribute is the scaling factor to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Factor	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

sequence_number in Axis_Array

Name: sequence_number			Version Id: 1.0.0.0
<i>Description:</i> The sequence_number attribute provides a number that is used to order axes in an array.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Axis_Array	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> 16	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Integer

Name: sequence_number			Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

sequence_number in Quaternion_Component

Name: sequence_number			Version Id: 1.0.0.0
<i>Description:</i> The sequence_number attribute provides a number that is used to order axes in an array.			
Namespace Id: pds	Steward: pds	Class Name: Quaternion_Component	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: 16	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

sequence_number in Vector_Component

Name: sequence_number			Version Id: 1.0.0.0
<i>Description:</i> The sequence_number attribute provides a number that is used to order axes in an array.			
Namespace Id: pds	Steward: pds	Class Name: Vector_Component	Type: ASCII_Integer
Minimum Value: 1	Maximum Value: 16	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Integer
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

serial_number in Instrument

Name: serial_number			Version Id: 1.0.0.0
<i>Description:</i> The serial number element provides the assigned manufacturer's serial number.			
Namespace Id: pds	Steward: pds	Class Name: Instrument	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: 1	Maximum Characters: 255
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

serial_number in Instrument_Host

Name: serial_number			Version Id: 1.0.0.0
<i>Description:</i> The serial number attribute provides the manufacturer's serial number assigned to an instrument host.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_dialect in Software_Source

Name: software_dialect			Version Id: 1.0.0.0
<i>Description:</i> The software dialect attribute indicates the variety of a language used to write the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_format_type in Software_Binary

Name: software_format_type			Version Id: 1.0.0.0
<i>Description:</i> The software format type attribute classifies the format of the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_format_type in Software_Source

Name: software_format_type			Version Id: 1.0.0.0
<i>Description:</i> The software format type attribute classifies the format of the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Short_String_Collapsed

Name: software_format_type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_id in Software

Name: software_id			Version Id: 1.0.0.0
<i>Description:</i> The software id attribute provides a formal name used to refer to the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_language in Software_Source

Name: software_language			Version Id: 1.0.0.0
<i>Description:</i> The software language attribute identifies the language used to write the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_type in Software

Name: software_type			Version Id: 1.0.0.0
<i>Description:</i> The software type attribute identifies the class of which the software is a member.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

software_version_id in Software

Name: software_version_id			Version Id: 1.0.0.0
<i>Description:</i> The software_version_id attribute provides the version of the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

solar_longitude in Time_Coordinates

Name: solar_longitude			Version Id: 1.0.0.0
<i>Description:</i> The solar_longitude attribute provides the angle between the body-Sun line at the time of interest and the body-Sun line at its vernal equinox.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Time_Coordinates	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> deg	<i>Attribute Concept:</i> Longitude	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sort_name in PDS_Affiliate

Name: sort_name			Version Id: 1.0.0.0
<i>Description:</i> The sort name attribute provides a string to be used in ordering. For people, the last name (surname) is typically first, followed by a comma and then other names.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sort_name in PDS_Guest

Name: sort_name			Version Id: 1.0.0.0
<i>Description:</i> The sort name attribute provides a string to be used in ordering. For people, the last name (surname) is typically first, followed by a comma and then other names.			

Name: sort_name			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Guest	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

specified_unit_id in DD_Value_Domain

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

specified_unit_id in DD_Value_Domain_Full

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

specified_unit_id in Unit_Of_Measure

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Unit_Of_Measure	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

specified_unit_id in Units_of_Acceleration

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Acceleration	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	m/s**2	Units_of_Acceleration maximum, minimum, and permissible values are given in the unit m/s**2	

specified_unit_id in Units_of_Amount_Of_Substance

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Amount_Of_Substance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	mol	Units_of_Amount_Of_Substance maximum, minimum, and permissible values are given in the unit mol	

specified_unit_id in Units_of_Angle

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angle	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	deg	Units_of_Angle maximum, minimum, and permissible values are given in the unit deg	

specified_unit_id in Units_of_Angular_Velocity

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angular_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	deg/s	Units_of_Angular_Velocity maximum, minimum, and permissible values are given in the unit deg/s	

specified_unit_id in Units_of_Area

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	m**2	Units_of_Area maximum, minimum, and permissible values are given in the unit m**2	

specified_unit_id in Units_of_Frame_Rate

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frame_Rate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	frames/s	Units_of_Frame_Rate maximum, minimum, and permissible values are given in the unit frames/s	

specified_unit_id in Units_of_Frequency

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frequency	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Hz	Units_of_Frequency maximum, minimum, and permissible values are given in the unit Hz	

specified_unit_id in Units_of_Length

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Length	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	m	Units_of_Length maximum, minimum, and permissible values are given in the unit m	

specified_unit_id in Units_of_Map_Scale

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Map_Scale	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	pixel/deg	Units_of_Map_Scale maximum, minimum, and permissible values are given in the unit pixel/deg	

specified_unit_id in Units_of_Mass

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Mass	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	kg	Units_of_Mass maximum, minimum, and permissible values are given in the unit kg	

specified_unit_id in Units_of_Misc

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Misc	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	DN	Units_of_Misc maximum, minimum, and permissible values are given in the unit DN	

specified_unit_id in Units_of_None

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_None	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	none	Units_of_None maximum, minimum, and permissible values are given in the unit none	

specified_unit_id in Units_of_Optical_Path_Length

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Optical_Path_Length	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	airmass	Units_of_Optical_Path_Length maximum, minimum, and permissible values are given in the unit airmass	

specified_unit_id in Units_of_Pressure

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Pressure	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: specified_unit_id		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	bar	Units_of_Pressure maximum, minimum, and permissible values are given in the unit bar

specified_unit_id in Units_of_Radiance

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	W*m**-2*sr**-1	Units_of_Radiance maximum, minimum, and permissible values are given in the unit W*m**-2*sr**-1	

specified_unit_id in Units_of_Rates

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Rates	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	counts/bin	Units_of_Rates maximum, minimum, and permissible values are given in the unit counts/bin	

specified_unit_id in Units_of_Solid_Angle

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Solid_Angle	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	sr	Units_of_Solid_Angle maximum, minimum, and permissible values are given in the unit sr	

specified_unit_id in Units_of_Spectral_Irradiance

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Irradiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	W*m**-3	Units_of_Spectral_Irradiance maximum, minimum, and permissible values are given in the unit W*m**-3	

specified_unit_id in Units_of_Spectral_Radiance

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	W*m**-3*sr**-1	Units_of_Spectral_Radiance maximum, minimum, and permissible values are given in the unit W*m**-3*sr**-1	

specified_unit_id in Units_of_Storage

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Storage	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	byte	Units_of_Storage maximum, minimum, and permissible values are given in the unit byte	

specified_unit_id in Units_of_Temperature

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Temperature	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	degC	Units_of_Temperature maximum, minimum, and permissible values are given in the unit degC	

specified_unit_id in Units_of_Time

Name: specified_unit_id			Version Id: 1.0.0.0
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Name: specified_unit_id		Version Id: 1.0.0.0
	s	Units_of_Time maximum, minimum, and permissible values are given in the unit s

specified_unit_id in Units_of_Velocity

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	m/s	Units_of_Velocity maximum, minimum, and permissible values are given in the unit m/s	

specified_unit_id in Units_of_Voltage

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Voltage	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	V	Units_of_Voltage maximum, minimum, and permissible values are given in the unit V	

specified_unit_id in Units_of_Volume

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Volume	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String

Name: specified_unit_id		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	Value	Value Meaning
	L	Units_of_Volume maximum, minimum, and permissible values are given in the unit L

specified_unit_id in Units_of_Wavenumber

Name: specified_unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The specified_unit_id attribute provides the units chosen for maximum_value, minimum_value, and permissible_value.			
Namespace Id: pds	Steward: pds	Class Name: Units_of_Wavenumber	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	cm** ⁻¹	Units_of_Wavenumber maximum, minimum, and permissible values are given in the unit cm** ⁻¹	

standard_deviation in Band_Bin

Deprecated

Name: standard_deviation		Version Id: 1.0.0.0	
<i>Description:</i> The standard_deviation attribute provides the standard deviation of values in the associated object; empty and Special_Constants values are excluded.			
Namespace Id: pds	Steward: img	Class Name: Band_Bin *Deprecated*	Type: ASCII_Real
Minimum Value: 0	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Number	Conceptual Domain: Real
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

standard_deviation in Field_Statistics

Name: standard_deviation		Version Id: 1.0.0.0	
<i>Description:</i> The standard_deviation attribute provides the standard deviation of the stored field over all records (empty fields and Special_Constants values are excluded from the computation).			
Namespace Id: pds	Steward: pds	Class Name: Field_Statistics	Type: ASCII_Real
Minimum Value: 0	Maximum Value: None	Minimum Characters: None	Maximum Characters: None

Name: standard_deviation			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

standard_deviation in Object_Statistics

Name: standard_deviation			Version Id: 1.0.0.0
<i>Description:</i> The standard_deviation attribute provides the standard deviation of the stored array element values after application of any bit mask (Special_Constants values are excluded from the computation).			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Object_Statistics	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

start_bit in Field_Bit

Name: start_bit			Version Id: 1.0.0.0
<i>Description:</i> The start_bit attribute provides the position of the first bit within an ordered sequence of bits.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Bit	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

start_date in Investigation

Name: start_date			Version Id: 1.0.0.0
<i>Description:</i> The start_date attribute provides the date when an activity began.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Investigation	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

start_date_time in Data_Set_PDS3

Deprecated

Name: start_date_time *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The start_date_time attribute provides the date and time at the beginning of the data set.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Deprecated	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

start_date_time in Time_Coordinates

Name: start_date_time			Version Id: 1.0.0.0
<i>Description:</i> The start_date_time attribute provides the date and time appropriate to the beginning of the product being labeled.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Time_Coordinates	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

start_time in Data_Set_PDS3

Name: start_time			Version Id: 1.0.0.0
<i>Description:</i> The start_time attribute provides the date and time of the beginning of an event or observation (whether it be a spacecraft, ground-based, or system event) in UTC.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Date_Time
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

starting_point_identifier in Document_Format

Name: starting_point_identifier			Version Id: 1.0.0.0
<i>Description:</i> The starting_point attribute provides the local_identifier of the object to be accessed first.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Document_Format	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

steward_id in DD_Attribute_Full

Name: steward_id			Version Id: 1.0.0.0
<i>Description:</i> The steward attribute indicates the person or organization who manages a set of registered attributes and classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	atm	Steward of the attribute is the PDS Atmospheres Discipline Node	
	geo	Steward of the attribute is the PDS Geosciences Discipline Node	
	img	Steward of the attribute is the PDS Imaging support node	
	naif	Steward of the attribute is the PDS Navigation and Ancillary Information support node	
	ops	Steward of the attribute is the PDS operations function	
	pds	Steward of the attribute is the Planetary Data System	
	ppi	Steward of the attribute is the PDS Planetary Plasma Interaction Discipline Node	
	rings	Steward of the attribute is the PDS Rings Discipline Node	
	rs	Steward of the attribute is the PDS radio science function	
	sbn	Steward of the attribute is the PDS Small Bodies Discipline Node	

steward_id in DD_Class_Full

Name: steward_id			Version Id: 1.0.0.0
<i>Description:</i> The steward_id attribute provides the abbreviation of the organization that manages the set of registered attributes and classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	atm	Steward of the attribute is the PDS Atmospheres Discipline Node	
	geo	Steward of the attribute is the PDS Geosciences Discipline Node	
	img	Steward of the attribute is the PDS Imaging support node	
	naif	Steward of the attribute is the PDS Navigation and Ancillary Information support node	
	ops	Steward of the attribute is the PDS operations function	
	pds	Steward of the attribute is the Planetary Data System	
	ppi	Steward of the attribute is the PDS Planetary Plasma Interaction Discipline Node	
	rings	Steward of the attribute is the PDS Rings Discipline Node	
	rs	Steward of the attribute is the PDS radio science function	
	sbn	Steward of the attribute is the PDS Small Bodies Discipline Node	

steward_id in Ingest_LDD

Name: steward_id			Version Id: 1.0.0.0
<i>Description:</i> The steward_id attribute provides the abbreviation of the organization that manages the set of registered attributes and classes.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Ingest_LDD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

stop_bit in Field_Bit

Name: stop_bit			Version Id: 1.0.0.0
<i>Description:</i> The stop-bit attribute provides the location of the last bit in this bit field relative to the first bit in the packed_data field. Bits are numbered continuously across byte boundaries. The first bit location in the packed data field is "1".			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Bit	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

stop_date in Investigation

Name: stop_date			Version Id: 1.0.0.0
<i>Description:</i> The stop_date attribute provides the date when an activity ended.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Investigation	<i>Type:</i> ASCII_Date_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

stop_date_time in Data_Set_PDS3

Deprecated

Name: stop_date_time *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The stop_date_time attribute provides the date and time at the end of the data set.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Deprecated	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

stop_date_time in Time_Coordinates

Name: stop_date_time			Version Id: 1.0.0.0
<i>Description:</i> The stop_date_time attribute provides the date and time appropriate to the end of the product being labeled.			

Name: stop_date_time			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Time_Coordinates	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

stop_time in Data_Set_PDS3

Name: stop_time			Version Id: 1.0.0.0
<i>Description:</i> The stop_time element provides the date and time of the end of an observation or event (whether it be a spacecraft, ground-based, or system event) in UTC.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Data_Set_PDS3	<i>Type:</i> ASCII_Date_Time
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

subfacet1 in Group_Facet1

Name: subfacet1			Version Id: 1.0.0.0
<i>Description:</i> The subfacet1 attribute provides a sub-categorization under the facet1 value. The allowed values are restricted according to the value of facet1.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Facet1	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

subfacet2 in Group_Facet2

Name: subfacet2			Version Id: 1.0.0.0
<i>Description:</i> The subfacet2 attribute provides a sub-categorization under the facet2 value. The allowed values are restricted according to the value of facet2.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Group_Facet2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: subfacet2			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

submitter_name in DD_Attribute

Name: submitter_name			Version Id: 1.0.0.0
<i>Description:</i> The submitter_name attribute provides the name of the author, who submits the item to the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

submitter_name in DD_Attribute_Full

Name: submitter_name			Version Id: 1.0.0.0
<i>Description:</i> The submitter_name attribute provides the name of the author, who submits the item to the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

submitter_name in DD_Class

Name: submitter_name			Version Id: 1.0.0.0
<i>Description:</i> The submitter_name attribute provides the name of the author, who submits the item to the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: submitter_name		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	No Values	

submitter_name in DD_Class_Full

Name: submitter_name		Version Id: 1.0.0.0	
<i>Description:</i> The submitter_name attribute provides the name of the author, who submits the item to the steward.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

subscription_id in Subscriber_PDS3

Name: subscription_id		Version Id: 1.0.0.0	
<i>Description:</i> The subscriber_id provides the identification of a PDS subscription.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Subscriber_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

supported_architecture_note in Software_Binary

Name: supported_architecture_note		Version Id: 1.0.0.0	
<i>Description:</i> The supported architecture note attribute identifies the hardware architecture that can process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

supported_architecture_note in Software_Source

Name: supported_architecture_note			Version Id: 1.0.0.0
<i>Description:</i> The supported architecture note attribute identifies the hardware architecture that can process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

supported_environment_note in Software_Script

Name: supported_environment_note			Version Id: 1.0.0.0
<i>Description:</i> The supported environment note attribute identifies the environment that can process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Script	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

supported_operating_system_note in Software_Binary

Name: supported_operating_system_note			Version Id: 1.0.0.0
<i>Description:</i> The supported operating system note attribute identifies the Operating System that supports the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

supported_operating_system_note in Software_Source

Name: supported_operating_system_note			Version Id: 1.0.0.0
<i>Description:</i> The supported operating system note attribute identifies the Operating System that supports the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Source	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

system_requirements_note in Software_Binary

Name: system_requirements_note			Version Id: 1.0.0.0
<i>Description:</i> The system requirements note attribute identifies what is necessary to process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Binary	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

system_requirements_note in Software_Script

Name: system_requirements_note			Version Id: 1.0.0.0
<i>Description:</i> The system requirements note attribute identifies what is necessary to process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_Script	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

system_requirements_note in Software_ Source

Name: system_requirements_note			Version Id: 1.0.0.0
<i>Description:</i> The system requirements note attribute identifies what is necessary to process the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software_ Source	<i>Type:</i> ASCII_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Note	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

target_desc in Target_PDS3

Name: target_desc			Version Id: 1.0.0.0
<i>Description:</i> The target_desc attribute describes the characteristics of a particular target.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Target_ PDS3	<i>Type:</i> ASCII_Text_ Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Description	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

target_name in Target_PDS3

Name: target_name			Version Id: 1.0.0.0
<i>Description:</i> The target_name attribute provides a name by which the target is formally known.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Target_ PDS3	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

target_type in Target_PDS3

Name: target_type			Version Id: 1.0.0.0
<i>Description:</i> The target_type attribute identifies the type of a named target.			

Attributes in the common
(pds) namespace.

Name: target_type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Target_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

team_name in PDS_Affiliate

Name: team_name			Version Id: 1.0.0.0
<i>Description:</i> The team_name attribute provides the name of a group of individuals.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Engineering	Team name is Engineering	
	Geosciences	Team name is Geosciences	
	Headquarters	Team name is Headquarters	
	Imaging	Team name is Imaging	
	Management	Team name is Management	
	National Space Science Data Center	Team name is National Space Science Data Center	
	Navigation and Ancillary Information Facility	The Node has name Navigation and Ancillary Information Facility	
	Planetary Atmospheres	Team name is Planetary Atmospheres	
	Planetary Plasma Interactions	Team name is Planetary Plasma Interactions	
	Planetary Rings	Team name is Planetary Rings	
	Radio Science	Team name is Radio Science	
	Small Bodies	Team name is Radio Science	

telephone_number in PDS_Affiliate

Name: telephone_number			Version Id: 1.0.0.0
<i>Description:</i> The telephone_number attribute provides a telephone number in international notation in compliance with the E.164 telephone number format recommendation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> PDS_Affiliate	<i>Type:</i> ASCII_Short_String_Collapsed

Name: telephone_number			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

telescope_latitude in Telescope

Name: telescope_latitude			Version Id: 1.0.0.0
<i>Description:</i> The latitude attribute provides the angular distance north or south from the equator of a point on the object's surface, measured on the meridian of the point.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Telescope	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> deg	<i>Attribute Concept:</i> Latitude	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

telescope_longitude in Telescope

Name: telescope_longitude			Version Id: 1.0.0.0
<i>Description:</i> The longitude attribute provides the angular distance east or west on the object's surface, measured by the angle contained between the meridian of a particular place and some prime meridian.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Telescope	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> deg	<i>Attribute Concept:</i> Longitude	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

title in Identification_Area

Name: title			Version Id: 1.0.0.0
<i>Description:</i> The name given to the resource. Typically, a Title will be a name by which the resource is formally known. - Dublin Core - The title is used to refer to an object in a version independent manner.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Identification_Area	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Title	<i>Conceptual Domain:</i> Short_String

Name: title		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

transfer_manifest_checksum in Information_Package_Component

Name: transfer_manifest_checksum		Version Id: 1.0.0.0	
<i>Description:</i> The transfer manifest checksum provides the checksum for the transfer manifest file.			
Namespace Id: pds	Steward: ops	Class Name: Information_Package_Component	Type: ASCII_MD5_Checksum
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Checksum	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

type in DD_Attribute_Full

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
Namespace Id: pds	Steward: ops	Class Name: DD_Attribute_Full	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Type	Conceptual Domain: Short_String
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	Value	Value Meaning	
	PDS3	The attribute definition is classified as being of type PDS3	
	PDS4	The attribute definition is classified as being of type PDS4	

type in DD_Class_Full

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
Namespace Id: pds	Steward: ops	Class Name: DD_Class_Full	Type: ASCII_Short_String_Collapsed
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: Type	Conceptual Domain: Short_String

Attributes in the common
(pds) namespace.

Name: type		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	PDS3	The class definition is classified as being of type PDS3
	PDS4	The class definition is classified as being of type PDS4

type in Facility

Name: type		Version Id: 1.0.0.0	
<i>Description: The type attribute provides a classification for the resource.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Facility</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Type</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Laboratory	The Facility is classified as being of type Laboratory	
	Observatory	The Facility is classified as being of type Observatory	

type in Instrument

Name: type		Version Id: 1.0.0.0	
<i>Description: The type attribute provides a classification for the resource.</i>			
<i>Namespace Id: pds</i>	<i>Steward: pds</i>	<i>Class Name: Instrument</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Type</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Accelerometer	An instrument that measures proper (i.e., its own) acceleration.	
	Alpha Particle Detector	An instrument that measures the number and/or distribution of alpha particles.	
	Alpha Particle X-Ray Spectrometer	An instrument that bombards a sample with alpha particles and X-rays and measures the energy spectrum of scattered alpha particles and X-rays to determine the sample's elemental composition.	

Attributes in the common
(pds) namespace.

<i>Name: type</i>		<i>Version Id: 1.0.0.0</i>
	Altimeter	An instrument that measures its own altitude above a reference level (for example, a locally flat surface on the Earth)
	Anemometer	An in situ instrument that measures wind speed.
	Atomic Force Microscope	An instrument that uses atomic forces between a probe and a sample to produce high-resolution topographic scans of the sample.
	Barometer	An in situ instrument that measures atmospheric pressure.
	Biology Experiments	An instrument that conducts one or more experiments on samples to determine their potential for biological activity.
	Bolometer	An instrument that estimates radiation intensity by measuring changes in electrical resistivity as the temperature of its sensor varies in response to the incident power density.
	Camera	An instrument that records and stores analog images (compare 'imager').
	Cosmic Ray Detector	An instrument that detects and/or measures cosmic rays.
	Drilling Tool	A tool that drills into samples.
	Dust Detector	An instrument that detects and/or measures dust.
	Electrical Probe	An in situ instrument that measures electrical properties (e.g., conductivity) of a medium into which it is inserted.
	Energetic Particle Detector	An instrument that detects and/or measures energetic charged particles.
	Gamma Ray Detector	An instrument that detects and/or measures gamma rays.
	Gas Analyzer	A high-temperature furnace combined with a mass spectrometer that heats a sample and analyzes the mass distribution of the evolved gases.
	Grinding Tool	A tool that grinds into samples.
	Hygrometer	An instrument used to measure the moisture content of its environment.
	Imager	An instrument that records and stores digital images (compare 'camera').
	Imaging Spectrometer	An instrument that combines the functions of a spectrometer and an imager - i.e., it captures and stores multiple images, each at a slightly different wavelength.
	Inertial Measurement Unit	An instrument that measures changes in its own velocity and orientation by using a combination of accelerometers, gyroscopes, and/or other devices.
	Infrared Spectrometer	An instrument that measures the spectral distribution of infrared radiation.

Attributes in the common
(pds) namespace.

<i>Name: type</i>		<i>Version Id: 1.0.0.0</i>
	Laser Induced Breakdown Spectrometer	An instrument that uses an active laser to generate a plasma from a target and then measures the energy spectrum of the evolved plasma.
	Magnetometer	An instrument that measures the strength and/or direction of a magnetic field.
	Mass Spectrometer	An instrument that measures the number of particles in a sample as a function of their mass.
	Microwave Spectrometer	An instrument that measures the spectral distribution of microwave radiation.
	Moessbauer Spectrometer	An instrument that uses the Mossbauer effect to determine the abundance of Fe-bearing minerals in a sample.
	Naked Eye	Observations made with the naked eye and recorded in a data product.
	Neutral Particle Detector	An instrument that detects and/or measures neutral particles.
	Neutron Detector	An instrument that measures the number and/or energy distribution of neutrons.
	Photometer	An instrument that measures radiation intensity (e.g., of visible light), sometimes with the goal of inferring optical properties of materials illuminated by the source and observed by the photometer.
	Plasma Analyzer	An instrument that measures the spectral distribution of energy in a low-frequency plasma.
	Plasma Detector	An instrument that detects and/or measures low energy charged particles.
	Plasma Wave Spectrometer	An instrument that measures the energy distribution in a low-frequency plasma.
	Polarimeter	An instrument that measures the polarization of electromagnetic radiation.
	RADAR	An instrument that transmits and receives radio signals for the purpose of detecting, determining the range (distance) to, velocity of, and/or direction of one or more distant targets.
	Radio Science	An instrument suite used to conduct measurements at radio frequencies.
	Radio Spectrometer	An instrument that measures the spectral distribution of electromagnetic radiation at radio frequencies.
	Radio Telescope	An instrument used to focus and capture radio waves.
	Radiometer	An instrument which measures the radiant flux of electromagnetic radiation.
	Reflectometer	An instrument that measures the reflectance of surfaces. An electron reflectometer measures the properties of electrons trapped along magnetic

<i>Name: type</i>		<i>Version Id: 1.0.0.0</i>
		field lines to infer the strength and direction of the field remotely.
	Robotic Arm	A tool used to place in-situ instruments on surface rocks or soil, dig into a surface, and/or to collect surface samples for other instruments to analyze on a spacecraft.
	Spectrograph Imager	See Imaging Spectrometer.
	Spectrometer	An instrument used to measure properties over a specific portion of a spectrum - for example, a mass spectrometer measures the number of particles in discrete mass ranges, and a radio spectrometer measures the amount of electromagnetic radiation as a function of frequency or wavelength.
	Thermal Imager	An instrument that captures an image at thermal infrared wavelengths.
	Thermal Probe	An in situ instrument that measures thermal properties (e.g., temperature) at one or more points along its length.
	Thermometer	An instrument that measures temperature.
	Ultraviolet Spectrometer	An instrument that measures the spectral distribution of ultraviolet radiation.
	Wet Chemistry Laboratory	An instrument that mixes soil samples with solutions to measure material properties such as pH, conductivity, oxidation-reduction potential, etc.
	X-ray Detector	An instrument that detects and/or measures X-rays.
	X-ray Diffraction Spectrometer	An instrument that uses a beam of X-rays to probe the internal structure of a powdered sample and identify its mineral composition.
	X-ray Fluorescence Spectrometer	An instrument that measures the emission of secondary X-rays to determine the elemental composition of a sample that has been irradiated with primary X-rays.

type in Instrument_Host

<i>Name: type</i>		<i>Version Id: 1.0.0.0</i>	
<i>Description:</i> The type attribute classifies the instrument host. When more than one value is correct, the value with the finest granularity should be selected. That is, choose "rover" rather than "spacecraft" when both would be correct since rover more narrowly defines the type of instrument host.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String

Attributes in the common
(pds) namespace.

Name: type		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	Earth Based - *Deprecated*	The Instrument Host is classified as being of type Earth Based
	Earth-based	The instrument host is on or near the surface of Earth (no more than 100 km altitude above the surface).
	Lander	A spacecraft designed for descent to and operation at a single fixed point on the surface of a celestial body.
	Rover	A spacecraft designed for descent to and mobile operation on the surface of a celestial body.
	Spacecraft	A vehicle designed for travel in outer space ('outer space' is the region more than 100 km above the Earth's surface, a convention accepted in many contexts -- see http://en.wikipedia.org/wiki/Outer_space).

type in Investigation

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Investigation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Individual Investigation	A set of experiments and/or observations with a clearly defined purpose that uses existing facilities and is under the direction of a single individual. For example, a series of related laboratory experiments/observations conducted by a small university team and funded through a single proposal could be an Individual Investigation. Library research by one person on previously published results to distill common conclusions could also be an Individual Investigation.	
	Mission	A set of experiments and/or observations with a clearly defined purpose that occupies the designated resources for all (or at least a significant fraction) of the available time. A mission is usually conducted by a national or international space agency using a small number (often one) of spacecraft especially designed and built for the purpose. For example: (1) the NASA Voyager mission launched two spacecraft	

Name: type		Version Id: 1.0.0.0
		to Jupiter and Saturn; (2) the Deep Impact (DI) mission launched a spacecraft, part of which impacted the comet Tempel 2; and (3) the EPOXI mission redefined the objectives of the surviving DI hardware for further exploration of the solar system.
	Observing Campaign	A set of experiments and/or observations with a clearly defined purpose that uses (primarily) existing facilities, but not exclusively. After (and possibly during) the campaign other investigations are carried out using the same facilities. For example, the International Halley Watch mobilized observatories around the world for collection of data during the most recent apparition of Comet Halley. The Shoemaker-Levy-9 (SL9) campaign used both Earth-based and spacecraft instruments to monitor the SL9 impact on Jupiter.
	Other Investigation	Any other set of experiments and/or observations with a unifying theme.

type in Investigation_Area

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Investigation_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Individual Investigation	A set of experiments and/or observations with a clearly defined purpose that uses existing facilities and is under the direction of a single individual. For example, a series of related laboratory experiments/observations conducted by a small university team and funded through a single proposal could be an Individual Investigation. Library research by one person on previously published results to distill common conclusions could also be an Individual Investigation.	
	Mission	A set of experiments and/or observations with a clearly defined purpose that occupies the designated resources for all (or at least a significant fraction) of the available time. A mission is usually conducted by a national or international space agency using a small number (often one) of spacecraft especially designed and built for the purpose. For example: (1) the	

Name: type		Version Id: 1.0.0.0
		NASA Voyager mission launched two spacecraft to Jupiter and Saturn; (2) the Deep Impact (DI) mission launched a spacecraft, part of which impacted the comet Tempel 2; and (3) the EPOXI mission redefined the objectives of the surviving DI hardware for further exploration of the solar system.
	Observing Campaign	A set of experiments and/or observations with a clearly defined purpose that uses (primarily) existing facilities, but not exclusively. After (and possibly during) the campaign other investigations are carried out using the same facilities. For example, the International Halley Watch mobilized observatories around the world for collection of data during the most recent apparition of Comet Halley. The Shoemaker-Levy-9 (SL9) campaign used both Earth-based and spacecraft instruments to monitor the SL9 impact on Jupiter.
	Other Investigation	Any other set of experiments and/or observations with a unifying theme.

type in Observing_System_Component

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Observing_System_ Component	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Artificial Illumination	The observing system component is classified as Artificial Illumination	
	Instrument	The observing system component is classified as Instrument	
	Laboratory	The observing system component is classified as Laboratory	
	Literature Search	The observing system component is classified as Literature Search	
	Naked Eye	The observing system component is classified as Naked Eye (a person)	
	Observatory	The observing system component is classified as Observatory	
	Spacecraft	The observing system component is classified as Spacecraft	

Name: type		Version Id: 1.0.0.0
	Telescope	The observing system component is classified as Telescope

type in Primary_Result_Summary

Deprecated

Name: type *Deprecated*		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Primary_Result_Summary	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Deprecated	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Altimetry	Measurement of altitude.	
	Astrometry	Precise measurement of positions of heavenly bodies.	
	Count	A recording of the number of discrete events	
	E/B-Field Vectors	Arrays populated by values of the electric/ magnetic field in three orthogonal directions.	
	Gravity Model	An approximation to the gravity field of an object derived from measurement and/or theory	
	Image	A two-dimensional representation of a field of view	
	Lightcurves	This value indicates data products containing time-sequences of magnitude measurements for one or more individual targets (typically asteroids or comets).	
	Map	A two-dimensional representation of the plan view of a surface	
	Meteorology	Measurements of the meteorological conditions of an atmosphere such as pressure, temperature, wind speed, etc.	
	Null Result	Measurements which failed.	
	Occultation	Measurements conducted when one celestial body progressively hides another	
	Photometry	Measurement of light flux	
	Physical Parameters	This value indicates data products containing compilations of one or more physical parameters - like albedo, density, absolute magnitude, etc. It is generally used for data that combines these highly-derived results from multiple sources.	
	Polarimetry	Measurement of the polarization state of radiation.	

Name: type *Deprecated*		Version Id: 1.0.0.0
	Radiometry	Measurement of the radiation coming from a body, usually at infrared and longer wavelengths
	Reference	A Reference product provides ancillary information needed to support the use of another data product. Reference products include things like tables of foot notes or lists of detailed citations, and are usually associated with data products compiled from the published literature.
	Shape Model	An approximation to the shape of an object derived from measurements and/or theory
	Spectrum	An array containing values of a dependent variable as a function of an independent variable.

type in Quaternion

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	SPICE	Quaternion is type SPICE. This quaternion system defines components zero through three, with the 0th component as the scalar, and the 1st, 2nd and 3rd the vector components.	
	Spacecraft Telemetry	Quaternion is type Spacecraft Telemetry. This quaternion system defines components one through four, with the fourth component as the scalar, and the 1st, 2nd and 3rd as the vector components.	

type in Resource

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Resource	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Attributes in the common
(pds) namespace.

Name: type		Version Id: 1.0.0.0
	Information.Agency	An information resource that describes an agency.
	Information.Instrument	An information resource that describes an instrument
	Information.Instrument_Host	An information resource that describes an instrument host
	Information.Investigation	An information resource that describes an investigation
	Information.Node	An information resource that describes a node
	Information.Person	An information resource that describes a person
	Information.Resource	An information resource that describes a generic resource
	Information.Science_Portal	An information resource that describes a science portal
	Information.Target	An information resource that describes a target
	System.Browse	A system resource that provides browse functionality.
	System.Directory_Listing	A system resource that provides a directory listing.
	System.Registry_Query	A system resource for registry query.
	System.Search	A system resource that provides search functionality.
	System.Transform	A system resource that provides transform functionality.
	System.Transport	A system resource that provides transport functionality.

type in Target

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Asteroid	The Target is classified as an Asteroid	
	Comet	The Target is classified as a Comet	
	Dust	The Target is classified as Dust	
	Dwarf Planet	The Target is classified as a Dwarf Planet	
	Galaxy	The Target is classified as a Galaxy	
	Globular Cluster	The Target is classified as a Globular Cluster	

Attributes in the common
(pds) namespace.

Name: type		Version Id: 1.0.0.0
	Meteorite	The Target is classified as a Meteorite
	Meteoroid	The Target is classified as a Meteoroid
	Meteoroid Stream	The Target is classified as a Meteoroid Stream
	Nebula	The Target is classified as a Nebula
	Open Cluster	The Target is classified as an Open Cluster
	Planet	The Target is classified as a Planet
	Planetary Nebula	The Target is classified as a Planetary Nebula
	Planetary System	The Target is classified as a Planetary System
	Plasma Cloud	The Target is classified as a Plasma Cloud
	Ring	The Target is classified as a Ring
	Satellite	The Target is classified as a Satellite
	Star	The Target is classified as a Star
	Star Cluster	The Target is classified as a Star Cluster
	Sun	The Target is classified as a Sun
	Terrestrial Sample	The Target is classified as a Terrestrial Sample
	Trans-Neptunian Object	The Target is classified as a Trans-Neptunian Object

type in Target_Identification

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a target's type, used to determine correct nomenclature for the name field.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Target_Identification	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Asteroid	The Target is classified as an Asteroid	
	Comet	The Target is classified as a Comet	
	Dust	The Target is classified as Dust	
	Dwarf Planet	The Target is classified as a Dwarf Planet	
	Galaxy	The Target is classified as a Galaxy	
	Globular Cluster	The Target is classified as a Globular Cluster	
	Meteorite	The Target is classified as a Meteorite	
	Meteoroid	The Target is classified as a Meteoroid	
	Meteoroid Stream	The Target is classified as a Meteoroid Stream	
	Nebula	The Target is classified as a Nebula	
	Open Cluster	The Target is classified as an Open Cluster	
	Planet	The Target is classified as a Planet	

Name: type		Version Id: 1.0.0.0
	Planetary Nebula	The Target is classified as a Planetary Nebula
	Planetary System	The Target is classified as a Planetary System
	Plasma Cloud	The Target is classified as a Plasma Cloud
	Ring	The Target is classified as a Ring
	Satellite	The Target is classified as a Satellite
	Star	The Target is classified as a Star
	Star Cluster	The Target is classified as a Star Cluster
	Sun	The Target is classified as a Sun
	Terrestrial Sample	The Target is classified as a Terrestrial Sample
	Trans-Neptunian Object	The Target is classified as a Trans-Neptunian Object

type in Unit_Of_Measure

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Unit_Of_Measure	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

type in Units_of_Acceleration

Name: type		Version Id: 1.0.0.0	
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Acceleration	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Acceleration	Units_of_Acceleration is classified as being of type Acceleration	

type in Units_of_Amount_Of_Substance

Name: type		Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.		

Attributes in the common
(pds) namespace.

Name: type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Amount_Of_Substance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Amount_Of_Substance	Units_of_Amount_Of_Substance is classified as being of type Amount_Of_Substance	

type in Units_of_Angle

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angle	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Angle	Units_of_Angle is classified as being of type Angle	

type in Units_of_Angular_Velocity

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angular_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Angular_Velocity	Units_of_Angular_Velocity is classified as being of type Angular_Velocity	

type in Units_of_Area

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			

Name: type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Area	Units_of_Area is classified as being of type Area	

type in Units_of_Frame_Rate

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frame_Rate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Frame_Rate	Units_of_Frame_Rate is classified as being of type Frame Rate	

type in Units_of_Frequency

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frequency	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Frequency	Units_of_Frequency is classified as being of type Frequency	

type in Units_of_Length

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Length	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Length	Units_of_Length is classified as being of type Length	

type in Units_of_Map_Scale

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Map_Scale	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Scale	Units_of_Map_Scale is classified as being of type Scale	

type in Units_of_Mass

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Mass	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Mass	Units_of_Mass is classified as being of type Mass	

type in Units_of_Misc

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Misc	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Miscellaneous	Units_of_Misc is classified as being of type Miscellaneous	

type in Units_of_None

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_None	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	None	Units_of_None is classified as being of type None	

type in Units_of_Optical_Path_Length

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Optical_Path_Length	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Optical_Path_Length	Units_of_Optical_Path_Length is classified as being of type Optical_Path_Length	

type in Units_of_Pressure

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Pressure	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Pressure	Units_of_Pressure is classified as being of type Pressure	

type in Units_of_Radiance

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Radiance	Units_of_Radiance is classified as being of type Radiance	

type in Units_of_Rates

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Rates	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Rates	Units_of_Rates is classified as being of type Rates	

type in Units_of_Solid_Angle

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Solid_Angle	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Solid_Angle	Units_of_Solid_Angle is classified as being of type Solid_Angle	

type in Units_of_Spectral_Irradiance

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Irradiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Spectral_Irradiance	Units_of_Spectral_Irradiance is classified as being of the type Spectral_Irradiance	

type in Units_of_Spectral_Radiance

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Spectral_Radiance	Units_of_Spectral_Radiance is classified as being of the type Spectral_Radiance	

type in Units_of_Storage

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Storage	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Storage	Units_of_Storage is classified as being of type Storage	

type in Units_of_Temperature

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Temperature	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Temperature	Units_of_Temperature is classified as being of type Temperature	

type in Units_of_Time

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Time	Units_of_Time is classified as being of type Time	

type in Units_of_Velocity

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Velocity	Units_of_Velocity is classified as being of type Velocity	

type in Units_of_Voltage

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Voltage	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Voltage	Units_of_Voltage is classified as being of type Voltage	

type in Units_of_Volume

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Volume	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Volume	Units_of_Volume is classified as being of the type Volume	

type in Units_of_Wavenumber

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Wavenumber	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Wavenumber	Units_of_Wavenumber is classified as being of the type Wavenumber	

type in Vector

Name: type			Version Id: 1.0.0.0
<i>Description:</i> The type attribute provides a classification for the resource.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Acceleration	Vector is type Acceleration	
	Pointing	Vector is type Pointing	
	Position	Vector is type Position	
	Velocity	Vector is type Velocity	

unit in Axis_Array *Deprecated*

Name: unit *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Axis_Array	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Text
<i>Status:</i> Deprecated	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Element_Array

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Element_Array	<i>Type:</i> UTF8_Short_String_Collapsed

Name: unit			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Field_Binary

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Binary	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Field_Bit

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Field_Character

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Field_Delimited

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit in Vector_Component

Name: unit			Version Id: 1.0.0.0
<i>Description:</i> The unit attribute provides the unit of measurement.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Component	<i>Type:</i> UTF8_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Unit	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit_id in Unit_Of_Measure

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Unit_Of_Measure	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

unit_id in Units_of_Acceleration

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Acceleration	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: unit_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	cm/s**2	The abbreviated unit for Units_of_Acceleration is cm/s**2	
	km/s**2	The abbreviated unit for Units_of_Acceleration is km/s**2	
	m/s**2	The abbreviated unit for Units_of_Acceleration is m/s**2	

unit_id in Units_of_Amount_Of_Substance

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Amount_Of_Substance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	mol	The abbreviated unit for Units_of_Amount_Of_Substance is mol	

unit_id in Units_of_Angle

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angle	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	arcmin	The abbreviated unit for Units_of_Angle is arcmin	
	arcsec	The abbreviated unit for Units_of_Angle is arcsec	

Name: unit_id		Version Id: 1.0.0.0
	deg	The abbreviated unit for Units_of_Angle is deg
	hr	The abbreviated unit for Units_of_Angle is hr
	mrاد	The abbreviated unit for Units_of_Angle is mrاد
	rad	The abbreviated unit for Units_of_Angle is rad

unit_id in Units_of_Angular_Velocity

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Angular_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	deg/day	The abbreviated unit for Units_of_Angular_Velocity is deg/day	
	deg/s	The abbreviated unit for Units_of_Angular_Velocity is deg/s	
	rad/s	The abbreviated unit for Units_of_Angular_Velocity is rad/s	

unit_id in Units_of_Area

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Area	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	m**2	The abbreviated unit for Units_of_Area is m**2	

unit_id in Units_of_Frame_Rate

Name: unit_id		Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.		

Attributes in the common
(pds) namespace.

Name: unit_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frame_Rate	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	frames/s	The abbreviated unit for Units_of_Frame_Rate is frames/s	

unit_id in Units_of_Frequency

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Frequency	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Hz	The abbreviated unit for Units_of_Frequency is Hz	

unit_id in Units_of_Length

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Length	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	AU	The abbreviated unit for Units_of_Length is AU (astronomical unit)	
	Angstrom	The abbreviated unit for Units_of_Length is Angstrom	
	cm	The abbreviated unit for Units_of_Length is cm	
	km	The abbreviated unit for Units_of_Length is km	

Attributes in the common
(pds) namespace.

Name: unit_id		Version Id: 1.0.0.0
	m	The abbreviated unit for Units_of_Length is m
	micrometer	The abbreviated unit for Units_of_Length is micrometer
	mm	The abbreviated unit for Units_of_Length is mm
	nm	The abbreviated unit for Units_of_Length is nm

unit_id in Units_of_Map_Scale

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Map_Scale	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	km/pixel	The abbreviated unit for Units_of_Map_Scale is km/pixel	
	m/pixel	The abbreviated unit for Units_of_Map_Scale is m/pixel	
	mm/pixel	The abbreviated unit for Units_of_Map_Scale is mm/pixel	
	pixel/deg	The abbreviated unit for Units_of_Map_Scale is pixel/deg	

unit_id in Units_of_Mass

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Mass	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	g	The abbreviated unit for Units_of_Mass is g	
	kg	The abbreviated unit for Units_of_Mass is kg	

unit_id in Units_of_Misc

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Misc	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	DN	The abbreviated unit for Units_of_Misc is DN	
	electron/DN	The abbreviated unit for Units_of_Misc is electron/DN	
	pixel	The abbreviated unit for Units_of_Misc is pixel	

unit_id in Units_of_None

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_None	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	none	The abbreviated unit for Units_of_None is none	

unit_id in Units_of_Optical_Path_Length

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Optical_Path_Length	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Name: unit_id		Version Id: 1.0.0.0
	airmass	The abbreviated unit for Units_of_Optical_Path_Length is airmass

unit_id in Units_of_Pressure

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Pressure	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Pa	The abbreviated unit for Units_of_Pressure is Pa	
	bar	The abbreviated unit for Units_of_Pressure is bar (10**5 Pa)	
	hPa	The abbreviated unit for Units_of_Pressure is hPa (100 Pa)	
	mbar	The abbreviated unit for Units_of_Pressure is mbar (100 Pa)	

unit_id in Units_of_Radiance

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	W*m**-2*sr**-1	The abbreviated unit of Units_of_Radiance is W*m**-2*sr**-1	

unit_id in Units_of_Rates

Name: unit_id		Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.		

Name: unit_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Rates	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	counts/bin	The abbreviated unit for Units_of_Rates is counts/bin	
	kilobits/s	The abbreviated unit for Units_of_Rates is kilobits/s	

unit_id in Units_of_Solid_Angle

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Solid_Angle	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	sr	The abbreviated unit for Units_of_Solid_Angle is sr	

unit_id in Units_of_Spectral_Irradiance

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Irradiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	SFU	The abbreviated unit for Units_of_Spectral_Irradiance is SFU	

Attributes in the common
(pds) namespace.

Name: unit_id		Version Id: 1.0.0.0
	$W*m^{**2}*Hz^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**2}*Hz^{**1}$
	$W*m^{**2}*nm^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**2}*nm^{**1}$
	$W*m^{**3}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**3}$
	$uW*cm^{**2}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $uW*cm^{**2}*um^{**1}$

unit_id in Units_of_Spectral_Radiance

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Spectral_Radiance	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	$W*m^{**2}*sr^{**1}*Hz^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*Hz^{**1}$	
	$W*m^{**2}*sr^{**1}*nm^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*nm^{**1}$	
	$W*m^{**2}*sr^{**1}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*um^{**1}$	
	$W*m^{**3}*sr^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**3}*sr^{**1}$	
	$uW*cm^{**2}*sr^{**1}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $uW*cm^{**2}*sr^{**1}*um^{**1}$	

unit_id in Units_of_Storage

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Storage	<i>Type:</i> ASCII_Short_String_Collapsed

Attributes in the common
(pds) namespace.

Name: unit_id			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	byte	The abbreviated unit of Units_of_Storage is byte	

unit_id in Units_of_Temperature

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Temperature	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	K	The abbreviated unit of Units_of_Temperature is K	
	degC	The abbreviated unit of Units_of_Temperature is degC	

unit_id in Units_of_Time

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	day	The abbreviated unit for Units_of_Time is day	
	hr	The abbreviated unit for Units_of_Time is hr	
	julian day	The abbreviated unit for Units_of_Time is julian day	
	microseconds	The abbreviated unit for Units_of_Time is microseconds	
	min	The abbreviated unit for Units_of_Time is min	

Name: unit_id		Version Id: 1.0.0.0
	ms	The abbreviated unit for Units_of_Time is ms
	s	The abbreviated unit for Units_of_Time is s
	yr	The abbreviated unit for Units_of_Time is yr

unit_id in Units_of_Velocity

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Velocity	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	cm/s	The abbreviated unit for Units_of_Velocity is cm/s	
	km/s	The abbreviated unit for Units_of_Velocity is km/s	
	m/s	The abbreviated unit for Units_of_Velocity is m/s	

unit_id in Units_of_Voltage

Name: unit_id		Version Id: 1.0.0.0	
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Voltage	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	V	The abbreviated unit for Units_of_Voltage is V	
	mV	The abbreviated unit for Units_of_Voltage is mV	

unit_id in Units_of_Volume

Name: unit_id		Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.		

Name: unit_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Volume	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	L	The abbreviated unit for Units_of_Volume is L	
	m**3	The abbreviated unit for Units_of_Volume is m**3	

unit_id in Units_of_Wavenumber

Name: unit_id			Version Id: 1.0.0.0
<i>Description:</i> The unit_id attribute provides a character or character string which serves as an abbreviation for, or symbol representing, a unit of measure.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Units_of_Wavenumber	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	cm**-1	The abbreviated unit for Units_of_Wavenumber is cm**-1	
	m**-1	The abbreviated unit for Units_of_Wavenumber is m**-1	
	nm**-1	The abbreviated unit for Units_of_Wavenumber is nm**-1	

unit_of_measure_type in DD_Value_Domain

Name: unit_of_measure_type			Version Id: 1.0.0.0
<i>Description:</i> The unit_of_measure_type attribute provides the named grouping of units to be used for this attribute - for example Units_of_Length and Units_of_Time.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Attributes in the common
(pds) namespace.

Name: unit_of_measure_type		Version Id: 1.0.0.0
	Units_of_Acceleration	The value is given in a unit which conveys acceleration
	Units_of_Amount_Of_Substance	The value is given in a unit which conveys amount of substance
	Units_of_Angle	The value is given in a unit which conveys angle
	Units_of_Angular_Velocity	The value is given in a unit which conveys angular velocity
	Units_of_Area	The value is given in a unit which conveys area
	Units_of_Frame_Rate	The value is given in a unit which conveys frame rate
	Units_of_Frequency	The value is given in a unit which conveys frequency
	Units_of_Length	The value is given in a unit which conveys length
	Units_of_Map_Scale	The value is given in a unit which conveys map scale
	Units_of_Mass	The value is given in a unit which conveys mass
	Units_of_Misc	The value is given in a unit which is in a miscellaneous category
	Units_of_None	The value is given without regard to a unit of measure
	Units_of_Optical_Path_Length	The value is given in a unit which conveys optical path length
	Units_of_Pressure	The value is given in a unit which conveys pressure
	Units_of_Radiance	The value is given in a unit which conveys radiance
	Units_of_Rates	The value is given in a unit which conveys rates or counts per unit time
	Units_of_Solid_Angle	The value is given in a unit which conveys solid angle
	Units_of_Spectral_Irradiance	The value is given in a unit which conveys spectral irradiance
	Units_of_Spectral_Radiance	The value is given in a unit which conveys spectral radiance
	Units_of_Storage	The value is given in a unit which conveys computer storage
	Units_of_Temperature	The value is given in a unit which conveys temperature
	Units_of_Time	The value is given in a unit which conveys time
	Units_of_Velocity	The value is given in a unit which conveys velocity
	Units_of_Voltage	The value is given in a unit which conveys voltage
	Units_of_Volume	The value is given in a unit which conveys volume

Name: unit_of_measure_type		Version Id: 1.0.0.0
	Units_of_Wavenumber	The value is given in a unit which conveys wavenumber

unit_of_measure_type in DD_Value_Domain_Full

Name: unit_of_measure_type		Version Id: 1.0.0.0	
<i>Description:</i> The unit_of_measure_type attribute provides the named grouping of units to be used for this attribute - for example Units_of_Length and Units_of_Time.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Units_of_Amount_Of_Substance	The value is given in a unit which conveys amount of substance	
	Units_of_Angle	The value is given in a unit which conveys angle	
	Units_of_Angular_Velocity	The value is given in a unit which conveys angular velocity	
	Units_of_Area	The value is given in a unit which conveys area	
	Units_of_Frame_Rate	The value is given in a unit which conveys frame rate	
	Units_of_Frequency	The value is given in a unit which conveys frequency	
	Units_of_Length	The value is given in a unit which conveys length	
	Units_of_Map_Scale	The value is given in a unit which conveys map scale	
	Units_of_Mass	The value is given in a unit which conveys mass	
	Units_of_Misc	The value is given in a unit which is in a miscellaneous category	
	Units_of_None	The value is given without regard to a unit of measure	
	Units_of_Optical_Path_Length	The value is given in a unit which conveys optical path length	
	Units_of_Pressure	The value is given in a unit which conveys pressure	
	Units_of_Radiance	The value is given in a unit which conveys radiance	
	Units_of_Rates	The value is given in a unit which conveys rates or counts per unit time	
	Units_of_Solid_Angle	The value is given in a unit which conveys solid angle	

Name: unit_of_measure_type		Version Id: 1.0.0.0
	Units_of_Spectral_Irradiance	The value is given in a unit which conveys spectral irradiance
	Units_of_Spectral_Radiance	The value is given in a unit which conveys spectral radiance
	Units_of_Storage	The value is given in a unit which conveys computer storage
	Units_of_Temperature	The value is given in a unit which conveys temperature
	Units_of_Time	The value is given in a unit which conveys time
	Units_of_Velocity	The value is given in a unit which conveys velocity
	Units_of_Voltage	The value is given in a unit which conveys voltage
	Units_of_Volume	The value is given in a unit which conveys volume
	Units_of_Wavenumber	The value is given in a unit which conveys wavenumber

unknown_constant in Special_Constants

Name: unknown_constant			Version Id: 1.0.0.0
<i>Description:</i> The unknown_constant attribute provides a value that indicates the original value was unknown.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Constant	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

url in External_Reference_Extended

Name: url			Version Id: 1.0.0.0
<i>Description:</i> The url attribute provides a Uniform Resource Identifier (URI) that specifies where a resource is available and the mechanism for retrieving it.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> External_Reference_Extended	<i>Type:</i> ASCII_AnyURI
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

url in Resource

Name: url			Version Id: 1.0.0.0
<i>Description:</i> The url attribute provides a Uniform Resource Identifier (URI) that specifies where a resource is available and the mechanism for retrieving it.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Resource	<i>Type:</i> ASCII_AnyURI
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

users_manual_id in Software

Name: users_manual_id			Version Id: 1.0.0.0
<i>Description:</i> The users manual id attribute provides a formal name used to refer to a manual that describes how to use the software.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

valid_maximum in Special_Constants

Name: valid_maximum			Version Id: 1.0.0.0
<i>Description:</i> The valid_maximum attribute specifies the maximum valid value in the field or digital object with which the Special_Constants class is associated. Values above the valid_maximum have a special meaning. Values of this attribute should be represented in the same data_type as the elements in the object or field described. (Note that PDS3 had no qube-related valid_maximum values because all special constants were set below the valid_minimum.)			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Maximum	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	254	conventional ISIS 2/3 qube value for a one byte unsigned integer data type	
	32767	conventional ISIS 2/3 qube value for a two byte signed integer data type	

Name: valid_maximum		Version Id: 1.0.0.0
	65522	conventional ISIS 3 qube value for a two byte unsigned integer data type (Note that

valid_minimum in Special_Constants

Name: valid_minimum		Version Id: 1.0.0.0	
<i>Description:</i> The valid_minimum attribute specifies the minimum valid value in the field or digital object with which the Special_Constants class is associated. Values below the valid_minimum have a special meaning. Values of this attribute should be represented in the same data_type as the elements in the object or field described.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Special_Constants	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Minimum	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	-32752	conventional PDS3 and ISIS 2/3 qube value for a two byte signed integer data type	
	1	conventional ISIS 2/3 qube value for a one byte unsigned integer data type	
	3	conventional ISIS 3 qube value for a two byte unsigned integer data type	
	5	conventional PDS3 qube value for any unsigned integer data type	
	FF7FFFA	conventional ISIS 2 qube value for a four byte IEEE floating point data type	
	FFEFFFFF	conventional PDS3 and ISIS 2 qube value for a four byte VAX floating point data type	

value in DD_Permissible_Value

Name: value		Version Id: 1.0.0.0	
<i>Description:</i> The value attribute provides a single, allowed numerical or character string value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

value in DD_Permissible_Value_Full

Name: value			Version Id: 1.0.0.0
<i>Description:</i> The value attribute provides a single, allowed numerical or character string value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

value in Quaternion_Component

Name: value			Version Id: 1.0.0.0
<i>Description:</i> The value attribute provides a single, allowed numerical or character string value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Quaternion_Component	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

value in Vector_Component

Name: value			Version Id: 1.0.0.0
<i>Description:</i> The value attribute provides a single, allowed numerical or character string value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Component	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Value	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

value_begin_date in DD_Permissible_Value_Full

Name: value_begin_date			Version Id: 1.0.0.0
<i>Description:</i> The value_begin_date attribute provides the first date on which the permissible value is in effect.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value_Full	<i>Type:</i> ASCII_Date_Time_YMD
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

value_data_type in DD_Value_Domain

Name: value_data_type			Version Id: 1.0.0.0
<i>Description:</i> The value_data_type attribute provides the data type used to represent the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_AnyURI	The value is expressed using the data type ASCII_AnyURI	
	ASCII_Boolean	The value is expressed using the data type ASCII_Boolean	
	ASCII_DOI	The value is expressed using the data type ASCII_DOI	
	ASCII_Date_DOY	The value is expressed using the data type ASCII_Date_DOY	
	ASCII_Date_Time	The value is expressed using the data type ASCII_Date_Time	
	ASCII_Date_Time_DOY	The value is expressed using the data type ASCII_Date_Time_DOY	
	ASCII_Date_Time_UTC	The value is expressed using the data type ASCII_Date_Time_UTC	
	ASCII_Date_Time_YMD	The value is expressed using the data type ASCII_Date_Time_YMD	
	ASCII_Date_YMD	The value is expressed using the data type ASCII_Date_YMD	

Attributes in the common
(pds) namespace.

<i>Name: value_data_type</i>		<i>Version Id: 1.0.0.0</i>
ASCII_Directory_Path_Name	The value is expressed using the data type ASCII_Directory_Path_Name	
ASCII_File_Name	The value is expressed using the data type ASCII_File_Name	
ASCII_File_Specification_Name	The value is expressed using the data type ASCII_File_Specification_Name	
ASCII_Integer	The value is expressed using the data type ASCII_Integer	
ASCII_LID	The value is expressed using the data type ASCII_LID	
ASCII_LIDVID	The value is expressed using the data type ASCII_LIDVID	
ASCII_LIDVID_LID	The value is expressed using the data type ASCII_LIDVID_LID	
ASCII_MD5_Checksum	The value is expressed using the data type ASCII_MD5_Checksum	
ASCII_NonNegative_Integer	The value is expressed using the data type ASCII_NonNegative_Integer	
ASCII_Numeric_Base16	The value is expressed using the data type ASCII_Numeric_Base16	
ASCII_Numeric_Base2	The value is expressed using the data type ASCII_Numeric_Base2	
ASCII_Numeric_Base8	The value is expressed using the data type ASCII_Numeric_Base8	
ASCII_Real	The value is expressed using the data type ASCII_Real	
ASCII_Short_String_Collapsed	The value is expressed using the data type ASCII_Short_String_Collapsed	
ASCII_Short_String_Preserved	The value is expressed using the data type ASCII_Short_String_Preserved	
ASCII_Text_Collapsed	The value is expressed using the data type ASCII_Text_Collapsed	
ASCII_Text_Preserved	The value is expressed using the data type ASCII_Text_Preserved	
ASCII_Time	The value is expressed using the data type ASCII_Time	
ASCII_VID	The value is expressed using the data type ASCII_VID	
UTF8_Short_String_Collapsed	The value is expressed using the data type UTF8_Short_String_Collapsed	
UTF8_Short_String_Preserved	The value is expressed using the data type UTF8_Short_String_Preserved	
UTF8_Text_Preserved	The value is expressed using the data type UTF8_Text_Preserved	
Vector_Cartesian_3	The value is expressed using the data type Vector_Cartesian_3	

Name: value_data_type		Version Id: 1.0.0.0
	Vector_Cartesian_3_Acceleration	The value is expressed using the data type Vector_Cartesian_3_Acceleration
	Vector_Cartesian_3_Pointing	The value is expressed using the data type Vector_Cartesian_3_Pointing
	Vector_Cartesian_3_Position	The value is expressed using the data type Vector_Cartesian_3_Position
	Vector_Cartesian_3_Velocity	The value is expressed using the data type Vector_Cartesian_3_Velocity

value_data_type in DD_Value_Domain_Full

Name: value_data_type		Version Id: 1.0.0.0	
<i>Description:</i> The value_data_type attribute provides the data type used to represent the value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Value_Domain_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	ASCII_AnyURI	The value is expressed using the data type ASCII_AnyURI	
	ASCII_Boolean	The value is expressed using the data type ASCII_Boolean	
	ASCII_DOI	The value is expressed using the data type ASCII_DOI	
	ASCII_Date_DOY	The value is expressed using the data type ASCII_Date_DOY	
	ASCII_Date_Time	The value is expressed using the data type ASCII_Date_Time	
	ASCII_Date_Time_DOY	The value is expressed using the data type ASCII_Date_Time_DOY	
	ASCII_Date_Time_UTC	The value is expressed using the data type ASCII_Date_Time_UTC	
	ASCII_Date_Time_YMD	The value is expressed using the data type ASCII_Date_Time_YMD	
	ASCII_Date_YMD	The value is expressed using the data type ASCII_Date_YMD	
	ASCII_Directory_Path_Name	The value is expressed using the data type ASCII_Directory_Path_Name	
	ASCII_File_Name	The value is expressed using the data type ASCII_File_Name	
	ASCII_File_Specification_Name	The value is expressed using the data type ASCII_File_Specification_Name	
	ASCII_Integer	The value is expressed using the data type ASCII_Integer	

Attributes in the common
(pds) namespace.

<i>Name: value_data_type</i>		<i>Version Id: 1.0.0.0</i>
	ASCII_LID	The value is expressed using the data type ASCII_LID
	ASCII_LIDVID	The value is expressed using the data type ASCII_LIDVID
	ASCII_LIDVID_LID	The value is expressed using the data type ASCII_LIDVID_LID
	ASCII_MD5_Checksum	The value is expressed using the data type ASCII_MD5_Checksum
	ASCII_NonNegative_Integer	The value is expressed using the data type ASCII_NonNegative_Integer
	ASCII_Numeric_Base16	The value is expressed using the data type ASCII_Numeric_Base16
	ASCII_Numeric_Base2	The value is expressed using the data type ASCII_Numeric_Base2
	ASCII_Numeric_Base8	The value is expressed using the data type ASCII_Numeric_Base8
	ASCII_Real	The value is expressed using the data type ASCII_Real
	ASCII_Short_String_Collapsed	The value is expressed using the data type ASCII_Short_String_Collapsed
	ASCII_Short_String_Preserved	The value is expressed using the data type ASCII_Short_String_Preserved
	ASCII_Text_Collapsed	The value is expressed using the data type ASCII_Text_Collapsed
	ASCII_Text_Preserved	The value is expressed using the data type ASCII_Text_Preserved
	ASCII_Time	The value is expressed using the data type ASCII_Time
	ASCII_VID	The value is expressed using the data type ASCII_VID
	UTF8_Short_String_Collapsed	The value is expressed using the data type UTF8_Short_String_Collapsed
	UTF8_Short_String_Preserved	The value is expressed using the data type UTF8_Short_String_Preserved
	UTF8_Text_Preserved	The value is expressed using the data type UTF8_Text_Preserved

value_end_date in DD_Permissible_Value_Full

<i>Name: value_end_date</i>			<i>Version Id: 1.0.0.0</i>
<i>Description:</i> The value_end_date attribute provides the last date on which the permissible value is in effect.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value_Full	<i>Type:</i> ASCII_Date_Time_YMD

Name: value_end_date			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_meaning in DD_Permissible_Value

Name: value_meaning			Version Id: 1.0.0.0
<i>Description:</i> The value_meaning attribute provides the meaning, or semantic content, of the associated permissible value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_meaning in DD_Permissible_Value_Full

Name: value_meaning			Version Id: 1.0.0.0
<i>Description:</i> The value_meaning attribute provides the meaning, or semantic content, of the associated permissible value.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Permissible_Value_Full	<i>Type:</i> ASCII_Text_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Text	<i>Conceptual Domain:</i> Text
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Band_Bin *Deprecated*

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> img	<i>Class Name:</i> Band_Bin *Deprecated*	<i>Type:</i> ASCII_Real

Name: value_offset			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Element_Array

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Element_ Array	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Field_Binary

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_ Binary	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Field_Bit

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Bit	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: value_offset			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Field_Character

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Character	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

value_offset in Field_Delimited

Name: value_offset			Version Id: 1.0.0.0
<i>Description:</i> The value_offset attribute is the offset to be applied to each stored value in order to recover an original value. The observed value (Ov) is calculated from the stored value (Sv) thus: $Ov = (Sv * scaling_factor) + value_offset$. The default value is 0.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Field_Delimited	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Offset	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

vector_components in Vector

Name: vector_components			Version Id: 1.0.0.0
<i>Description:</i> The vector_components attribute provides a count of vector components.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

version_id in DD_Attribute

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\,){1}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in DD_Attribute_Full

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Attribute_Full	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\,){1}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in DD_Class

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_Class	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\,){1}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in DD_Class_Full

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			

Attributes in the common
(pds) namespace.

Name: version_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> DD_ Class_Full	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\.)\{1\}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in Identification_Area

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Identification_Area	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\.)\{1\}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in Instrument_Host *Deprecated*

Name: version_id *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Instrument_Host	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Deprecated	<i>Niltable:</i> false	<i>Pattern:</i> ([0-9]+)(\.)\{1\}([0-9]+)	
<i>Permissible Value(s)</i>	<i>No Values</i>		

version_id in Modification_Detail

Name: version_id			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Modification_Detail	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: version_id			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> ([0-9]+)(\,){1}([0-9]+)	
<i>Permissible Value(s)</i>	No Values		

version_id in Software *Deprecated*

Name: version_id *Deprecated*			Version Id: 1.0.0.0
<i>Description:</i> The version_id attribute provides the version of the product, expressed in the PDS [m.n] notation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Software	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Deprecated	<i>Nillable:</i> false	<i>Pattern:</i> ([0-9]+)(\,){1}([0-9]+)	
<i>Permissible Value(s)</i>	No Values		

volume_de_fullname in Volume_PDS3

Name: volume_de_fullname			Version Id: 1.0.0.0
<i>Description:</i> The volume_de_fullname attribute provide the full name of the data engineer.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

volume_format in Volume_PDS3

Name: volume_format			Version Id: 1.0.0.0
<i>Description:</i> The volume_format attribute identifies the logical format used in writing a data volume.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Format	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

volume_id in Volume_PDS3

Name: volume_id			Version Id: 1.0.0.0
<i>Description:</i> The volume_id attribute provides a unique identifier for a data volume. Example: MG_1001.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_name in Volume_PDS3

Name: volume_name			Version Id: 1.0.0.0
<i>Description:</i> The volume_name attribute contains the name of a data volume.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_series_name in Volume_Set_PDS3

Name: volume_series_name			Version Id: 1.0.0.0
<i>Description:</i> The volume_series_name element provides a full, formal name that describes a broad categorization of data products or data sets related to a planetary body or a research campaign (e.g. International Halley Watch). A volume series consists of one or more volume sets that represent data from one or more missions or campaigns.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_set_id in Volume_PDS3

Name: volume_set_id			Version Id: 1.0.0.0
<i>Description:</i> The volume_set_id attribute identifies a data volume or a set of volumes. Volume sets are normally considered as a single orderable entity. Examples: USA_NASA_PDS_MG_1001, USA_NASA_PDS_GR_0001_TO_GR_0009			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_set_id in Volume_Set_PDS3

Name: volume_set_id			Version Id: 1.0.0.0
<i>Description:</i> The volume_set_id attribute identifies a data volume or a set of volumes. Volume sets are normally considered as a single orderable entity. Examples: USA_NASA_PDS_MG_1001, USA_NASA_PDS_GR_0001_TO_GR_0009			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_set_name in Volume_Set_PDS3

Name: volume_set_name			Version Id: 1.0.0.0
<i>Description:</i> The volume_set_name element provides the full, formal name of one or more data volumes containing a single data set or a collection of related data sets. Volume sets are normally considered as a single orderable entity.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_Set_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_size in Volume_PDS3

Name: volume_size			Version Id: 1.0.0.0
<i>Description:</i> The volume size attribute provide the number of bytes in the volume.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_NonNegative_Integer
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Size	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volume_version_id in Volume_PDS3

Name: volume_version_id			Version Id: 1.0.0.0
<i>Description:</i> The volume_version_id attribute identifies the version of a data volume. All original volumes should use a volume_version_id of 'Version 1'.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_PDS3	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

volumes in Volume_Set_PDS3

Name: volumes			Version Id: 1.0.0.0
<i>Description:</i> The volumes element provides the number of physical data volumes contained in a volume set.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> Volume_Set_PDS3	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

wavelength_range in Science_Facets

Name: wavelength_range			Version Id: 1.0.0.0
<i>Description:</i> The wavelength range within which the data collection occurred or which otherwise characterizes the observation(s). Boundaries are vague, and there is overlap.			

Attributes in the common
(pds) namespace.

Name: wavelength_range			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Science_Facets	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Far Infrared	30 to 300 micrometers	
	Gamma Ray	less than 0.01 nm	
	Infrared	0.75 to 300 micrometers	
	Microwave	millimeters to one meter	
	Millimeter	one to a few millimeters	
	Near Infrared	0.65 to 5.0 micrometers	
	Radio	millimeters to hundreds of thousands of meters	
	Submillimeter	0.3-1.0 millimeter	
	Ultraviolet	10 to 400 nm	
	Visible	390-700 nm	
	X-ray	0.01 to 10 nm	

x in Vector_Cartesian_3

Name: x			Version Id: 1.0.0.0
<i>Description:</i> The x attribute provides the value of the x coordinate in a position vector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Cartesian_3	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

xml_schema_base_type in ASCII_AnyURI

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_AnyURI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: xml_schema_base_type		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	xsd:anyURI	ASCII_AnyURI has an XML schema base type of xsd:anyURI

xml_schema_base_type in ASCII_Boolean

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Boolean	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:boolean	ASCII_Boolean has an XML schema base type of xsd:boolean	

xml_schema_base_type in ASCII_DOI

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_DOI	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_DOI has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Date	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_DOY

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_DOY has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_Time

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_Time has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_Time_DOY

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_Time_DOY	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_Time_DOY has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_Time_UTC

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_Time_UTC	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_Time_UTC has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_Time_YMD

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_Time_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_Time_YMD has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Date_YMD

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Date_YMD	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Date_YMD has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Directory_Path_Name

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Directory_Path_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	ASCII_Directory_Path_Name has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_File_Name

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_File_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	

Name: xml_schema_base_type		Version Id: 1.0.0.0
	xsd:token	ASCII_File_Name has an XML schema base type of xsd:token

xml_schema_base_type in ASCII_File_Specification_Name

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_File_Specification_Name	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	ASCII_File_Specification_Name has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_Integer

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:int	ASCII_Integer has an XML schema base type of xsd:int	

xml_schema_base_type in ASCII_LID

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255

Attributes in the common
(pds) namespace.

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_LID has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_LIDVID

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_LIDVID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_LIDVID has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_LIDVID_LID

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_LIDVID_LID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_LIDVID_LID has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_MD5_Checksum

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_MD5_Checksum	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_MD5_Checksum has an XML schema base type xsd:string	

xml_schema_base_type in ASCII_NonNegative_Integer

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_NonNegative_Integer	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:long	ASCII_NonNegative_Integer has an XML schema base type of xsd:long	

xml_schema_base_type in ASCII_Numeric_Base16

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base16	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:hexBinary	ASCII_Numeric_Base16 has an XML schema base type of xsd:hexBinary	

xml_schema_base_type in ASCII_Numeric_Base2

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base2	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Numeric_Base2 has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Numeric_Base8

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Numeric_Base8	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Numeric_Base8 has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_Real

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Real	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String

Name: xml_schema_base_type		Version Id: 1.0.0.0
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	xsd:double	ASCII_Real has an XML schema base type of xsd:double

xml_schema_base_type in ASCII_Short_String_Collapsed

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	ASCII_Short_String_Collapsed has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_Short_String_Preserved

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Preserved
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Short_String_Preserved has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_String

Name: xml_schema_base_type		Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.		

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_String	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	ASCII_String has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_Text_Collapsed

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> ASCII_Text_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	ASCII_Text_Collapsed has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_Text_Preserved

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Text_Preserved has an XML schema base type of xsd:token	

xml_schema_base_type in ASCII_Time

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_Time	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_Time has an XML schema base type of xsd:string	

xml_schema_base_type in ASCII_VID

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> ASCII_VID	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	ASCII_VID has an XML schema base type of xsd:string	

xml_schema_base_type in Character_Data_Type

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Character_Data_Type	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

xml_schema_base_type in UTF8_Short_String_Collapsed

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> UTF8_Short_String_Collapsed	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:token	UTF8_Short_String_Collapsed has an XML schema base type of xsd:token	

xml_schema_base_type in UTF8_Short_String_Preserved

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> UTF8_Short_String_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	UTF8_Short_String_Preserved has an XML schema base type of xsd:string	

xml_schema_base_type in UTF8_String

Name: xml_schema_base_type			Version Id: 1.0.0.0
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> UTF8_String	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	

Name: xml_schema_base_type		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	xsd:token	UTF8_String must be normalized.

xml_schema_base_type in UTF8_Text_Preserved

Name: xml_schema_base_type		Version Id: 1.0.0.0	
<i>Description:</i> The xml schema base type attribute provides the data type needed for the XML schema implementation.			
<i>Namespace Id:</i> pds	<i>Steward:</i> ops	<i>Class Name:</i> UTF8_Text_Preserved	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Type	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	xsd:string	UTF8_Text_Preserved has an XML schema base type of xsd:string	

y in Vector_Cartesian_3

Name: y		Version Id: 1.0.0.0	
<i>Description:</i> The y attribute provides the value of the y coordinate in a position vector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Cartesian_3	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

z in Vector_Cartesian_3

Name: z		Version Id: 1.0.0.0	
<i>Description:</i> The z attribute provides the value of the z coordinate in a position vector.			
<i>Namespace Id:</i> pds	<i>Steward:</i> pds	<i>Class Name:</i> Vector_Cartesian_3	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Number	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

Chapter 9. Attributes in the Rings discipline namespace.

These attributes are used by the classes defined for the Rings namespace.

SCLK_start_time in Radio_Occultation

Name: SCLK_start_time			Version Id: 1.0.0.0
<i>Description:</i> SCLK_start_time is the value of the spacecraft clock corresponding to the start_date_time given in the label.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

SCLK_start_time in Stellar_Occultation

Name: SCLK_start_time			Version Id: 1.0.0.0
<i>Description:</i> SCLK_start_time is the value of the spacecraft clock corresponding to the start_date_time given in the label.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

SCLK_stop_time in Radio_Occultation

Name: SCLK_stop_time			Version Id: 1.0.0.0
<i>Description:</i> SCLK_stop_time is the value of the spacecraft clock corresponding to the stop_date_time given in the label.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: SCLK_stop_time		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

SCLK_stop_time in Stellar_Occultation

Name: SCLK_stop_time		Version Id: 1.0.0.0	
<i>Description: SCLK_stop_time is the value of the spacecraft clock corresponding to the stop_date_time given in the label.</i>			
<i>Namespace Id: rings</i>	<i>Steward: rings</i>	<i>Class Name: Stellar_Occultation</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: None</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

along_track_timing_offset in Radio_Occultation

Name: along_track_timing_offset		Version Id: 1.0.0.0	
<i>Description: along_track_timing_offset is a timing offset to the along track spacecraft position. It is the value that minimizes differences in radii of matching circular ring features observed on the ingress and egress sides of the occultation track. Optional in labels for radio occultation. Nillable in which case the nil_reason should be 'inapplicable'.</i>			
<i>Namespace Id: rings</i>	<i>Steward: rings</i>	<i>Class Name: Radio_Occultation</i>	<i>Type: ASCII_Real</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: Units_of_Time</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: None</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

dsn_station_number in Radio_Occultation

Name: dsn_station_number		Version Id: 1.0.0.0	
<i>Description: dsn_station_number identifies the receiving DSN station. Required in labels for radio occultations; not used for stellar occultations. Nillable in which case the nil_reason should be 'inapplicable'.</i>			
<i>Namespace Id: rings</i>	<i>Steward: rings</i>	<i>Class Name: Radio_Occultation</i>	<i>Type: ASCII_Integer</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: None</i>

Name: dsn_station_number		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

dsn_station_number in Radio_Occultation_Support

Name: dsn_station_number		Version Id: 1.0.0.0	
<i>Description:</i> dsn_station_number identifies the receiving DSN station. Required in labels for radio occultations; not used for stellar occultations. Nillable in which case the nil_reason should be 'inapplicable'.			
Namespace Id: rings	Steward: rings	Class Name: Radio_Occultation_Support	Type: ASCII_Integer
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: None	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

earth_received_start_time_utc in Radio_Occultation

Name: earth_received_start_time_utc		Version Id: 1.0.0.0	
<i>Description:</i> earth_received_start_time_utc gives the UTC time corresponding to the earliest time for the data product at which telemetry or other photons were received on Earth. Optional for occultation data. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			
Namespace Id: rings	Steward: rings	Class Name: Radio_Occultation	Type: ASCII_Date_Time_UTC
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Time	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

earth_received_stop_time_utc in Radio_Occultation

Name: earth_received_stop_time_utc		Version Id: 1.0.0.0	
<i>Description:</i> earth_received_stop_time_utc gives the UTC time corresponding to the latest time for the data product at which telemetry or other photons were received on Earth. Optional for occultation data. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			

Name: earth_received_stop_time_utc			Version Id: 1.0.0.0
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

frequency_band in Radio_Occultation

Name: frequency_band			Version Id: 1.0.0.0
<i>Description:</i> frequency_band is the one or two letter identifier of the frequency band. Required in labels for radio occultations; not used for stellar occultations. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	C	Frequency range: 5.85 to 8.20 GHz	
	D	Frequency range: 2.20 to 3.30 GHz	
	E	Frequency range: 3.30 to 4.90 GHz	
	F	Frequency range: 4.90 to 7.05 GHz	
	G	Frequency range: 3.95 to 5.85 GHz	
	H	Frequency range: 7.05 to 10.10 GHz	
	K	Frequency range: 5.0 to 26.5 GHz	
	Ka	Frequency range: 26.5 to 40.0 GHz	
	Ku	Frequency range: 12.4 to 18.0 GHz	
	Q	Frequency range: 33 to 50 GHz	
	R	Frequency range: 1.70 to 2.60 GHz	
	S	Frequency range: 2.60 to 3.95 GHz	
	U	Frequency range: 40 to 60 GHz	
	V	Frequency range: 50 to 75 GHz	
	W	Frequency range: 75 to 110 GHz	
	X	Frequency range: 8.2 to 12.4 GHz	
	Y	Frequency range: 325 to 500 GHz	

frequency_band in Radio_Occultation_Support

Name: frequency_band			Version Id: 1.0.0.0
<i>Description:</i> frequency_band is the one or two letter identifier of the frequency band. Required in labels for radio occultations; not used for stellar occultations. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	C	Frequency range: 5.85 to 8.20 GHz	
	D	Frequency range: 2.20 to 3.30 GHz	
	E	Frequency range: 3.30 to 4.90 GHz	
	F	Frequency range: 4.90 to 7.05 GHz	
	G	Frequency range: 3.95 to 5.85 GHz	
	H	Frequency range: 7.05 to 10.10 GHz	
	K	Frequency range: 5.0 to 26.5 GHz	
	Ka	Frequency range: 26.5 to 40.0 GHz	
	Ku	Frequency range: 12.4 to 18.0 GHz	
	Q	Frequency range: 33 to 50 GHz	
	R	Frequency range: 1.70 to 2.60 GHz	
	S	Frequency range: 2.60 to 3.95 GHz	
	U	Frequency range: 40 to 60 GHz	
	V	Frequency range: 50 to 75 GHz	
	W	Frequency range: 75 to 110 GHz	
	X	Frequency range: 8.2 to 12.4 GHz	
	Y	Frequency range: 325 to 500 GHz	

highest_detectable_opacity in Radio_Occultation

Name: highest_detectable_opacity		Version Id: 1.0.0.0
<i>Description:</i> highest_detectable_opacity indicates the sensitivity of a ring occultation data set to nearly opaque rings. It specifies the rough value for the largest normal ring opacity that can be detected in the data at the resolution provided, incorporating both statistical effects and calibration uncertainties. Strongly recommended in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.		

Name: highest_detectable_opacity			Version Id: 1.0.0.0
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

highest_detectable_opacity in Stellar_ Occultation

Name: highest_detectable_opacity			Version Id: 1.0.0.0
<i>Description:</i> highest_detectable_opacity indicates the sensitivity of a ring occultation data set to nearly opaque rings. It specifies the rough value for the largest normal ring opacity that can be detected in the data at the resolution provided, incorporating both statistical effects and calibration uncertainties. Strongly recommended in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

light_source_incidence_angle in Radio_ Occultation

Name: light_source_incidence_angle			Version Id: 1.0.0.0
<i>Description:</i> light_source_incidence_angle is an angle measured from the local surface normal vector to the direction of a photon arriving from the light source. For rings, the normal vector is that on the same side of the rings as the light source, so values always range between 0 and 90 in units of degrees. The value is always equal to $90 - \text{observed_ring_elevation} $. This will enable users to perform database searches based on the effective ring opening angle when they are not concerned about the the distinction between north-side and southside viewpoints. We have included the 'light source' prefix to the term so that this quantity is not confused with 'incidence angle', a term that is generally associated with sunlight rather than stars or radio transmitters. Required in the label if the value is constant for the observation. If the angle varies for the observation, the min and max attributes are required in the label. Optional as a field in the data table. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: light_source_incidence_angle			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

light_source_incidence_angle in Stellar Occultation

Name: light_source_incidence_angle			Version Id: 1.0.0.0
<i>Description:</i> light_source_incidence_angle is an angle measured from the local surface normal vector to the direction of a photon arriving from the light source. For rings, the normal vector is that on the same side of the rings as the light source, so values always range between 0 and 90 in units of degrees. The value is always equal to $90 - \text{observed_ring_elevation} $. This will enable users to perform database searches based on the effective ring opening angle when they are not concerned about the the distinction between north-side and southside viewpoints. We have included the 'light source' prefix to the term so that this quantity is not confused with 'incidence angle', a term that is generally associated with sunlight rather than stars or radio transmitters. Required in the label if the value is constant for the observation. If the angle varies for the observation, the min and max attributes are required in the label. Optional as a field in the data table. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lowest_detectable_opacity in Radio Occultation

Name: lowest_detectable_opacity			Version Id: 1.0.0.0
<i>Description:</i> lowest_detectable_opacity indicates the sensitivity of a ring occultation data set to nearly opaque rings. It specifies the rough value for the smallest normal ring opacity that can be detected in the data at the resolution provided, incorporating both statistical effects and calibration uncertainties. Strongly recommended in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

lowest_detectable_opacity in Stellar_ Occultation

Name: lowest_detectable_opacity			Version Id: 1.0.0.0
<i>Description:</i> lowest_detectable_opacity indicates the sensitivity of a ring occultation data set to nearly opaque rings. It specifies the rough value for the smallest normal ring opacity that can be detected in the data at the resolution provided, incorporating both statistical effects and calibration uncertainties. Strongly recommended in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_light_source_incidence_angle in Radio_Occultation

Name: maximum_light_source_incidence_angle			Version Id: 1.0.0.0
<i>Description:</i> maximum_light_source_incidence_angle specifies the largest value for observed_ring_elevation in the observation. Only used if the value is not constant over the observation. Values range from 0 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_observed_event_time in Radio_ Occultation_Support

Name: maximum_observed_event_time			Version Id: 1.0.0.0
<i>Description:</i> maximum_observed_event_time indicates the value for latest time in the described data, and is given in observed_event_tdb format.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation_Support	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: maximum_observed_event_time			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_observed_ring_azimuth in Radio_Occultation

Name: maximum_observed_ring_azimuth			Version Id: 1.0.0.0
<i>Description:</i> maximum_observed_ring_azimuth specifies the largest value for observed_ring_azimuth in the data file. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_observed_ring_azimuth in Stellar_Occultation

Name: maximum_observed_ring_azimuth			Version Id: 1.0.0.0
<i>Description:</i> maximum_observed_ring_azimuth specifies the largest value for observed_ring_azimuth in the data file. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

maximum_observed_ring_elevation in Radio_Occultation

Name: maximum_observed_ring_elevation			Version Id: 1.0.0.0
<i>Description:</i> maximum_observed_ring_elevation specifies the largest value for observed_ring_elevation in the data file. Only used if the value is not constant over the			

Name: maximum_observed_ring_elevation			Version Id: 1.0.0.0
observation. Values range from -90 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_observed_ring_elevation in Stellar_Occultation

Name: maximum_observed_ring_elevation			Version Id: 1.0.0.0
<i>Description:</i> maximum_observed_ring_elevation specifies the largest value for observed_ring_elevation in the data file. Only used if the value is not constant over the observation. Values range from -90 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_radial_sampling_interval in Radio_Occultation

Name: maximum_radial_sampling_interval			Version Id: 1.0.0.0
<i>Description:</i> maximum_radial_sampling_interval indicates the smallest radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. If the value of radial_sampling_interval varies, the minimum and maximum attributes are required in labels. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_radial_sampling_interval in Stellar_Occultation

Name: maximum_radial_sampling_interval			Version Id: 1.0.0.0
<i>Description:</i> maximum_radial_sampling_interval indicates the smallest radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. If the value of radial_sampling_interval varies, the minimum and maximum attributes are required in labels. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_ring_longitude in Radio_Occultation

Name: maximum_ring_longitude			Version Id: 1.0.0.0
<i>Description:</i> maximum_ring_longitude specifies one boundary for the ring longitude range in the data; normally the largest value. However, for ranges that cross the prime meridian, the maximum ring longitude will have a value less than the minimum ring longitude. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_ring_longitude in Stellar_Occultation

Name: maximum_ring_longitude			Version Id: 1.0.0.0
<i>Description:</i> maximum_ring_longitude specifies one boundary for the ring longitude range in the data; normally the largest value. However, for ranges that cross the prime meridian, the maximum ring longitude will have a value less than the minimum ring longitude. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			

Name: maximum_ring_longitude			Version Id: 1.0.0.0
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_ring_radius in Radio_Occultation

Name: maximum_ring_radius			Version Id: 1.0.0.0
<i>Description:</i> maximum_ring_radius indicates the largest ring radius value in the data table. Units are km and are always positive. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_ring_radius in Stellar_Occultation

Name: maximum_ring_radius			Version Id: 1.0.0.0
<i>Description:</i> maximum_ring_radius indicates the largest ring radius value in the data table. Units are km and are always positive. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_wavelength in Radio_Occultation

Name: maximum_wavelength			Version Id: 1.0.0.0
<i>Description:</i> maximum_wavelength is the largest wavelength used in the observation. Optional in labels. Used with minimum_wavelength when the observation is over a wavelength range. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real

Name: maximum_wavelength			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

maximum_wavelength in Stellar_Occultation

Name: maximum_wavelength			Version Id: 1.0.0.0
<i>Description:</i> maximum_wavelength is the largest wavelength used in the observation. Optional in labels. Used with minimum_wavelength when the observation is over a wavelength range. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_light_source_incidence_angle in Radio_Occultation

Name: minimum_light_source_incidence_angle			Version Id: 1.0.0.0
<i>Description:</i> minimum_light_source_incidence_angle specifies the smallest value for observed_ring_elevation in the observation. Only used if the value is not constant over the observation. Values range from 0 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_observed_event_time in Radio_Occultation_Support

Name: minimum_observed_event_time			Version Id: 1.0.0.0
<i>Description:</i> minimum_observed_event_time indicates the value for earliest time in the described data, and is given in observed_event_tdb format.			

Name: minimum_observed_event_time			Version Id: 1.0.0.0
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_observed_ring_azimuth in Radio_Occultation

Name: minimum_observed_ring_azimuth			Version Id: 1.0.0.0
<i>Description:</i> minimum_observed_ring_azimuth specifies the smallest value for observed_ring_azimuth in the data file. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_observed_ring_azimuth in Stellar_Occultation

Name: minimum_observed_ring_azimuth			Version Id: 1.0.0.0
<i>Description:</i> minimum_observed_ring_azimuth specifies the smallest value for observed_ring_azimuth in the data file. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_observed_ring_elevation in Radio_Occultation

Name: minimum_observed_ring_elevation			Version Id: 1.0.0.0
<i>Description:</i> minimum_observed_ring_elevation specifies the smallest value for observed_ring_elevation in the data file. Only used if the value is not constant over the observation. Values range from -90 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_observed_ring_elevation in Stellar_Occultation

Name: minimum_observed_ring_elevation			Version Id: 1.0.0.0
<i>Description:</i> minimum_observed_ring_elevation specifies the smallest value for observed_ring_elevation in the data file. Only used if the value is not constant over the observation. Values range from -90 to +90 in units of degrees. Not intended for use in the data file. Nillable, in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> -90	<i>Maximum Value:</i> 90	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_radial_sampling_interval in Radio_Occultation

Name: minimum_radial_sampling_interval			Version Id: 1.0.0.0
<i>Description:</i> minimum_radial_sampling_interval indicates the smallest radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. If the value of radial_sampling_interval varies, the minimum and maximum attributes are required in labels. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real

Name: minimum_radial_sampling_interval			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_radial_sampling_interval in Stellar_Occultation

Name: minimum_radial_sampling_interval			Version Id: 1.0.0.0
<i>Description:</i> minimum_radial_sampling_interval indicates the smallest radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. If the value of radial_sampling_interval varies, the minimum and maximum attributes are required in labels. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_ring_longitude in Radio_Occultation

Name: minimum_ring_longitude			Version Id: 1.0.0.0
<i>Description:</i> minimum_ring_longitude specifies one boundary for the ring longitude range in the data; normally the smallest value. However, for ranges that cross the prime meridian, the minimum ring longitude will have a value greater than the maximum ring longitude. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

minimum_ring_longitude in Stellar_Occultation

Name: minimum_ring_longitude			Version Id: 1.0.0.0
<i>Description:</i> minimum_ring_longitude specifies one boundary for the ring longitude range in the data; normally the smallest value. However, for ranges that cross the prime meridian, the minimum ring longitude will have a value greater than the maximum ring longitude. Values range from 0 to 360 in units of degrees. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> 360	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_ring_radius in Radio_Occultation

Name: minimum_ring_radius			Version Id: 1.0.0.0
<i>Description:</i> minimum_ring_radius indicates the smallest ring radius value in the data table. Units are km and are always positive. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_ring_radius in Stellar_Occultation

Name: minimum_ring_radius			Version Id: 1.0.0.0
<i>Description:</i> minimum_ring_radius indicates the smallest ring radius value in the data table. Units are km and are always positive. Required in label files for ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_wavelength in Radio_Occultation

Name: minimum_wavelength			Version Id: 1.0.0.0
<i>Description:</i> minimum_wavelength is the smallest wavelength used in the observation. Optional in labels. Used with maximum_wavelength when the observation is over a wavelength range. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

minimum_wavelength in Stellar_Occultation

Name: minimum_wavelength			Version Id: 1.0.0.0
<i>Description:</i> minimum_wavelength is the smallest wavelength used in the observation. Optional in labels. Used with maximum_wavelength when the observation is over a wavelength range. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

observed_event_start_tdb in Radio_Occultation

Name: observed_event_start_tdb			Version Id: 1.0.0.0
<i>Description:</i> observed_event_start_tdb indicates the value for earliest time in the described data, and is given in observed_event_tdb format. Optional in labels; not intended for use as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

observed_event_start_tdb in Stellar_ Occultation

Name: observed_event_start_tdb			Version Id: 1.0.0.0
<i>Description:</i> observed_event_start_tdb indicates the value for earliest time in the described data, and is given in observed_event_tdb format. Optional in labels; not intended for use as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

observed_event_stop_tdb in Radio_ Occultation

Name: observed_event_stop_tdb			Version Id: 1.0.0.0
<i>Description:</i> observed_event_stop_tdb indicates the value for latest time in the described data, and is given in observed_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

observed_event_stop_tdb in Stellar_ Occultation

Name: observed_event_stop_tdb			Version Id: 1.0.0.0
<i>Description:</i> observed_event_stop_tdb indicates the value for latest time in the described data, and is given in observed_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None

Name: observed_event_stop_tdb		Version Id: 1.0.0.0
Status: Active	Nillable: false	Pattern: None
Permissible Value(s)	No Values	

observed_ring_elevation in Radio_ Occultation

Name: observed_ring_elevation		Version Id: 1.0.0.0	
<p><i>Description:</i> observed_ring_elevation is an angle measured at a point in the ring plane, starting from the ring plane to the direction of a photon heading to the observer. This angle is positive on the side of the ring plane defined by positive angular momentum, and negative on the opposite side. Values range from -90 to +90 in units of degrees. This angle is constant for stellar occultations, but may vary significantly during radio occultations. Note: The direction of positive angular momentum points toward the IAU-defined north side of the ring plane for Jupiter, Saturn and Neptune, but IAU-defined south side of the ring plane for Uranus. Required in the label if the value is constant for the observation. If the angle varies for the observation, the min and max attributes are required in the label, and observed_ring_elevation is strongly recommended as a field in the data table. Nillable, in which case the nil_reason should be 'inapplicable'. The above definition of observed_ring_elevation is equivalent to the most common usage of the term 'ring open angle', B.</p>			
Namespace Id: rings	Steward: rings	Class Name: Radio_ Occultation	Type: ASCII_Real
Minimum Value: -90	Maximum Value: 90	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Angle	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

observed_ring_elevation in Stellar_ Occultation

Name: observed_ring_elevation		Version Id: 1.0.0.0	
<p><i>Description:</i> observed_ring_elevation is an angle measured at a point in the ring plane, starting from the ring plane to the direction of a photon heading to the observer. This angle is positive on the side of the ring plane defined by positive angular momentum, and negative on the opposite side. Values range from -90 to +90 in units of degrees. This angle is constant for stellar occultations, but may vary significantly during radio occultations. Note: The direction of positive angular momentum points toward the IAU-defined north side of the ring plane for Jupiter, Saturn and Neptune, but IAU-defined south side of the ring plane for Uranus. Required in the label if the value is constant for the observation. If the angle varies for the observation, the min and max attributes are required in the label, and observed_ring_elevation is strongly recommended as a field in the data table. Nillable, in which case the nil_reason should be 'inapplicable'. The above definition of observed_ring_elevation is equivalent to the most common usage of the term 'ring open angle', B.</p>			
Namespace Id: rings	Steward: rings	Class Name: Stellar_ Occultation	Type: ASCII_Real
Minimum Value: -90	Maximum Value: 90	Minimum Characters: None	Maximum Characters: None

Name: observed_ring_elevation			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> Units_of_Angle	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

occultation_type in Radio_Occultation

Name: occultation_type			Version Id: 1.0.0.0
<i>Description:</i> occultation_type distinguishes between three types of occultation experiments: Stellar, Solar, and Radio. Stellar occultations involve observing a star as a targeted ring or body passes in front, as seen from either a spacecraft or Earth-based observatory. Solar occultations are similar to stellar occultations except that the Sun is used in place of a star. Radio occultations typically involve observing the continuous-wave radio transmissions from a spacecraft as it passes behind the target as seen from a radio telescope on Earth or another spacecraft. Required in labels of occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Radio	Radio occultation	
	Solar	Solar occultation	
	Stellar	Stellar occultation	

occultation_type in Radio_Occultation_Support

Name: occultation_type			Version Id: 1.0.0.0
<i>Description:</i> occultation_type distinguishes between three types of occultation experiments: Stellar, Solar, and Radio. Stellar occultations involve observing a star as a targeted ring or body passes in front, as seen from either a spacecraft or Earth-based observatory. Solar occultations are similar to stellar occultations except that the Sun is used in place of a star. Radio occultations typically involve observing the continuous-wave radio transmissions from a spacecraft as it passes behind the target as seen from a radio telescope on Earth or another spacecraft. Required in labels of occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: occultation_type		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	Radio	Radio occultation
	Solar	Solar occultation
	Stellar	Stellar occultation

occultation_type in Stellar_Occultation

Name: occultation_type		Version Id: 1.0.0.0	
<i>Description:</i> occultation_type distinguishes between three types of occultation experiments: Stellar, Solar, and Radio. Stellar occultations involve observing a star as a targeted ring or body passes in front, as seen from either a spacecraft or Earth-based observatory. Solar occultations are similar to stellar occultations except that the Sun is used in place of a star. Radio occultations typically involve observing the continuous-wave radio transmissions from a spacecraft as it passes behind the target as seen from a radio telescope on Earth or another spacecraft. Required in labels of occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Radio	Radio occultation	
	Solar	Solar occultation	
	Stellar	Stellar occultation	

orbit_number in Radio_Occultation

Name: orbit_number		Version Id: 1.0.0.0	
<i>Description:</i> orbit_number if present is the value assigned by the mission for the orbit number associated with the observation. Optional in labels of occultation observations and may be used multiple times. Nillable, the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

orbit_number in Radio_Occultation_Support

Name: orbit_number			Version Id: 1.0.0.0
<i>Description:</i> orbit_number if present is the value assigned by the mission for the orbit number associated with the observation. Optional in labels of occultation observations and may be used multiple times. Nillable, the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

orbit_number in Stellar_Occultation

Name: orbit_number			Version Id: 1.0.0.0
<i>Description:</i> orbit_number if present is the value assigned by the mission for the orbit number associated with the observation. Optional in labels of occultation observations and may be used multiple times. Nillable, the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

planetary_occultation_flag in Radio_Occultation

Name: planetary_occultation_flag			Version Id: 1.0.0.0
<i>Description:</i> The planetary_occultation_flag is a yes-or-no flag that indicates whether a ring occultation track also intersects the planet. Required in labels of ring occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 1
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: planetary_occultation_flag		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	N	The ring occultation track does not intersect the planet.
	Y	Some portion of the ring occultation track also intersects the planet.

planetary_occultation_flag in Radio_Occultation_Support

Name: planetary_occultation_flag		Version Id: 1.0.0.0	
<i>Description:</i> The planetary_occultation_flag is a yes-or-no flag that indicates whether a ring occultation track also intersects the planet. Required in labels of ring occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 1
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	N	The ring occultation track does not intersect the planet.	
	Y	Some portion of the ring occultation track also intersects the planet.	

planetary_occultation_flag in Stellar_Occultation

Name: planetary_occultation_flag		Version Id: 1.0.0.0	
<i>Description:</i> The planetary_occultation_flag is a yes-or-no flag that indicates whether a ring occultation track also intersects the planet. Required in labels of ring occultation observations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'. Normally not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 1
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	N	The ring occultation track does not intersect the planet.	

Name: planetary_occultation_flag		Version Id: 1.0.0.0
	Y	Some portion of the ring occultation track also intersects the planet.

radial_resolution in Radio_Occultation

Name: radial_resolution		Version Id: 1.0.0.0	
<i>Description:</i> radial_resolution indicates the nominal radial distance over which changes in ring properties can be detected within a data product. Note: this value may be larger than the radial_sampling_interval value, because a data product can be over-sampled. Required in labels if the value is fixed, as it is for stellar occultations. If the value varies, the corresponding minimum and maximum attributes must be used instead. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

radial_resolution in Stellar_Occultation

Name: radial_resolution		Version Id: 1.0.0.0	
<i>Description:</i> radial_resolution indicates the nominal radial distance over which changes in ring properties can be detected within a data product. Note: this value may be larger than the radial_sampling_interval value, because a data product can be over-sampled. Required in labels if the value is fixed, as it is for stellar occultations. If the value varies, the corresponding minimum and maximum attributes must be used instead. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

radial_sampling_interval in Radio_Occultation

Name: radial_sampling_interval		Version Id: 1.0.0.0
<i>Description:</i> radial_sampling_interval indicates the radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. Required in labels if the value is fixed. If the value varies, the corresponding minimum and and maximum attributes must be used instead. Nillable if the observation is not a		

Name: radial_sampling_interval			Version Id: 1.0.0.0
ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

radial_sampling_interval in Stellar Occultation

Name: radial_sampling_interval			Version Id: 1.0.0.0
<i>Description:</i> radial_sampling_interval indicates the radial spacing between consecutive points in a ring profile. In practice, this may be somewhat smaller than the radial_resolution because a profile may be over-sampled. Required in labels if the value is fixed. If the value varies, the corresponding minimum and and maximum attributes must be used instead. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended to be used as a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Length	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

reference_time_utc in Radio Occultation

Name: reference_time_utc			Version Id: 1.0.0.0
<i>Description:</i> reference_time_utc provides a date and time in UTC format. Given in a label when time values in a table are given as elapsed seconds offset from a reference time. Specifically required in the label for radio occultation data, but is not used for stellar occultation data. Required in the label for radio occultation data, or anytime spacecraft_event_time is a table field. Not used for stellar occultations. Nillable, the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

reference_time_utc in Radio_Occultation_Support

Name: reference_time_utc			Version Id: 1.0.0.0
<i>Description:</i> reference_time_utc provides a date and time in UTC format. Given in a label when time values in a table are given as elapsed seconds offset from a reference time. Specifically required in the label for radio occultation data, but is not used for stellar occultation data. Required in the label for radio occultation data, or anytime spacecraft_event_time is a table field. Not used for stellar occultations. Nillable, the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_event_start_tdb in Radio_Occultation

Name: ring_event_start_tdb			Version Id: 1.0.0.0
<i>Description:</i> ring_event_start_tdb indicates the value for earliest time in the described data, and is given in ring_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_event_start_tdb in Stellar_Occultation

Name: ring_event_start_tdb			Version Id: 1.0.0.0
<i>Description:</i> ring_event_start_tdb indicates the value for earliest time in the described data, and is given in ring_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_event_start_time_utc in Radio_Occultation

Name: ring_event_start_time_utc		Version Id: 1.0.0.0	
<i>Description:</i> ring_event_start_time_utc gives the UTC time corresponding to the earliest time given by ring_event_time or ring_event_tdb in the data table. ring_event_start_time_utc is required for all ring occultation data. ring_event_start_time_utc is required label attribute for all ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_event_start_time_utc in Stellar_Occultation

Name: ring_event_start_time_utc		Version Id: 1.0.0.0	
<i>Description:</i> ring_event_start_time_utc gives the UTC time corresponding to the earliest time given by ring_event_time or ring_event_tdb in the data table. ring_event_start_time_utc is required for all ring occultation data. ring_event_start_time_utc is required label attribute for all ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_event_stop_tdb in Radio_Occultation

Name: ring_event_stop_tdb		Version Id: 1.0.0.0	
<i>Description:</i> ring_event_stop_tdb indicates the value for latest time in the described data, and is given in ring_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None

Name: ring_event_stop_tdb			Version Id: 1.0.0.0
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

ring_event_stop_tdb in Stellar_Occultation

Name: ring_event_stop_tdb			Version Id: 1.0.0.0
<i>Description:</i> ring_event_stop_tdb indicates the value for latest time in the described data, and is given in ring_event_tdb format. Optional in labels; not intended for use as a table field. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_ Occultation	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

ring_event_stop_time_utc in Radio_Occultation

Name: ring_event_stop_time_utc			Version Id: 1.0.0.0
<i>Description:</i> ring_event_stop_time_utc gives the UTC time corresponding to the latest time given by ring_event_time or ring_event_tdb in the data table. ring_event_stop_time_utc is required for all ring occultation data. ring_event_stop_time_utc is required label attribute for all ring occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Date_ Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

ring_event_stop_time_utc in Stellar_Occultation

Name: ring_event_stop_time_utc			Version Id: 1.0.0.0
<i>Description:</i> ring_event_stop_time_utc gives the UTC time corresponding to the latest time given by ring_event_time or ring_event_tdb in the data table. ring_event_stop_time_utc is required for all ring occultation data. ring_event_stop_time_utc is required label attribute for all ring			

Name: ring_event_stop_time_utc			Version Id: 1.0.0.0
occultation data. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_observation_id in Radio_Occultation

Name: ring_observation_id			Version Id: 1.0.0.0
<i>Description:</i> The ring_observation_id uniquely identifies a single experiment or observation (image, occultation profile, spectrum, etc.) within a rings-related data set. This is the common id by which data are identified within the Rings Node catalog. It describes the smallest quantity of data that can be usefully cataloged or analyzed by itself. Note that a single observation may be associated with multiple data products (e.g. raw and calibrated versions of an image). Note also that a single data product may be associated with multiple observations (e.g. a single WFPC2 image file containing four different images). A ring observation id is constructed using numbers, upper case letters, forward slash, colon, period, dash, and underscore as follows: p/type/host/inst/time/... where p is a single-letter planet id (one of J, S, U, or N); type is IMG for images, OCC for occultation profile, etc.; host is the instrument host id, inst is the instrument id; time is the observation time as a date or instrument clock count; further information identifying the observation can then be appended as appropriate. Optional in labels. Nillable, in which case the nil_reason should be 'inapplicable'. Examples: J/IMG/VG2/ISS/20693.01/N J/IMG/VG2/ISS/20693.02/W S/IMG/HST/WFPC2/1995-08-10/U2TF020B/PC1 U/OCC/VG2/RSS/1986-01-24/S U/OCC/VG2/RSS/1986-01-24/X N/OCC/VG2/PPS/1989-08-25/SIGMA_SGR			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_observation_id in Radio_Occultation_Support

Name: ring_observation_id			Version Id: 1.0.0.0
<i>Description:</i> The ring_observation_id uniquely identifies a single experiment or observation (image, occultation profile, spectrum, etc.) within a rings-related data set. This is the common id by which data are identified within the Rings Node catalog. It describes the smallest quantity of data that can be usefully cataloged or analyzed by itself. Note that a single observation may be associated with multiple data products (e.g. raw and calibrated versions of an image). Note also that a single data product may be associated with multiple observations (e.g. a single WFPC2 image file containing four different images). A ring observation id is constructed using numbers,			

Name: ring_observation_id		Version Id: 1.0.0.0	
<p>upper case letters, forward slash, colon, period, dash, and underscore as follows: p/type/host/inst/time/... where p is a single-letter planet id (one of J, S, U, or N); type is IMG for images, OCC for occultation profile, etc.; host is the instrument host id, inst is the instrument id; time is the observation time as a date or instrument clock count; further information identifying the observation can then be appended as appropriate. Optional in labels. Nillable, in which case the nil_reason should be 'inapplicable'. Examples: J/IMG/VG2/ISS/20693.01/N J/IMG/VG2/ISS/20693.02/W S/IMG/HST/WFPC2/1995-08-10/U2TF020B/PC1 U/OCC/VG2/RSS/1986-01-24/S U/OCC/VG2/RSS/1986-01-24/X N/OCC/VG2/PPS/1989-08-25/SIGMA_SGR</p>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_observation_id in Rings_Supplement

Name: ring_observation_id		Version Id: 1.0.0.0	
<p><i>Description:</i> The ring_observation_id uniquely identifies a single experiment or observation (image, occultation profile, spectrum, etc.) within a rings-related data set. This is the common id by which data are identified within the Rings Node catalog. It describes the smallest quantity of data that can be usefully cataloged or analyzed by itself. Note that a single observation may be associated with multiple data products (e.g. raw and calibrated versions of an image). Note also that a single data product may be associated with multiple observations (e.g. a single WFPC2 image file containing four different images). A ring observation id is constructed using numbers, upper case letters, forward slash, colon, period, dash, and underscore as follows: p/type/host/inst/time/... where p is a single-letter planet id (one of J, S, U, or N); type is IMG for images, OCC for occultation profile, etc.; host is the instrument host id, inst is the instrument id; time is the observation time as a date or instrument clock count; further information identifying the observation can then be appended as appropriate. Optional in labels. Nillable, in which case the nil_reason should be 'inapplicable'. Examples: J/IMG/VG2/ISS/20693.01/N J/IMG/VG2/ISS/20693.02/W S/IMG/HST/WFPC2/1995-08-10/U2TF020B/PC1 U/OCC/VG2/RSS/1986-01-24/S U/OCC/VG2/RSS/1986-01-24/X N/OCC/VG2/PPS/1989-08-25/SIGMA_SGR</p>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Rings_Supplement	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_observation_id in Stellar_Occultation

Name: ring_observation_id		Version Id: 1.0.0.0	
<p><i>Description:</i> The ring_observation_id uniquely identifies a single experiment or observation (image, occultation profile, spectrum, etc.) within a rings-related data set. This is the common id by which data are identified within the Rings Node catalog. It describes the smallest quantity of</p>			

Name: ring_observation_id		Version Id: 1.0.0.0	
<p>data that can be usefully cataloged or analyzed by itself. Note that a single observation may be associated with multiple data products (e.g. raw and calibrated versions of an image). Note also that a single data product may be associated with multiple observations (e.g. a single WFPC2 image file containing four different images). A ring observation id is constructed using numbers, upper case letters, forward slash, colon, period, dash, and underscore as follows: p/type/host/inst/time/... where p is a single-letter planet id (one of J, S, U, or N); type is IMG for images, OCC for occultation profile, etc.; host is the instrument host id, inst is the instrument id; time is the observation time as a date or instrument clock count; further information identifying the observation can then be appended as appropriate. Optional in labels. Nillable, in which case the nil_reason should be 'inapplicable'. Examples: J/IMG/VG2/ISS/20693.01/N J/IMG/VG2/ISS/20693.02/W S/IMG/HST/WFPC2/1995-08-10/U2TF020B/PC1 U/OCC/VG2/RSS/1986-01-24/S U/OCC/VG2/RSS/1986-01-24/X N/OCC/VG2/PPS/1989-08-25/SIGMA_SGR</p>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

ring_occultation_direction in Radio Occultation

Name: ring_occultation_direction		Version Id: 1.0.0.0	
<p><i>Description:</i> ring_occultation_direction indicates the radial direction of an occultation track. This refers to the observed occultation track overall, not to the subset that might appear in a particular file. Permitted values are 'Ingress', 'Egress', 'Both', and 'Multiple'. The value 'multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.</p>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Both	The ring radius along the a portion of the occultation track decreases with time, and along a different portion increases with time.	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	

Name: ring_occultation_direction		Version Id: 1.0.0.0
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.

ring_occultation_direction in Radio_Occultation_Support

Name: ring_occultation_direction		Version Id: 1.0.0.0	
<i>Description:</i> ring_occultation_direction indicates the radial direction of an occultation track. This refers to the observed occultation track overall, not to the subset that might appear in a particular file. Permitted values are 'Ingress', 'Egress', 'Both', and 'Multiple'. The value 'multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Both	The ring radius along the a portion of the occultation track decreases with time, and along a different portion increases with time.	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.	

ring_occultation_direction in Stellar_Occultation

Name: ring_occultation_direction		Version Id: 1.0.0.0	
<i>Description:</i> ring_occultation_direction indicates the radial direction of an occultation track. This refers to the observed occultation track overall, not to the subset that might appear in a particular file. Permitted values are 'Ingress', 'Egress', 'Both', and 'Multiple'. The value 'multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed

Name: ring_occultation_direction			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Both	The ring radius along the a portion of the occultation track decreases with time, and along a different portion increases with time.	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.	

ring_profile_direction in Radio_Occultation

Name: ring_profile_direction			Version Id: 1.0.0.0
<i>Description:</i> ring_profile_direction indicates the radial direction of a ring occultation within a particular data product. Possible values are 'Ingress', 'Egress', or 'Multiple'. The value 'Multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.	

ring_profile_direction in Radio_Occultation_Support

Name: ring_profile_direction		Version Id: 1.0.0.0	
<i>Description:</i> ring_profile_direction indicates the radial direction of a ring occultation within a particular data product. Possible values are 'Ingress', 'Egress', or 'Multiple'. The value 'Multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.	

ring_profile_direction in Stellar_Occultation

Name: ring_profile_direction		Version Id: 1.0.0.0	
<i>Description:</i> ring_profile_direction indicates the radial direction of a ring occultation within a particular data product. Possible values are 'Ingress', 'Egress', or 'Multiple'. The value 'Multiple' is only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales. Required in labels of ring occultation observations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not intended as a value for a table field.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Egress	The ring radius along the occultation track increases with time.	
	Ingress	The ring radius along the occultation track decreases with time.	

Name: ring_profile_direction		Version Id: 1.0.0.0
	Multiple	Only used for some Hubble-based occultations where the occultation track is not monotonic over relatively short time scales.

sampling_parameter_interval in Radio_Occultation_Support

Name: sampling_parameter_interval		Version Id: 1.0.0.0	
<i>Description:</i> sampling_parameter_interval specifies the spacing of points at which data are sampled and at which a value for an instrument or dataset parameter is available. Used in labels for radio occultation supplemental files. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sampling_parameter_name in Radio_Occultation_Support

Name: sampling_parameter_name		Version Id: 1.0.0.0	
<i>Description:</i> sampling_parameter_name provides the name of the parameter which determines the sampling interval for uniformly sampled data. Used in labels for radio occultation supplemental files. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sampling_parameter_unit in Radio_Occultation_Support

Name: sampling_parameter_unit		Version Id: 1.0.0.0	
<i>Description:</i> sampling_parameter_unit provides the units of the parameter which determines the sampling interval for uniformly sampled data. Used in labels for radio occultation supplemental files. Nillable in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed

Name: sampling_parameter_unit			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

source_pds3_id in Radio_Occultation

Name: source_pds3_id			Version Id: 1.0.0.0
<i>Description:</i> source_pds3_id is the PDS3 product identifier for the source product. If the source product has been archived under PDS4, use the Internal_Reference class in the Investigation_Area. source_pds3_id is required in occultation labels and may be used multiple times. The acceptable nil_reasons are 'inapplicable' and 'unknown'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_ Occultation	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

source_pds3_id in Rings_Supplement

Name: source_pds3_id			Version Id: 1.0.0.0
<i>Description:</i> source_pds3_id is the PDS3 product identifier for the source product. If the source product has been archived under PDS4, use the Internal_Reference class in the Investigation_Area. source_pds3_id is required in occultation labels and may be used multiple times. The acceptable nil_reasons are 'inapplicable' and 'unknown'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Rings_ Supplement	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

source_pds3_id in Stellar_Occultation

Name: source_pds3_id			Version Id: 1.0.0.0
<i>Description:</i> source_pds3_id is the PDS3 product identifier for the source product. If the source product has been archived under PDS4, use the Internal_Reference class in the Investigation_Area. source_pds3_id is required in occultation labels and may be used multiple times. The acceptable nil_reasons are 'inapplicable' and 'unknown'.			

Name: source_pds3_id			Version Id: 1.0.0.0
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

spacecraft_event_start_time_utc in Radio_Occultation

Name: spacecraft_event_start_time_utc			Version Id: 1.0.0.0
<i>Description:</i> spacecraft_event_start_time_utc gives the UTC time corresponding to the earliest time given by spacecraft_event_time in the data table. However, while spacecraft_event_time is given as seconds offset from a reference time, spacecraft_event_start_time_utc is given as a UTC date time. spacecraft_event_start_time_utc is required in the label for radio occultation data, but is not used for stellar occultation data. Required in the label for radio occultation data. Not used for stellar occultations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

spacecraft_event_stop_time_utc in Radio_Occultation

Name: spacecraft_event_stop_time_utc			Version Id: 1.0.0.0
<i>Description:</i> spacecraft_event_stop_time_utc gives the UTC time corresponding to the latest time given by spacecraft_event_time in the data table. However, while spacecraft_event_time is given as seconds offset from a reference time, spacecraft_event_stop_time_utc is given as a UTC date time. spacecraft_event_stop_time_utc is required in the label for radio occultation data, but is not used for stellar occultation data. Required in the label for radio occultation data. Not used for stellar occultations. Nillable if the observation is not an occultation in which case the nil_reason should be 'inapplicable'.			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation	<i>Type:</i> ASCII_Date_Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> true	<i>Pattern:</i> None	

Name: spacecraft_event_stop_time_utc		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

spice_filename in Radio_Occultation_Support

Name: spice_filename		Version Id: 1.0.0.0	
<i>Description: spice_filename gives the file name(s) of SPICE files used in the analysis. Only used if the SPICE files can not be identified using a LID or LIDVID. Otherwise the association is made in the Reference_Class using the Internal_Reference class. Optional in labels for radio occultation. Nillable in which case the nil_reason should be 'inapplicable'.</i>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Radio_Occultation_Support	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

star_name in Stellar_Occultation

Name: star_name		Version Id: 1.0.0.0	
<i>Description: star_name provides the identifying name of star, including the catalog name if necessary. Examples include 'sigma Sgr' and 'SAO 123456' (for star number 123456 in the Smithsonian Astrophysical Observatory catalog). Use 'Sun' for solar occultations. Required in labels for stellar and solar occultations. Nillable if the observation is not a ring occultation in which case the nil_reason should be 'inapplicable'. Not used for radio occultations.</i>			
<i>Namespace Id:</i> rings	<i>Steward:</i> rings	<i>Class Name:</i> Stellar_Occultation	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

sub_stellar_clock_angle in Stellar_Occultation

Name: sub_stellar_clock_angle		Version Id: 1.0.0.0	
<i>Description: sub_stellar_clock_angle is an angle measured at a point in the ring plane, from the direction toward a star to the local radial direction. This angle is projected into the ring plane and measured in the clockwise (retrograde) direction. Equivalently, this is the prograde angle from the local radial direction to the direction toward the star. For stellar occultation data, this angle is equal to (180 - OBSERVED_RING_AZIMUTH) mod 360. It is available only for backward compatibility with previously published Cassini VIMS occultation data analysis;</i>			

Name: sub_stellar_clock_angle		Version Id: 1.0.0.0	
observed_ring_azimuth is the preferred quantity for archiving. sub_stellar_clock_angle is an optional data table field for Cassini VIMS occultation data; not recommended for other occultation data. In a label, the min and max variation attributes are optional for Cassini VIMS occultation data; not recommended for other occultation data.			
Namespace Id: rings	Steward: rings	Class Name: Stellar_Occultation	Type: ASCII_Real
Minimum Value: 0	Maximum Value: 360	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Angle	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

sub_stellar_ring_azimuth in Stellar_Occultation

Name: sub_stellar_ring_azimuth		Version Id: 1.0.0.0	
<i>Description:</i> sub_stellar_ring_azimuth is an angle measured at a point in the ring plane, starting from the direction of a photon arriving from a star, and ending at the direction of a local radial vector. This angle is projected into the ring plane and measured in the prograde direction. Values range from 0 to 360 in units of degrees. For stellar occultation data, this angle is equal to (observed_ring_azimuth + 180) mod 360. It is available only for backward compatibility with previously published Cassini UVIS occultation data analysis; observed_ring_azimuth is the preferred quantity for archiving. sub_stellar_ring_azimuth is an optional data table field for Cassini UVIS occultation data; not recommended for other occultation data. In a label, the min and max variation attributes are optional for Cassini UVIS occultation data; not recommended for other occultation data.			
Namespace Id: rings	Steward: rings	Class Name: Stellar_Occultation	Type: ASCII_Real
Minimum Value: 0	Maximum Value: 360	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Angle	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None
Status: Active	Nillable: false	Pattern: None	
Permissible Value(s)	No Values		

wavelength in Radio_Occultation

Name: wavelength		Version Id: 1.0.0.0	
<i>Description:</i> wavelength of the observation. Optional in labels. If the observation is over a wavelength range, use the corresponding minimum and maximum attributes instead. Nillable in which case the nil_reason should be 'inapplicable'.			
Namespace Id: rings	Steward: rings	Class Name: Radio_Occultation	Type: ASCII_Real
Minimum Value: None	Maximum Value: None	Minimum Characters: None	Maximum Characters: None
Unit of Measure Type: Units_of_Length	Default Unit Id: None	Attribute Concept: None	Conceptual Domain: None

Name: wavelength		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>No Values</i>	

wavelength in Stellar_Occultation

Name: wavelength		Version Id: 1.0.0.0	
<i>Description: wavelength of the observation. Optional in labels. If the observation is over a wavelength range, use the corresponding minimum and maximum attributes instead. Nillable in which case the nil_reason should be 'inapplicable'.</i>			
<i>Namespace Id: rings</i>	<i>Steward: rings</i>	<i>Class Name: Stellar_Occultation</i>	<i>Type: ASCII_Real</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: Units_of_Length</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: None</i>	<i>Conceptual Domain: None</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

Chapter 10. Attributes in the Imaging discipline namespace.

These attributes are used by the classes defined for the Imaging namespace.

application_process_id in Telemetry_ Parameters

Name: application_process_id			Version Id: 1.0.0.0
<i>Description:</i> The application_process_id attribute identifies the process, or source, which created the data.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

application_process_name in Telemetry_ Parameters

Name: application_process_name			Version Id: 1.0.0.0
<i>Description:</i> The application_process_name attribute provides the name associated with the source or process which created the data.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 127
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

earth_received_start_date_time in Telemetry_ Parameters

Name: earth_received_start_date_time			Version Id: 1.0.0.0
<i>Description:</i> The earth_received_start_date_time attribute provides the earliest time at which any component telemetry data for a particular product was received.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Date_Time_UTC

Name: earth_received_start_date_time			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

earth_received_stop_date_time in Telemetry_Parameters

Name: earth_received_stop_date_time			Version Id: 1.0.0.0
<i>Description:</i> The earth_received_stop_date_time attribute provides the latest time at which any component telemetry data for a particular product was received.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Date_ Time_UTC
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Time	<i>Conceptual Domain:</i> Time
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

expected_packets in Telemetry_Parameters

Name: expected_packets			Version Id: 1.0.0.0
<i>Description:</i> The expected_packets attribute provides the total number of telemetry packets which constitute a complete data product, i.e., a data product without missing data.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

packet_map_mask in Telemetry_Parameters

Name: packet_map_mask			Version Id: 1.0.0.0
<i>Description:</i> The packet_map_mask attribute is a binary or hexadecimal number identifying which of a data file's expected packets were actually received. The digits correspond positionally with the relative packet numbers of the data file. The bits are to be read left to right; i.e., the first (left-most) digit of the number corresponds to the first packet of the data file. A bit value of 1 indicates that the packet was received; a value of 0 indicates that it was not received.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_ Numeric_Base16

Name: packet_map_mask			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Mask	<i>Conceptual Domain:</i> Numeric
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

received_packets in Telemetry_Parameters

Name: received_packets			Version Id: 1.0.0.0
<i>Description:</i> The received_packets attribute provides the total number of telemetry packets which constitute a reconstructed data product, cf. expected_packets.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Count	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

spice_file_name in Telemetry_Parameters

Name: spice_file_name			Version Id: 1.0.0.0
<i>Description:</i> The spice_file_name attribute provides the names of the SPICE files used in processing the data.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> Name	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	No Values		

telemetry_format_id in Telemetry_Parameters

Name: telemetry_format_id			Version Id: 1.0.0.0
<i>Description:</i> The telemetry_format_id attribute supplies a telemetry format code.			
<i>Namespace Id:</i> img	<i>Steward:</i> img	<i>Class Name:</i> Telemetry_Parameters	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 4
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> ID	<i>Conceptual Domain:</i> Short_String
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	

Name: telemetry_format_id		Version Id: 1.0.0.0
<i>Permissible Value(s)</i>	<i>No Values</i>	

telemetry_provider_id in Telemetry_ Parameters

Name: telemetry_provider_id		Version Id: 1.0.0.0	
<i>Description: The telemetry_provider_id attribute identifies the provider and or version of the telemetry data used in the generation of this data.</i>			
<i>Namespace Id: img</i>	<i>Steward: img</i>	<i>Class Name: Telemetry_Parameters</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: 20</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: ID</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

telemetry_source_name in Telemetry_ Parameters

Name: telemetry_source_name		Version Id: 1.0.0.0	
<i>Description: The telemetry_source_name attribute identifies the telemetry source used in creation of a data set.</i>			
<i>Namespace Id: img</i>	<i>Steward: img</i>	<i>Class Name: Telemetry_Parameters</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: 1</i>	<i>Maximum Characters: 60</i>
<i>Unit of Measure Type: None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Name</i>	<i>Conceptual Domain: Short_String</i>
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>	
<i>Permissible Value(s)</i>	<i>No Values</i>		

telemetry_source_type in Telemetry_ Parameters

Name: telemetry_source_type		Version Id: 1.0.0.0	
<i>Description: The telemetry_source_type attribute classifies the source of the telemetry used in creation of this data collection.</i>			
<i>Namespace Id: img</i>	<i>Steward: img</i>	<i>Class Name: Telemetry_Parameters</i>	<i>Type: ASCII_Short_String_Collapsed</i>
<i>Minimum Value: None</i>	<i>Maximum Value: None</i>	<i>Minimum Characters: None</i>	<i>Maximum Characters: None</i>
<i>Unit of Measure Type: Units_of_None</i>	<i>Default Unit Id: None</i>	<i>Attribute Concept: Type</i>	<i>Conceptual Domain: Short_String</i>

Attributes in the Imaging
discipline namespace.

Name: telemetry_source_type		Version Id: 1.0.0.0
<i>Status: Active</i>	<i>Nillable: false</i>	<i>Pattern: None</i>
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>
	DATA_PRODUCT	The telemetry source is a data product.
	SFDU	The telemetry source is an SFDU

Chapter 11. Attributes in the Display namespace.

These attributes are used by the classes defined for the Display namespace.

blue_channel_band in Color_Display_Settings

Name: blue_channel_band			Version Id: 1.0.0.0
<i>Description:</i> The blue_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by default, into the blue channel of a display device. The first band along the band axis has band number 1.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Color_Display_Settings	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

color_display_axis in Color_Display_Settings

Name: color_display_axis			Version Id: 1.0.0.0
<i>Description:</i> The color_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be displayed in the color dimension of a display device. I.e., bands from this dimension will be loaded into the red, green, and blue bands of the display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Color_Display_Settings	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nilable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

frame_rate in Movie_Display_Settings

Name: frame_rate			Version Id: 1.0.0.0
<i>Description:</i> The frame_rate attribute indicates the number of still pictures (or frames) that should be displayed per unit of time in a video. Note this is NOT necessarily the same as the rate at which the images were acquired.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Real

Name: frame_rate			Version Id: 1.0.0.0
<i>Minimum Value:</i> 1.0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Frame_Rate	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

green_channel_band in Color_Display_Settings

Name: green_channel_band			Version Id: 1.0.0.0
<i>Description:</i> The green_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by default, into the green channel of a display device. The first band along the band axis has band number 1.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Color_Display_Settings	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

horizontal_display_axis in Display_Direction

Name: horizontal_display_axis			Version Id: 1.0.0.0
<i>Description:</i> The horizontal_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be displayed in the horizontal or 'sample' dimension on a display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Display_Direction	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

horizontal_display_direction in Display_Direction

Name: horizontal_display_direction			Version Id: 1.0.0.0
<i>Description:</i> The horizontal_display_direction attribute specifies the direction across the screen of a display device that data along the horizontal axis of an Array is supposed to be displayed.			

Name: horizontal_display_direction			Version Id: 1.0.0.0
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Display_Direction	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Left to Right	The lowest indexed element along an array axis should be displayed at the left edge of a display device and elements with higher indices should be displayed further to the right. Note that this is the standard display direction for most major image formats.	
	Right to Left	The lowest indexed element along an array axis should be displayed at the right edge of a display device and elements with higher indices should be displayed further to the left. Note that virtually no image display formats use this display direction. Use this only when deliberately mirroring the image around the vertical axis.	

loop_back_and_forth_flag in Movie_Display_Settings

Name: loop_back_and_forth_flag			Version Id: 1.0.0.0
<i>Description:</i> The loop_back_and_forth_flag attribute specifies whether or not a movie should only be 'looped' or played repeatedly in the forward direction, or whether it should be played forward followed by played in reverse, iteratively.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	false	When looping, the movie should only be played in the forward direction. This is the default behavior.	
	true	When looping, the movie should be played in the forward direction, followed by the reverse direction, iteratively.	

loop_count in Movie_Display_Settings

Name: loop_count			Version Id: 1.0.0.0
<i>Description:</i> The loop_count attribute specifies the number of times a movie should be 'looped' or replayed before stopping.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

loop_delay in Movie_Display_Settings

Name: loop_delay			Version Id: 1.0.0.0
<i>Description:</i> The loop_delay attribute specifies the amount of time to pause between 'loops' or repeated playbacks of a movie.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Real
<i>Minimum Value:</i> 0.0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> Units_of_Time	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Real
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

loop_flag in Movie_Display_Settings

Name: loop_flag			Version Id: 1.0.0.0
<i>Description:</i> The loop_flag attribute specifies whether or not a movie object should be played repeatedly without prompting from the user.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Boolean
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Boolean
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	false	The movie should be not be 'looped' or played repeatedly.	
	true	The movie should be 'looped' or played repeatedly.	

red_channel_band in Color_Display_Settings

Name: red_channel_band			Version Id: 1.0.0.0
<i>Description:</i> The red_channel_band attribute identifies the number of the band, along the band axis, that should be loaded, by default, into the red channel of a display device. The first band along the band axis has band number 1.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Color_Display_Settings	<i>Type:</i> ASCII_Integer
<i>Minimum Value:</i> 1	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> Integer
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

time_display_axis in Movie_Display_Settings

Name: time_display_axis			Version Id: 1.0.0.0
<i>Description:</i> The time_display_axis attribute identifies, by name, the axis of an Array (or Array subclass), the bands of which are intended to be displayed sequentially in time on a display device. The frame_rate attribute, if present, provides the rate at which these bands are to be displayed.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Movie_Display_Settings	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

vertical_display_axis in Display_Direction

Name: vertical_display_axis			Version Id: 1.0.0.0
<i>Description:</i> The vertical_display_axis attribute identifies, by name, the axis of an Array (or Array subclass) that is intended to be displayed in the vertical or 'line' dimension on a display device. The value of this attribute must match the value of one, and only one, axis_name attribute in an Axis_Array class of the associated Array.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Display_Direction	<i>Type:</i> ASCII_Short_String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>No Values</i>		

vertical_display_direction in Display_ Direction

Name: vertical_display_direction			Version Id: 1.0.0.0
<i>Description:</i> The vertical_display_direction attribute specifies the direction along the screen of a display device that data along the vertical axis of an Array is supposed to be displayed.			
<i>Namespace Id:</i> disp	<i>Steward:</i> img	<i>Class Name:</i> Display_ Direction	<i>Type:</i> ASCII_Short_ String_Collapsed
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Unit of Measure Type:</i> None	<i>Default Unit Id:</i> None	<i>Attribute Concept:</i> None	<i>Conceptual Domain:</i> None
<i>Status:</i> Active	<i>Nillable:</i> false	<i>Pattern:</i> None	
<i>Permissible Value(s)</i>	<i>Value</i>	<i>Value Meaning</i>	
	Bottom to Top	The lowest indexed element along an array axis should be displayed at the bottom edge of a display device and elements with higher indices should be displayed higher up. This is the display direction typically used for FITS formatted data.	
	Top to Bottom	The lowest indexed element along an array axis should be displayed at the top edge of a display device and elements with higher indices should be displayed lower down. This is the display direction typically used for VICAR formatted data.	

Chapter 12. Data Types in the common (pds) namespace.

These classes define the PDS4 data types.

ASCII_AnyURI

Name: ASCII_AnyURI			Version Id: 1.0.0.0
<i>Description</i> The ASCII AnyURI class indicates a URI or its subclasses URN and URL.			
<i>Schema Base Type:</i> anyURI			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_Boolean

Name: ASCII_Boolean			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Boolean class indicates a boolean. The allowed values are 'true' and 'false'.			
<i>Schema Base Type:</i> boolean			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_DOI

Name: ASCII_DOI			Version Id: 1.0.0.0
<i>Description</i> The ASCII DOI class indicates a digital object identifier (DOI).			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
10\.\S+\S+			

ASCII_Date

Name: ASCII_Date			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Date class indicates a date in either YMD or DOY format.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			

Data Types in the
common (pds) namespace.

Name: ASCII_Date		Version Id: 1.0.0.0	
	(-)?[0-9]{4}		
	(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))		

ASCII_Date_DOY

Name: ASCII_Date_DOY		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_DOY class indicates a date in DOY format.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))			

ASCII_Date_Time

Name: ASCII_Date_Time		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_Time class indicates a date in either YMD or DOY format and time.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))(T)(([0-1][0-9]) (2[0-4]))(Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3((([0-5][0-9]) (6[0-6]))))))(T)24:00(:00(\.0+)?)?(Z)?			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?			

Name: ASCII_Date_Time		Version Id: 1.0.0.0	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-4]))(Z)?		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)24:00((:00(\.0+)?)?)(Z)?		

ASCII_Date_Time_DOY

Name: ASCII_Date_Time_DOY		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_Time_DOY class indicates a date in DOY format and time.			
<i>Schema Base Type:</i>			
string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:(([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-4]))(Z)?			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)24:00((:00(\.0+)?)?)(Z)?			

ASCII_Date_Time_UTC

Name: ASCII_Date_Time_UTC		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_Time_UTC class indicates a date and time in UTC format.			
<i>Schema Base Type:</i>			
string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}(Z)			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:(([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)(([0-1][0-9]) (2[0-4]))(Z)			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(T)24:00((:00(\.0+)?)?)(Z)			
(-)?[0-9]{4}-((00[1-9]) (0[1-9][0-9]) ([1-2][0-9][0-9]) (3([0-5][0-9]) (6[0-6]))))(Z)			

Name: ASCII_Date_Time_UTC		Version Id: 1.0.0.0	
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))(Z)		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-4]))(Z)		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)24:00(:00(\.0+)?)?(Z)		
	(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(Z)		

ASCII_Date_Time_YMD

Name: ASCII_Date_Time_YMD		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_Time_YMD class indicates a date in YMD format and time.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9](Z)?			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)\.([0-9]{1,4}))?(Z)?			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)(([0-1][0-9]) (2[0-4]))(Z)?			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))(T)24:00(:00(\.0+)?)?(Z)?			

ASCII_Date_YMD

Name: ASCII_Date_YMD		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Date_YMD class indicates a date in YMD format.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
(-)?[0-9]{4}			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))			
(-)?[0-9]{4}-((0[1-9]) (1[0-2]))-((0[1-9]) ([1-2][0-9]) (3[0-1]))			

ASCII_Directory_Path_Name

Name: ASCII_Directory_Path_Name		Version Id: 1.0.0.0	
<i>Description</i> The ASCII Directory Path Name class indicates a system directory path.			

Name: ASCII_Directory_Path_Name			Version Id: 1.0.0.0
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_File_Name

Name: ASCII_File_Name			Version Id: 1.0.0.0
<i>Description</i> The ASCII File Name class indicates a system file name.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_File_Specification_Name

Name: ASCII_File_Specification_Name			Version Id: 1.0.0.0
<i>Description</i> The ASCII File Specification Name class indicates a system file including directory path, file name, and file extension.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_Integer

Name: ASCII_Integer			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Integer class indicates an integer.			
<i>Schema Base Type:</i> int			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_LID

Name: ASCII_LID			Version Id: 1.0.0.0
<i>Description</i> The ASCII_LID class indicates a logical identifier.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 14	<i>Maximum Characters:</i> 255
<i>Pattern</i>			

Name: ASCII_LID	Version Id: 1.0.0.0

ASCII_LIDVID

Name: ASCII_LIDVID		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_LIDVID class indicates a logical identifier and version identifier.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 19	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_LIDVID_LID

Name: ASCII_LIDVID_LID		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_LIDVID_LID class indicates a logical identifier and version identifier or simply the logical identifier.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 14	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_MD5_Checksum

Name: ASCII_MD5_Checksum		Version Id: 1.0.0.0	
<i>Description</i> The ASCII MD5 Checksum class indicates a checksum computed by the Message-Digest algorithm 5 (MD5).			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 32	<i>Maximum Characters:</i> 32
<i>Pattern</i>			
[0-9a-fA-F]{32}			

ASCII_NonNegative_Integer

Name: ASCII_NonNegative_Integer		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_NonNegative_Integer class indicates a non-negative integer.			
<i>Schema Base Type:</i> long			
<i>Minimum Value:</i> 0	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_Numeric_Base16

Name: ASCII_Numeric_Base16			Version Id: 1.0.0.0
<i>Description</i> The ASCII Numeric Base16 class indicates a ASCII encoded string constrained to hexadecimal digits.			
<i>Schema Base Type:</i> hexBinary			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Pattern</i>			

ASCII_Numeric_Base2

Name: ASCII_Numeric_Base2			Version Id: 1.0.0.0
<i>Description</i> The ASCII Numeric Base2 class indicates a ASCII encoded string constrained to binary digits.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Pattern</i>			
[0-1]{1,255}			

ASCII_Numeric_Base8

Name: ASCII_Numeric_Base8			Version Id: 1.0.0.0
<i>Description</i> The ASCII Numeric Base8 class indicates a ASCII encoded string constrained to octal digits.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>Pattern</i>			
[0-7]{1,255}			

ASCII_Real

Name: ASCII_Real			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Real class indicates a real.			
<i>Schema Base Type:</i> double			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_Short_String_Collapsed

Name: ASCII_Short_String_Collapsed		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Short_String_Collapsed class indicates a limited length, whitespace-collapsed string.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_Short_String_Preserved

Name: ASCII_Short_String_Preserved		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Short_String_Preserved class indicates a limited length, whitespace-preserved string.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

ASCII_String

Name: ASCII_String		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_String class indicates a limited length ASCII text string with whitespaces removed.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_Text_Collapsed

Name: ASCII_Text_Collapsed		Version Id: 1.0.0.0	
<i>Description</i> The ASCII_Text_Collapsed class indicates an unlimited length, whitespace-collapsed text string.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ASCII_Text_Preserved

Name: ASCII_Text_Preserved			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Text_Preserved class indicates an unlimited length, whitespace-preserved text string.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>Pattern</i>			

ASCII_Time

Name: ASCII_Time			Version Id: 1.0.0.0
<i>Description</i> The ASCII_Time class indicates a time value.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			
((([0-1][0-9]) (2[0-3])):[0-5][0-9](Z))			
((([0-1][0-9]) (2[0-3])):[0-5][0-9]:((([0-5][0-9]) 60)((\.[0-9]+)))(Z))			
((([0-1][0-9]) (2[0-4]))(Z))			
24:00((:00((\.[0-9]+)))(Z))			

ASCII_VID

Name: ASCII_VID			Version Id: 1.0.0.0
<i>Description</i> The ASCII_VID class indicates a version identifier.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 3	<i>Maximum Characters:</i> 100
<i>Pattern</i>			
0\,([1-9] ([0-9][0-9]+))			
[1-9][0-9]*			
[1-9][0-9]*\.[0-9]+			

Binary_Data_Type

Name: Binary_Data_Type			Version Id: 1.0.0.0
<i>Description</i> The Binary Data Type class is the abstract parent class for binary data types found in the digital objects.			
<i>Schema Base Type:</i> None			

Name: Binary_Data_Type			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

Character_Data_Type

Name: Character_Data_Type			Version Id: 1.0.0.0
<i>Description</i> The Character Data Type class is the parent class for data types used to classify the values of attributes in class descriptions, i.e., product labels and character digital objects.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>Pattern</i>			

Complex

Name: Complex			Version Id: 1.0.0.0
<i>Description</i> Complex Binary Data Types			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ComplexLSB16

Name: ComplexLSB16			Version Id: 1.0.0.0
<i>Description</i> Complex number consisting of two LSB 8 byte decimal reals.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ComplexLSB8

Name: ComplexLSB8			Version Id: 1.0.0.0
<i>Description</i> Complex number consisting of two LSB 4 byte decimal reals.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ComplexMSB16

Name: ComplexMSB16			Version Id: 1.0.0.0
<i>Description</i> Complex number consisting of two MSB 8 byte decimal reals.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

ComplexMSB8

Name: ComplexMSB8			Version Id: 1.0.0.0
<i>Description</i> Complex number consisting of two MSB 4 byte decimal reals.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

Data_Type

Name: Data_Type			Version Id: 1.0.0.0
<i>Description</i> The Data Type class is the abstract parent class for several classes of data types.			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

Decimal_Integer

Name: Decimal_Integer			Version Id: 1.0.0.0
<i>Description</i> Decimal Integer Binary Data Types			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

Decimal_Real

Name: Decimal_Real			Version Id: 1.0.0.0
<i>Description</i> Floating Point Binary Data Types			
<i>Schema Base Type:</i> None			

Name: Decimal_Real			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

IEEE754LSBDouble

Name: IEEE754LSBDouble			Version Id: 1.0.0.0
<i>Description</i> IEEE 754 LSB double precision floating point			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

IEEE754LSBSingle

Name: IEEE754LSBSingle			Version Id: 1.0.0.0
<i>Description</i> IEEE 754 LSB single precision floating point			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

IEEE754MSBDouble

Name: IEEE754MSBDouble			Version Id: 1.0.0.0
<i>Description</i> IEEE 754 MSB double precision floating point			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

IEEE754MSBSingle

Name: IEEE754MSBSingle			Version Id: 1.0.0.0
<i>Description</i> IEEE 754 MSB single precision floating point			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedBitString

Name: SignedBitString			Version Id: 1.0.0.0
<i>Description</i> Signed Bit String			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedByte

Name: SignedByte			Version Id: 1.0.0.0
<i>Description</i> Signed 8-bit byte			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedLSB2

Name: SignedLSB2			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement LSB 2-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedLSB4

Name: SignedLSB4			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement LSB 4-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedLSB8

Name: SignedLSB8			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement LSB 8-byte integer			
<i>Schema Base Type:</i> None			

Name: SignedLSB8			Version Id: 1.0.0.0
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedMSB2

Name: SignedMSB2			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement MSB 2-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedMSB4

Name: SignedMSB4			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement MSB 4-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

SignedMSB8

Name: SignedMSB8			Version Id: 1.0.0.0
<i>Description</i> Signed 2's-complement MSB 8-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UTF8_Short_String_Collapsed

Name: UTF8_Short_String_Collapsed			Version Id: 1.0.0.0
<i>Description</i> The UTF8_Short_String_Collapsed class indicates a limited length, whitespace-collapsed string constrained to the UTF-8 character encoding.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

UTF8_Short_String_Preserved

Name: UTF8_Short_String_Preserved		Version Id: 1.0.0.0	
<i>Description</i> The UTF8_Short_String_Preserved class indicates a limited length, whitespace-preserved string constrained to the UTF-8 character encoding.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> 255
<i>No Pattern</i>			

UTF8_String

Name: UTF8_String		Version Id: 1.0.0.0	
<i>Description</i> The UTF8_String class indicates a limited length UTF8 text string with whitespaces removed.			
<i>Schema Base Type:</i> token			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UTF8_Text_Preserved

Name: UTF8_Text_Preserved		Version Id: 1.0.0.0	
<i>Description</i> The UTF8_Text_Preserved class indicates an unlimited length, whitespace-preserved text string constrained to the UTF-8 character encoding.			
<i>Schema Base Type:</i> string			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> 1	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedBitString

Name: UnsignedBitString		Version Id: 1.0.0.0	
<i>Description</i> Unsigned Bit String			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedByte

Name: UnsignedByte		Version Id: 1.0.0.0	
<i>Description</i> Unsigned 8-bit byte			

Name: UnsignedByte			Version Id: 1.0.0.0
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedLSB2

Name: UnsignedLSB2			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement LSB 2-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedLSB4

Name: UnsignedLSB4			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement LSB 4-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedLSB8

Name: UnsignedLSB8			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement LSB 8-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedMSB2

Name: UnsignedMSB2			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement MSB 2-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedMSB4

Name: UnsignedMSB4			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement MSB 4-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

UnsignedMSB8

Name: UnsignedMSB8			Version Id: 1.0.0.0
<i>Description</i> Unsigned 2's-complement MSB 8-byte integer			
<i>Schema Base Type:</i> None			
<i>Minimum Value:</i> None	<i>Maximum Value:</i> None	<i>Minimum Characters:</i> None	<i>Maximum Characters:</i> None
<i>No Pattern</i>			

Chapter 13. Units of Measure in the common (pds) namespace.

These classes define the PDS4 units of measure.

Unit_Of_Measure

Name: Unit_Of_Measure		Version Id: 1.0.0.0
<i>Description:</i> The Unit_Of_Measure is a definite magnitude of a quantity.		
	<i>Unit Id</i>	
	None	

Units_of_Acceleration

Name: Units_of_Acceleration		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Acceleration is a magnitude of acceleration.		
	<i>Unit Id</i>	
	cm/s**2	The abbreviated unit for Units_of_Acceleration is cm/s**2
	km/s**2	The abbreviated unit for Units_of_Acceleration is km/s**2
	m/s**2	The abbreviated unit for Units_of_Acceleration is m/s**2

Units_of_Amount_Of_Substance

Name: Units_of_Amount_Of_Substance		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Amount_Of_Substance is a magnitude of mass.		
	<i>Unit Id</i>	
	mol	The abbreviated unit for Units_of_Amount_Of_Substance is mol

Units_of_Angle

Name: Units_of_Angle		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Angle is a magnitude of angle.		
	<i>Unit Id</i>	
	arcmin	The abbreviated unit for Units_of_Angle is arcmin
	arcsec	The abbreviated unit for Units_of_Angle is arcsec
	deg	The abbreviated unit for Units_of_Angle is deg
	hr	The abbreviated unit for Units_of_Angle is hr
	mrad	The abbreviated unit for Units_of_Angle is mrad
	rad	The abbreviated unit for Units_of_Angle is rad

Units_of_Angular_Velocity

Name: Units_of_Angular_Velocity		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Angular_Velocity is a magnitude of speed of rotation.		
	<i>Unit Id</i>	
	deg/day	The abbreviated unit for Units_of_Angular_Velocity is deg/day
	deg/s	The abbreviated unit for Units_of_Angular_Velocity is deg/s
	rad/s	The abbreviated unit for Units_of_Angular_Velocity is rad/s

Units_of_Area

Name: Units_of_Area		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Area is a magnitude of area.		
	<i>Unit Id</i>	
	m**2	The abbreviated unit for Units_of_Area is m**2

Units_of_Frame_Rate

Name: Units_of_Frame_Rate		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Frame_Rate is a magnitude of change.		
	<i>Unit Id</i>	
	frames/s	The abbreviated unit for Units_of_Frame_Rate is frames/s

Units_of_Frequency

Name: Units_of_Frequency		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Frequency is a magnitude of frequency.		
	<i>Unit Id</i>	
	Hz	The abbreviated unit for Units_of_Frequency is Hz

Units_of_Length

Name: Units_of_Length		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Length is a magnitude of length.		
	<i>Unit Id</i>	
	AU	The abbreviated unit for Units_of_Length is AU (astronomical unit)
	Angstrom	The abbreviated unit for Units_of_Length is Angstrom
	cm	The abbreviated unit for Units_of_Length is cm
	km	The abbreviated unit for Units_of_Length is km

Units of Measure in the
common (pds) namespace.

Name: Units_of_Length		Version Id: 1.0.0.0
	m	The abbreviated unit for Units_of_Length is m
	micrometer	The abbreviated unit for Units_of_Length is micrometer
	mm	The abbreviated unit for Units_of_Length is mm
	nm	The abbreviated unit for Units_of_Length is nm

Units_of_Map_Scale

Name: Units_of_Map_Scale		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Map_Scale is a proportional representation.		
	<i>Unit Id</i>	
	km/pixel	The abbreviated unit for Units_of_Map_Scale is km/pixel
	m/pixel	The abbreviated unit for Units_of_Map_Scale is m/pixel
	mm/pixel	The abbreviated unit for Units_of_Map_Scale is mm/pixel
	pixel/deg	The abbreviated unit for Units_of_Map_Scale is pixel/deg

Units_of_Mass

Name: Units_of_Mass		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Mass is a magnitude of mass.		
	<i>Unit Id</i>	
	g	The abbreviated unit for Units_of_Mass is g
	kg	The abbreviated unit for Units_of_Mass is kg

Units_of_Misc

Name: Units_of_Misc		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Misc provides an assortment of derived units.		
	<i>Unit Id</i>	
	DN	The abbreviated unit for Units_of_Misc is DN
	electron/DN	The abbreviated unit for Units_of_Misc is electron/DN
	pixel	The abbreviated unit for Units_of_Misc is pixel

Units_of_None

Name: Units_of_None		Version Id: 1.0.0.0
<i>Description:</i> Units_of_None indicates that no unit of measure applies.		
	<i>Unit Id</i>	
	none	The abbreviated unit for Units_of_None is none

Units_of_Optical_Path_Length

Name: Units_of_Optical_Path_Length		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Optical_Path_Length is a magnitude of optical path length.		
	<i>Unit Id</i>	
	airmass	The abbreviated unit for Units_of_Optical_Path_Length is airmass

Units_of_Pressure

Name: Units_of_Pressure		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Pressure is a magnitude of pressure.		
	<i>Unit Id</i>	
	Pa	The abbreviated unit for Units_of_Pressure is Pa
	bar	The abbreviated unit for Units_of_Pressure is bar (10**5 Pa)
	hPa	The abbreviated unit for Units_of_Pressure is hPa (100 Pa)
	mbar	The abbreviated unit for Units_of_Pressure is mbar (100 Pa)

Units_of_Radiance

Name: Units_of_Radiance		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Radiance is a magnitude of radiance.		
	<i>Unit Id</i>	
	$W*m^{**2}*sr^{**1}$	The abbreviated unit of Units_of_Radiance is $W*m^{**2}*sr^{**1}$

Units_of_Rates

Name: Units_of_Rates		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Rate is a magnitude of change.		
	<i>Unit Id</i>	
	counts/bin	The abbreviated unit for Units_of_Rates is counts/bin
	kilobits/s	The abbreviated unit for Units_of_Rates is kilobits/s

Units_of_Solid_Angle

Name: Units_of_Solid_Angle		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Solid_Angle is a magnitude of a solid angle.		
	<i>Unit Id</i>	
	sr	The abbreviated unit for Units_of_Solid_Angle is sr

Units_of_Spectral_Irradiance

Name: Units_of_Spectral_Irradiance		Version Id: 1.0.0.0
<i>Description:</i> A measure of the power of radiation at a particular frequency or wavelength that passes through a unit area.		
	<i>Unit Id</i>	
	SFU	The abbreviated unit for Units_of_Spectral_Irradiance is SFU
	$W*m^{**2}*Hz^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**2}*Hz^{**1}$
	$W*m^{**2}*nm^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**2}*nm^{**1}$
	$W*m^{**3}$	The abbreviated unit for Units_of_Spectral_Irradiance is $W*m^{**3}$
	$uW*cm^{**2}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Irradiance is $uW*cm^{**2}*um^{**1}$

Units_of_Spectral_Radiance

Name: Units_of_Spectral_Radiance		Version Id: 1.0.0.0
<i>Description:</i> A measure of the power of radiation at a particular frequency or wavelength that passes through a unit area and a unit solid angle in a specified direction.		
	<i>Unit Id</i>	
	$W*m^{**2}*sr^{**1}*Hz^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*Hz^{**1}$
	$W*m^{**2}*sr^{**1}*nm^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*nm^{**1}$
	$W*m^{**2}*sr^{**1}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**2}*sr^{**1}*um^{**1}$
	$W*m^{**3}*sr^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $W*m^{**3}*sr^{**1}$
	$uW*cm^{**2}*sr^{**1}*um^{**1}$	The abbreviated unit for Units_of_Spectral_Radiance is $uW*cm^{**2}*sr^{**1}*um^{**1}$

Units_of_Storage

Name: Units_of_Storage		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Storage is an amount of computer storage.		
	<i>Unit Id</i>	
	byte	The abbreviated unit of Units_of_Storage is byte

Units_of_Temperature

Name: Units_of_Temperature		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Temperature is a magnitude of temperature.		
	<i>Unit Id</i>	
	K	The abbreviated unit of Units_of_Temperature is K
	degC	The abbreviated unit of Units_of_Temperature is degC

Units_of_Time

Name: Units_of_Time		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Time is a magnitude of time.		
	<i>Unit Id</i>	
	day	The abbreviated unit for Units_of_Time is day
	hr	The abbreviated unit for Units_of_Time is hr
	julian day	The abbreviated unit for Units_of_Time is julian day
	microseconds	The abbreviated unit for Units_of_Time is microseconds
	min	The abbreviated unit for Units_of_Time is min
	ms	The abbreviated unit for Units_of_Time is ms
	s	The abbreviated unit for Units_of_Time is s
	yr	The abbreviated unit for Units_of_Time is yr

Units_of_Velocity

Name: Units_of_Velocity		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Velocity is a magnitude of velocity.		
	<i>Unit Id</i>	
	cm/s	The abbreviated unit for Units_of_Velocity is cm/s
	km/s	The abbreviated unit for Units_of_Velocity is km/s
	m/s	The abbreviated unit for Units_of_Velocity is m/s

Units_of_Voltage

Name: Units_of_Voltage		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Voltage is a magnitude of voltage.		
	<i>Unit Id</i>	
	V	The abbreviated unit for Units_of_Voltage is V

Name: Units_of_Voltage		Version Id: 1.0.0.0
	mV	The abbreviated unit for Units_of_Voltage is mV

Units_of_Volume

Name: Units_of_Volume		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Volume is a magnitude of volume.		
	<i>Unit Id</i>	
	L	The abbreviated unit for Units_of_Volume is L
	m**3	The abbreviated unit for Units_of_Volume is m**3

Units_of_Wavenumber

Name: Units_of_Wavenumber		Version Id: 1.0.0.0
<i>Description:</i> Units_of_Wavenumber is the number of waves that occur per unit distance, i.e., inverse length		
	<i>Unit Id</i>	
	cm**-1	The abbreviated unit for Units_of_Wavenumber is cm**-1
	m**-1	The abbreviated unit for Units_of_Wavenumber is m**-1
	nm**-1	The abbreviated unit for Units_of_Wavenumber is nm**-1